ACE Model (Full Data)

Step 0: Install and load required packages (as in `ace-subset.qmd`)

```
library(cmdstanr)
```

```
This is cmdstanr version 0.9.0
```

```
- CmdStanR documentation and vignettes: mc-stan.org/cmdstanr
```

```
- CmdStan path: /home/marklai/.cmdstan/cmdstan-2.39.0
```

```
- CmdStan version: 2.39.0
```

```
register_knitr_engine()
options(mc.cores = min(parallel::detectCores() - 1, 4)) # Use four CPU cores for
MCMC sampling, if available
library(bayesplot)
```

```
This is bayesplot version 1.15.0
```

```
- Online documentation and vignettes at mc-stan.org/bayesplot
```

```
- bayesplot theme set to bayesplot::theme_default()
```

```
   * Does _not_ affect other ggplot2 plots
```

```
   * See ?bayesplot_theme_set for details on theme setting
```

```
library(ggplot2)
```

Step 1: Data import

```
n_mz <- c(325, 60, 7, 78, 150, 40, 8, 38, 88)
n_dz <- c(202, 97, 19, 96, 112, 64, 46, 56, 66)
```

```r
# Convert to long format data frame
dat_mz <- data.frame(
    twin1 = rep(rep(1:3, 3), n_mz),
    twin2 = rep(rep(1:3, each = 3), n_mz)
)
dat_dz <- data.frame(
    twin1 = rep(rep(1:3, 3), n_dz),
    twin2 = rep(rep(1:3, each = 3), n_dz)
)
dat_mz[] <- lapply(dat_mz, ordered, labels = c("normal", "overweight", "obese"))
dat_dz[] <- lapply(dat_dz, ordered, labels = c("normal", "overweight", "obese"))
dat_full <- rbind(
    data.frame(zygosity = "MZ", dat_mz),
    data.frame(zygosity = "DZ", dat_dz)
)
dat <- dat_full
```

```r
str(dat)
```

```
'data.frame':   1552 obs. of  3 variables:
 $ zygosity: chr  "MZ" "MZ" "MZ" "MZ" ...
 $ twin1   : Ord.factor w/ 3 levels "normal"<"overweight"<..: 1 1 1 1 1 1 1 1
1 1 ...
 $ twin2   : Ord.factor w/ 3 levels "normal"<"overweight"<..: 1 1 1 1 1 1 1 1
1 1 ...
```

```r
summary(dat)
```

```
      zygosity           twin1            twin2
 Length   :1552   normal    :755   normal    :710
 N.unique :   2   overweight:513   overweight:540
 N.blank  :   0   obese     :284   obese     :302
 Min.nchar:   2
 Max.nchar:   2
```

```r
tab_mz <- with(dat[dat$zygosity == "MZ", ], table(twin1, twin2))
tab_dz <- with(dat[dat$zygosity == "DZ", ], table(twin1, twin2))
```

Step 2: Compile the Stan model

```
//
// This Stan program estimates the polychoric correlation between two
// ordinal variables, and decompose based on an ACE model. This model
// assumes symmetry in the contingency table.
//
functions {
  #include "ace_fun.stan"
}
data {
  int<lower=0> k;  // number of categories
  array[k * (k + 1) %/% 2] int<lower=0> ltri_ns1;  // mz
  array[k * (k + 1) %/% 2] int<lower=0> ltri_ns2;  // dz
}
transformed data {
  int kprime = k * (k + 1) %/% 2;
  int N1 = sum(ltri_ns1);
  real N1real = N1;
  int N2 = sum(ltri_ns2);
  real N2real = N2;
}
parameters {
  real<lower=0, upper=1> scaled_rho1;
  real<lower=0, upper=1> scaled_rho2;
  ordered[k - 1] thres;
}
transformed parameters {
  real rho1 = scaled_rho1 * 2 - 1;
  real rho2 = scaled_rho2 * 2 - 1;
  vector<lower=0>[kprime] theta1 =
    vec_symm(polycor_to_prob(thres, rho1));
  vector<lower=0>[kprime] theta2 =
    vec_symm(polycor_to_prob(thres, rho2));
}
// The model to be estimated.
model {
  scaled_rho1 ~ beta(1.5, 1.5);
  scaled_rho2 ~ beta(1.5, 1.5);
  thres ~ student_t(4, 0, 2.5);
  ltri_ns1 ~ multinomial(theta1);
  ltri_ns2 ~ multinomial(theta2);
}
generated quantities {
```

```
  real h2 = 2 * (rho1 - rho2);
  real c2 = 2 * rho2 - rho1;
  real e2 = 1 - rho1;
  array[kprime] int ltri_ns1_tilde = multinomial_rng(theta1, N1);
  array[kprime] int ltri_ns2_tilde = multinomial_rng(theta2, N2);
  real X2_1_samp = 0.0;
  real X2_2_samp = 0.0;
  int<lower=0, upper=1> X2_1_gt;
  int<lower=0, upper=1> X2_2_gt;
  {
    vector[kprime] N1theta = N1real .* theta1;
    vector[kprime] N2theta = N2real .* theta2;
    real X2_1_rep = 0.0;
    real X2_2_rep = 0.0;
    for (idx in 1:kprime) {
      real ns1_exp = N1theta[idx];
      real ns2_exp = N2theta[idx];
      X2_1_samp += (ltri_ns1[idx] - ns1_exp)^2 / ns1_exp;
      X2_2_samp += (ltri_ns2[idx] - ns2_exp)^2 / ns2_exp;
      X2_1_rep += (ltri_ns1_tilde[idx] - ns1_exp)^2 / ns1_exp;
      X2_2_rep += (ltri_ns2_tilde[idx] - ns2_exp)^2 / ns2_exp;
    }
    X2_1_gt = X2_1_rep > X2_1_samp;
    X2_2_gt = X2_2_rep > X2_2_samp;
  }
}
```

Step 3: Prepare data and sampling

```
# Reduced frequency vector
to_ltri <- function(tab_x) {
    symm_x <- tab_x + t(tab_x) - diag(diag(tab_x))
    ltri_x <- symm_x[lower.tri(symm_x, diag = TRUE)]
}
(ltri_nmz <- to_ltri(tab_mz))
```

```
[1] 325 138  15 150  78  88
```

```
(ltri_ndz <- to_ltri(tab_dz))
```

```
[1] 202 193  65 112 120  66
```

```
ace_fit <- ace$sample(
    list(k = 3, ltri_ns1 = ltri_nmz, ltri_ns2 = ltri_ndz),
    chains = 4,
    iter_warmup = 1000,
    iter_sampling = 1000,
    seed = 732 # for reproducibility
)
```

Step 4: Check convergence

```
params <- c("rho1", "rho2", "thres", "h2", "c2", "e2")
ace_fit$print(params)
```

```
 variable  mean median   sd  mad    q5   q95 rhat ess_bulk ess_tail
 rho1      0.81   0.81 0.02 0.02  0.77  0.84 1.00     3401     3067
 rho2      0.45   0.45 0.04 0.04  0.39  0.51 1.00     3542     2690
 thres[1] -0.08  -0.08 0.03 0.03 -0.12 -0.03 1.00     3696     2746
 thres[2]  0.87   0.87 0.03 0.03  0.82  0.92 1.00     4922     2874
 h2        0.71   0.71 0.08 0.08  0.57  0.85 1.00     3633     2840
 c2        0.10   0.10 0.08 0.08 -0.03  0.22 1.00     3590     2758
 e2        0.19   0.19 0.02 0.02  0.16  0.23 1.00     3401     3067
```

```
ace_fit$diagnostic_summary()
```

```
$num_divergent
[1] 0 0 0 0

$num_max_treedepth
[1] 0 0 0 0

$ebfmi
[1] 1.059781 1.086534 1.067425 1.050812
```

```
ace_fit$draws(params) |>
    mcmc_rank_hist()
```




Figure 1: Rank histograms for the main model parameters

Step 5: Model checking

Repeat Steps 3 and 4 with reparameterized model

With unreasonable h2 and c2, we reparameterize the model to enforce theory-informed priors/ constraints.

```
//
// This Stan program estimates the polychoric correlation between two
// ordinal variables, and decompose based on an ACE model. The model is
// parameterized using a simplex for the ACE components to enforce
// nonzero variances, and assumes symmetry in the contingency table.
//
functions {
  #include "ace_fun.stan"
}
data {
  int<lower=0> k;  // number of categories
  array[k * (k + 1) %/% 2] int<lower=0> ltri_ns1;  // mz
  array[k * (k + 1) %/% 2] int<lower=0> ltri_ns2;  // dz
}
transformed data {
  int kprime = k * (k + 1) %/% 2;
  int N1 = sum(ltri_ns1);
```

```
  real N1real = N1;
  int N2 = sum(ltri_ns2);
  real N2real = N2;
}
parameters {
  simplex[3] ace;
  ordered[k - 1] thres;
}
transformed parameters {
  real rho1 = ace[1] + ace[2];
  real rho2 = ace[1] / 2 + ace[2];
  vector<lower=0>[kprime] theta1 =
    vec_symm(polycor_to_prob(thres, rho1));
  vector<lower=0>[kprime] theta2 =
    vec_symm(polycor_to_prob(thres, rho2));
}
// The model to be estimated.
model {
  thres ~ student_t(4, 0, 2.5);
  ltri_ns1 ~ multinomial(theta1);
  ltri_ns2 ~ multinomial(theta2);
}
generated quantities {
  real h2 = ace[1];
  real c2 = ace[2];
  real e2 = ace[3];
  array[kprime] int ltri_ns1_tilde = multinomial_rng(theta1, N1);
  array[kprime] int ltri_ns2_tilde = multinomial_rng(theta2, N2);
  real X2_1_samp = 0.0;
  real X2_2_samp = 0.0;
  int<lower=0, upper=1> X2_1_gt;
  int<lower=0, upper=1> X2_2_gt;
  {
    vector[kprime] N1theta = N1real .* theta1;
    vector[kprime] N2theta = N2real .* theta2;
    real X2_1_rep = 0.0;
    real X2_2_rep = 0.0;
    for (idx in 1:kprime) {
      real ns1_exp = N1theta[idx];
      real ns2_exp = N2theta[idx];
      X2_1_samp += (ltri_ns1[idx] - ns1_exp)^2 / ns1_exp;
      X2_2_samp += (ltri_ns2[idx] - ns2_exp)^2 / ns2_exp;
      X2_1_rep += (ltri_ns1_tilde[idx] - ns1_exp)^2 / ns1_exp;
```

```
      X2_2_rep += (ltri_ns2_tilde[idx] - ns2_exp)^2 / ns2_exp;
    }
    X2_1_gt = X2_1_rep > X2_1_samp;
    X2_2_gt = X2_2_rep > X2_2_samp;
  }
}
```

One can then repeat steps 3 and 4 to obtain the posterior samples and convergence diagnostics, which we do not repeat the details here. The posterior summaries of the main parameters are in Table 1.

```
ace_s_fit <- ace_simplex$sample(
    list(k = 3, ltri_ns1 = ltri_nmz, ltri_ns2 = ltri_ndz),
    chains = 4,
    iter_warmup = 1000,
    iter_sampling = 1000,
    seed = 732 # for reproducibility
)
```

```
ace_s_fit$summary(params) |>
    knitr::kable(digits = 2)
```

Table 1: Posterior summary of the main model parameters

variable	mean	median	sd	mad	q5	q95	rhat	ess_bulk	ess_tail
rho1	0.81	0.81	0.02	0.02	0.78	0.84	1	4296.22	3068.38
rho2	0.46	0.46	0.03	0.03	0.41	0.52	1	1425.42	1159.38
thres[1]	−0.08	−0.08	0.03	0.03	−0.12	−0.03	1	1909.01	1690.90
thres[2]	0.87	0.87	0.03	0.03	0.82	0.92	1	2781.60	2396.95
h2	0.69	0.70	0.07	0.07	0.57	0.80	1	1394.46	1249.69
c2	0.12	0.11	0.06	0.07	0.02	0.23	1	1245.87	794.18
e2	0.19	0.19	0.02	0.02	0.16	0.22	1	4296.22	3068.38

Global fit

Local fit

```
x_scale <- scale_x_continuous(
    breaks = seq_along(ltri_nmz),
    labels = c(
```

```
        "(1,1)",
        "(2,1)+(1,2)",
        "(2,2)",
        "(3,1)+(1,3)",
        "(3,2)+(2,3)",
        "(3,3)"
    )
)
```

```
ace_s_fit$draws("ltri_ns1_tilde", format = "matrix") |>
    ppc_intervals(y = ltri_nmz) +
    xlab("Cell (twin1, twin2)") +
    x_scale
```

```
Warning: Using `size` aesthetic for lines was deprecated in ggplot2 3.4.0.
ℹ Please use `linewidth` instead.
ℹ The deprecated feature was likely used in the bayesplot package.
  Please report the issue at <https://github.com/stan-dev/bayesplot/issues/>.
```




Figure 2: Posterior predictive check for each cell count in the contingency tables for MZ twins

```
ace_s_fit$draws("ltri_ns2_tilde", format = "matrix") |>
    ppc_intervals(y = ltri_ndz) +
```

```
    xlab("Cell (twin1, twin2)") +
    x_scale
```




Figure 3: Posterior predictive check for each cell count in the contingency tables for DZ twins

Step 6: Summarizing the posterior

```
ace_s_fit$draws(params) |>
    mcmc_hist()
```

```
`stat_bin()` using `bins = 30`. Pick better value `binwidth`.
```




Figure 4: Posterior distributions of the main model parameters