
Uncertainty Estimate with SVM

Release 0.0.1

Marko Djordjic

Nov 28, 2019

Contents:

1.1 Functions

<code>compute_predictive_entropy(probability)</code>	Estimate epistemic uncertainty via predictive entropy [1]
<code>generate_ensemble(number_of_estimators, ...)</code>	Generates a collection of estimators
<code>generate_predictions(...)</code>	Generate predictions from ensemble
<code>get_all_files_within_folder(path, ...)</code>	Catalogue all files within a folder according to negative condition
<code>get_all_sub_folders_within_folder(path)</code>	Catalogue names of all sub-folders within folder
<code>get_data(folder_wh_data)</code>	Build an inventory of data sets out of individual files within a folder.
<code>make_confusion_matrix(reference, output, ...)</code>	Compute confusion matrix
<code>plot_comparison(coordinates, reference, ...)</code>	Plot comparison across different classification solutions.
<code>plot_confusion_matrix(content[, save_plot, path])</code>	Plot confusion matrix
<code>plot_individual_classes(coordinates, ...[, ...])</code>	Plot class membership in individual plot
<code>plot_solution(coordinates, original_labels, ...)</code>	Plotting of solution of classification task
<code>reduce_set_to_equal_distribution_of_classes</code>	Reduces the training set to the size $N = K \times$ size of the least frequent class
<code>scatter_plot_with_groups(coordinates, ...[, ...])</code>	Produce scatter plot with coloration according to the labels

1.1.1 compute_predictive_entropy

`ucf.compute_predictive_entropy(probability)`
Estimate epistemic uncertainty via predictive entropy¹

¹ Further details about about predictive entropy available at: [https://en.wikipedia.org/wiki/Entropy_\(information_theory\)](https://en.wikipedia.org/wiki/Entropy_(information_theory))

Parameters **probability** (*numpy.array*) – A *numpy.array* (N x C) with the probabilities obtained from the underlying classifier (soft voting).

Returns Uncertainty estimate for each prediction.

Return type *numpy.array*

Notes

For the computation of uncertainty value equal to zero are replaced with a small constant near zero.

References

1.1.2 generate_ensemble

`ucf.generate_ensemble` (*number_of_estimators*, *features_for_training*, *targets_for_training*)

Generates a collection of estimators

Each estimator is trained on a sub-set of the training data, and appended to the ensemble. Support Vector Classifier has been selected as the classifier of choice, but can be replaced with any other classifier.

Parameters

- **number_of_estimators** (*int*) – How much estimators will be in the ensemble.
- **features_for_training** (*numpy.array*) – Features which will be utilized for training of individual estimators.
- **targets_for_training** (*numpy.array*) – Targets which will be utilized for training of individual estimators.

Returns A collection of SVCs trained on different sections of features and targets pairs.

Return type List

Notes

The function does not shuffle the data. If shuffling is necessary, it has to be done before call to the function.

1.1.3 generate_predictions

`ucf.generate_predictions` (*inventory_of_estimators*, *features*)

Generate predictions from ensemble

The function applies 'predict_proba' method to a collection of estimators, in order to get predictions and compute uncertainty estimate via predictive entropy.

Parameters

- **inventory_of_estimators** (*list*) – A collection of estimators placed in a list.
- **features** (*numpy.array*) – Features on which to perform prediction.

Returns

- **ensemble_predictions** (*numpy.array*) – Prediction of class membership.
- **uncertainty_estimate** (*numpy.array*) – Uncertainty estimate.

1.1.4 get_all_files_within_folder

`ucf.get_all_files_within_folder(path, negative_condition)`

Catalogue all files within a folder according to negative condition

Parameters

- **path** (*str*) – Path to the folder.
- **negative_condition** (*str*) – Exact text contained with the name of the files, which is utilized to identify files which will not be catalogued.

Returns Names of all files within folder except file names designated in *negative_condition* parameter.

Return type list

1.1.5 get_all_sub_folders_within_folder

`ucf.get_all_sub_folders_within_folder(path)`

Catalogue names of all sub-folders within folder

Parameters **path** (*str*) – Path to the main folder.

Returns Names of all sub-folder within folder designated in *path* parameter.

Return type list

1.1.6 get_data

`ucf.get_data(folder_wh_data)`

Build an inventory of data sets out of individual files within a folder.

Function omits files which are having *txt* inside their name.

Parameters **folder_wh_data** (*str*) – Folder in which data files are residing.

Returns All the data sets generated from individual data files.

Return type list

1.1.7 make_confusion_matrix

`ucf.make_confusion_matrix(reference, output, prediction_labels)`

Compute confusion matrix

Parameters

- **reference** (*numpy.array*) – A vector with reference.
- **output** (*numpy.array*) – A vector with targets.
- **prediction_labels** (*list*) – Descriptions of labels.

Returns

Return type Confusion matrix as the pandas.DataFrame.

Notes

Reference group is placed in row. Proportion of each prediction within the reference group is computed across columns (horizontally).

1.1.8 plot_comparison

`ucf.plot_comparison(coordinates, reference, solutions, description, coloration, save=True, path=None)`

Plot comparison across different classification solutions.

Parameters

- **coordinates** (*numpy.array*) – Coordinates of the points.
- **reference** (*numpy.array*) – Labels of the reference.
- **solutions** (*list*) – List containing solutions of classification problem.
- **description** (*dict*) – Description of each label.
- **coloration** (*dict*) – Vector with coloration.

Returns No explicit return. Plot is displayed on the screen, or saved into a file.

Return type None

1.1.9 plot_confusion_matrix

`ucf.plot_confusion_matrix(content, save_plot=False, path=None)`

Plot confusion matrix

Confusion matrix will always be tabulated and plotted. Optionally, picture of confusion matrix can be saved.

Parameters

- **content** (*numpy.array*) – Numpy array with the complete content of the confusion matrix.
- **save_plot** (*bool*) – Indication whether to save the plot. Default set to false.
- **path** (*str*) – Path including the file name where to save the plot.

Returns No explicit return. Optionally plot can be saved.

Return type None

Notes

Content must consist all numeric content, as well as headings of all rows and columns.

1.1.10 plot_individual_classes

`ucf.plot_individual_classes(coordinates, class_membership, description, coloration_mode, coloration, save=False, path=None)`

Plot class membership in individual plot

Point within scatter plots indicating class membership with multiple classes can often overlap, therefore debilitating correct analysis. This function plots all classes independently.

Parameters

- **coordinates** (*numpy.array*) – Coordinates of points.
- **class_membership** (*numpy.array*) – Indication of class membership.
- **description** (*dict*) – Description of each label.
- **coloration_mode** (*str*) – Indication of the mode of coloration.
- **coloration** (*numpy.array*) – Vector with coloration.
- **save** (*bool*) – Option to save the plot.
- **path** (*str*) – Absolute path towards the file in which to save the plot.

Returns No explicit return.

Return type None

1.1.11 plot_solution

`ucf.plot_solution(coordinates, original_labels, predicted_labels, legend_colors, legend_descriptions, uncertainty, save=False, path=None)`
Plotting of solution of classification task

Convenience function to plot: (a) original labels, (b) predicted labels, and (c) uncertainty estimate of the model.

Parameters

- **coordinates** (*numpy.array*) – Coordinates of labels
- **original_labels** (*numpy.array*) – Reference one-dimensional encoding of the class membership. One-hot encoding is not supported.
- **predicted_labels** (*numpy.array*) – Predicted one-dimensional encoding of the class membership. One-hot encoding is not supported.
- **legend_colors** (*dict*) – Colors to be utilized for coloration of points.
- **legend_descriptions** (*dict*) – Labels to be utilized for description in plot legend.
- **uncertainty** (*numpy.array*) – Uncertainty of the models estimate of class membership.
- **save** (*bool*) – Option to save the plot. Default set to false.
- **path** (*str*) – Absolute path to the file in which to save a plot.

Returns No explicit return. Plot is displayed on the screen, or saved into a file.

Return type None

1.1.12 reduce_set_to_equal_distribution_of_classes

`ucf.reduce_set_to_equal_distribution_of_classes(features_for_training, targets_for_training)`
Reduces the training set to the size $N = K \times \text{size of the least frequent class}$

Firstly, the count of least frequent class is computed. Than a pair with features and targets is constructed consisting of samples of all classes. Therefore, generated pair is balanced in regards to distribution of classes.

Parameters

- **features_for_training** (*numpy.array*) – Features which will be used for generating reduced sets.
- **targets_for_training** (*numpy.array*) – Targets which will be used for generating reduced sets.

Returns Two separate *numpy.array*s Features and targets reduced to the size of equal to the number of samples belonging to the leas frequent class.

Return type *numpy.array*

1.1.13 scatter_plot_with_groups

`ucf.scatter_plot_with_groups` (*coordinates, labels, legend_colors, legend_descriptions, save_plot=False, path=None*)

Produce scatter plot with coloration according to the labels

Parameters

- **coordinates** (*numpy.array*) – Coordinates of points.
- **labels** (*numpy.array*) – Vector indicating class membership of each point.
- **legend_colors** (*dict*) – Colors to be utilized for coloration of points.
- **legend_descriptions** (*dict*) – Labels to be utilized for description in plot legend.
- **save_plot** (*bool*) – Indication whether to save a plot. Defaults to none
- **path** (*str*) – Path including the file name where to save the plot.

Returns No explicit return.

Return type None

1.2 Classes

<code>PCA([n_components, copy, whiten, ...])</code>	Principal component analysis (PCA)
<code>SVC([C, kernel, degree, gamma, coef0, ...])</code>	C-Support Vector Classification.
<code>TrainingDataSets(features_and_targets_data_set)</code>	Class for generating training, validation, and testing data sets.
<code>product</code>	<code>product(*iterables, repeat=1) -> product object</code>

1.2.1 TrainingDataSets

class `ucf.TrainingDataSets` (*features_and_targets_data_set*)

Bases: `object`

Class for generating training, validation, and testing data sets.

original_data

Original features and targets.

Type `pandas.DataFrame`

indices_of_features

Numeric indication of position of features in *original_data*

Type `list`

indices_of_targets

Numeric indication of position of targets in *original_data*

Type list

train_features

Unscaled training features.

Type numpy.array

train_targets

Training targets. Shuffled if desired.

Type numpy.array

validation_features

Validation features

Type numpy.array

validation_targets

Validation Targets

Type numpy.array

test_features

Testing features

Type numpy.array

test_targets

Testing targets

Type numpy.array

scaled_train_features

Train features scaled to mean zero and unit variance. Shuffled if desired.

Type numpy.array

scaled_validation_features

Validation features scaled to mean zero and unit variance.

Type Numpy Array

scaled_test_features

Test features scaled to mean zero and unit variance.

Type Numpy Array

Methods Summary

<i>compute_mean_and_standard_deviation()</i>	Computation of mean and standard deviation of features in the training data set.
<i>get_scaled_features()</i>	Convenience method to return scaled features.
<i>get_targets()</i>	Convenience method to return targets and features
<i>make_training_data(train_size, validation_size)</i>	Make features and targets
<i>scale_features()</i>	Standardize features in such manner that their mean is centered to zero, and unit of measurement is set to variance.

Continued on next page

Table 3 – continued from previous page

<code>shuffle()</code>	Shuffle scaled features and unscaled targets for training
------------------------	-----------------------------------------------------------

Methods Documentation

`compute_mean_and_standard_deviation()`

Computation of mean and standard deviation of features in the training data set.

Returns No explicit return.

Return type None

Notes

Values are stored in the 'features_mean' and 'features_standard_deviation' attribute of the class.

`get_scaled_features()`

Convenience method to return scaled features.

Returns

- **scaled_train_features** (*numpy.array*) – Scaled features for training.
- **scaled_validation_features** (*numpy.array*) – Scaled features for validation.
- **scaled_test_features** (*numpy.array*) – Scaled features for testing.

`get_targets()`

Convenience method to return targets and features

Returns

- **train_targets** (*numpy.array*) – Targets for training.
- **validation_targets** (*numpy.array*) – Targets for validation.
- **test_targets** (*numpy.array*) – Targets for testing.

`make_training_data(train_size, validation_size)`

Make features and targets

Parameters

- **train_size** (*int*) – Proportion of the training set.
- **validation_size** (*int*) – Proportion of the validation set.

Notes

Size of the testing set is determined implicitly.

`scale_features()`

Standardize features in such manner that their mean is centered to zero, and unit of measurement is set to variance.

Returns Standardized features are placed inside appropriate attributes of the class.

Return type *numpy.array*

`shuffle()`

Shuffle scaled features and unscaled targets for training

Notes

Only scaled training features and targets are shuffled. Validation, and test data sets are not shuffled.

1.3 Class Inheritance Diagram

```
classDiagram
    class TrainingDataSets
```

TrainingDataSets

CHAPTER 2

Indices and tables

- `genindex`
- `modindex`
- `search`

u

ucf, ??