

# On Solving the Multiple Variable Gapped Longest Common Subsequence Problem

Marko Djukanović<sup>1,2, 6</sup>   Nikola Balaban<sup>2</sup>   Christian Blum<sup>3</sup>  
Aleksandar Kartelj<sup>4</sup>   Sašo Džeroski<sup>5</sup>   Žiga Zebec<sup>6</sup>

<sup>1</sup>University of Nova Gorica, Nova Gorica, Slovenia

<sup>2</sup>Faculty of Natural Sciences and Mathematics, University of Banja Luka, Banja Luka,  
Bosnia and Herzegovina

<sup>3</sup>Artificial Intelligence Research Institute (IIIA-CSIC), Barcelona, Spain

<sup>4</sup>Faculty of Mathematics, University of Belgrade, Belgrade, Serbia

<sup>5</sup>Jožef Stefan Institute, Ljubljana, Slovenia

<sup>6</sup>Institute of Information Sciences (IZUM), Maribor, Slovenia

- Eurocast 2026: 20th International Conference on Computer Aided Systems Theory,  
February 23-27, 2026, Las Palmas de Gran Canaria, Spain–



# Outline

- Introduction & Preliminaries
- Problem Definition
- Graph state space
- Iterative multi-source Beam Search
- Experimental Evaluation
  - General problem
  - Special problem
- Conclusions

# Introduction

- Objects we deal with: sequences (strings) over finite alphabet
  - DNA/RNA over  $\{A, T, G, C/U\}$
  - Proteins over 20 (canonical) amino acids:  $\{A, C, D, E, P, Q, \dots\}$
- Computational biology
  - **One of central tasks:** sequence comparison, finding common motifs between sequences
  - compare structurally but also semantically/functionality
  - sequence alignment problems
- Subsequences: reveal structural similarities → **Longest common subsequence problem** variants

# Longest common subsequence problem (LCSP)

- Basic problem in Computational biology
- Intensively solved over last 50 years
  - theoretically as well as practically
  - Practically: many approximation algorithms, (meta-) heuristics, exact approaches, etc.

## Definition (LCSP)

**Input:** Given a set of sequences  $S = \{s_1, \dots, s_m\}$

**Task:** Find a subsequence  $s$  which is **common** for all sequences from  $S$  of **maximum** possible length.

## Example

Input:  $S = \{\text{AATTGC}, \text{ATTAC}\}$

LCS solution:  $s = \text{ATTC}$

# Literature & LCS Problem Variants

Theoretically:

- When  $m = 2$  – polynomially solvable (in  $O(n^2)$ ): [Dynamic programming](#), Hunt-Schlimanski, ...
- When  $m$  arbitrary large –  $\mathcal{NP}$ -hard:
  - subject of interest within last 30 years: approximation approaches, meta-heuristics (ACO, [Beam search](#), ...), but also exact approaches ( $A^*$ , anytime approaches,...)

Problem-related variants:

- Arc-annotated LCS problem
- Constrained (restricted/imposed) LCS problem
- Repetition-free, Longest filled LCS,...
- **Gapped LCS problem**

# The gaped LCS problem

## Definition (A gap sequence)

Given is a sequence  $s$  and an assigned function  $G_s: \{1, \dots, |s|\} \mapsto \mathbb{N}$ . An ordered pair  $(s, G_s)$  is called a **sequence with gaps**.

## Definition (A gapped subsequence )

Sequence  $\tilde{s}$  is a gapped subsequence of  $(s, G_s)$  iff

- $\tilde{s}$  is a subsequence of  $s$
- the gapped constraint  $G_s$  is fulfilled

# Literature & Motivation

content...