

R6E8A Trailing 7-Day Instrument Report

Unit 2709 | 2026-07-29 through 2026-08-04 | HDF and EHZ kept separate

* Account for up to 30 minutes of source-archive lag.

Daily HDF highest-event record

Date	Time EST	Dur.	Freq.	Peak RMS	% above median	EHZ z
2026-07-29	1:49:38 AM EST	14.0 s	0.320 Hz	143,934	16,158.6%	-0.89
2026-07-30	5:47:31 PM EST	3.0 s	1.188 Hz	305,022	32,034.7%	0.38
2026-07-31	6:38:31 PM EST	6.0 s	1.055 Hz	343,640	38,030.3%	1.04
2026-08-01	4:25:35 PM EST	2.0 s	1.180 Hz	260,814	11,865.7%	0.88
2026-08-02	1:28:26 AM EST	2.0 s	0.730 Hz	410,812	32,668.5%	1.22
2026-08-03	7:00:02 PM EST	4.0 s	1.134 Hz	377,237	43,036.6%	0.78
2026-08-04	5:22:37 AM EST	1.0 s	8.156 Hz	7,038	741.7%	0.37

Daily percentage values are same-HDF-channel descriptive comparisons to each day's median. They are not distribution-rank statistics and are not external-standard exceedances.

Seven-day instrument summary

Metric	Result
Highest HDF peak RMS day	2026-08-02 - 410,812.1 counts
Largest same-day relative difference	2026-08-03 - 43,036.6% above median
Documented days in this report	7
Channel handling	HDF primary; EHZ independent vertical-motion context

August 3 early-morning archived detector reference

Aug 3 - 2:18:49 AM EST: 5.0 s, 5.7923 Hz, 22,570.9 HDF RMS counts, 2,712.4% above the then-current HDF median. This preserved detector record is not a complete 2:30-3:00 AM interval analysis.

Four-tier monitoring framework

Tier	Meaning	Rule
Tier 1	Within named reference	At or below a valid external reference
Tier 2	Intermittent exceedance	Verified intervals, each under 30 minutes
Tier 3	Prolonged exceedance	One or more verified intervals of 30-119 minutes
Tier 4	Extended exceedance	One or more verified intervals of 120 minutes or longer

No tier is assigned from the raw-count table above. A tier requires the matching calibrated external-reference metric and a verified continuous duration.

External reference status

External reference	Current comparison status
ISO 7196	HDF frequency scope is relevant; calibrated G-weighted dB(G) is not currently computed.
ANSI/ASA S12.2 and ASHRAE RC/NC	N/A from raw HDF counts; calibrated octave-band room sound levels are required.
Defra NANR45	N/A until calibrated 1/3-octave values from 10-160 Hz are available.
WHO night noise and ISO 1996	N/A from HDF/EHZ counts; the required environmental acoustic metrics are not present.

Sources and methods

Source: Raspberry Shake FDSN DataSelect and the repository's preserved hourly derived records. Raw MiniSEED is not redistributed. HDF and EHZ are evaluated independently. Missing samples remain unavailable and are never treated as zero. Official verification: Raspberry Shake FDSN.

*This Data may lag. Account for up to 30 minutes of source-archive lag.