

Small Loss Regret Bounds for Thompson Sampling

Mark Sellke

with Sébastien Bubeck

August 29, 2018

Overview

- 1 Learning from Experts
- 2 Analysis of Thompson Sampling for Full Feedback
- 3 Small Loss Bound for Full Feedback
- 4 Bandit and Semibandit Cases
- 5 Open Problems

Learning from Experts

- Finite (static) set $[n] = \{1, 2, \dots, n\}$ of possible actions each round.

Learning from Experts

- Finite (static) set $[n] = \{1, 2, \dots, n\}$ of possible actions each round.
- Beforehand, an (oblivious) adversary chooses a sequence $(\ell_t(i))_{t=1}^T$ of loss functions $\ell_t : [n] \rightarrow [0, 1]$.

Learning from Experts

- Finite (static) set $[n] = \{1, 2, \dots, n\}$ of possible actions each round.
- Beforehand, an (oblivious) adversary chooses a sequence $(\ell_t(i))_{t=1}^T$ of loss functions $\ell_t : [n] \rightarrow [0, 1]$.
- Each round, the player chooses an action i_t and pays loss $\ell_t(i_t)$.

Learning from Experts

- Finite (static) set $[n] = \{1, 2, \dots, n\}$ of possible actions each round.
- Beforehand, an (oblivious) adversary chooses a sequence $(\ell_t(i))_{t=1}^T$ of loss functions $\ell_t : [n] \rightarrow [0, 1]$.
- Each round, the player chooses an action i_t and pays loss $\ell_t(i_t)$.
- In the *full feedback* setting we observe the entire vector $\vec{\ell}_t$ after timestep t , while in the *bandit* setting we observe only $\ell_t(i_t)$.

Learning from Experts

- Finite (static) set $[n] = \{1, 2, \dots, n\}$ of possible actions each round.
- Beforehand, an (oblivious) adversary chooses a sequence $(\ell_t(i))_{t=1}^T$ of loss functions $\ell_t : [n] \rightarrow [0, 1]$.
- Each round, the player chooses an action i_t and pays loss $\ell_t(i_t)$.
- In the *full feedback* setting we observe the entire vector $\vec{\ell}_t$ after timestep t , while in the *bandit* setting we observe only $\ell_t(i_t)$.
- At the end, each action has a total loss $L_{i,T} = \sum_{t=1}^T \ell_t(i)$. Player has total loss $L_T = \sum_{t=1}^T \ell_t(i_t)$. Denote by $i^* = \arg \min_i L_{i,T}$ the coordinate with smallest loss $L^* = \sum_{t=1}^T \ell_t(i^*)$.

Learning from Experts

- Finite (static) set $[n] = \{1, 2, \dots, n\}$ of possible actions each round.
- Beforehand, an (oblivious) adversary chooses a sequence $(\ell_t(i))_{t=1}^T$ of loss functions $\ell_t : [n] \rightarrow [0, 1]$.
- Each round, the player chooses an action i_t and pays loss $\ell_t(i_t)$.
- In the *full feedback* setting we observe the entire vector $\vec{\ell}_t$ after timestep t , while in the *bandit* setting we observe only $\ell_t(i_t)$.
- At the end, each action has a total loss $L_{i,T} = \sum_{t=1}^T \ell_t(i)$. Player has total loss $L_T = \sum_{t=1}^T \ell_t(i_t)$. Denote by $i^* = \arg \min_i L_{i,T}$ the coordinate with smallest loss $L^* = \sum_{t=1}^T \ell_t(i^*)$.
- The *regret* is $R_T = L_T - L^*$.

Learning from Experts

- Finite (static) set $[n] = \{1, 2, \dots, n\}$ of possible actions each round.
- Beforehand, an (oblivious) adversary chooses a sequence $(\ell_t(i))_{t=1}^T$ of loss functions $\ell_t : [n] \rightarrow [0, 1]$.
- Each round, the player chooses an action i_t and pays loss $\ell_t(i_t)$.
- In the *full feedback* setting we observe the entire vector $\vec{\ell}_t$ after timestep t , while in the *bandit* setting we observe only $\ell_t(i_t)$.
- At the end, each action has a total loss $L_{i,T} = \sum_{t=1}^T \ell_t(i)$. Player has total loss $L_T = \sum_{t=1}^T \ell_t(i_t)$. Denote by $i^* = \arg \min_i L_{i,T}$ the coordinate with smallest loss $L^* = \sum_{t=1}^T \ell_t(i^*)$.
- The *regret* is $R_T = L_T - L^*$.
- Player's objective: minimize expected regret $\mathbb{E}[R_T]$.

Learning from Experts

- Finite (static) set $[n] = \{1, 2, \dots, n\}$ of possible actions each round.
- Beforehand, an (oblivious) adversary chooses a sequence $(\ell_t(i))_{t=1}^T$ of loss functions $\ell_t : [n] \rightarrow [0, 1]$.
- Each round, the player chooses an action i_t and pays loss $\ell_t(i_t)$.
- In the *full feedback* setting we observe the entire vector $\vec{\ell}_t$ after timestep t , while in the *bandit* setting we observe only $\ell_t(i_t)$.
- At the end, each action has a total loss $L_{i,T} = \sum_{t=1}^T \ell_t(i)$. Player has total loss $L_T = \sum_{t=1}^T \ell_t(i_t)$. Denote by $i^* = \arg \min_i L_{i,T}$ the coordinate with smallest loss $L^* = \sum_{t=1}^T \ell_t(i^*)$.
- The *regret* is $R_T = L_T - L^*$.
- Player's objective: minimize expected regret $\mathbb{E}[R_T]$.
- Later we also consider the *semibandit* case: player picks m of n actions each round.

The Bayesian Approach

- As stated, we have no probability distribution over adversaries; we have to do well on average against all adversaries at once.

The Bayesian Approach

- As stated, we have no probability distribution over adversaries; we have to do well on average against all adversaries at once.
- If we only care about the value of this player-adversary game, by the mini-max theorem, suffices to do well against any *fixed* probability distribution over adversaries.

The Bayesian Approach

- As stated, we have no probability distribution over adversaries; we have to do well on average against all adversaries at once.
- If we only care about the value of this player-adversary game, by the mini-max theorem, suffices to do well against any *fixed* probability distribution over adversaries.
- Hence we may assume we are given a prior distribution over loss sequences. If we can always keep $\mathbb{E}[R_T]$ low, great!

The Bayesian Approach

- As stated, we have no probability distribution over adversaries; we have to do well on average against all adversaries at once.
- If we only care about the value of this player-adversary game, by the mini-max theorem, suffices to do well against any *fixed* probability distribution over adversaries.
- Hence we may assume we are given a prior distribution over loss sequences. If we can always keep $\mathbb{E}[R_T]$ low, great!
- As we observe losses, we update our distribution to obtain a new posterior distribution each round.

The Bayesian Approach

- As stated, we have no probability distribution over adversaries; we have to do well on average against all adversaries at once.
- If we only care about the value of this player-adversary game, by the mini-max theorem, suffices to do well against any *fixed* probability distribution over adversaries.
- Hence we may assume we are given a prior distribution over loss sequences. If we can always keep $\mathbb{E}[R_T]$ low, great!
- As we observe losses, we update our distribution to obtain a new posterior distribution each round.
- Given initial prior distribution, finding optimal play is a complicated, deterministic computation.

The Bayesian Approach

- As stated, we have no probability distribution over adversaries; we have to do well on average against all adversaries at once.
- If we only care about the value of this player-adversary game, by the mini-max theorem, suffices to do well against any *fixed* probability distribution over adversaries.
- Hence we may assume we are given a prior distribution over loss sequences. If we can always keep $\mathbb{E}[R_T]$ low, great!
- As we observe losses, we update our distribution to obtain a new posterior distribution each round.
- Given initial prior distribution, finding optimal play is a complicated, deterministic computation.
- Thompson Sampling is a simple strategy for any probability distribution. Not exactly optimal, but it does very well and is feasible in practice.

Thompson Sampling

Thompson Sampling Procedure

At each time t , compute the posterior distribution p_t for the best coordinate $i^* = \arg \min_{i \in [n]} L_{i,T}$. Then pick the next action i_t according to the distribution p_t .

Thompson Sampling

Thompson Sampling Procedure

At each time t , compute the posterior distribution p_t for the best coordinate $i^* = \arg \min_{i \in [n]} L_{i,T}$. Then pick the next action i_t according to the distribution p_t .

- In the full-information case, this strategy intuitively hedges by softly following the leader. In the bandit case, this strategy intuitively balances explore/exploit similarly to multiplicative weights or upper confidence bound algorithms.

Thompson Sampling

Thompson Sampling Procedure

At each time t , compute the posterior distribution p_t for the best coordinate $i^* = \arg \min_{i \in [n]} L_{i,T}$. Then pick the next action i_t according to the distribution p_t .

- In the full-information case, this strategy intuitively hedges by softly following the leader. In the bandit case, this strategy intuitively balances explore/exploit similarly to multiplicative weights or upper confidence bound algorithms.
- Unlike the exact optimal strategy, Thompson Sampling is often efficient to simulate, and is amenable to analysis.

Small Loss Regret Bounds

- Standard regret bounds show $\mathbb{E}[R_T] = O(\sqrt{T})$.

Small Loss Regret Bounds

- Standard regret bounds show $\mathbb{E}[R_T] = O(\sqrt{T})$.
- However, if L^* is very small, not so impressive. Why should we do worse when the same loss comes more slowly?

Small Loss Regret Bounds

- Standard regret bounds show $\mathbb{E}[R_T] = O(\sqrt{T})$.
- However, if L^* is very small, not so impressive. Why should we do worse when the same loss comes more slowly?
- Slow accumulation of small losses? But we can always assume losses are binary, either 0 or 1.

Small Loss Regret Bounds

- Standard regret bounds show $\mathbb{E}[R_T] = O(\sqrt{T})$.
- However, if L^* is very small, not so impressive. Why should we do worse when the same loss comes more slowly?
- Slow accumulation of small losses? But we can always assume losses are binary, either 0 or 1.
- Hence, interest in showing more refined $O(\sqrt{L^*})$ regret bounds.

What Was Known?

- Optimal $O(\sqrt{T})$ regret bounds are well established. E.g. Multiplicative weights, online mirror descent.

What Was Known?

- Optimal $O(\sqrt{T})$ regret bounds are well established. E.g Multiplicative weights, online mirror descent.
- Multiplicative weights gives $O(\sqrt{L^*})$ small loss bound in the full feedback setting. In the bandit/semibandit cases, modify to never play bad actions ([Lykouris, Sridharan, and Tardos '18]).

What Was Known?

- Optimal $O(\sqrt{T})$ regret bounds are well established. E.g Multiplicative weights, online mirror descent.
- Multiplicative weights gives $O(\sqrt{L^*})$ small loss bound in the full feedback setting. In the bandit/semibandit cases, modify to never play bad actions ([Lykouris, Sridharan, and Tardos '18]).
- Russo and Van Roy show that Thompson Sampling achieves regret bounds of the form $O(\sqrt{T})$ in a variety of situations including those we consider here [Russo and Van Roy '16].

What Was Known?

	Full Feedback	Bandit	Semibandit
Regret	$\sqrt{T \log n}$	\sqrt{nT}	\sqrt{nmT}
Small Loss	$\sqrt{L^* \log n}$	$\sqrt{nL^* \log n}$	$\tilde{O}(\sqrt{L^*(m^3 + n) \log(T)})$
Thompson	$\sqrt{TH(\vec{p}_0)}$	$\tilde{O}(\sqrt{nT})$	$\tilde{O}(\sqrt{nmT})$ (*)

- Optimal $O(\sqrt{T})$ regret bounds are well established. E.g Multiplicative weights, online mirror descent.
- Multiplicative weights gives $O(\sqrt{L^*})$ small loss bound in the full feedback setting. In the bandit/semibandit cases, modify to never play bad actions ([Lykouris, Sridharan, and Tardos '18]).
- Russo and Van Roy show that Thompson Sampling achieves regret bounds of the form $O(\sqrt{T})$ in a variety of situations including those we consider here [Russo and Van Roy '16].

What Was Known?

	Full Feedback	Bandit	Semibandit
Regret	$\sqrt{T \log n}$	\sqrt{nT}	\sqrt{nmT}
Small Loss	$\sqrt{L^* \log n}$	$\sqrt{nL^* \log n}$	$\tilde{O}(\sqrt{L^*(m^3 + n) \log(T)})$
Thompson	$\sqrt{TH(\vec{p}_0)}$	$\tilde{O}(\sqrt{nT})$	$\tilde{O}(\sqrt{nmT})$ (*)

- Optimal $O(\sqrt{T})$ regret bounds are well established. E.g Multiplicative weights, online mirror descent.
- Multiplicative weights gives $O(\sqrt{L^*})$ small loss bound in the full feedback setting. In the bandit/semibandit cases, modify to never play bad actions ([Lykouris, Sridharan, and Tardos '18]).
- Russo and Van Roy show that Thompson Sampling achieves regret bounds of the form $O(\sqrt{T})$ in a variety of situations including those we consider here [Russo and Van Roy '16].
- (*) Thompson Sampling for semibandits was only analyzed when different coordinate losses are independent of each other.

What's New?

	Full Feedback	Bandit	Semibandit
Regret	$\sqrt{T \log n}$	\sqrt{nT}	\sqrt{nmT}
Small Loss	$\sqrt{L^* \log n}$	$\sqrt{nL^* \log n}$	$\tilde{O}(\sqrt{L^*(m^3 + n) \log(T)})$
Thompson	$\sqrt{TH(\vec{p}_0)}$	$\tilde{O}(\sqrt{nT})$	$\tilde{O}(\sqrt{nmT})$
Thompson	$\sqrt{L^*H(\vec{p}_0)}$	$\tilde{O}(\sqrt{nL^*})$	$\tilde{O}(\sqrt{nL^*})$

What's New?

	Full Feedback	Bandit	Semibandit
Regret	$\sqrt{T \log n}$	\sqrt{nT}	\sqrt{nmT}
Small Loss	$\sqrt{L^* \log n}$	$\sqrt{nL^* \log n}$	$\tilde{O}(\sqrt{L^*(m^3 + n) \log(T)})$
Thompson	$\sqrt{TH(\vec{p}_0)}$	$\tilde{O}(\sqrt{nT})$	$\tilde{O}(\sqrt{nmT})$
Thompson	$\sqrt{L^*H(\vec{p}_0)}$	$\tilde{O}(\sqrt{nL^*})$	$\tilde{O}(\sqrt{nL^*})$

- We prove analogous small loss regret bounds for Thompson Sampling. The first two cases match existing tight upper bounds while the semi-bandit upper bound is the best known.

What's New?

	Full Feedback	Bandit	Semibandit
Regret	$\sqrt{T \log n}$	\sqrt{nT}	\sqrt{nmT}
Small Loss	$\sqrt{L^* \log n}$	$\sqrt{nL^* \log n}$	$\tilde{O}(\sqrt{L^*(m^3 + n) \log(T)})$
Thompson	$\sqrt{TH(\vec{p}_0)}$	$\tilde{O}(\sqrt{nT})$	$\tilde{O}(\sqrt{nmT})$
Thompson	$\sqrt{L^*H(\vec{p}_0)}$	$\tilde{O}(\sqrt{nL^*})$	$\tilde{O}(\sqrt{nL^*})$

- We prove analogous small loss regret bounds for Thompson Sampling. The first two cases match existing tight upper bounds while the semi-bandit upper bound is the best known.
- We also address the semibandit case with arbitrary priors.

What's New?

	Full Feedback	Bandit	Semibandit
Regret	$\sqrt{T \log n}$	\sqrt{nT}	\sqrt{nmT}
Small Loss	$\sqrt{L^* \log n}$	$\sqrt{nL^* \log n}$	$\tilde{O}(\sqrt{L^*(m^3 + n) \log(T)})$
Thompson	$\sqrt{TH(\vec{p}_0)}$	$\tilde{O}(\sqrt{nT})$	$\tilde{O}(\sqrt{nmT})$
Thompson	$\sqrt{L^*H(\vec{p}_0)}$	$\tilde{O}(\sqrt{nL^*})$	$\tilde{O}(\sqrt{nL^*})$

- We prove analogous small loss regret bounds for Thompson Sampling. The first two cases match existing tight upper bounds while the semi-bandit upper bound is the best known.
- We also address the semibandit case with arbitrary priors.
- To achieve full T -independence in the bandit/semibandit settings, we have to modify Thompson Sampling by never playing low probability actions. Otherwise upper bounds have $\log(T)$ terms.

Information Theoretic Analysis for Full Feedback

- Denote the regret incurred in timestep t by

$$r_t = \ell_t(i_t) - \ell_t(i^*).$$

Information Theoretic Analysis for Full Feedback

- Denote the regret incurred in timestep t by

$$r_t = \ell_t(i_t) - \ell_t(i^*).$$

- By linearity, $\mathbb{E}[\sum_{t \leq T} r_t] = \mathbb{E}[R_T]$ is the expected total regret.

Information Theoretic Analysis for Full Feedback

- Denote the regret incurred in timestep t by

$$r_t = \ell_t(i_t) - \ell_t(i^*).$$

- By linearity, $\mathbb{E}[\sum_{t \leq T} r_t] = \mathbb{E}[R_T]$ is the expected total regret.
- Claim: $\mathbb{E}^{p_t}[r_t]$ is given by

$$\mathbb{E}^{p_t}[r_t] = \mathbb{E}^{p_t} \left[\sum_i \ell_t(i) \cdot (p_t(i) - p_{t+1}(i)) \right].$$

Information Theoretic Analysis for Full Feedback

- Denote the regret incurred in timestep t by

$$r_t = \ell_t(i_t) - \ell_t(i^*).$$

- By linearity, $\mathbb{E}[\sum_{t \leq T} r_t] = \mathbb{E}[R_T]$ is the expected total regret.
- Claim: $\mathbb{E}^{p_t}[r_t]$ is given by

$$\mathbb{E}^{p_t}[r_t] = \mathbb{E}^{p_t} \left[\sum_i \ell_t(i) \cdot (p_t(i) - p_{t+1}(i)) \right].$$

- Proof: the expected loss from round t is $\sum_i p_t(i) \mathbb{E}[\ell_t(i)]$ while the in-hindsight expected loss of the best action from that round is $\mathbb{E}^{p_t}[\sum_i p_{t+1}(i) \ell_t(i)]$.

Information Theoretic Analysis for Full Feedback

- Denote the regret incurred in timestep t by

$$r_t = \ell_t(i_t) - \ell_t(i^*).$$

- By linearity, $\mathbb{E}[\sum_{t \leq T} r_t] = \mathbb{E}[R_T]$ is the expected total regret.
- Claim: $\mathbb{E}^{p_t}[r_t]$ is given by

$$\mathbb{E}^{p_t}[r_t] = \mathbb{E}^{p_t} \left[\sum_i \ell_t(i) \cdot (p_t(i) - p_{t+1}(i)) \right].$$

- Proof: the expected loss from round t is $\sum_i p_t(i) \mathbb{E}[\ell_t(i)]$ while the in-hindsight expected loss of the best action from that round is $\mathbb{E}^{p_t}[\sum_i p_{t+1}(i) \ell_t(i)]$.
- As $\ell_t(i) \in [0, 1]$, we obtain

$$\mathbb{E}[r_t] \leq \frac{1}{2} \mathbb{E}[\|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1}].$$

Information Theoretic Analysis for Full Feedback

- Denote the regret incurred in timestep t by

$$r_t = \ell_t(i_t) - \ell_t(i^*).$$

- By linearity, $\mathbb{E}[\sum_{t \leq T} r_t] = \mathbb{E}[R_T]$ is the expected total regret.
- Claim: $\mathbb{E}^{p_t}[r_t]$ is given by

$$\mathbb{E}^{p_t}[r_t] = \mathbb{E}^{p_t} \left[\sum_i \ell_t(i) \cdot (p_t(i) - p_{t+1}(i)) \right].$$

- Proof: the expected loss from round t is $\sum_i p_t(i) \mathbb{E}[\ell_t(i)]$ while the in-hindsight expected loss of the best action from that round is $\mathbb{E}^{p_t}[\sum_i p_{t+1}(i) \ell_t(i)]$.
- As $\ell_t(i) \in [0, 1]$, we obtain

$$\mathbb{E}[r_t] \leq \frac{1}{2} \mathbb{E}[\|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1}].$$

- New goal: estimate ℓ^1 movement of \vec{p}_t .

Information Theoretic Analysis for Full-Feedback

- Now the information theory appears. Review:

Information Theoretic Analysis for Full-Feedback

- Now the information theory appears. Review:
- Entropy is $H(\vec{p}) = -\sum_i p(i) \log p(i)$.

Information Theoretic Analysis for Full-Feedback

- Now the information theory appears. Review:
- Entropy is $H(\vec{p}) = -\sum_i p(i) \log p(i)$.
- The KL divergence or *relative entropy* between distributions \vec{q}, \vec{p} is $Ent[\vec{q}; \vec{p}] = \sum_i q(i) \log \left(\frac{q(i)}{p(i)} \right)$.

Information Theoretic Analysis for Full-Feedback

- Now the information theory appears. Review:
- Entropy is $H(\vec{p}) = -\sum_i p(i) \log p(i)$.
- The KL divergence or *relative entropy* between distributions \vec{q}, \vec{p} is $Ent[\vec{q}; \vec{p}] = \sum_i q(i) \log \left(\frac{q(i)}{p(i)} \right)$.
- Since $\mathbb{E}^{p_t}[\vec{p}_{t+1}] = \vec{p}_t$, we have

$$\mathbb{E}^{p_t}[H(\vec{p}_t) - H(\vec{p}_{t+1})] = \mathbb{E}^{p_t}[Ent[\vec{p}_{t+1}; \vec{p}_t]].$$

Information Theoretic Analysis for Full-Feedback

- Now the information theory appears. Review:
- Entropy is $H(\vec{p}) = -\sum_i p(i) \log p(i)$.
- The KL divergence or *relative entropy* between distributions \vec{q}, \vec{p} is $Ent[\vec{q}; \vec{p}] = \sum_i q(i) \log \left(\frac{q(i)}{p(i)} \right)$.
- Since $\mathbb{E}^{p_t}[\vec{p}_{t+1}] = \vec{p}_t$, we have

$$\mathbb{E}^{p_t}[H(\vec{p}_t) - H(\vec{p}_{t+1})] = \mathbb{E}^{p_t}[Ent[\vec{p}_{t+1}; \vec{p}_t]].$$

- Expected information on i^* is also the mutual information

$$I_t := I_t[i^*, (i_t, \ell_t(i_t))] = \mathbb{E}^{p_t}[H(\vec{p}_{t+1}) - H(\vec{p}_t)] = \mathbb{E}^{p_t}[Ent[\vec{p}_{t+1}; \vec{p}_t]].$$

Information Theoretic Analysis for Full-Feedback

- Now the information theory appears. Review:
- Entropy is $H(\vec{p}) = -\sum_i p(i) \log p(i)$.
- The KL divergence or *relative entropy* between distributions \vec{q}, \vec{p} is $Ent[\vec{q}; \vec{p}] = \sum_i q(i) \log \left(\frac{q(i)}{p(i)} \right)$.
- Since $\mathbb{E}^{p_t}[\vec{p}_{t+1}] = \vec{p}_t$, we have

$$\mathbb{E}^{p_t}[H(\vec{p}_t) - H(\vec{p}_{t+1})] = \mathbb{E}^{p_t}[Ent[\vec{p}_{t+1}; \vec{p}_t]].$$

- Expected information on i^* is also the mutual information

$$I_t := I_t[i^*, (i_t, \ell_t(i_t))] = \mathbb{E}^{p_t}[H(\vec{p}_{t+1}) - H(\vec{p}_t)] = \mathbb{E}^{p_t}[Ent[\vec{p}_{t+1}; \vec{p}_t]].$$

- Pinsker's Inequality controls the movement:

$$\|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1}^2 \leq 2 \cdot Ent[\vec{p}_{t+1}; \vec{p}_t]$$

Information Theoretic Analysis for Full-Feedback

- Goal: estimate

$$\mathbb{E} \left[\sum_{t=0}^{T-1} \|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1} \right].$$

We will just use that $(\vec{p}_t)_{t \geq 0}$ is a martingale in the simplex.

Information Theoretic Analysis for Full-Feedback

- Goal: estimate

$$\mathbb{E} \left[\sum_{t=0}^{T-1} \|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1} \right].$$

We will just use that $(\vec{p}_t)_{t \geq 0}$ is a martingale in the simplex.

- Cauchy-Schwarz:

$$\mathbb{E} \left[\sum_{t=0}^{T-1} \|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1} \right] \leq \sqrt{T \cdot \mathbb{E} \left[\sum_{t=0}^{T-1} \|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1}^2 \right]}$$

Information Theoretic Analysis for Full-Feedback

- Goal: estimate

$$\mathbb{E} \left[\sum_{t=0}^{T-1} \|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1} \right].$$

We will just use that $(\vec{p}_t)_{t \geq 0}$ is a martingale in the simplex.

- Cauchy-Schwarz:

$$\mathbb{E} \left[\sum_{t=0}^{T-1} \|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1} \right] \leq \sqrt{T \cdot \mathbb{E} \left[\sum_{t=0}^{T-1} \|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1}^2 \right]}$$

- Pinsker:

$$\mathbb{E} \left[\sum_{t=0}^{T-1} \|\vec{p}_t - \vec{p}_{t+1}\|_{\ell^1}^2 \right] \leq 2 \cdot \mathbb{E} \left[\sum_{t \geq 0} \text{Ent}[\vec{p}_{t+1}; \vec{p}_t] \right] \leq 2H(\vec{p}_0) \leq 2 \log(n).$$

Theorem [Russo and Van Roy '16]

Thompson Sampling gives expected regret

$$\mathbb{E}[R_T] \leq \sqrt{\frac{T \cdot H(\vec{p}_0)}{2}} \leq \sqrt{\frac{T \log(n)}{2}}.$$

Information Theoretic Analysis for Full-Feedback

Theorem [Russo and Van Roy '16]

Thompson Sampling gives expected regret

$$\mathbb{E}[R_T] \leq \sqrt{\frac{T \cdot H(\vec{p}_0)}{2}} \leq \sqrt{\frac{T \log(n)}{2}}.$$

- Another way to understand this:

Information Ratio

For time-step t , define the *information ratio* between squared regret and information obtained to be

$$\Gamma_t := \frac{\mathbb{E}^{p_t}[r_t]^2}{I_t(i^*, (i_t, \ell_t(i_t)))}.$$

Here the mutual information I_t is the average amount of new information we obtain about the best coordinate i^* on round t .

Information Ratio

For time-step t , define the *information ratio* between squared regret and information obtained to be

$$\Gamma_t := \frac{\mathbb{E}^{p_t}[r_t]^2}{I_t(i^*, (i_t, \ell_t(i_t)))}.$$

Here the mutual information I_t is the average amount of new information we obtain about the best coordinate i^* on round t .

Information Ratio

For time-step t , define the *information ratio* between squared regret and information obtained to be

$$\Gamma_t := \frac{\mathbb{E}^{p_t}[r_t]^2}{I_t(i^*, (i_t, \ell_t(i_t)))}.$$

Here the mutual information I_t is the average amount of new information we obtain about the best coordinate i^* on round t .

- The goal is to upper-bound Γ_t ; then regret implies learning.
- Pinsker tells us that $\Gamma_t \leq \frac{1}{2}$ for Thompson Sampling.

Information Ratio

For time-step t , define the *information ratio* between squared regret and information obtained to be

$$\Gamma_t := \frac{\mathbb{E}^{p_t}[r_t]^2}{I_t(i^*, (i_t, \ell_t(i_t)))}.$$

Here the mutual information I_t is the average amount of new information we obtain about the best coordinate i^* on round t .

- The goal is to upper-bound Γ_t ; then regret implies learning.
- Pinsker tells us that $\Gamma_t \leq \frac{1}{2}$ for Thompson Sampling.
- In general, if $\mathbb{E}[\Gamma_t] \leq a_t$, we obtain:

$$\mathbb{E}[R_T]^2 = \left(\mathbb{E} \left[\sum_t \mathbb{E}^{p_t}[r_t] \right] \right)^2 \leq \mathbb{E} \left[\sum_t I_t \right] \mathbb{E} \left[\sum_t \Gamma_t \right] \leq H(\vec{p}_0) \sum_t a_t$$

Obtaining a Small Loss Bound

Theorem

Thompson Sampling satisfies

$$\mathbb{E}[R_T] = O(\sqrt{\mathbb{E}[L^*]H(\vec{p}_0)}).$$

- To prove this, we could try to prove $\Gamma_t = O(\bar{\ell}_t)$ where $\bar{\ell}_t = \mathbb{E}^{p_t}[\ell_t(i_t)] = \sum_i p_t(i)\bar{\ell}_t(i)$. Then $\mathbb{E}[\Gamma_t] = O(\mathbb{E}^{p_0}[\ell_t])$ and we'd obtain:

$$\mathbb{E}[L_T - L^*] = \mathbb{E}[R_T] \leq O\left(\sqrt{H(\vec{p}_0) \sum_t \mathbb{E}^{p_0}[\ell_t]}\right) = O\left(\sqrt{H(\vec{p}_0)\mathbb{E}[L_T]}\right).$$

- Simple algebra would now yield the result.

Obtaining a Small-Loss Bound

- We try to prove $\Gamma_t = O(\bar{\ell}_t)$:

Obtaining a Small-Loss Bound

- We try to prove $\Gamma_t = O(\bar{\ell}_t)$:

$$\mathbb{E}^{p_t}[r_t]^2 = \left(\sum_i \mathbb{E}^{p_t} [\ell_t(i) \cdot (p_t(i) - p_{t+1}(i))] \right)^2$$

Obtaining a Small-Loss Bound

- We try to prove $\Gamma_t = O(\bar{\ell}_t)$:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t]^2 &= \left(\sum_i \mathbb{E}^{p_t} [\ell_t(i) \cdot (p_t(i) - p_{t+1}(i))] \right)^2 \\ &\leq \left(\mathbb{E}^{p_t} \left[\sum_i \ell_t(i) \cdot p_t(i) \right] \right) \left(\mathbb{E}^{p_t} \left[\sum_i \frac{(p_t(i) - p_{t+1}(i))^2}{p_t(i)} \right] \right)\end{aligned}$$

Obtaining a Small-Loss Bound

- We try to prove $\Gamma_t = O(\bar{\ell}_t)$:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t]^2 &= \left(\sum_i \mathbb{E}^{p_t} [\ell_t(i) \cdot (p_t(i) - p_{t+1}(i))] \right)^2 \\ &\leq \left(\mathbb{E}^{p_t} \left[\sum_i \ell_t(i) \cdot p_t(i) \right] \right) \left(\mathbb{E}^{p_t} \left[\sum_i \frac{(p_t(i) - p_{t+1}(i))^2}{p_t(i)} \right] \right) \\ &= 2\bar{\ell}_t \cdot \mathbb{E}^{p_t}[\chi^2[\vec{p}_{t+1}; \vec{p}_t]].\end{aligned}$$

Obtaining a Small-Loss Bound

- We try to prove $\Gamma_t = O(\bar{\ell}_t)$:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t]^2 &= \left(\sum_i \mathbb{E}^{p_t} [\ell_t(i) \cdot (p_t(i) - p_{t+1}(i))] \right)^2 \\ &\leq \left(\mathbb{E}^{p_t} \left[\sum_i \ell_t(i) \cdot p_t(i) \right] \right) \left(\mathbb{E}^{p_t} \left[\sum_i \frac{(p_t(i) - p_{t+1}(i))^2}{p_t(i)} \right] \right) \\ &= 2\bar{\ell}_t \cdot \mathbb{E}^{p_t}[\chi^2[\vec{p}_{t+1}; \vec{p}_t]].\end{aligned}$$

- Does $\chi^2[p_{t+1}; p_t] \leq \text{Ent}[p_{t+1}; p_t]$ hold? Then we'd be done.

Obtaining a Small-Loss Bound

- We try to prove $\Gamma_t = O(\bar{\ell}_t)$:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t]^2 &= \left(\sum_i \mathbb{E}^{p_t} [\ell_t(i) \cdot (p_t(i) - p_{t+1}(i))] \right)^2 \\ &\leq \left(\mathbb{E}^{p_t} \left[\sum_i \ell_t(i) \cdot p_t(i) \right] \right) \left(\mathbb{E}^{p_t} \left[\sum_i \frac{(p_t(i) - p_{t+1}(i))^2}{p_t(i)} \right] \right) \\ &= 2\bar{\ell}_t \cdot \mathbb{E}^{p_t}[\chi^2[\vec{p}_{t+1}; \vec{p}_t]].\end{aligned}$$

- Does $\chi^2[p_{t+1}; p_t] \leq \text{Ent}[p_{t+1}; p_t]$ hold? Then we'd be done.
- No! In fact $\chi^2[p_{t+1}; p_t] \geq 2\text{Ent}[p_{t+1}; p_t]$ always holds.

Obtaining a Small-Loss Bound

Lemma

For any probability distributions p_{t+1}, p_t we have

$$\sum_{i: p_t(i) \geq p_{t+1}(i)} \frac{(p_t(i) - p_{t+1}(i))^2}{2p_t(i)} \leq \text{Ent}[p_{t+1}; p_t].$$

Obtaining a Small-Loss Bound

Lemma

For any probability distributions p_{t+1}, p_t we have

$$\sum_{i: p_t(i) \geq p_{t+1}(i)} \frac{(p_t(i) - p_{t+1}(i))^2}{2p_t(i)} \leq \text{Ent}[p_{t+1}; p_t].$$

- Proof: second order Taylor expansion in \vec{q} for KL divergence

$$\text{Ent}[\vec{q}; \vec{p}] = \sum_i q(i) \log \left(\frac{q(i)}{p(i)} \right).$$

Obtaining a Small-Loss Bound

Lemma

For any probability distributions p_{t+1}, p_t we have

$$\sum_{i: p_t(i) \geq p_{t+1}(i)} \frac{(p_t(i) - p_{t+1}(i))^2}{2p_t(i)} \leq \text{Ent}[p_{t+1}; p_t].$$

- Proof: second order Taylor expansion in \vec{q} for KL divergence


$$\text{Ent}[\vec{q}; \vec{p}] = \sum_i q(i) \log \left(\frac{q(i)}{p(i)} \right).$$

- The first-order terms cancel because p_t, p_{t+1} are both probability distributions. The second-order derivatives are given by

$$\partial_{q(i)}^2 \left[q(i) \log \left(\frac{q(i)}{p(i)} \right) \right] = \frac{1}{q(i)}.$$

Obtaining a Small-Loss Bound

- Since the 2nd derivative is decreasing and positive, lower bound $x \log \left(\frac{x}{p(i)} \right)$ quadratically for $x < p(i)$ and linearly for $x > p(i)$.



Obtaining a Small-Loss Bound

- Terms with $p_{t+1}(i) \geq p_t(i)$ only reduce the regret, so we ignore them.

Obtaining a Small-Loss Bound

- Terms with $p_{t+1}(i) \geq p_t(i)$ only reduce the regret, so we ignore them.
- Putting it together:

$$\mathbb{E}^{p_t}[r_t] = \left(\mathbb{E}^{p_t} \sum_i \bar{\ell}_t(i) (p_t(i) - p_{t+1}(i)) \right)$$

Obtaining a Small-Loss Bound

- Terms with $p_{t+1}(i) \geq p_t(i)$ only reduce the regret, so we ignore them.
- Putting it together:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t] &= \left(\mathbb{E}^{p_t} \sum_i \bar{\ell}_t(i)(p_t(i) - p_{t+1}(i)) \right) \\ &\leq \left(\mathbb{E}^{p_t} \sum_{i: p_t(i) \geq p_{t+1}(i)} \ell_t(i)(p_t(i) - p_{t+1}(i)) \right)\end{aligned}$$

Obtaining a Small-Loss Bound

- Terms with $p_{t+1}(i) \geq p_t(i)$ only reduce the regret, so we ignore them.
- Putting it together:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t] &= \left(\mathbb{E}^{p_t} \sum_i \bar{\ell}_t(i)(p_t(i) - p_{t+1}(i)) \right) \\ &\leq \left(\mathbb{E}^{p_t} \sum_{i: p_t(i) \geq p_{t+1}(i)} \ell_t(i)(p_t(i) - p_{t+1}(i)) \right) \\ &\leq \left(\mathbb{E}^{p_t} \sum_i p_t(i) \ell_t(i)^2 \right)^{1/2} \left(\mathbb{E}^{p_t} \sum_{i: p_t(i) \geq p_{t+1}(i)} \frac{(p_t(i) - p_{t+1}(i))^2}{p_t(i)} \right)^{1/2}\end{aligned}$$

Obtaining a Small-Loss Bound

- Terms with $p_{t+1}(i) \geq p_t(i)$ only reduce the regret, so we ignore them.
- Putting it together:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t] &= \left(\mathbb{E}^{p_t} \sum_i \bar{\ell}_t(i)(p_t(i) - p_{t+1}(i)) \right) \\ &\leq \left(\mathbb{E}^{p_t} \sum_{i: p_t(i) \geq p_{t+1}(i)} \ell_t(i)(p_t(i) - p_{t+1}(i)) \right) \\ &\leq \left(\mathbb{E}^{p_t} \sum_i p_t(i) \ell_t(i)^2 \right)^{1/2} \left(\mathbb{E}^{p_t} \sum_{i: p_t(i) \geq p_{t+1}(i)} \frac{(p_t(i) - p_{t+1}(i))^2}{p_t(i)} \right)^{1/2} \\ &\leq \sqrt{\bar{\ell}_t \cdot \mathbb{E}[Ent[\vec{p}_{t+1}; \vec{p}_t]]} \leq \sqrt{\bar{\ell}_t \cdot I_t}.\end{aligned}$$

Obtaining a Small-Loss Bound

Theorem

Thompson Sampling satisfies

$$\frac{\mathbb{E}[(r_t)_+]^2}{I_t(i^*)} \leq \bar{\ell}_t.$$

Obtaining a Small-Loss Bound

Theorem

Thompson Sampling satisfies

$$\frac{\mathbb{E}[(r_t)_+]^2}{I_t(i^*)} \leq \bar{\ell}_t.$$

Theorem

Thompson Sampling satisfies

$$\mathbb{E}[R_T] = O(\sqrt{\mathbb{E}[L^*]H(\vec{p}_0)}).$$

Obtaining a Small-Loss Bound

Theorem

Thompson Sampling satisfies

$$\frac{\mathbb{E}[(r_t)_+]^2}{l_t(i^*)} \leq \bar{\ell}_t.$$

Theorem

Thompson Sampling satisfies

$$\mathbb{E}[R_T] = O(\sqrt{\mathbb{E}[L^*]H(\vec{p}_0)}).$$

Remark

We can also show that $\Gamma_t = O(\bar{\ell}_t + \bar{\ell}_t^)$ by using a cruder entropy inequality.*

The Bandit Case

- In the bandit case, the expected regret for time t is

$$\mathbb{E}[r_t] = \sum_i p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i))$$

where $\bar{\ell}_t(i, i) = \mathbb{E}[\ell_t(i) | i^* = i]$.

The Bandit Case

- In the bandit case, the expected regret for time t is

$$\mathbb{E}[r_t] = \sum_i p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i))$$

where $\bar{\ell}_t(i, i) = \mathbb{E}[\ell_t(i) | i^* = i]$.

- The information gain $I_t(i^*)$ is lower-bounded by

$$I_t(i^*) \geq \sum_i p_t(i)^2 \text{Ent}[(\ell_t(i) | i^* = i); \ell_t(i)].$$

This is the information gain when $i^* = i_t = i$.

The Bandit Case

- In the bandit case, the expected regret for time t is

$$\mathbb{E}[r_t] = \sum_i p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i))$$

where $\bar{\ell}_t(i, i) = \mathbb{E}[\ell_t(i) | i^* = i]$.

- The information gain $I_t(i^*)$ is lower-bounded by

$$I_t(i^*) \geq \sum_i p_t(i)^2 \text{Ent}[(\ell_t(i) | i^* = i); \ell_t(i)].$$

This is the information gain when $i^* = i_t = i$.

- A similar Pinsker's inequality argument shows that the expected regret is $O(\sqrt{nT \cdot H(\vec{p}_0)})$. Optimal is $O(\sqrt{nT})$ and most methods (e.g. multiplicative weights) give $O(\sqrt{nT \log(n)})$.

The Bandit Case

- Ordinary regret estimate:

$$\mathbb{E}^{p_t}[r_t]^2 = \left(\mathbb{E}^{p_t} \left[\sum_i p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i)) \right] \right)^2$$

The Bandit Case

- Ordinary regret estimate:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t]^2 &= \left(\mathbb{E}^{p_t} \left[\sum_i p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i)) \right] \right)^2 \\ &\leq \left(\mathbb{E}^{p_t} \sum_i 1 \right) \left(\mathbb{E}^{p_t} \sum_i p_t(i)^2 \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i))^2 \right)\end{aligned}$$

The Bandit Case

- Ordinary regret estimate:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t]^2 &= \left(\mathbb{E}^{p_t} \left[\sum_i p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i)) \right] \right)^2 \\ &\leq \left(\mathbb{E}^{p_t} \sum_i 1 \right) \left(\mathbb{E}^{p_t} \sum_i p_t(i)^2 \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i))^2 \right) \\ &\leq n \cdot \mathbb{E}^{p_t} \left[\sum_i p_t(i)^2 \text{Ent}[\ell_t(i, i); \ell(i)] \right] \leq n l_t(i^*).\end{aligned}$$

The Bandit Case

- Ordinary regret estimate:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t]^2 &= \left(\mathbb{E}^{p_t} \left[\sum_i p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i)) \right] \right)^2 \\ &\leq \left(\mathbb{E}^{p_t} \sum_i 1 \right) \left(\mathbb{E}^{p_t} \sum_i p_t(i)^2 \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i))^2 \right) \\ &\leq n \cdot \mathbb{E}^{p_t} \left[\sum_i p_t(i)^2 \text{Ent}[\ell_t(i, i); \ell(i)] \right] \leq n l_t(i^*).\end{aligned}$$

- Hence $\Gamma_t \leq n$.

The Bandit Case

- Ordinary regret estimate:

$$\begin{aligned}\mathbb{E}^{p_t}[r_t]^2 &= \left(\mathbb{E}^{p_t} \left[\sum_i p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i)) \right] \right)^2 \\ &\leq \left(\mathbb{E}^{p_t} \sum_i 1 \right) \left(\mathbb{E}^{p_t} \sum_i p_t(i)^2 \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i, i))^2 \right) \\ &\leq n \cdot \mathbb{E}^{p_t} \left[\sum_i p_t(i)^2 \text{Ent}[\ell_t(i, i); \ell(i)] \right] \leq n l_t(i^*).\end{aligned}$$

- Hence $\Gamma_t \leq n$.

Theorem [Russo and Van Roy '16]

Thompson Sampling for bandits satisfies $\mathbb{E}[R_T] = O(\sqrt{nT \cdot H(\vec{p}_0)})$.

The Bandit Case

- For small-loss bound, we assume L^* is given (or bounded) and aim for $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nL^*})$. A first attempt:

The Bandit Case

- For small-loss bound, we assume L^* is given (or bounded) and aim for $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nL^*})$. A first attempt:

$$\mathbb{E}[R_T]^2 = \left(\mathbb{E} \left[\sum_{i,t} p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i,i)) \right] \right)^2$$

The Bandit Case

- For small-loss bound, we assume L^* is given (or bounded) and aim for $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nL^*})$. A first attempt:

$$\begin{aligned}\mathbb{E}[R_T]^2 &= \left(\mathbb{E} \left[\sum_{i,t} p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i,i)) \right] \right)^2 \\ &\leq \left(\mathbb{E} \sum_{i,t} \ell_t(i) \right) \left(\mathbb{E} \sum_{i,t} p_t(i)^2 \cdot \frac{(\bar{\ell}_t(i) - \bar{\ell}_t(i,i))^2}{\ell_t(i)} \right)\end{aligned}$$

The Bandit Case

- For small-loss bound, we assume L^* is given (or bounded) and aim for $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nL^*})$. A first attempt:

$$\begin{aligned}\mathbb{E}[R_T]^2 &= \left(\mathbb{E} \left[\sum_{i,t} p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i,i)) \right] \right)^2 \\ &\leq \left(\mathbb{E} \sum_{i,t} \ell_t(i) \right) \left(\mathbb{E} \sum_{i,t} p_t(i)^2 \cdot \frac{(\bar{\ell}_t(i) - \bar{\ell}_t(i,i))^2}{\ell_t(i)} \right) \\ &\leq \left(\mathbb{E} \sum_{i,t} \bar{\ell}_t(i) \right) H(\vec{p}_0).\end{aligned}$$

The Bandit Case

- For small-loss bound, we assume L^* is given (or bounded) and aim for $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nL^*})$. A first attempt:

$$\begin{aligned}\mathbb{E}[R_T]^2 &= \left(\mathbb{E} \left[\sum_{i,t} p_t(i) \cdot (\bar{\ell}_t(i) - \bar{\ell}_t(i,i)) \right] \right)^2 \\ &\leq \left(\mathbb{E} \sum_{i,t} \ell_t(i) \right) \left(\mathbb{E} \sum_{i,t} p_t(i)^2 \cdot \frac{(\bar{\ell}_t(i) - \bar{\ell}_t(i,i))^2}{\ell_t(i)} \right) \\ &\leq \left(\mathbb{E} \sum_{i,t} \bar{\ell}_t(i) \right) H(\vec{p}_0).\end{aligned}$$

- If the player could track this sum, then $p_t(i) = 0$ once $\sum_{s \leq t} \ell_s(i) \geq L^*$. After that, ignore coordinate i . This would result in $\mathbb{E}[R_T] \leq \sqrt{nL^* \cdot H(\vec{p}_0)}$.

The Bandit Case

- Actually Thompson Sampling does NOT give T -independent small-loss regret for bandits.

The Bandit Case

- Actually Thompson Sampling does NOT give T -independent small-loss regret for bandits.
- If T is VERY large (think $\text{Tower}(L^*)$), turns out you can force Thompson Sampling to keep playing every action until it is 100% sure that this action had loss at least L^* .

The Bandit Case

- Actually Thompson Sampling does NOT give T -independent small-loss regret for bandits.
- If T is VERY large (think $\text{Tower}(L^*)$), turns out you can force Thompson Sampling to keep playing every action until it is 100% sure that this action had loss at least L^* .
- Hence you will eventually pay nL^* total cost. Not good!

The Bandit Case

- Actually Thompson Sampling does NOT give T -independent small-loss regret for bandits.
- If T is VERY large (think $\text{Tower}(L^*)$), turns out you can force Thompson Sampling to keep playing every action until it is 100% sure that this action had loss at least L^* .
- Hence you will eventually pay nL^* total cost. Not good!

Thresholded Thompson Sampling

In Thresholded Thompson Sampling, we pick small $\gamma > 0$ and play from p_t but restrict to actions i with probability $p_t(i) \geq \gamma$ to be optimal.

The Bandit Case

- Actually Thompson Sampling does NOT give T -independent small-loss regret for bandits.
- If T is VERY large (think $\text{Tower}(L^*)$), turns out you can force Thompson Sampling to keep playing every action until it is 100% sure that this action had loss at least L^* .
- Hence you will eventually pay nL^* total cost. Not good!

Thresholded Thompson Sampling

In Thresholded Thompson Sampling, we pick small $\gamma > 0$ and play from p_t but restrict to actions i with probability $p_t(i) \geq \gamma$ to be optimal.

- Thresholded Thompson Sampling avoids the bad case above. It also parallels the thresholded EXP3 algorithm which circumvents the same issue for multiplicative weights.

The Bandit Case

- Threshold with $\gamma = \frac{1}{L^*}$.

The Bandit Case

- Threshold with $\gamma = \frac{1}{L^*}$.
- Redo the algebra, but no real change. Main thing is to estimate:

$$\mathbb{E} \left[\sum_{i, t: p_t(i) \geq \gamma} \ell_t(i) \right].$$

The Bandit Case

- Threshold with $\gamma = \frac{1}{L^*}$.
- Redo the algebra, but no real change. Main thing is to estimate:

$$\mathbb{E} \left[\sum_{i, t: p_t(i) \geq \gamma} \ell_t(i) \right].$$

- Claim: for each i , we have $\mathbb{E} \left[\sum_{t: p_t(i) \geq \gamma} \ell_t(i) \right] \leq L^* + \tilde{O}(\sqrt{L^*/\gamma})$.

The Bandit Case

- Threshold with $\gamma = \frac{1}{L^*}$.
- Redo the algebra, but no real change. Main thing is to estimate:

$$\mathbb{E} \left[\sum_{i, t: p_t(i) \geq \gamma} \ell_t(i) \right].$$

- Claim: for each i , we have $\mathbb{E} \left[\sum_{t: p_t(i) \geq \gamma} \ell_t(i) \right] \leq L^* + \tilde{O}(\sqrt{L^*/\gamma})$.
- From observing $\ell_t(i_t)$, we can compute an unbiased estimator for this sum via importance sampling; when you play an i_t which had probability $p_t(i_t)$ you should count the loss as $\tilde{\ell}_t(i_t) = \frac{\ell_t(i_t)}{p_t(i_t)}$.

The Bandit Case

- Threshold with $\gamma = \frac{1}{L^*}$.
- Redo the algebra, but no real change. Main thing is to estimate:

$$\mathbb{E} \left[\sum_{i, t: p_t(i) \geq \gamma} \ell_t(i) \right].$$

- Claim: for each i , we have $\mathbb{E} \left[\sum_{t: p_t(i) \geq \gamma} \ell_t(i) \right] \leq L^* + \tilde{O}(\sqrt{L^*/\gamma})$.
- From observing $\ell_t(i_t)$, we can compute an unbiased estimator for this sum via importance sampling; when you play an i_t which had probability $p_t(i_t)$ you should count the loss as $\tilde{\ell}_t(i_t) = \frac{\ell_t(i_t)}{p_t(i_t)}$.
- Since $p_t(i) \geq \gamma$ the unbiased estimator is a sum of bounded random variables in $[0, \frac{1}{\gamma}]$, so it is concentrated near the true value.

The Bandit Case

- Threshold with $\gamma = \frac{1}{L^*}$.
- Redo the algebra, but no real change. Main thing is to estimate:

$$\mathbb{E} \left[\sum_{i: p_t(i) \geq \gamma} \ell_t(i) \right].$$

- Claim: for each i , we have $\mathbb{E} \left[\sum_{t: p_t(i) \geq \gamma} \ell_t(i) \right] \leq L^* + \tilde{O}(\sqrt{L^*/\gamma})$.
- From observing $\ell_t(i_t)$, we can compute an unbiased estimator for this sum via importance sampling; when you play an i_t which had probability $p_t(i_t)$ you should count the loss as $\tilde{\ell}_t(i_t) = \frac{\ell_t(i_t)}{p_t(i_t)}$.
- Since $p_t(i) \geq \gamma$ the unbiased estimator is a sum of bounded random variables in $[0, \frac{1}{\gamma}]$, so it is concentrated near the true value.
- Hence for each i , the player has a good estimate for $\sum_{s \leq t: p_s(i) \geq \gamma} \ell_s(i)$. When this sum gets significantly above L^* , $p_t(i)$ will usually be very small.

The Bandit Case

Theorem

Thresholded Thompson Sampling achieves T -independent regret

$$\tilde{O}(\sqrt{nL^*} + n).$$

The Bandit Case

Theorem

Thresholded Thompson Sampling achieves T -independent regret

$$\tilde{O}(\sqrt{nL^*} + n).$$

We can also analyze ordinary Thompson Sampling the same way. Separately estimate the expected loss $p_t(i)\ell_t(i)$ for $p_t(i) < \gamma$. When the observed loss exceeds $\tilde{O}(\log T)$, we expect $p_t(i) \leq \frac{1}{T}$. So the total small-probability contribution should be $\tilde{O}(\log T)$ per action.

The Bandit Case

Theorem

Thresholded Thompson Sampling achieves T -independent regret

$$\tilde{O}(\sqrt{nL^*} + n).$$

We can also analyze ordinary Thompson Sampling the same way. Separately estimate the expected loss $p_t(i)\ell_t(i)$ for $p_t(i) < \gamma$. When the observed loss exceeds $\tilde{O}(\log T)$, we expect $p_t(i) \leq \frac{1}{T}$. So the total small-probability contribution should be $\tilde{O}(\log T)$ per action.

Theorem

Ordinary Thompson Sampling achieves regret

$$\tilde{O}(\sqrt{nL^*} + n \log(T)).$$

The Semibandit Case

- Now we play a subset $A = (i_1, \dots, i_m)$ of size m from a given collection $\mathcal{A} \subseteq \binom{[n]}{m}$. We observe and pay all m losses $\ell_t(i_k)$ each turn.

The Semibandit Case

- Now we play a subset $A = (i_1, \dots, i_m)$ of size m from a given collection $\mathcal{A} \subseteq \binom{[n]}{m}$. We observe and pay all m losses $\ell_t(i_k)$ each turn.
- Example: \mathcal{A} consists of shortest paths in a graph from $u \rightarrow v$, the player chooses such a path, each round there is a loss from each edge.

The Semibandit Case

- Now we play a subset $A = (i_1, \dots, i_m)$ of size m from a given collection $\mathcal{A} \subseteq \binom{[n]}{m}$. We observe and pay all m losses $\ell_t(i_k)$ each turn.
- Example: \mathcal{A} consists of shortest paths in a graph from $u \rightarrow v$, the player chooses such a path, each round there is a loss from each edge.
- Again need to fix L^* .

The Semibandit Case

- Now we play a subset $A = (i_1, \dots, i_m)$ of size m from a given collection $\mathcal{A} \subseteq \binom{[n]}{m}$. We observe and pay all m losses $\ell_t(i_k)$ each turn.
- Example: \mathcal{A} consists of shortest paths in a graph from $u \rightarrow v$, the player chooses such a path, each round there is a loss from each edge.
- Again need to fix L^* .
- Not obvious what entropy to use. Entropy of A^* or probabilities $p_t(i \in A^*)$?

The Semibandit Case

- Now we play a subset $A = (i_1, \dots, i_m)$ of size m from a given collection $\mathcal{A} \subseteq \binom{[n]}{m}$. We observe and pay all m losses $\ell_t(i_k)$ each turn.
- Example: \mathcal{A} consists of shortest paths in a graph from $u \rightarrow v$, the player chooses such a path, each round there is a loss from each edge.
- Again need to fix L^* .
- Not obvious what entropy to use. Entropy of A^* or probabilities $p_t(i \in A^*)$?
- We simply add the entropies for probabilities that the individual coordinates are in A^* :

$$H_t = \sum_i H(p_t(i \in A^*)).$$

The Semibandit Case

- Now we play a subset $A = (i_1, \dots, i_m)$ of size m from a given collection $\mathcal{A} \subseteq \binom{[n]}{m}$. We observe and pay all m losses $\ell_t(i_k)$ each turn.
- Example: \mathcal{A} consists of shortest paths in a graph from $u \rightarrow v$, the player chooses such a path, each round there is a loss from each edge.
- Again need to fix L^* .
- Not obvious what entropy to use. Entropy of A^* or probabilities $p_t(i \in A^*)$?
- We simply add the entropies for probabilities that the individual coordinates are in A^* :

$$H_t = \sum_i H(p_t(i \in A^*)).$$

- By doing separate information theory for each coordinate, we can handle arbitrary priors unlike previous analysis.

The Semibandit Case

- Now we play a subset $A = (i_1, \dots, i_m)$ of size m from a given collection $\mathcal{A} \subseteq \binom{[n]}{m}$. We observe and pay all m losses $\ell_t(i_k)$ each turn.
- Example: \mathcal{A} consists of shortest paths in a graph from $u \rightarrow v$, the player chooses such a path, each round there is a loss from each edge.
- Again need to fix L^* .
- Not obvious what entropy to use. Entropy of A^* or probabilities $p_t(i \in A^*)$?
- We simply add the entropies for probabilities that the individual coordinates are in A^* :

$$H_t = \sum_i H(p_t(i \in A^*)).$$

- By doing separate information theory for each coordinate, we can handle arbitrary priors unlike previous analysis.
- Total entropy at most $m \log(n)$. Similarly obtain $\tilde{O}(\sqrt{nmT})$ regret.

The Semibandit Case

- Now we play a subset $A = (i_1, \dots, i_m)$ of size m from a given collection $\mathcal{A} \subseteq \binom{[n]}{m}$. We observe and pay all m losses $\ell_t(i_k)$ each turn.
- Example: \mathcal{A} consists of shortest paths in a graph from $u \rightarrow v$, the player chooses such a path, each round there is a loss from each edge.
- Again need to fix L^* .
- Not obvious what entropy to use. Entropy of A^* or probabilities $p_t(i \in A^*)$?
- We simply add the entropies for probabilities that the individual coordinates are in A^* :

$$H_t = \sum_i H(p_t(i \in A^*)).$$

- By doing separate information theory for each coordinate, we can handle arbitrary priors unlike previous analysis.
- Total entropy at most $m \log(n)$. Similarly obtain $\tilde{O}(\sqrt{nmT})$ regret.
- For small loss, new $\tilde{O}(\sqrt{nL^*})$ bound! No contradiction, $L^* \leq mT$.

The Semibandit Case

- If we copy bandit proof, again for each i : $\mathbb{E}[\sum_{t:p_t(i) \geq \gamma} \ell_t(i)] \lesssim L^*$.
- Initial entropy $m \log(n)$. Hence $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nmL^*})$.

The Semibandit Case

- If we copy bandit proof, again for each i : $\mathbb{E}[\sum_{t: p_t(i) \geq \gamma} \ell_t(i)] \lesssim L^*$.
- Initial entropy $m \log(n)$. Hence $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nmL^*})$.
- Idea: sort $A^* = (i_1^*, i_2^*, \dots, i_m^*)$ so that $L_{i_1^*, T} \geq L_{i_2^*, T} \geq \dots \geq L_{i_m^*, T}$.

The Semibandit Case

- If we copy bandit proof, again for each i : $\mathbb{E}[\sum_{t: p_t(i) \geq \gamma} \ell_t(i)] \lesssim L^*$.
- Initial entropy $m \log(n)$. Hence $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nmL^*})$.
- Idea: sort $A^* = (i_1^*, i_2^*, \dots, i_m^*)$ so that $L_{i_1^*, T} \geq L_{i_2^*, T} \geq \dots \geq L_{i_m^*, T}$.
- We know that $L_{i_k^*, T} \leq \frac{L^*}{k}$.

The Semibandit Case

- If we copy bandit proof, again for each i : $\mathbb{E}[\sum_{t: p_t(i) \geq \gamma} \ell_t(i)] \lesssim L^*$.
- Initial entropy $m \log(n)$. Hence $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nmL^*})$.
- Idea: sort $A^* = (i_1^*, i_2^*, \dots, i_m^*)$ so that $L_{i_1^*, T} \geq L_{i_2^*, T} \geq \dots \geq L_{i_m^*, T}$.
- We know that $L_{i_k^*, T} \leq \frac{L^*}{k}$.
- Now we can do information theory separately for each of the unknown coordinates i_k^* . Setting $\bar{\ell}_t(i, k) = \mathbb{E}[\ell_t(i) | i_k^* = i]$:

The Semibandit Case

- If we copy bandit proof, again for each i : $\mathbb{E}[\sum_{t: p_t(i) \geq \gamma} \ell_t(i)] \lesssim L^*$.
- Initial entropy $m \log(n)$. Hence $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nmL^*})$.
- Idea: sort $A^* = (i_1^*, i_2^*, \dots, i_m^*)$ so that $L_{i_1^*, T} \geq L_{i_2^*, T} \geq \dots \geq L_{i_m^*, T}$.
- We know that $L_{i_k^*, T} \leq \frac{L^*}{k}$.
- Now we can do information theory separately for each of the unknown coordinates i_k^* . Setting $\bar{\ell}_t(i, k) = \mathbb{E}[\ell_t(i) | i_k^* = i]$:

$$\mathbb{E}[R_T] = \sum_{i, k, t} \mathbb{E}^{p_t}[p_t(i = i_k^*)(\bar{\ell}_t(i) - \bar{\ell}_t(i, k))].$$

The Semibandit Case

- If we copy bandit proof, again for each i : $\mathbb{E}[\sum_{t: p_t(i) \geq \gamma} \ell_t(i)] \lesssim L^*$.
- Initial entropy $m \log(n)$. Hence $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nmL^*})$.
- Idea: sort $A^* = (i_1^*, i_2^*, \dots, i_m^*)$ so that $L_{i_1^*, T} \geq L_{i_2^*, T} \geq \dots \geq L_{i_m^*, T}$.
- We know that $L_{i_k^*, T} \leq \frac{L^*}{k}$.
- Now we can do information theory separately for each of the unknown coordinates i_k^* . Setting $\bar{\ell}_t(i, k) = \mathbb{E}[\ell_t(i) | i_k^* = i]$:

$$\mathbb{E}[R_T] = \sum_{i, k, t} \mathbb{E}^{p_t}[p_t(i = i_k^*)(\bar{\ell}_t(i) - \bar{\ell}_t(i, k))].$$

- Now do the same argument for each k , gaining information on i_k^* in exchange for regret. Then sum over k .

The Semibandit Case

- If we copy bandit proof, again for each i : $\mathbb{E}[\sum_{t: p_t(i) \geq \gamma} \ell_t(i)] \lesssim L^*$.
- Initial entropy $m \log(n)$. Hence $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nmL^*})$.
- Idea: sort $A^* = (i_1^*, i_2^*, \dots, i_m^*)$ so that $L_{i_1^*, T} \geq L_{i_2^*, T} \geq \dots \geq L_{i_m^*, T}$.
- We know that $L_{i_k^*, T} \leq \frac{L^*}{k}$.
- Now we can do information theory separately for each of the unknown coordinates i_k^* . Setting $\bar{\ell}_t(i, k) = \mathbb{E}[\ell_t(i) | i_k^* = i]$:

$$\mathbb{E}[R_T] = \sum_{i, k, t} \mathbb{E}^{p_t}[p_t(i = i_k^*)(\bar{\ell}_t(i) - \bar{\ell}_t(i, k))].$$

- Now do the same argument for each k , gaining information on i_k^* in exchange for regret. Then sum over k .
- This also doesn't work: we pay $\tilde{O}\left(\sqrt{\frac{nL^*}{k}}\right)$ for i_k^* , these sum to $\tilde{O}(\sqrt{nmL^*})$. No change!

The Semibandit Case

- If we copy bandit proof, again for each i : $\mathbb{E}[\sum_{t: p_t(i) \geq \gamma} \ell_t(i)] \lesssim L^*$.
- Initial entropy $m \log(n)$. Hence $\mathbb{E}[R_T] = \tilde{O}(\sqrt{nmL^*})$.
- Idea: sort $A^* = (i_1^*, i_2^*, \dots, i_m^*)$ so that $L_{i_1^*, T} \geq L_{i_2^*, T} \geq \dots \geq L_{i_m^*, T}$.
- We know that $L_{i_k^*, T} \leq \frac{L^*}{k}$.
- Now we can do information theory separately for each of the unknown coordinates i_k^* . Setting $\bar{\ell}_t(i, k) = \mathbb{E}[\ell_t(i) | i_k^* = i]$:

$$\mathbb{E}[R_T] = \sum_{i, k, t} \mathbb{E}^{p_t}[p_t(i = i_k^*)(\bar{\ell}_t(i) - \bar{\ell}_t(i, k))].$$

- Now do the same argument for each k , gaining information on i_k^* in exchange for regret. Then sum over k .
- This also doesn't work: we pay $\tilde{O}\left(\sqrt{\frac{nL^*}{k}}\right)$ for i_k^* , these sum to $\tilde{O}(\sqrt{nmL^*})$. No change!
- Detail: we need to threshold separately for each i_k^* .

The Semibandit Case

- Splitting up A^* gained efficiency in thresholding.

The Semibandit Case

- Splitting up A^* gained efficiency in thresholding.
- But the information usage is worse. Now when we pick coordinate i , we guess that $i = i_k^*$ for some fixed k , gain info when this holds.

The Semibandit Case

- Splitting up A^* gained efficiency in thresholding.
- But the information usage is worse. Now when we pick coordinate i , we guess that $i = i_k^*$ for some fixed k , gain info when this holds.
- Chance to learn decreases: $\sum_i p_t(i \in A^*)^2 \rightarrow \sum_{i,k} p_t(i = i_k^*)^2$.

The Semibandit Case

- Splitting up A^* gained efficiency in thresholding.
- But the information usage is worse. Now when we pick coordinate i , we guess that $i = i_k^*$ for some fixed k , gain info when this holds.
- Chance to learn decreases: $\sum_i p_t(i \in A^*)^2 \rightarrow \sum_{i,k} p_t(i = i_k^*)^2$.
- We can do the same argument for any partition of $[m]$. Find a partition with good thresholding and information properties.

The Semibandit Case

- Splitting up A^* gained efficiency in thresholding.
- But the information usage is worse. Now when we pick coordinate i , we guess that $i = i_k^*$ for some fixed k , gain info when this holds.
- Chance to learn decreases: $\sum_i p_t(i \in A^*)^2 \rightarrow \sum_{i,k} p_t(i = i_k^*)^2$.
- We can do the same argument for any partition of $[m]$. Find a partition with good thresholding and information properties.
- For a index subset $S \subseteq [m]$, consider the set

$$A_S^* = \{i_s^* : s \in S\}.$$

The Semibandit Case

- Splitting up A^* gained efficiency in thresholding.
- But the information usage is worse. Now when we pick coordinate i , we guess that $i = i_k^*$ for some fixed k , gain info when this holds.
- Chance to learn decreases: $\sum_i p_t(i \in A^*)^2 \rightarrow \sum_{i,k} p_t(i = i_k^*)^2$.
- We can do the same argument for any partition of $[m]$. Find a partition with good thresholding and information properties.
- For a index subset $S \subseteq [m]$, consider the set

$$A_S^* = \{i_s^* : s \in S\}.$$

- Essentially, A_S^* has entropy $|S| \log n$. For each i the sum

$$\sum_{t: p_t(i \in A_S^*) \geq \gamma} \ell_t(i)$$

reaches $\frac{L^*}{\min_{s \in S} s}$ before $p_t(i)$ becomes small and the sum freezes.

The Semibandit Case

- As a result, if we partition $[m]$ into subsets S_1, \dots, S_k we get a regret bound like

$$\tilde{O} \left(\sqrt{nL^*} \sum_{j=1}^k \sqrt{\frac{|S_j|}{\min_{s \in S_j} s}} \right).$$

The Semibandit Case

- As a result, if we partition $[m]$ into subsets S_1, \dots, S_k we get a regret bound like

$$\tilde{O} \left(\sqrt{nL^*} \sum_{j=1}^k \sqrt{\frac{|S_j|}{\min_{s \in S_j} s}} \right).$$

- We saw $S_1 = [m]$ gives $\tilde{O}(\sqrt{nmL^*})$, as does $S_j = \{j\}$.

The Semibandit Case

- As a result, if we partition $[m]$ into subsets S_1, \dots, S_k we get a regret bound like

$$\tilde{O} \left(\sqrt{nL^*} \sum_{j=1}^k \sqrt{\frac{|S_j|}{\min_{s \in S_j} s}} \right).$$

- We saw $S_1 = [m]$ gives $\tilde{O}(\sqrt{nmL^*})$, as does $S_j = \{j\}$.
- However, taking a dyadic decomposition $S_j = [2^{j-1}, 2^j - 1]$ gives $\tilde{O}(\sqrt{nL^* \log(m)}) = \tilde{O}(\sqrt{nL^*})$.

The Semibandit Case

- As a result, if we partition $[m]$ into subsets S_1, \dots, S_k we get a regret bound like

$$\tilde{O} \left(\sqrt{nL^*} \sum_{j=1}^k \sqrt{\frac{|S_j|}{\min_{s \in S_j} s}} \right).$$

- We saw $S_1 = [m]$ gives $\tilde{O}(\sqrt{nmL^*})$, as does $S_j = \{j\}$.
- However, taking a dyadic decomposition $S_j = [2^{j-1}, 2^j - 1]$ gives $\tilde{O}(\sqrt{nL^* \log(m)}) = \tilde{O}(\sqrt{nL^*})$.

Theorem

A variant of thresholded Thompson Sampling achieves T -independent $\tilde{O}(\sqrt{nL^})$ regret in the semibandit setting. Without thresholding the regret is $\tilde{O}(\sqrt{nL^*})$ with T -dependence.*

Open Problems

- What about Contextual Bandits? A small-loss algorithm was found here last year: [Allen-Zhu, Bubeck, and Li '18]

Open Problems

- What about Contextual Bandits? A small-loss algorithm was found here last year: [Allen-Zhu, Bubeck, and Li '18]
- General graph feedback? An $O(\sqrt{T})$ analysis for Thompson Sampling has been done. [Liu, Zheng, and Shroff '18]

- What about Contextual Bandits? A small-loss algorithm was found here last year: [Allen-Zhu, Bubeck, and Li '18]
- General graph feedback? An $O(\sqrt{T})$ analysis for Thompson Sampling has been done. [Liu, Zheng, and Shroff '18]
- Can we turn our semibandit analysis into a non-Bayesian algorithm achieving the optimal small loss bound?

- What about Contextual Bandits? A small-loss algorithm was found here last year: [Allen-Zhu, Bubeck, and Li '18]
- General graph feedback? An $O(\sqrt{T})$ analysis for Thompson Sampling has been done. [Liu, Zheng, and Shroff '18]
- Can we turn our semibandit analysis into a non-Bayesian algorithm achieving the optimal small loss bound?
- Any formal connections between Thompson Sampling and other algorithms?

References



Russo and Van Roy (2016)

An information-theoretic analysis of Thompson sampling

The Journal of Machine Learning Research The Journal of Machine Learning Research 17.1 (2016): 2442-2471.



Lykouris, Sridharan, and Tardos (2018)

Small-loss bounds for online learning with partial information

[arXiv:1711.03639](#).



Liu, Zheng, and Shroff (2018)

Analysis of Thompson Sampling for Graphical Bandits Without the Graphs.

[arXiv:1805.08930](#).]



Allen-Zhu, Bubeck, and Li (2018)

Make the Minority Great Again: First-Order Regret Bound for Contextual Bandits.

[arXiv:1802.03386](#).

Thank You