

Data Sheet Issue 09/2012

# SCONA TSPOE 1002 CMB 1-2

Impact strength modifier for polyamide and PET.

# **Product Data**

# Composition

Ethylene octen copolymer functionalized with maleic anhydride

## **Typical Properties**

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

MFR (190 °C, 21.6 kg): 6-20 g/10 min Drying loss (3 h, 230 °F): < 0.5 % MAH content: 0.55 %

Supplied as: Translucent granulate

#### **Food Contact Legal Status**

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

## **Storage and Transportation**

Storage temperature max. 35 °C / 95 °F, relative humidity < 80 %. Avoid direct sunlight and contact with water.

# **Applications**

# **Thermoplastics**

# **Special Features and Benefits**

SCONA TSPOE 1002 CMB 1-2 is a high impact strength modifier for polyamide 6, polyamide 6.6, and polyamide 12 as well as polyethylene terephthalate (PET). In polyamides, it significantly increases low temperature impact strength, and for PET, it improves notch impact strength and tear resistance. Its low yellowness index makes the product suitable for lighter compounds as well.

### **Recommended Levels**

3-15 % additive (as supplied) based upon total formulation for polyamide.6-18 % additive (as supplied) based upon total formulation for PET. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

# **Incorporation and Processing Instructions**

Incorporate the product with high shear forces by means of a twin-screw extruder.

**BYK USA Inc.** 524 South Cherry Street

P.O. Box 5670
Wallingford, CT 06492
USA

USA SCONA® is a registered trademark. Tel 203 265-2086 The information and data stated hk Fax 203 284-9158 believed to be accurate. No warrar

The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty, either expressed or implied, is made or intended. Use by a customer should be based upon their own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERBYK®, DISPERPLAST®, LACTIMON®, NANOBYK®, PAPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

cs.usa@byk.com www.byk.com/additives

This issue replaces all previous versions – Printed in the USA