

Data Sheet Issue 11/2013

# **BYK-1719**

VOC-free silicone defoamer for aqueous printing inks and overprint varnishes with spontaneous defoaming effect and high efficiency. Glycol free.

## **Product Data**

Composition VOC-free (< 1500 ppm)

Blend of foam-destroying polysiloxanes and hydrophobic solids

# **Typical Properties**

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (68 °F): 8.38 lbs/US gal

Active substance: 100 %

# **Food Contact Legal Status**

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

# **Storage and Transportation**

Separation may occur. Mix well before use.

# **Applications**

# **Printing Inks and Overprint Varnishes**

## **Special Features and Benefits**

The additive is recommended for defoaming aqueous printing inks and overprint varnishes; it can also be used in pigment concentrates and has a good spontaneous defoaming effect. BYK-1719 is very effective even at a low dosage, with only a low cratering tendency and a high efficiency. The additive is VOC-free, contains no glycols and has a good shelf life.

## **Recommended Levels**

0.1-0.5 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## **Incorporation and Processing Instructions**

The additive can be incorporated during any stage of the production process. As a result of its high activity, the defoamer must be incorporated at high shear forces to ensure a good distribution and to avoid defects in the system.



#### **BYK-1719**

Data Sheet Issue 11/2013







#### BYK USA Inc.

524 South Cherry Street P.O. Box 5670 Wallingford, CT 06492 USA Tel 203 265-2086 Fax 203 284-9158

cs.usa@byk.com www.byk.com/additives

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera. SCONA® is a registered trademark of BYK Kometra. The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty, either expressed or implied, is made or intended. Use by a customer should be based upon their own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

This issue replaces all previous versions - Printed in the USA