

# BENTOLITE 2422

## Rheological Additive

### Product Data

#### Special Features and Benefits

BENTOLITE 2422 is a specially processed calcium bentonite which is suited for coating applications where control of settling and syneresis are needed. BENTOLITE 2422 is a high brightness bentonite clay. BENTOLITE 2422 will also improve hiding.

BENTOLITE 2422 improves hold-out, particularly when used in conjunction with cellulose. Improved hold-out is useful when painting over a porous substrate, painting a substrate with different densities (i.e. gypsum wall board with joint compound), and touchup of a previously painted surface.

- Controls Settling
- Controls Syneresis
- Improves Hiding
- Improves Hold-out
- Excellent Wet Edge Properties

#### Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Color:	Off White
Moisture Content:	8 %
Dry Sieve Size (%-200 M):	95 % *
pH 2 % Slurry:	9.5
Soluble Iron:	0.6 %
Bulk Density Loose/Packed:	30/45 lb/cu. ft.

\*The Dry Sieve analysis does not indicate the true particle size in water. The clay will delaminate to sub-micron particles in water.

**BYK-Chemie GmbH**  
 P.O. Box 10 02 45  
 46462 Wesel  
 Germany  
 Tel +49 281 670-0  
 Fax +49 281 65735

**info@byk.com**  
**www.byk.com/additives**

ACTAL®, ADJUST-4®, ADVITROL®, BENTOLITE®, CLAYTONE®, CLOISITE®, COPISIL®, FULACOLOR®, FULCAT®, FULGEL®, FULMONT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PERMONT®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, SCP®, TIXOGEL®, Y25® are registered trademarks of BYK Additives.

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERPLAST®, LACTIMON®, NANOBYPK®, PAPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAX®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

SCONA® is a registered trademark of BYK Kometra.

This information is given to the best of our knowledge. Because of the multitude of formulations, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

This issue replaces all previous versions – Printed in Germany