

Data Sheet Issue 10/2013

CLOISITE 15

Product Data

Composition

CLOISITE 15 is bis(hydrogenated tallow alkyl)dimethyl, salt with bentonite.

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Moisture: <3 % Typical Dry Particle Size: <10 μ m (d₅₀) Color: Off White Packed Bulk Density: 165g/l Density: 1.66g/cm³ X Ray Results: d₀₀₁= 3.63nm

Recommended Use

CLOISITE 15 is an additive for plastics and rubber to improve various physical properties, such as reinforcement, CLTE, synergistic flame retardant and barrier.

BYK-Chemie GmbHP.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

ACTAL®, ADJUST-4®, ADVITROL®, BENTOLITE®, CLAYTONE®, CLOISITE®, COPISIL®, FULACOLOR®, FULCAT®, FULGEL®, FULMONT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PERMONT®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, SCP®, TIXOGEL®, Y25® are registered trademarks of BYK Additives.

ANTI-TERRA®, BYK® BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, ADJUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

SCONA® is a registered trademark of BYK Kometra.

info@byk.com www.byk.com/additives

This information is given to the best of our knowledge. Because of the multitude of formulations, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived

from this fact for individual cases.
This issue replaces all previous versions – Printed in Germany