

# **CERAFLOUR 915**

Micronized polypropylene wax for solvent-borne and aqueous systems, to achieve medium surface textures.

# **Product Data**

#### Composition

Micronized polypropylene wax

#### **Typical Properties**

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density: 0.9 g/ml Melting point: 160 °C

Particle size distribution (laser diffraction, volume distribution): D50: 34 μm D90: 57 μm

## **Food Contact Legal Status**

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

#### **Storage and Transportation**

Temperature sensitive. To be stored and transported at a temperature below 50 °C.

# **Applications**

## **Coatings Industry**

#### **Special Features and Benefits**

CERAFLOUR 915 generates a uniform and easily reproducible texture effect with a medium surface texture in aqueous and solvent-borne coating systems.

# **Recommended Use**

Industrial coatings	
Coil coatings	
Wood and furniture coatings	

especially recommended

#### **CERAFLOUR 915**

Data Sheet Issue 07/2013

#### **Recommended Levels**

1-10 % additive (as supplied) based upon total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## **Incorporation and Processing Instructions**

The additive is preferably incorporated at the end of the production process at a moderate shear rate.







**BYK-Chemie GmbH** P.O. Box 10 02 45 46462 Wesel Germany
Tel +49 281 670-0 Fax +49 281 65735

info@byk.com www.byk.com/additives ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKIPT®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERBYKS, DISPERBYKS, SILBYK®, VISCOBYKS, and Greenability® are registered trademarks of BYK-Chemie. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

SCONA® is a registered trademark of BYK Kometra.

This information is given to the best of our knowledge. Because of the multitude of formulations, production, and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor. No liabilities, including those for patent rights, can be derived from this fact for individual cases.

This issue replaces all previous versions – Printed in Germany