Data Sheet Issue 11/2014

# **AQUACER 527**

Wax emulsion based on a modified EVA copolymer wax to improve surface characteristics in aqueous coating systems and printing inks.

# **Product Data**

#### Composition

Non-ionic aqueous emulsion of a modified EVA copolymer wax

# **Typical Properties**

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Non-volatile matter (1 h, 125 °C): 35 % Carrier: Water Melting point (wax content): 105 °C pH value (20 °C): 9

## **Food Contact Legal Status**

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

## **Storage and Transportation**

Temperature sensitive. To be stored and transported between 5 °C and 35 °C. Mix well before use.

# **Applications**

## **Coatings and Printing Inks**

### **Special Features and Benefits**

The additive improves the orientation of effect pigments (aluminum, mica) in aqueous coating systems. In aqueous printing inks, it enhances the anti-slip effect.

#### **Recommended Use**

The additive is recommended for aqueous effect coating systems, printing inks, and overprint varnishes.

#### **Recommended Levels**

5-9 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## **Incorporation and Processing Instructions**

The additive should preferably be post-added using a low shear rate. Mix well before use.

#### **AQUACER 527**

Data Sheet Issue 11/2014







**BYK-Chemie GmbH** P.O. Box 10 02 45 46462 Wesel Germany Tel +49 281 670-0 Fax +49 281 65735

info@byk.com www.byk.com ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, DISPERBYK®, AND Greenability® are registered trademarks of BYK-Chemie. ACTAL®, ADJUST®, ADVITROL®, ASTRABEN®, BENTOLITE®, CLAYTONE®, CLOISITE®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, TIXOGEL®, and VISCOSEAL® are registered trademarks of BYK Additives.

AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera.

SCONA® is a registered trademark of BYK Kometra.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological

progress or further developments. This issue replaces all previous versions – Printed in Germany