GREEEN tallgrass prairie restoration: Seeded richness ~ Seeding time * Herbicide pre-treatment (SW Station)

Markus Bauer

2025-09-08

Contents

Preparation **1**

Statistics **2**
Data exploration . . . 2
Means and deviations . . . 2
Graphs of raw data (Step 2, 6, 7) . . . 4
Outliers, zero-inflation, transformations? (Step 1, 3, 4) . . . 7
Check collinearity part 1 (Step 5) . . . 7
Models . . . 7
Model check . . . 8
DHARMa . . . 8
Check collinearity part 2 (Step 5) . . . 10
Model comparison . . . 10
R2 values . . . 10
AICc . . . 10
Predicted values . . . 11
Summary table . . . 11
Forest plot . . . 11
Effect sizes . . . 12

Session info **13**

Markus Bauer

Technichal University of Munich, TUM School of Life Sciences, Chair of Restoration Ecology, Emil-Ramann-Straße 6, 85354 Freising, Germany

markus1.bauer@tum.de

ORCiD ID: 0000-0001-5372-4174 Google Scholar GitHub: markus1bauer

> **NOTE:** To compare different models, you only have to change the models in the section 'Load models'

Preparation

Protocol of data exploration (Steps 1-8) used from Zuur et al. (2010) Methods Ecol Evol DOI: 10.1111/2041-210X.12577

```r
library(here)
library(tidyverse)
library(ggbeeswarm)
library(patchwork)
library(lme4)
library(glmmTMB)
library(DHARMa)
library(emmeans)
```

Packages

```r
sites <- read_csv(
  here("data", "processed", "data_processed_sites.csv"),
  col_names = TRUE, na = c("na", "NA", ""), col_types = cols(
    .default = "?",
    id_plot = "f",
    year = "f",
    seeding_time = col_factor(
      levels = c("unseeded", "fall", "spring"), ordered = FALSE
      ),
    herbicide = col_factor(levels = c("0", "1"), ordered = FALSE),
    treatment_id = "f",
    richness_type = "f"
  )
) %>%
  filter(
    site == "SW Station",
    richness_type == "seeded_richness",
    treatment_id %in% c("1", "2", "3", "4")
  ) %>%
  mutate(
    treatment = str_c(seeding_time, herbicide, seeded_pool, sep = "_"),
    treatment = factor(treatment)
  ) %>%
  mutate(y = richness_1qm + richness_25qm)
```

Load data

Statistics

Data exploration

Means and deviations

```r
Rmisc::CI(sites$y, ci = .95)
```

```
##    upper     mean    lower
## 4.115493 3.562500 3.009507
```

```r
median(sites$y)
```

```
## [1] 3
```

```r
sd(sites$y)
```

```
## [1] 2.729228
```

```r
quantile(sites$y, probs = c(0.05, 0.95), na.rm = TRUE)
```

```
##  5% 95%
##   0   8
```

```r
sites %>% count(site, year)
```

```
## # A tibble: 4 x 3
##   site       year      n
##   <chr>      <fct> <int>
## 1 SW Station 2015     24
## 2 SW Station 2016     24
## 3 SW Station 2017     24
## 4 SW Station 2018     24
```

```r
sites %>% count(treatment)
```

```
## # A tibble: 4 x 2
##   treatment        n
##   <fct>        <int>
## 1 fall_0_33       24
## 2 spring_0_33     24
## 3 spring_1_33     24
## 4 unseeded_0_0    24
```

Graphs of raw data (Step 2, 6, 7)






2015
2016
2017
2018
SW Station
Cover (1qm) [%]
7.5
5.0
2.5
0.0
Survey year
treatment
fall_0_33
spring_0_33
spring_1_33
unseeded_0_0


7.5
5.0
2.5
0.0
Cover (1qm) [%]
0.40
0.45
0.50
0.55
Water capacity [%]

Outliers, zero-inflation, transformations? (Step 1, 3, 4)



Check collinearity part 1 (Step 5)

Exclude r > 0.7 Dormann et al. 2013 Ecography DOI: 10.1111/j.1600-0587.2012.07348.x

```
# sites %>%
#   select(where(is.numeric), -y, -starts_with("cwm.")) %>%
#   GGally::ggpairs(
#     lower = list(continuous = "smooth_loess")
#     ) +
#   theme(strip.text = element_text(size = 7))

# -> no continuous variables
```

Models

NOTE: Only here you have to modify the script to compare other models

```
load(file = here("outputs", "models", "model_richness_timing_herbicide_sws_2.Rdata"))
#load(file = here("outputs", "models", "model_sla_esy4_3.Rdata"))
m_1 <- m2
#m_2 <- m2
```

```
m_1@call
## glmer(formula = y ~ treatment + (1 | year), data = sites, family = poisson(link = "log"))
# m_2@call
```

```
# formula(m_1)
# formula(m_2)
```

Model check

DHARMa

```
simulation_output_1 <- simulateResiduals(m_1, plot = TRUE)
```




```
# simulation_output_2 <- simulateResiduals(m_2, plot = TRUE)
```

```
plotResiduals(simulation_output_1$scaledResiduals, sites$treatment)
```




```
# plotResiduals(simulation_output_2$scaledResiduals, sites$treatment)
# plotResiduals(simulation_output_1$scaledResiduals, sites$year)
# plotResiduals(simulation_output_2$scaledResiduals, sites$year)
plotResiduals(simulation_output_1$scaledResiduals, sites$water_cap)
```




```
# plotResiduals(simulation_output_2$scaledResiduals, sites$water_cap)
```

```
testDispersion(simulation_output_1)
```



Test for overdispersion

```
##
##  DHARMa nonparametric dispersion test via sd of residuals fitted vs.
##  simulated
##
## data:  simulationOutput
## dispersion = 0.97905, p-value = 0.968
## alternative hypothesis: two.sided
# testDispersion(simulation_output_2)
```

Check collinearity part 2 (Step 5)

Remove VIF > 3 or > 10 Zuur et al. 2010 Methods Ecol Evol DOI: 10.1111/j.2041-210X.2009.00001.x

```
# car::vif(m_1)
# car::vif(m_2)
```

Model comparison

R2 values

```
MuMIn::r.squaredGLMM(m_1)
## Warning: the null model is only correct if all the variables it uses are identical
## to those used in fitting the original model.
##                 R2m       R2c
## delta     0.7222126 0.7248729
## lognormal 0.7465752 0.7493251
## trigamma  0.6929870 0.6955396
# MuMIn::r.squaredGLMM(m_2)
```

AICc

Use AICc and not AIC since ratio n/K < 40 Burnahm & Anderson 2002 p. 66 ISBN: 978-0-387-95364-9

```
# MuMIn::AICc(m_1, m_2) %>%
#   arrange(AICc)
```

Predicted values

Summary table

```r
car::Anova(m_1, type = 2)
```

```
## Analysis of Deviance Table (Type II Wald chisquare tests)
##
## Response: y
##            Chisq Df Pr(>Chisq)
## treatment 81.696  3  < 2.2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```r
summary(m_1)
```

```
## Generalized linear mixed model fit by maximum likelihood (Laplace
##   Approximation) [glmerMod]
##  Family: poisson  ( log )
## Formula: y ~ treatment + (1 | year)
##    Data: sites
##
##       AIC       BIC    logLik -2*log(L)  df.resid
##     364.3     377.1    -177.2     354.3        91
##
## Scaled residuals:
##     Min      1Q  Median      3Q     Max
## -2.3154 -0.6919  0.1884  0.6342  1.8395
##
## Random effects:
##  Groups Name        Variance Std.Dev.
##  year   (Intercept) 0.002714 0.0521
## Number of obs: 96, groups:  year, 4
##
## Fixed effects:
##                       Estimate Std. Error z value Pr(>|z|)
## (Intercept)             1.0253     0.1250   8.202 2.36e-16 ***
## treatmentspring_0_33    0.6316     0.1512   4.178 2.95e-05 ***
## treatmentspring_1_33    0.6857     0.1498   4.577 4.71e-06 ***
## treatmentunseeded_0_0  -1.4321     0.2782  -5.147 2.64e-07 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##             (Intr) t_0_33 t_1_33
## trtmnt_0_33 -0.790
## trtmnt_1_33 -0.797  0.659
## trtmntn_0_0 -0.429  0.355  0.358
```

Forest plot

```r
dotwhisker::dwplot(
  list(m_1),
  ci = 0.95,
  show_intercept = FALSE,
```

```
  vline = geom_vline(xintercept = 0, colour = "grey60", linetype = 2)) +
  theme_classic()
```



Effect sizes

Effect sizes of chosen model just to get exact values of means etc. if necessary.

```
(emm <- emmeans(
  m_1,
  revpairwise ~ treatment,
  type = "response"
  ))
```

```
## $emmeans
##  treatment     rate    SE  df asymp.LCL asymp.UCL
##  fall_0_33    2.788 0.348 Inf     2.182      3.56
##  spring_0_33  5.243 0.487 Inf     4.370      6.29
##  spring_1_33  5.534 0.502 Inf     4.633      6.61
##  unseeded_0_0 0.666 0.167 Inf     0.407      1.09
##
```

```
## Confidence level used: 0.95
## Intervals are back-transformed from the log scale
##
## $contrasts
##  contrast                   ratio     SE  df null z.ratio p.value
##  spring_0_33 / fall_0_33    1.881 0.2840 Inf    1   4.178  0.0002
##  spring_1_33 / fall_0_33    1.985 0.2970 Inf    1   4.577  <.0001
##  spring_1_33 / spring_0_33  1.056 0.1310 Inf    1   0.435  0.9725
##  unseeded_0_0 / fall_0_33   0.239 0.0664 Inf    1  -5.147  <.0001
##  unseeded_0_0 / spring_0_33 0.127 0.0337 Inf    1  -7.777  <.0001
##  unseeded_0_0 / spring_1_33 0.120 0.0318 Inf    1  -8.004  <.0001
##
## P value adjustment: tukey method for comparing a family of 4 estimates
## Tests are performed on the log scale
```

```r
plot(emm, comparison = TRUE)
```



Session info

```
## R version 4.5.1 (2025-06-13 ucrt)
## Platform: x86_64-w64-mingw32/x64
## Running under: Windows 11 x64 (build 26100)
##
## Matrix products: default
##   LAPACK version 3.12.1
```

```
##
## locale:
## [1] LC_COLLATE=German_Germany.utf8  LC_CTYPE=German_Germany.utf8
## [3] LC_MONETARY=German_Germany.utf8 LC_NUMERIC=C
## [5] LC_TIME=German_Germany.utf8
##
## time zone: America/New_York
## tzcode source: internal
##
## attached base packages:
## [1] stats     graphics  grDevices utils     datasets  methods   base
##
## other attached packages:
##  [1] emmeans_1.11.1   DHARMa_0.4.7     glmmTMB_1.1.12   lme4_1.1-37
##  [5] Matrix_1.7-3     patchwork_1.3.1  ggbeeswarm_0.7.2 lubridate_1.9.4
##  [9] forcats_1.0.0    stringr_1.5.1    dplyr_1.1.4      purrr_1.1.0
## [13] readr_2.1.5      tidyr_1.3.1      tibble_3.3.0     ggplot2_3.5.2
## [17] tidyverse_2.0.0  here_1.0.1
##
## loaded via a namespace (and not attached):
##  [1] mnormt_2.1.1           Rdpack_2.6.4           gridExtra_2.3
##  [4] sandwich_3.1-1         rlang_1.1.6            magrittr_2.0.3
##  [7] compiler_4.5.1         mgcv_1.9-3             vctrs_0.6.5
## [10] quadprog_1.5-8         pkgconfig_2.0.3        crayon_1.5.3
## [13] fastmap_1.2.0          backports_1.5.0        labeling_0.4.3
## [16] pbivnorm_0.6.0         utf8_1.2.6             ggstance_0.3.7
## [19] promises_1.3.3         rmarkdown_2.29         tzdb_0.5.0
## [22] nloptr_2.2.1           bit_4.6.0              xfun_0.52
## [25] later_1.4.2            lavaan_0.6-19          parallel_4.5.1
## [28] R6_2.6.1               gap.datasets_0.0.6     stringi_1.8.7
## [31] qgam_2.0.0             RColorBrewer_1.1-3     car_3.1-3
## [34] boot_1.3-31            numDeriv_2016.8-1.1    estimability_1.5.1
## [37] Rcpp_1.1.0             iterators_1.0.14       knitr_1.50
## [40] zoo_1.8-14             parameters_0.27.0      httpuv_1.6.16
## [43] splines_4.5.1          timechange_0.3.0       tidyselect_1.2.1
## [46] rstudioapi_0.17.1      abind_1.4-8            yaml_2.3.10
## [49] MuMIn_1.48.11          doParallel_1.0.17      TMB_1.9.17
## [52] codetools_0.2-20       nonnest2_0.5-8         lattice_0.22-7
## [55] plyr_1.8.9             shiny_1.11.1           withr_3.0.2
## [58] bayestestR_0.16.1      coda_0.19-4.1          evaluate_1.0.4
## [61] marginaleffects_0.28.0 CompQuadForm_1.4.4     pillar_1.11.0
## [64] gap_1.6                carData_3.0-5          foreach_1.5.2
## [67] stats4_4.5.1           reformulas_0.4.1       insight_1.3.1
## [70] generics_0.1.4         vroom_1.6.5            rprojroot_2.0.4
## [73] hms_1.1.3              scales_1.4.0           minqa_1.2.8
## [76] xtable_1.8-4           glue_1.8.0             tools_4.5.1
## [79] data.table_1.17.8      mvtnorm_1.3-3          grid_4.5.1
## [82] rbibutils_2.3          datawizard_1.1.0       nlme_3.1-168
## [85] Rmisc_1.5.1            performance_0.15.0     beeswarm_0.4.0
## [88] vipor_0.4.7            Formula_1.2-5          cli_3.6.5
## [91] gtable_0.3.6           digest_0.6.37          farver_2.1.2
## [94] htmltools_0.5.8.1      lifecycle_1.0.4        mime_0.13
## [97] bit64_4.6.0-1          dotwhisker_0.8.4       MASS_7.3-65
```