GREEEN tallgrass prairie restoration: RLQ analyses timing x herbicide (NW Station)

MB

2025-10-23

Contents

Preparation **1**
Checks . . . 2
Finalize preparation . . . 3

Statistics **4**
Descriptive analyses . . . 4
Descriptive analyses . . . 4
Ordinations . . . 4
RLQ analyses . . . 4
Global test . . . 5
Traits by environment crossed table . . . 5
RLQ Plots . . . 5
Fourth-corner analysis . . . 10
Plot . . . 11

Save **13**

Session info **13**

Preparation

```
library(here)
library(tidyverse)
library(ade4)
```

Packages

```
sites <- read_csv(
  here("data", "processed", "data_processed_sites.csv"),
  col_names = TRUE, na = c("na", "NA", ""), col_types =
    cols(
    .default = "?",
    seeding_time = "f"
  )) %>%
  arrange(id_plot_year) %>%
  filter(
```

```r
    site == "NW Station",
    richness_type == "seeded_richness",
    treatment_id %in% c("1", "2", "3", "4")
  ) %>%
  mutate(
    treatment = str_c(seeding_time, herbicide, seeded_pool, sep = "_"),
    treatment = factor(treatment)
  ) %>%
  filter(treatment != "unseeded_0_0") %>%
  select(
    id_plot_year, year, treatment, water_cap, cover_non_seeded,
    cover_seeded_grass
    )

traits <- read_csv(
  here("data", "processed", "data_processed_traits.csv"),
  col_names = TRUE, na = c("na", "NA", ""), col_types = cols(.default = "?")
  ) %>%
  filter(seeded == "1", family != "Poaceae") %>%
  select(accepted_name, sla, height, seedmass) %>%
  mutate(seedmass = log(seedmass)) %>%
  drop_na()

species <- read_csv(
  here("data", "processed", "data_processed_species.csv"),
  col_names = TRUE, na = c("na", "NA", ""), col_types = cols(.default = "?")
  ) %>%
  filter(plot_size %in% c("1", "25")) %>%
  mutate(abundance = 1) %>%
  select(id_plot_year, accepted_name, abundance) %>%
  semi_join(sites, by = "id_plot_year") %>%
  semi_join(traits, by = "accepted_name") %>%
  arrange(id_plot_year)
```

Load data

Checks

```r
sites %>%
  group_by(year) %>%
  count()
```

Plots per year

```
## # A tibble: 4 x 2
## # Groups:   year [4]
##    year     n
##   <dbl> <int>
## 1  2015    18
## 2  2016    18
## 3  2017    18
## 4  2018    18
```

```r
species %>%
  group_by(id_plot_year) %>%
  count(name = "seeded_forb_richness") %>%
  ungroup() %>%
  count(seeded_forb_richness, name = "number_of_plots") %>%
  mutate(
    "plots_>=_1_species" = sum(number_of_plots),
    total_number_plots = 72
    )
```

Seeded species richness

```
## # A tibble: 6 x 4
##   seeded_forb_richness number_of_plots `plots_>=_1_species` total_number_plots
##                  <int>           <int>                <int>              <dbl>
## 1                    1              22                   48                 72
## 2                    2              16                   48                 72
## 3                    3               4                   48                 72
## 4                    4               3                   48                 72
## 5                    5               2                   48                 72
## 6                    7               1                   48                 72
```

```r
traits %>% anti_join(species, by = "accepted_name")
```

Check non-occuring seeded species

```
## # A tibble: 16 x 4
##    accepted_name                   sla height seedmass
##    <chr>                         <dbl>  <dbl>    <dbl>
##  1 Asclepias syriaca             158.   1.23     -5.08
##  2 Baptisia alba                 268.   0.940    -4.12
##  3 Chamaecrista fasciculata      297.   0.73     -4.87
##  4 Eryngium yuccifolium           91.7  1.01     -5.57
##  5 Helianthus occidentalis       184.   0.537    -6.11
##  6 Lespedeza virginica           126.   0.708    -6.26
##  7 Liatris cylindracea           110.   0.564    -5.73
##  8 Lupinus perennis              167.   0.326    -3.84
##  9 Silphium terebinthinaceum     171.   0.716    -4.53
## 10 Solidago juncea               130.   0.783    -7.79
## 11 Solidago nemoralis            122.   0.61     -7.84
## 12 Solidago speciosa             263.   0.71     -8.27
## 13 Symphyotrichum oolentangiense 143.   0.362    -8.68
## 14 Tradescantia ohiensis         103.   0.921    -5.61
## 15 Verbena stricta               183.   0.765    -6.89
## 16 Zizia aptera                  100.   0.34     -6.42
```

Finalize preparation

```r
traits <- traits %>%
  semi_join(species, by = "accepted_name") %>%
  column_to_rownames(var = "accepted_name")

sites <- sites %>%
```

```r
  semi_join(species, by = "id_plot_year") %>%
  column_to_rownames(var = "id_plot_year") %>%
  select(-water_cap)

species <- species %>%
  pivot_wider(
    names_from = "accepted_name", values_from = "abundance", values_fill = 0
    ) %>%
  column_to_rownames(var = "id_plot_year")
```

Statistics

Descriptive analyses

Descriptive analyses

```r
sites %>%
  group_by(year) %>%
  count()
```

```
## # A tibble: 4 x 2
## # Groups:   year [4]
##    year     n
##   <dbl> <int>
## 1  2015    10
## 2  2016    11
## 3  2017    13
## 4  2018    14
```

Ordinations

```r
dudi_l <- dudi.coa(species, scannf = FALSE)
dudi_r <- dudi.hillsmith(
  sites,
  row.w = dudi_l$lw,
  scannf = FALSE
  )
dudi_q <- dudi.pca(
  traits,
  row.w = dudi_l$cw,
  scannf = FALSE
  )
```

RLQ analyses

```r
m_rlq <- rlq(
  dudiR = dudi_r,
  dudiL = dudi_l,
  dudiQ = dudi_q,
  scannf = FALSE
  )
```

Global test

Model 2: species-environment relationship

Model 4: species-traits relationship

```r
randtest(m_rlq, nrepet = 999, modeltype = 6)
```

```
## class: krandtest lightkrandtest
## Monte-Carlo tests
## Call: randtest.rlq(xtest = m_rlq, nrepet = 999, modeltype = 6)
##
## Number of tests:   2
##
## Adjustment method for multiple comparisons:   none
## Permutation number:   999
##      Test       Obs  Std.Obs   Alter Pvalue
## 1 Model 2 0.4568022 6.005105 greater  0.002
## 2 Model 4 0.4568022 1.097631 greater  0.141
```

Traits by environment crossed table

```r
m_rlq$tab
```

```
##                            sla       height    seedmass
## year               -0.01299173 -0.004456629  0.13956776
## treat.fall_0_33     0.36564228  0.163100606  0.14298539
## treat.spring_0_33  -0.56375792  0.188699132 -0.33220408
## treat.spring_1_33  -0.36267361 -0.449581414 -0.06876043
## cover_non_seeded   -0.14627404  0.116675616 -0.29630898
## cover_seeded_grass  0.10112771  0.017336840  0.17106333
```

RLQ Plots

```r
plot(m_rlq)
```




```
s.label(m_rlq$lR)
```




```
s.label(m_rlq$lQ)
```




```
s.arrow(m_rlq$l1)
```




```
s.arrow(m_rlq$c1)
```



Fourth-corner analysis

```
m_4th <- fourthcorner(
  tabR = sites,
  tabL = species,
  tabQ = traits,
  modeltype = 6,
  p.adjust.method.G = "none",
  p.adjust.method.D = "none",
  nrepet = 49999
)
```

```
m_4th_adj <- p.adjust.4thcorner(
  m_4th,
  p.adjust.method.G = "fdr",
  p.adjust.method.D = "fdr",
  p.adjust.D = "global"
)
m_4th_adj
```

```
## Fourth-corner Statistics
## ------------------------
## Permutation method  Comb. 2 and 4  ( 49999  permutations)
##
## Adjustment method for multiple comparisons:   fdr
```

```
## call:  fourthcorner(tabR = sites, tabL = species, tabQ = traits, modeltype = 6,      nrepet = 49999,
##
## ---
##
##                              Test   Stat          Obs     Std.Obs     Alter
## 1                      year / sla      r -0.012991726 -0.05111528 two-sided
## 2          treat.fall_0_33 / sla Homog.  0.752069717  4.06381442      less
## 3        treat.spring_0_33 / sla Homog.  0.044383927 -1.22057450      less
## 4        treat.spring_1_33 / sla Homog.  0.037494470 -1.38579283      less
## 5         cover_non_seeded / sla      r -0.146274042 -1.10533210 two-sided
## 6       cover_seeded_grass / sla      r  0.101127714  1.11303339 two-sided
## 7                  year / height      r -0.004456629 -0.03523114 two-sided
## 8       treat.fall_0_33 / height Homog.  0.581440365  1.32399235      less
## 9     treat.spring_0_33 / height Homog.  0.264661673  1.73024684      less
## 10    treat.spring_1_33 / height Homog.  0.077647131 -1.67500155      less
## 11     cover_non_seeded / height      r  0.116675616  0.70959682 two-sided
## 12   cover_seeded_grass / height      r  0.017336840  0.23201292 two-sided
## 13               year / seedmass      r  0.139567759  1.39301222 two-sided
## 14    treat.fall_0_33 / seedmass Homog.  0.379597696 -0.56037523      less
## 15  treat.spring_0_33 / seedmass Homog.  0.214637021  0.72396063      less
## 16  treat.spring_1_33 / seedmass Homog.  0.373531903  1.81737276      less
## 17   cover_non_seeded / seedmass      r -0.296308977 -1.88005070 two-sided
## 18 cover_seeded_grass / seedmass      r  0.171063326  1.67743206 two-sided
##     Pvalue Pvalue.adj
## 1  0.96098          1
## 2        1          1
## 3  0.09186    0.33696
## 4  0.04484    0.26904
## 5  0.30246    0.60492
## 6  0.27164    0.60492
## 7  0.97644          1
## 8  0.90218          1
## 9  0.95928          1
## 10 0.02918    0.26904
## 11 0.57474          1
## 12 0.81528          1
## 13 0.16756    0.50268
## 14 0.29132    0.60492
## 15 0.75332          1
## 16 0.95442          1
## 17 0.03214    0.26904
## 18  0.0936    0.33696
##
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Plot

```r
plot(m_4th_adj, alpha = 0.05, stat = "D2")
```




```r
plot(m_4th_adj,
  x.rlq = m_rlq,
  alpha = 0.05,
  stat = "D2",
  type = "biplot"
)
```



Save

Session info

```
## R version 4.5.1 (2025-06-13 ucrt)
## Platform: x86_64-w64-mingw32/x64
## Running under: Windows 11 x64 (build 26100)
##
## Matrix products: default
##   LAPACK version 3.12.1
##
## locale:
## [1] LC_COLLATE=German_Germany.utf8  LC_CTYPE=German_Germany.utf8
## [3] LC_MONETARY=German_Germany.utf8 LC_NUMERIC=C
## [5] LC_TIME=German_Germany.utf8
##
## time zone: Europe/Berlin
## tzcode source: internal
##
## attached base packages:
## [1] stats     graphics  grDevices utils     datasets  methods   base
##
## other attached packages:
##  [1] ade4_1.7-23     lubridate_1.9.4 forcats_1.0.0   stringr_1.5.1
```

```
##  [5] dplyr_1.1.4     purrr_1.1.0     readr_2.1.5     tidyr_1.3.1
##  [9] tibble_3.3.0    ggplot2_3.5.2   tidyverse_2.0.0 here_1.0.1
## [13] tinytex_0.57
##
## loaded via a namespace (and not attached):
##  [1] bit_4.6.0          gtable_0.3.6       crayon_1.5.3       compiler_4.5.1
##  [5] Rcpp_1.1.0         tidyselect_1.2.1   parallel_4.5.1     scales_1.4.0
##  [9] yaml_2.3.10        fastmap_1.2.0      R6_2.6.1           generics_0.1.4
## [13] knitr_1.50         MASS_7.3-65        rprojroot_2.1.1    pillar_1.11.0
## [17] RColorBrewer_1.1-3 tzdb_0.5.0         rlang_1.1.6        utf8_1.2.6
## [21] stringi_1.8.7      xfun_0.52          bit64_4.6.0-1      timechange_0.3.0
## [25] cli_3.6.5          withr_3.0.2        magrittr_2.0.3     digest_0.6.37
## [29] grid_4.5.1         vroom_1.6.5        rstudioapi_0.17.1  hms_1.1.3
## [33] lifecycle_1.0.4    vctrs_0.6.5        evaluate_1.0.4     glue_1.8.0
## [37] farver_2.1.2       rmarkdown_2.29     tools_4.5.1        pkgconfig_2.0.3
## [41] htmltools_0.5.8.1
```