

Inverse Sizing and Exploration Based on Diffusion Models and Structural Knowledge

Abstract—Quick and effortless exploration of design spaces is of major importance in the face of rapid development cycles, varying specifications and increasingly complex circuits. It is also well known, that the exploitation of slack in specifications by making adjustments to transistor device sizes can lead to improved yield. We address those challenges by combining two state of the art machine learning approaches to achieve accurate generation of optimal performance points, while also allowing for the possibility to explore nearby sizings that might lead to more robust designs. To this end, a diffusion model is combined with an algorithm, that analyzes the circuit and splits the problem into simpler subproblems. The models are tested on a set of typical operational amplifiers.

I. INTRODUCTION

Since the development of SPICE, the industry accepted method for designing analog circuits has not changed much. While the SPICE models keep becoming more complex [1], the approach of manual device tuning persists [2]. Key challenges of making analog CAD tools useful in practice are robustness, ease of use and applicability to a high range of use cases. All those aspects are not easy to grasp on a fundamental level. On the other hand, machine learning approaches excel in modeling nonlinear black box phenomena. Their combination with already existing conventional techniques has a high potential to bridge remaining gaps, that prevent the adoption of tools in industry.

Analog design is inherently an inverse problem. While the calculation of performances, yield etc., is satisfactorily possible via simulation, the inverse, i.e. getting a circuit with optimal parametrization requires experience, trial and error and complex numerical routines. As shown in previous works [3], [4], machine learning (ML) methods can be used to accurately reproduce sizings on (pareto) optimal fronts. Furthermore, it has been shown [5] that diffusion models are well adaptable to the inverse sizing problem. Other ML based works attempted to solve this same problem. In [6], artificial neural networks (ANNs) are used to guess circuit sizings, utilizing only one ANN for modeling an entire netlist, leading to a higher learning task complexity and thus large sample sizes (in [6] 16600 or roughly $16 - 160x$ sample sizes used in this work) are required to learn the inverse problem within a smaller performance range. In [7], the problem is broken down into smaller tasks, and one ANN is trained to sequentially size a single device, in the same vein as [3], feeding the outputs of the previous ANNs to the input of the next, producing

a cascade of networks that can be sorted in different ways, until an optimal order is found. The drawback is that for more complex circuits of e.g. 15 devices, optimally ordering the ANNs for sizing leads to a complexity of $15!$.

Other works follow the traditional approach of tackling the direct sizing problem, treating it as an optimization problem [8]–[11]. Reinforcement learning was also studied, with [12]–[14] replacing the optimizer with an artificial neural network (ANN), leading to improvements in prediction speed, accuracy, and scalability. In the end, all of these works suffer from lengthy training and simulation times.

In this work, we explore the application of denoising diffusion probabilistic models (DDPM) to the sizing of OpAmps, utilizing the approach in [3] of subdividing the circuits into simpler structures, and by leveraging sampled sizings from the open-source tool FUBOCO [25]. These models efficacy in the inverse sizing problem were proven in [5]. Each DDPM is trained on a different structure of the target circuit, learning the corresponding distribution of sizes and respective performances by the noising and denoising process. After training, the DDPMs can be sampled to generate sizing values for each structure, which when combined make up the whole sizing solution of the target OpAmp. As shown in Section IV, this approach to the inverse problem can produce a more varied set of possible sizings, which is very helpful when exploring sizing options in the vicinity of performance optima. The contributions of this work are as follows:

- suggest valid sizings that perform in the vicinity of the required metrics, allowing for exploration of a sizing area of interest
- generate sizing solutions at push-button speed

In section II, we provide an overview of the proposed method and its connection to structural analysis. In sec. ??, we describe the sizing process in detail. We conclude with a presentation of results for two OpAmps.

II. FROM STRUCTURAL ANALYSIS TO CIRCUIT SIZING VIA MACHINE LEARNING

A. Basics of Structural and Functional Blocks

Our method heavily relies on decomposing circuits into subcircuits, which we call structural building blocks. Most building blocks are known to the analog designer by names such as *current mirror* or *differential pair*.

We further distinguish different functional variants of one and the same structural block. To this end, we assign to every transistor in a circuit its functional property, out of

Parts of this work have been done within the collaborative project HoLoDEC funded by the Federal Ministry of Education and Research Germany (BMBF) under the funding code 16ME0705.




Fig. 1: Splitting various OpAmps into canonical building blocks with different functional characteristics and accumulating intrinsic design know-how by training each building block with random optimal samples from all available OpAmps. Indices b , l and t represent *bias*, *load* and *transconductance* functionality of devices. Every building block maps the overall OpAmp performance to its sizing.

three different possibilities: *bias*, *load* or *transconductance*. For example, a *simple current mirror* (scm) can act as *load*, but in other parts of a circuit, the same building block can act as *bias*. And sometimes, some part of a current mirror can act as *load*, while another part acts as *bias*. Figure 1 shows all structural blocks and their functional variants from our dataset. An example of decomposing a Folded-Cascode OpAmp into blocks can be seen in figure 2a. Its structural building blocks are shaded, the names annotated close by. Structural and functional block recognition is fully automated. The time required for this is much less than one second.

B. Overview of the Method

III. CONCLUSION

REFERENCES

- [1] C. Gatermann and R. Sommer, “Teaching the mosfet: A circuit designer’s view,” in *2022 18th International Conference on Synthesis, Modeling, Analysis and Simulation Methods and Applications to Circuit Design (SMACD)*, 2022, pp. 1–4.
- [2] G. Gielen, “Analog synthesis 3.0: Ai/ml to synthesize and test analog ics: hope or hype ?” in *2023 ACM/IEEE 5th Workshop on Machine Learning for CAD (MLCAD)*, 2023, pp. 1–1.
- [3] M. Leibl and H. Graeb, “Optimizer-free sizing of opamps leveraging structural and functional properties,” in *2024 20th International Conference on Synthesis, Modeling, Analysis and Simulation Methods and Applications to Circuit Design (SMACD)*, 2024, pp. 1–4.
- [4] N. Lourenço, E. Afacan, R. Martins, F. Passos, A. Canelas, R. Póvoa, N. Horta, and G. Dundar, “Using polynomial regression and artificial neural networks for reusable analog ic sizing,” in *2019 16th International Conference on Synthesis, Modeling, Analysis and Simulation Methods and Applications to Circuit Design (SMACD)*, 2019, pp. 13–16.
- [5] P. Eid, F. Azevedo, R. Martins, and N. Lourenço, “Solving the inverse problem of analog integrated circuit sizing with diffusion models,” in *2024 20th International Conference on Synthesis, Modeling, Analysis and Simulation Methods and Applications to Circuit Design (SMACD)*, 2024, pp. 1–4.
- [6] N. Lourenço, J. Rosa, R. Martins, H. Aidos, A. Canelas, R. Póvoa, and N. Horta, “On the exploration of promising analog ic designs via artificial neural networks,” in *2018 15th International Conference on Synthesis, Modeling, Analysis and Simulation Methods and Applications to Circuit Design (SMACD)*, 2018, pp. 133–136.




Fig. 2: Instead of training one huge network per OpAmp, we can split an Opamp, e.g. OpAmp A, into blocks (shading and coloring in fig. 2a) and use weights from our network-database as initial training points to merely fine-tune our networks (2b).




Fig. 3: Histograms of some performance features for the Folded-Cascode OpAmp in Fig. 2a.

- [7] P.-O. Beaulieu, E. Dumesnil, F. Nabki, and M. Boukadoum, “Analog rf circuit sizing by a cascade of shallow neural networks,” *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, pp. 1–1, 2023.
- [8] M. Fayazi, M. T. Taba, E. Afshari, and R. Dreslinski, “Angel: Fully-automated analog circuit generator using a neural network assisted semi-supervised learning approach,” *IEEE Transactions on Circuits and Systems I: Regular Papers*, pp. 1–14, 2023.
- [9] A. F. Budak, D. Smart, B. Swahn, and D. Z. Pan, “Apostle: Asynchronously parallel optimization for sizing analog transistors using dnn learning,” in *2023 28th Asia and South Pacific Design Automation Conference (ASP-DAC)*, 2023, pp. 70–75.
- [10] G. Wolfe and R. Vemuri, “Extraction and use of neural network models in automated synthesis of operational amplifiers,” *IEEE Transactions*

on *Computer-Aided Design of Integrated Circuits and Systems*, vol. 22, no. 2, pp. 198–212, 2003.

- [11] K. Hakhamaneshi, M. Nassar, M. Phielipp, P. Abbeel, and V. Stojanovic, “Pretraining graph neural networks for few-shot analog circuit modeling and design,” *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, vol. 42, no. 7, pp. 2163–2173, 2023.
- [12] J. Gao, W. Cao, and X. Zhang, “Rose: Robust analog circuit parameter optimization with sampling-efficient reinforcement learning,” in *2023 60th ACM/IEEE Design Automation Conference (DAC)*, 2023, pp. 1–6.
- [13] K. Settaluri, Z. Liu, R. Khurana, A. Mirhaji, R. Jain, and B. Nikolic, “Automated design of analog circuits using reinforcement learning,” *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, vol. 41, no. 9, pp. 2794–2807, 2022.
- [14] J. Zhang, J. Bao, Z. Huang, X. Zeng, and Y. Lu, “Automated design of complex analog circuits with multiagent based reinforcement learning,” in *2023 60th ACM/IEEE Design Automation Conference (DAC)*, 2023, pp. 1–6.
- [15] B. Prautsch, U. Eichler, S. Rao, B. Zeugmann, A. Puppala, T. Reich, and J. Lienig, “Tip framework: A tool for reuse-centric analog circuit design,” in *2016 13th International Conference on Synthesis, Modeling, Analysis and Simulation Methods and Applications to Circuit Design (SMACD)*, 2016, pp. 1–4.
- [16] J. Crossley, A. Puggelli, H.-P. Le, B. Yang, R. Nancollas, K. Jung, L. Kong, N. Narevsky, Y. Lu, N. Sutardja, E. J. An, A. L. Sangiovanni-Vincentelli, and E. Alon, “Bag: A designer-oriented integrated framework for the development of ams circuit generators,” in *2013 IEEE/ACM International Conference on Computer-Aided Design (ICCAD)*, 2013, pp. 74–81.
- [17] M. Schweikardt and J. Scheible, “Expert design plan: A toolbox for procedural automation of analog integrated circuit design,” in *2022 18th International Conference on Synthesis, Modeling, Analysis and Simulation Methods and Applications to Circuit Design (SMACD)*, 2022, pp. 1–4.
- [18] M. Meissner and L. Hedrich, “Feats: Framework for explorative analog topology synthesis,” *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, vol. 34, no. 2, pp. 213–226, 2015.
- [19] I. Abel and H. Graeb, “Fuboco: Structure synthesis of basic op-amps by functional block composition,” *ACM Trans. Des. Autom. Electron. Syst.*, vol. 27, no. 6, jun 2022. [Online]. Available: <https://doi.org/10.1145/3522738>
- [20] K. Mendhurwar, H. Sundani, P. Aggarwal, R. Raut, and V. Devabhaktuni, “A new approach to sizing analog cmos building blocks using pre-compiled neural network models,” *Analog Integrated Circuits and Signal Processing*, vol. 70, pp. 265–281, 2012.
- [21] Z. Zhao, J. Luo, J. Liu, and L. Zhang, “Signal-division-aware analog circuit topology synthesis aided by transfer learning,” *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, vol. 42, no. 11, pp. 3481–3490, 2023.
- [22] A. Canelas, F. Passos, N. Lourenço, R. Martins, E. Roca, R. Castro-López, N. Horta, and F. V. Fernández, “Hierarchical yield-aware synthesis methodology covering device-, circuit-, and system-level for radiofrequency ics,” *IEEE Access*, vol. 9, pp. 124 152–124 164, 2021.
- [23] E. Tlelo-Cuautle, E. Martínez-Romero, C. Sánchez-López, and S. X.D.-Tan, “Symbolic behavioral modeling of low voltage amplifiers,” in *2010 7th International Conference on Electrical Engineering Computing Science and Automatic Control*, 2010, pp. 510–514.
- [24] P. Wambacq, F. Fernandez, G. Gielen, W. Sansen, and A. Rodriguez-Vazquez, “Efficient symbolic computation of approximated small-signal characteristics of analog integrated circuits,” *IEEE Journal of Solid-State Circuits*, vol. 30, no. 3, pp. 327–330, 1995.
- [25] Abel, I. and Neuner, M. and Eick M. Fuboco: Github repository. Technical University of Munich. [Online]. Available: <https://github.com/inga000/acst>