

Halogen-free, mud resistant instrumentation cable RFOU(i) 150/250(300)V, S1/S5

Flame retardant halogen-free instrumentation cable. Mud resistant

RFOU(i) 150/250(300)V

EPR/EPR/TCWB/EVA

NEK TS 606 CodeS1/S5



Operating temperature : 90°C
Operating Voltage : 150/250(300)V

Standards applied

Application

Fixed installation for instrumentation, communication, Control and alarm systems in both EX (Zone 0, 1 & 2)- and safe areas. Meets the mud resistant requirements in NEK TS 606:2009.

IEC 60092-376 (2003-05)	- Design
IEC 60228 class 2	- Conductor
IEC 60092-360	- Insulation
IEC 60092-360	- Sheath
IEC 60332-1-2	- Flame Retardant
IEC 60332-3-22	- Flame Retardant
IEC 60754-1,2	- Halogen Free
IEC 61034-1,2	- Low Smoke

Construction

	Code Letter	
Conductor		Tinned annealed stranded circular copper (STCC), IEC 60228 class 2
Insulation	R	EP-rubber, IEC 60092-360 (EPR)
Pair / Triple / Quad twisting		Color coded cores twisted together. Pairs/Triples are screened by copper backed polyester tape with tinned copper drain wire. Each pair/triple is wrapped with polyester tape to prevent electrical contact with adjacent pairs/triples. Pairs/triples are identified by numbered tape or by numbers printed directly on the insulated conductors.
Lay up / Shielding		Individually shielded pairs/triples/quads are laid up in concentric layers and wrapped with a PETP tape.
Inner covering	F	Flame retardant and halogen-free thermoset compound
Tape over inner covering		PET tape
Armour/screen	O	Tinned annealed copper wire braid
Tape over armour/screen		PET tape
Outer sheath	U	Flame retardant, halogen-free and mud resistant thermoset compound, SHF2 (IEC 60092-360)
Marking text		E.g. "meter" "year" DRAKA 01 RFOU(i) 250V S1/S5 4 PAIR 0,75 mm ² IEC 60092-376 IEC 60332-3-22
Manufacturing unit		DRAKA 01 = Draka Norsk Kabel,
Outer sheath colour		Grey or Blue

Core identification instrumentation cables

Pair - Black - Light Blue

Triple - Black - Light Blue - Brown

Quad - Black - Light Blue - Brown - Grey

Range and dimensions

Number of elements	No of cores in element	Cross section core, mm ²	Conductor Diameter, mm	Insulation Thickness, mm	Thickness Inner covering, mm	Diameter inner covering, mm	Diameter Braid Wire, mm	Mechanical cross-section of the braid, mm ²	Thickness Outer Sheath, mm	Diameter outer sheath, mm	Weight of Cable Approx. (Kg/Km)	Copper content Approx. (kg/km)
1	2	0.75	1.1	0.6	1.1	7 ± 0.5	0.2	3.8	1.1	10 ± 0.8	185	54
1	2	0.75	1.1	0.6	1.1	7 ± 0.5	0.2	3.8	1.1	10 ± 0.8	185	54
2	2	0.75	1.1	0.6	1.1	10 ± 0.8	0.2	5.3	1.2	13 ± 0.8	275	85
2	2	0.75	1.1	0.6	1.1	10 ± 0.8	0.2	5.3	1.2	13 ± 0.8	275	85
4	2	0.75	1.1	0.6	1.1	11.5 ± 0.8	0.3	10.2	1.3	15 ± 0.8	430	166
4	2	0.75	1.1	0.6	1.1	11.5 ± 0.8	0.3	10.2	1.3	15 ± 0.8	430	166
8	2	0.75	1.1	0.6	1.1	15.5 ± 0.8	0.3	13.6	1.5	19.5 ± 0.8	690	265
8	2	0.75	1.1	0.6	1.1	15.5 ± 0.8	0.3	13.6	1.5	19.5 ± 0.8	690	265
12	2	0.75	1.1	0.6	1.4	18.5 ± 0.8	0.3	15.3	1.6	23 ± 1	940	348
12	2	0.75	1.1	0.6	1.4	18.5 ± 0.8	0.3	15.3	1.6	23 ± 1	940	348
16	2	0.75	1.1	0.6	1.9	21.5 ± 1	0.3	17.8	1.7	26 ± 1	1240	439
16	2	0.75	1.1	0.6	1.9	21.5 ± 1	0.3	17.8	1.7	26 ± 1	1240	439
19	2	0.75	1.1	0.6	1.9	22.5 ± 1	0.3	17.8	1.7	27 ± 1	1360	489
19	2	0.75	1.1	0.6	1.9	22.5 ± 1	0.3	17.8	1.7	27 ± 1	1360	489
24	2	0.75	1.1	0.6	2.1	26.5 ± 1	0.3	20.4	1.9	31.5 ± 1.5	1720	596
24	2	0.75	1.1	0.6	2.1	26.5 ± 1	0.3	20.4	1.9	31.5 ± 1.5	1720	596
1	3	0.75	1.1	0.6	1.1	7.5 ± 0.5	0.2	3.8	1.1	10.5 ± 0.8	200	60
1	3	0.75	1.1	0.6	1.1	7.5 ± 0.5	0.2	3.8	1.1	10.5 ± 0.8	200	60
2	3	0.75	1.1	0.6	1.1	11 ± 0.8	0.3	8.5	1.3	14.5 ± 0.8	360	130
2	3	0.75	1.1	0.6	1.1	11 ± 0.8	0.3	8.5	1.3	14.5 ± 0.8	360	130
4	3	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	10.2	1.4	16.5 ± 0.8	510	192
4	3	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	10.2	1.4	16.5 ± 0.8	510	192
8	3	0.75	1.1	0.6	1.1	17 ± 0.8	0.3	13.6	1.5	21.5 ± 1	800	317
8	3	0.75	1.1	0.6	1.1	17 ± 0.8	0.3	13.6	1.5	21.5 ± 1	800	317
12	3	0.75	1.1	0.6	1.4	21 ± 1	0.3	17.8	1.7	25.5 ± 1	1160	450
12	3	0.75	1.1	0.6	1.4	21 ± 1	0.3	17.8	1.7	25.5 ± 1	1160	450
16	3	0.75	1.1	0.6	2.1	24.5 ± 1	0.3	17.8	1.8	29.5 ± 1	1540	542
16	3	0.75	1.1	0.6	2.1	24.5 ± 1	0.3	17.8	1.8	29.5 ± 1	1540	542
19	3	0.75	1.1	0.6	2.1	25.5 ± 1	0.3	20.4	1.8	30 ± 1.5	1720	636
24	3	0.75	1.1	0.6	2.5	30.5 ± 1.5	0.3	22.9	2	36 ± 1.5	2240	776
24	3	0.75	1.1	0.6	2.5	30.5 ± 1.5	0.3	22.9	2	36 ± 1.5	2240	776
1	2	1.5	1.6	0.7	1.1	8 ± 0.5	0.2	3.8	1.1	11 ± 0.8	230	71
1	2	1.5	1.6	0.7	1.1	8 ± 0.5	0.2	3.8	1.1	11 ± 0.8	230	71
2	2	1.5	1.6	0.7	1.1	12 ± 0.8	0.3	10.2	1.3	15.5 ± 0.8	420	168
2	2	1.5	1.6	0.7	1.1	12 ± 0.8	0.3	10.2	1.3	15.5 ± 0.8	420	168
4	2	1.5	1.6	0.7	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	600	252
4	2	1.5	1.6	0.7	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	600	252
8	2	1.5	1.6	0.7	1.1	19 ± 0.8	0.3	15.3	1.6	23.5 ± 1	980	420
8	2	1.5	1.6	0.7	1.1	19 ± 0.8	0.3	15.3	1.6	23.5 ± 1	980	420
12	2	1.5	1.6	0.7	1.4	23 ± 1	0.3	17.8	1.8	28 ± 1	1380	580
12	2	1.5	1.6	0.7	1.4	23 ± 1	0.3	17.8	1.8	28 ± 1	1380	580
16	2	1.5	1.6	0.7	1.9	26.5 ± 1	0.3	20.4	1.9	31.5 ± 1.5	1830	740

Number of elements	No of cores in element	Cross section core, mm ²	Conductor Diameter, mm	Insulation Thickness, mm	Thickness Inner covering, mm	Diameter inner covering, mm	Diameter Braid Wire, mm	Mechanical cross-section of the braid, mm ²	Thickness Outer Sheath, mm	Diameter outer sheath, mm	Weight of Cable Approx. (Kg/Km)	Copper content Approx. (kg/km)
16	2	1.5	1.6	0.7	1.9	26.5 ± 1	0.3	20.4	1.9	31.5 ± 1.5	1830	740
19	2	1.5	1.6	0.7	1.9	27.5 ± 1	0.3	22.9	1.9	32.5 ± 1.5	2040	866
19	2	1.5	1.6	0.7	1.9	27.5 ± 1	0.3	22.9	1.9	32.5 ± 1.5	2040	866
24	2	1.5	1.6	0.7	2.3	33 ± 1.5	0.4	36.2	2.2	39 ± 1.5	2790	1165
24	2	1.5	1.6	0.7	2.3	33 ± 1.5	0.4	36.2	2.2	39 ± 1.5	2790	1165
32	2	1.5	1.6	0.7	2.4	37 ± 1.5	0.4	40.7	2.3	43 ± 2	3440	1480
1	3	1.5	1.6	0.7	1.1	8.5 ± 0.5	0.2	4.5	1.1	11.5 ± 0.8	260	93
1	3	1.5	1.6	0.7	1.1	8.5 ± 0.5	0.2	4.5	1.1	11.5 ± 0.8	260	93
2	3	1.5	1.6	0.7	1.1	13.5 ± 0.8	0.3	11.9	1.4	17.5 ± 0.8	510	212
4	3	1.5	1.6	0.7	1.1	15.5 ± 0.8	0.3	13.6	1.5	20 ± 1	740	325
4	3	1.5	1.6	0.7	1.1	15.5 ± 0.8	0.3	13.6	1.5	20 ± 1	740	325
8	3	1.5	1.6	0.7	1.1	21.5 ± 1	0.3	17.8	1.7	26 ± 1	1230	557
8	3	1.5	1.6	0.7	1.1	21.5 ± 1	0.3	17.8	1.7	26 ± 1	1230	557
12	3	1.5	1.6	0.7	1.4	26 ± 1	0.3	20.4	1.9	31 ± 1.5	1740	774
12	3	1.5	1.6	0.7	1.4	26 ± 1	0.3	20.4	1.9	31 ± 1.5	1740	774
16	3	1.5	1.6	0.7	2.3	31 ± 1.5	0.3	22.9	2	36 ± 1.5	2420	990
16	3	1.5	1.6	0.7	2.3	31 ± 1.5	0.3	22.9	2	36 ± 1.5	2420	990
24	3	1.5	1.6	0.7	2.5	38 ± 1.5	0.4	40.7	2.3	44 ± 2	3570	1547
24	3	1.5	1.6	0.7	2.5	38 ± 1.5	0.4	40.7	2.3	44 ± 2	3570	1547
1	2	2.5	2	0.7	1.1	9 ± 0.5	0.2	4.5	1.1	12 ± 0.8	280	99
2	2	2.5	2	0.7	1.1	13.5 ± 0.8	0.3	11.9	1.4	17.5 ± 0.8	530	225
2	2	2.5	2	0.7	1.1	13.5 ± 0.8	0.3	11.9	1.4	17.5 ± 0.8	530	225
4	2	2.5	2	0.7	1.1	16 ± 0.8	0.3	13.6	1.5	20 ± 1	770	350

Electrical values instrumentation cables

Type	Capacitance, approx. (nF/km)	Inductance, approx. (mH/km)	Resistance at 20°C, max. (Ohm/km)	L/R ratio, (microH/Ohm)
Shielded pair 0,75 mm ²	110	0,67	26,3	12,7
Shielded triple 0,75 mm ²	110	0,67	26,3	12,7
Shielded pair 1,5 mm ²	125	0,63	12,9	24,4
Shielded triple 1,5 mm ²	125	0,63	12,9	24,4
Shielded pair 2,5 mm ²	145	0,59	8,02	36,8
Shielded triple 2,5 mm ²	145	0,59	8,02	36,8

Ordering information

New Part number	Old Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
20110590		RFOU(I) 1PAIR 0.75mm ² S1/S5	GREY	Yes	7021528920000	1044620
20105042		RFOU(I) 1PAIR 0.75mm ² S1/S5	BLUE	Yes	7021528920017	1044619
20110591		RFOU(I) 2PAIR 0.75mm ² S1/S5	GREY	Yes	7021528920062	1044621
20110592		RFOU(I) 2PAIR 0.75mm ² S1/S5	BLUE	-	7021528920079	1044622
20110593		RFOU(I) 4PAIR 0.75mm ² S1/S5	GREY	Yes	7021528920185	1044623
20110849		RFOU(I) 4PAIR 0.75mm ² S1/S5	BLUE	-	7021528920192	1044624
20110594		RFOU(I) 8PAIR 0.75mm ² S1/S5	GREY	Yes	7021528920307	1044628
20104951		RFOU(I) 8PAIR 0.75mm ² S1/S5	BLUE	-	7021528920314	1044629
20110850		RFOU(I) 12PAIR 0.75mm ² S1/S5	GREY	-	7021528920369	1044630
20131006		RFOU(I) 12PAIR 0.75mm ² S1/S5	BLUE	-	7021528920376	1044631
	892042	RFOU(I) 16PAIR 0.75mm ² S1/S5	GREY	-	7021528920420	1044633
	892043	RFOU(I) 16PAIR 0.75mm ² S1/S5	BLUE	-	7021528920437	1044632
	892045	RFOU(I) 19PAIR 0.75mm ² S1/S5	GREY	-	7021528920451	1044634
	892046	RFOU(I) 19PAIR 0.75mm ² S1/S5	BLUE	-	7021528920468	1044635
20110595		RFOU(I) 24PAIR 0.75mm ² S1/S5	GREY	-	7021528920482	1044636
	892049	RFOU(I) 24PAIR 0.75mm ² S1/S5	BLUE	-	7021528920499	1044637

New Part number	Old Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
20104949		RFOU(I) 1TRIP 0.75mm ² S1/S5	GREY	Yes	7021528920604	1044690
20110596		RFOU(I) 1TRIP 0.75mm ² S1/S5	BLUE	-	7021528920611	1044689
20110851		RFOU(I) 2TRIP 0.75mm ² S1/S5	GREY	-	7021528920666	1044691
	892067	RFOU(I) 2TRIP 0.75mm ² S1/S5	BLUE	-	7021528920673	1044692
20110852		RFOU(I) 4TRIP 0.75mm ² S1/S5	GREY	-	7021528920789	1044693
	892079	RFOU(I) 4TRIP 0.75mm ² S1/S5	BLUE	-	7021528920796	1044694
	892090	RFOU(I) 8TRIP 0.75mm ² S1/S5	GREY	-	7021528920901	1044697
	892091	RFOU(I) 8TRIP 0.75mm ² S1/S5	BLUE	-	7021528920918	1044698
	892096	RFOU(I) 12TRIP 0.75mm ² S1/S5	GREY	-	7021528920963	1044699
	892097	RFOU(I) 12TRIP 0.75mm ² S1/S5	BLUE	-	7021528920970	1044700
	892102	RFOU(I) 16TRIP 0.75mm ² S1/S5	GREY	-	7021528921021	1044701
	892103	RFOU(I) 16TRIP 0.75mm ² S1/S5	BLUE	-	7021528921038	1044702
	892106	RFOU(I) 19TRIP 0.75mm ² S1/S5	GREY	-	7021528921069	-
	892108	RFOU(I) 24TRIP 0.75mm ² S1/S5	GREY	-	7021528921083	1044707
	892109	RFOU(I) 24TRIP 0.75mm ² S1/S5	BLUE	-	7021528921090	1044708
20110597		RFOU(I) 1PAIR 1.5mm ² S1/S5	GREY	Yes	7021528922004	1044460
20110598		RFOU(I) 1PAIR 1.5mm ² S1/S5	BLUE	Yes	7021528922011	1044459
20110599		RFOU(I) 2PAIR 1.5mm ² S1/S5	GREY	Yes	7021528922066	1044661
20111211		RFOU(I) 2PAIR 1.5mm ² S1/S5	BLUE	-	7021528922073	1044662
20110600		RFOU(I) 4PAIR 1.5mm ² S1/S5	GREY	Yes	7021528922189	1044663
20110601		RFOU(I) 4PAIR 1.5mm ² S1/S5	BLUE	-	7021528922196	1044664
20110602		RFOU(I) 8PAIR 1.5mm ² S1/S5	GREY	Yes	7021528922301	1044668
20110603		RFOU(I) 8PAIR 1.5mm ² S1/S5	BLUE	Yes	7021528922318	1044669
20110604		RFOU(I) 12PAIR 1.5mm ² S1/S5	GREY	Yes	7021528922363	1044670
20110605		RFOU(I) 12PAIR 1.5mm ² S1/S5	BLUE	-	7021528922370	1044671
20110606		RFOU(I) 16PAIR 1.5mm ² S1/S5	GREY	Yes	7021528922424	1044673
20110607		RFOU(I) 16PAIR 1.5mm ² S1/S5	BLUE	-	7021528922431	1044672
	892245	RFOU(I) 19PAIR 1.5mm ² S1/S5	GREY	-	7021528922455	1044674
	892246	RFOU(I) 19PAIR 1.5mm ² S1/S5	BLUE	-	7021528922462	1044675
	892248	RFOU(I) 24PAIR 1.5mm ² S1/S5	GREY	-	7021528922486	1044678
20110853		RFOU(I) 24PAIR 1.5mm ² S1/S5	BLUE	-	7021528922493	1044679
	892254	RFOU(I) 32PAIR 1.5mm ² S1/S5	GREY	-	7021528922547	-
20110608		RFOU(I) 1TRIP 1.5mm ² S1/S5	GREY	-	7021528922608	1044560
20110609		RFOU(I) 1TRIP 1.5mm ² S1/S5	BLUE	-	7021528922615	1044559
	892266	RFOU(I) 2TRIP 1.5mm ² S1/S5	GREY	-	7021528922660	1044762
	892278	RFOU(I) 4TRIP 1.5mm ² S1/S5	GREY	-	7021528922783	1044764
	892279	RFOU(I) 4TRIP 1.5mm ² S1/S5	BLUE	-	7021528922790	1044765
20110610		RFOU(I) 8TRIP 1.5mm ² S1/S5	GREY	-	7021528922905	1044768
	892291	RFOU(I) 8TRIP 1.5mm ² S1/S5	BLUE	-	7021528922912	1044769
	892296	RFOU(I) 12TRIP 1.5mm ² S1/S5	GREY	-	7021528922967	1044770
	892297	RFOU(I) 12TRIP 1.5mm ² S1/S5	BLUE	-	7021528922974	1044771
	892302	RFOU(I) 16TRIP 1.5mm ² S1/S5	GREY	-	7021528923025	1044773
	892303	RFOU(I) 16TRIP 1.5mm ² S1/S5	BLUE	-	7021528923032	1044772
	892308	RFOU(I) 24TRIP 1.5mm ² S1/S5	GREY	-	7021528923087	1044779
	892309	RFOU(I) 24TRIP 1.5mm ² S1/S5	BLUE	-	7021528923094	1044780
20110854		RFOU(I) 1PAIR 2.5mm ² S1/S5	GREY	-	7021528924008	-
20110855		RFOU(I) 2PAIR 2.5mm ² S1/S5	GREY	-	7021528924060	-
	892407	RFOU(I) 2PAIR 2.5mm ² S1/S5	BLUE	-	7021528924077	-
20110856		RFOU(I) 4PAIR 2.5mm ² S1/S5	GREY	-	7021528924183	-

Installation recommendations

Minimum Bending Radius during Installation	Minimum Bending Radius Fixed Installed	Maximum Tensile Load During Installation	Minimum Installation Temperature
8 x D	6 x D	50 N /mm ²	-20°C

Halogen-free, mud resistant instrumentation cable RFOU(c) 150/250(300)V, S2/S6

Flame retardant halogen-free instrumentation cable. Mud resistant

RFOU(c) 150/250(300)V

EPR/EPR/TCWB/EVA

NEK TS 606 CodeS2/S6



Operating temperature
Operating Voltage

: 90°C
: 150/250(300)V

Standards applied

Application

Fixed installation for instrumentation, communication, Control and alarm systems in both EX (Zone 0, 1 & 2)- and safe areas. Meets the mud resistant requirements in NEK TS 606:2009.

IEC 60092-376 (2003-05)
IEC 60228 class 2
IEC 60092-360
IEC 60092-360
IEC 60332-1-2
IEC 60332-3-22
IEC 60754-1,2
IEC 61034-1,2

- Design
- Conductor
- Insulation
- Sheath
- Flame Retardant
- Flame Retardant
- Halogen Free
- Low Smoke

Construction

	Code Letter	
Conductor		Tinned annealed stranded circular copper (STCC), IEC 60228 class 2
Insulation	R	EP-rubber, IEC 60092-360 (EPR)
Pair / Triple / Quad twisting		Color coded cores twisted together and wrapped with polyester tape. Pairs/Triples are laid up collectively and screened by copper backed polyester tape with tinned copper drain wire. Pairs/triples are identified by numbered tape or by numbers printed directly on the insulated conductors.
Inner covering	F	Flame retardant and halogen-free thermoset compound
Tape over inner covering		PET tape
Armour/screen	O	Tinned annealed copper wire braid
Tape over armour/screen		PET tape
Outer sheath	U	Flame retardant, halogen-free and mud resistant thermoset compound, SHF2 (IEC 60092-360)
Marking text		E.g. "meter" "year" DRAKA 01 RFOU(c) 250V S2/S6 8 PAIR 0,75 mm ² IEC 60092-376 IEC 60332-3-22
Manufacturing unit		DRAKA 01 = Draka Norsk Kabel,
Outer sheath colour		Grey or Blue

Core identification instrumentation cables

Pair - Black - Light Blue

Triple - Black - Light Blue - Brown

Quad - Black - Light Blue - Brown - Grey

Range and dimensions

Number of elements	No of cores in element	Cross section core, mm ²	Conductor Diameter, mm	Insulation Thickness, mm	Thickness Inner covering, mm	Diameter inner covering, mm	Diameter Braid Wire, mm	Mechanical cross-section of the braid, mm ²	Thickness Outer Sheath, mm	Diameter outer sheath, mm	Weight of Cable Approx. (Kg/Km)	Copper content Approx. (kg/km)
2	2	0.75	1.1	0.6	1.1	10 ± 0.8	0.2	5.3	1.2	13 ± 0.8	270	81
2	2	0.75	1.1	0.6	1.1	10 ± 0.8	0.2	5.3	1.2	13 ± 0.8	270	81
4	2	0.75	1.1	0.6	1.1	11.5 ± 0.8	0.3	8.5	1.3	15 ± 0.8	390	138
4	2	0.75	1.1	0.6	1.1	11.5 ± 0.8	0.3	8.5	1.3	15 ± 0.8	390	139
8	2	0.75	1.1	0.6	1.1	15 ± 0.8	0.3	11.9	1.4	19 ± 0.8	600	223
8	2	0.75	1.1	0.6	1.1	15 ± 0.8	0.3	11.9	1.4	19 ± 0.8	600	223
12	2	0.75	1.1	0.6	1.4	18 ± 0.8	0.3	15.3	1.5	22 ± 1	820	307
12	2	0.75	1.1	0.6	1.4	18 ± 0.8	0.3	15.3	1.5	22 ± 1	820	307
16	2	0.75	1.1	0.6	1.9	20.5 ± 1	0.3	15.3	1.6	24.5 ± 1	1040	358
16	2	0.75	1.1	0.6	1.9	20.5 ± 1	0.3	15.3	1.6	24.5 ± 1	1040	358
19	2	0.75	1.1	0.6	1.9	21.5 ± 1	0.3	17.8	1.6	25.5 ± 1	1160	422
24	2	0.75	1.1	0.6	2.1	25 ± 1	0.3	20.4	1.8	29.5 ± 1	1450	510
24	2	0.75	1.1	0.6	2.1	25 ± 1	0.3	20.4	1.8	29.5 ± 1	1450	510
2	3	0.75	1.1	0.6	1.1	11 ± 0.8	0.2	5.3	1.2	14 ± 0.8	310	94
2	3	0.75	1.1	0.6	1.1	11 ± 0.8	0.2	5.3	1.2	14 ± 0.8	310	94
4	3	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	10.2	1.3	16.5 ± 0.8	470	181
4	3	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	10.2	1.3	16.5 ± 0.8	470	181
8	3	0.75	1.1	0.6	1.1	17 ± 0.8	0.3	13.6	1.5	21 ± 1	740	291
8	3	0.75	1.1	0.6	1.1	17 ± 0.8	0.3	13.6	1.5	21 ± 1	740	291
12	3	0.75	1.1	0.6	1.4	20 ± 1	0.3	15.3	1.6	24.5 ± 1	1010	384
12	3	0.75	1.1	0.6	1.4	20 ± 1	0.3	15.3	1.6	24.5 ± 1	1010	384
16	3	0.75	1.1	0.6	2.1	23 ± 1	0.3	17.8	1.7	27.5 ± 1	1350	486
24	3	0.75	1.1	0.6	2.3	28 ± 1	0.3	20.4	1.9	33 ± 1.5	1860	664
24	3	0.75	1.1	0.6	2.3	28 ± 1	0.3	20.4	1.9	33 ± 1.5	1860	664
2	2	1.5	1.6	0.7	1.1	12 ± 0.8	0.3	10.2	1.3	15.5 ± 0.8	410	162
2	2	1.5	1.6	0.7	1.1	12 ± 0.8	0.3	10.2	1.3	15.5 ± 0.8	410	162
4	2	1.5	1.6	0.7	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	560	234
4	2	1.5	1.6	0.7	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	560	234
8	2	1.5	1.6	0.7	1.1	18.5 ± 0.8	0.3	15.3	1.6	23 ± 1	890	379
8	2	1.5	1.6	0.7	1.1	18.5 ± 0.8	0.3	15.3	1.6	23 ± 1	890	379
10	2	1.5	1.6	0.7	1.2	21 ± 1	0.3	17.8	1.7	25.5 ± 1	1070	459
10	2	1.5	1.6	0.7	1.2	21 ± 1	0.3	17.8	1.7	25.5 ± 1	1070	459
12	2	1.5	1.6	0.7	1.4	22 ± 1	0.3	17.8	1.7	26.5 ± 1	1210	515
12	2	1.5	1.6	0.7	1.4	22 ± 1	0.3	17.8	1.7	26.5 ± 1	1210	515
16	2	1.5	1.6	0.7	1.9	25 ± 1	0.3	20.4	1.8	29.5 ± 1	1580	651
16	2	1.5	1.6	0.7	1.9	25 ± 1	0.3	20.4	1.8	29.5 ± 1	1580	651
19	2	1.5	1.6	0.7	1.9	26.5 ± 1	0.3	20.4	1.9	31 ± 1.5	1750	735
24	2	1.5	1.6	0.7	2.3	31 ± 1.5	0.3	25.4	2.1	36.5 ± 1.5	2270	924
32	2	1.5	1.6	0.7	2.4	34 ± 1.5	0.4	36.2	2.2	40 ± 2	2890	1252
32	2	1.5	1.6	0.7	2.4	34 ± 1.5	0.4	36.2	2.2	40 ± 2	2890	1252
2	3	1.5	1.6	0.7	1.1	13 ± 0.8	0.3	10.2	1.4	17 ± 0.8	480	190
2	3	1.5	1.6	0.7	1.1	13 ± 0.8	0.3	10.2	1.4	17 ± 0.8	480	190
4	3	1.5	1.6	0.7	1.1	15.5 ± 0.8	0.3	11.9	1.4	19.5 ± 0.8	670	290
8	3	1.5	1.6	0.7	1.1	21 ± 1	0.3	17.8	1.7	25.5 ± 1	1130	516
12	3	1.5	1.6	0.7	1.4	24.5 ± 1	0.3	20.4	1.8	29.5 ± 1	1560	708
12	3	1.5	1.6	0.7	1.4	24.5 ± 1	0.3	20.4	1.8	29.5 ± 1	1560	708
16	3	1.5	1.6	0.7	2.1	28 ± 1	0.3	22.9	1.9	33 ± 1.5	2080	900
16	3	1.5	1.6	0.7	2.1	28 ± 1	0.3	22.9	1.9	33 ± 1.5	2080	900
24	3	1.5	1.6	0.7	2.5	35 ± 1.5	0.4	36.2	2.2	41 ± 2	3110	1365

Number of elements	No of cores in element	Cross section core, mm ²	Conductor Diameter, mm	Insulation Thickness, mm	Thickness Inner covering, mm	Diameter inner covering, mm	Diameter Braid Wire, mm	Mechanical cross-section of the braid, mm ²	Thickness Outer Sheath, mm	Diameter outer sheath, mm	Weight of Cable Approx. (Kg/Km)	Copper content Approx. (kg/km)
24	3	1.5	1.6	0.7	2.5	35 ± 1.5	0.4	36.2	2.2	41 ± 2	3110	1365
2	2	2.5	2	0.7	1.1	13.5 ± 0.8	0.3	10.2	1.4	17.5 ± 0.8	490	200
4	2	2.5	2	0.7	1.1	16 ± 0.8	0.3	11.9	1.4	19.5 ± 0.8	680	309
4	2	2.5	2	0.7	1.1	16 ± 0.8	0.3	11.9	1.4	19.5 ± 0.8	680	309
12	2	2.5	2	0.7	2.1	27 ± 1	0.3	20.4	1.8	31.5 ± 1.5	1740	759

Electrical values instrumentation cables

Type	Capacitance, approx. (nF/km)	Inductance, approx. (mH/km)	Resistance at 20°C, max. (Ohm/km)	L/R ratio, (microH/Ohm)
Unshielded pair 0,75 mm ²	100	0,67	26,3	12,7
Unshielded triple 0,75 mm ²	100	0,67	26,3	12,7
Unshielded pair 1,5 mm ²	110	0,63	12,9	24,4
Unshielded triple 1,5 mm ²	110	0,63	12,9	24,4
Unshielded pair 2,5 mm ²	125	0,59	8,02	36,8
Unshielded triple 2,5 mm ²	125	0,59	8,02	36,8

Ordering information

New Part number	Old Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
20110611		RFOU(C) 2PAIR 0.75mm ² S2/S6	GREY	Yes	7021528926064	1044421
20110857		RFOU(C) 2PAIR 0.75mm ² S2/S6	BLUE	-	7021528926071	1044422
20110612		RFOU(C) 4PAIR 0.75mm ² S2/S6	GREY	Yes	7021528926187	1044423
20110613		RFOU(C) 4PAIR 0.75mm ² S2/S6	BLUE	-	7021528926194	1044424
20110614		RFOU(C) 8PAIR 0.75mm ² S2/S6	GREY	-	7021528926309	1044428
20110772		RFOU(C) 8PAIR 0.75mm ² S2/S6	BLUE	-	7021528926316	1044429
20110615		RFOU(C) 12PAIR 0.75mm ² S2/S6	GREY	-	7021528926361	1044430
	892637	RFOU(C) 12PAIR 0.75mm ² S2/S6	BLUE	-	7021528926378	1044431
20109493		RFOU(C) 16PAIR 0.75mm ² S2/S6	GREY	-	7021528926422	1044433
	892643	RFOU(C) 16PAIR 0.75mm ² S2/S6	BLUE	-	7021528926439	1044432
	892645	RFOU(C) 19PAIR 0.75mm ² S2/S6	GREY	-	7021528926453	1044434
20109494		RFOU(C) 24PAIR 0.75mm ² S2/S6	GREY	-	7021528926484	1044438
	892649	RFOU(C) 24PAIR 0.75mm ² S2/S6	BLUE	-	7021528926491	1044437
20110858		RFOU(C) 2TRIP 0.75mm ² S2/S6	GREY	-	7021528926668	1044490
20110616		RFOU(C) 2TRIP 0.75mm ² S2/S6	BLUE	-	7021528926675	1044491
20110859		RFOU(C) 4TRIP 0.75mm ² S2/S6	GREY	-	7021528926781	1044492
	892679	RFOU(C) 4TRIP 0.75mm ² S2/S6	BLUE	-	7021528926798	1044493
20120514		RFOU(C) 8TRIP 0.75mm ² S2/S6	GREY	-	7021528926903	1044496
	892691	RFOU(C) 8TRIP 0.75mm ² S2/S6	BLUE	-	7021528926910	1044497
	892696	RFOU(C) 12TRIP 0.75mm ² S2/S6	GREY	-	7021528926965	1044499
	892697	RFOU(C) 12TRIP 0.75mm ² S2/S6	BLUE	-	7021528926972	1044500
	892702	RFOU(C) 16TRIP 0.75mm ² S2/S6	GREY	-	7021528927023	1044501
	892708	RFOU(C) 24TRIP 0.75mm ² S2/S6	GREY	-	7021528927085	1044507
	892709	RFOU(C) 24TRIP 0.75mm ² S2/S6	BLUE	-	7021528927092	1044508
20110617		RFOU(C) 2PAIR 1.5mm ² S2/S6	GREY	Yes	7021528928068	1044461
20110618		RFOU(C) 2PAIR 1.5mm ² S2/S6	BLUE	-	7021528928075	1044462
20110619		RFOU(C) 4PAIR 1.5mm ² S2/S6	GREY	Yes	7021528928181	1044463
20110620		RFOU(C) 4PAIR 1.5mm ² S2/S6	BLUE	-	7021528928198	1044464
20110621		RFOU(C) 8PAIR 1.5mm ² S2/S6	GREY	Yes	7021528928303	1044468
	892831	RFOU(C) 8PAIR 1.5mm ² S2/S6	BLUE	-	7021528928310	1044469
	892834	RFOU(C) 10PAIR 1.5mm ² S2/S6	GREY	-	7021528928341	-
	892835	RFOU(C) 10PAIR 1.5mm ² S2/S6	BLUE	-	7021528928358	-
20110622		RFOU(C) 12PAIR 1.5mm ² S2/S6	GREY	-	7021528928365	1044470
	892837	RFOU(C) 12PAIR 1.5mm ² S2/S6	BLUE	-	7021528928372	-
20109495		RFOU(C) 16PAIR 1.5mm ² S2/S6	GREY	Yes	7021528928426	1044472
	892843	RFOU(C) 16PAIR 1.5mm ² S2/S6	BLUE	-	7021528928433	1044473
	892845	RFOU(C) 19PAIR 1.5mm ² S2/S6	GREY	-	7021528928457	1044474
20110860		RFOU(C) 24PAIR 1.5mm ² S2/S6	GREY	-	7021528928488	1044478
	892854	RFOU(C) 32PAIR 1.5mm ² S2/S6	GREY	-	7021528928549	-

New Part number	Old Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
	892855	RFOU(C) 32PAIR 1.5mm ² S2/S6	BLUE	-	7021528928556	-
20110861		RFOU(C) 2TRIP 1.5mm ² S2/S6	GREY	-	7021528928662	1044561
	892867	RFOU(C) 2TRIP 1.5mm ² S2/S6	BLUE	-	7021528928679	-
	892878	RFOU(C) 4TRIP 1.5mm ² S2/S6	GREY	-	7021528928785	1044563
	892891	RFOU(C) 8TRIP 1.5mm ² S2/S6	BLUE	-	7021528928914	1044568
	892896	RFOU(C) 12TRIP 1.5mm ² S2/S6	GREY	-	7021528928969	1044569
	892897	RFOU(C) 12TRIP 1.5mm ² S2/S6	BLUE	-	7021528928976	1044570
	892902	RFOU(C) 16TRIP 1.5mm ² S2/S6	GREY	-	7021528929027	1044571
	892903	RFOU(C) 16TRIP 1.5mm ² S2/S6	BLUE	-	7021528929034	1044572
	892908	RFOU(C) 24TRIP 1.5mm ² S2/S6	GREY	-	7021528929089	1044577
	892909	RFOU(C) 24TRIP 1.5mm ² S2/S6	BLUE	-	7021528929096	1044578
	893006	RFOU(C) 2PAIR 2.5mm ² S2/S6	GREY	-	7021528930061	-
20120742		RFOU(C) 4PAIR 2.5mm ² S2/S6	GREY	-	7021528930184	-
20110862		RFOU(C) 4PAIR 2.5mm ² S2/S6	BLUE	-	7021528930191	-
20110863		RFOU(C) 12PAIR 2.5mm ² S2/S6	GREY	-	7021528930368	-

Installation recommendations

Minimum Bending Radius during Installation	Minimum Bending Radius Fixed Installed	Maximum Tensile Load During Installation	Minimum Installation Temperature
8 x D	6 x D	50 N /mm ²	-20°C

Halogen-free, mud resistant, fire resistant instrumentation cable BFOU(i)
150/250(300)V, S3/S7



Fire resistant, flame retardant halogen-free instrumentation cable. Mud resistant

BFOU(i) 150/250(300)V
MGT/EPR/EPR/TCWB/EVA

NEK TS 606 CodeS3/S7

Operating temperature : 90°C
Operating Voltage : 150/250(300)V

Application

Fixed installation for instrumentation, communication, control and alarm systems in both EX (Zone 0, 1 & 2)- and safe areas, emergency and critical systems where requirement for fire resistance exists. Meets the mud resistant requirements in NEK TS 606:2009.

Standards applied

IEC 60092-376 (2003-05)	- Design
IEC 60228 class 2	- Conductor
IEC 60092-360	- Insulation
IEC 60092-360	- Sheath
IEC 60332-1-2	- Flame Retardant
IEC 60332-3-22	- Flame Retardant
IEC 60331-1, -2, -21	- Fire Resistant
IEC 60754-1,2	- Halogen Free
IEC 61034-1,2	- Low Smoke

Construction

	Code Letter	
Conductor		Tinned annealed stranded circular copper (STCC), IEC 60228 class 2
Insulation	B	Mica-tape + EP-rubber, IEC 60092-360 (EPR)
Pair / Triple / Quad twisting		Color coded cores twisted together. Pairs/Triples are screened by copper backed polyester tape with tinned copper drain wire. Each pair/triple is wrapped with polyester tape to prevent electrical contact with adjacent pairs/triples. Pairs/triples are identified by numbered tape or by numbers printed directly on the insulated conductors.
Lay up / Shielding		Individually shielded pairs/triples/quads are laid up in concentric layers and wrapped with a PETP tape.
Inner covering	F	Flame retardant and halogen-free thermoplastic compound
Tape over inner covering		PET tape
Armour/screen	O	Tinned annealed copper wire braid
Tape over armour/screen		PET tape
Outer sheath	U	Flame retardant, halogen-free and mud resistant thermoset compound, SHF2 (IEC 60092-360)
Marking text		Eg. "meter" "year" DRAKA 01 BFOU(i) 250V S3/S7 16 PAIR 0,75 mm ² FLEX - FLAME IEC 60092-376 IEC 60331-1*) or IEC 60331-2*) IEC 60331-21**) IEC 60332-3-22
Manufacturing unit		DRAKA 01 = Draka Norsk Kabel
Outer sheath colour		Grey or Blue

*) IEC 60331-1 for cables with an overall diameter exceeding 20 mm and IEC 60331-2 for cables with an overall diameter not exceeding 20 mm

**) IEC 60331-21 also at enhanced temperature 1000°C for 180 minutes

Core identification instrumentation cables

Pair - Black - Light Blue

Triple - Black - Light Blue - Brown

Quad - Black - Light Blue - Brown - Grey

Range and dimensions

Number of elements	No of cores in element	Cross section core, mm ²	Conductor Diameter, mm	Insulation Thickness, mm	Thickness Inner covering, mm	Diameter inner covering, mm	Diameter Braid Wire, mm	Mechanical cross-section of the braid, mm ²	Thickness Outer Sheath, mm	Diameter outer sheath, mm	Weight of Cable Approx. (Kg/Km)	Copper content Approx. (kg/km)
1	2	0.75	1.1	0.6	1.1	7.5 ± 0.5	0.2	3.8	1.1	10.5 ± 0.8	200	54
1	2	0.75	1.1	0.6	1.1	7.5 ± 0.5	0.2	3.8	1.1	10.5 ± 0.8	200	54
1	4	0.75	1.1	0.6	1.1	8.5 ± 0.5	0.2	4.5	1.2	12 ± 0.8	250	74
2	2	0.75	1.1	0.6	1.1	11 ± 0.8	0.3	10.2	1.3	14.5 ± 0.8	360	133
2	2	0.75	1.1	0.6	1.1	11 ± 0.8	0.3	10.2	1.3	14.5 ± 0.8	360	133
4	2	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	11.9	1.4	16.5 ± 0.8	490	183
4	2	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	11.9	1.4	16.5 ± 0.8	490	183
8	2	0.75	1.1	0.6	1.1	17 ± 0.8	0.3	15.3	1.6	21.5 ± 1	780	283
8	2	0.75	1.1	0.6	1.1	17 ± 0.8	0.3	15.3	1.6	21.5 ± 1	780	283
12	2	0.75	1.1	0.6	1.4	20.5 ± 1	0.3	17.8	1.7	25 ± 1	1060	373
12	2	0.75	1.1	0.6	1.4	20.5 ± 1	0.3	17.8	1.7	25 ± 1	1060	373
16	2	0.75	1.1	0.6	1.9	24 ± 1	0.3	20.4	1.8	28.5 ± 1	1400	465
16	2	0.75	1.1	0.6	1.9	24 ± 1	0.3	20.4	1.8	28.5 ± 1	1400	465
19	2	0.75	1.1	0.6	1.9	25 ± 1	0.3	20.4	1.9	29.5 ± 1	1550	514
19	2	0.75	1.1	0.6	1.9	25 ± 1	0.3	20.4	1.9	29.5 ± 1	1550	514
24	2	0.75	1.1	0.6	2.3	30 ± 1.5	0.4	31.7	2.1	35.5 ± 1.5	2100	708
24	2	0.75	1.1	0.6	2.3	30 ± 1.5	0.4	31.7	2.1	35.5 ± 1.5	2100	708
1	3	0.75	1.1	0.6	1.1	8 ± 0.5	0.2	4.5	1.1	11 ± 0.8	220	68
1	3	0.75	1.1	0.6	1.1	8 ± 0.5	0.2	4.5	1.1	11 ± 0.8	220	68
2	3	0.75	1.1	0.6	1.1	12 ± 0.8	0.3	10.2	1.4	15.5 ± 0.8	410	146
2	3	0.75	1.1	0.6	1.1	12 ± 0.8	0.3	10.2	1.4	15.5 ± 0.8	410	146
4	3	0.75	1.1	0.6	1.1	14 ± 0.8	0.3	11.9	1.4	17.5 ± 0.8	570	209
4	3	0.75	1.1	0.6	1.1	14 ± 0.8	0.3	11.9	1.4	17.5 ± 0.8	570	209
8	3	0.75	1.1	0.6	1.1	18.5 ± 0.8	0.3	17.8	1.7	23 ± 1	960	359
8	3	0.75	1.1	0.6	1.1	18.5 ± 0.8	0.3	17.8	1.7	23 ± 1	960	359
12	3	0.75	1.1	0.6	1.4	22.5 ± 1	0.3	20.4	1.8	27.5 ± 1	1310	477
12	3	0.75	1.1	0.6	1.4	22.5 ± 1	0.3	20.4	1.8	27.5 ± 1	1310	477
16	3	0.75	1.1	0.6	2.1	26.5 ± 1	0.3	22.9	1.9	31.5 ± 1.5	1770	594
16	3	0.75	1.1	0.6	2.1	26.5 ± 1	0.3	22.9	1.9	31.5 ± 1.5	1770	594
19	3	0.75	1.1	0.6	2.3	28 ± 1	0.3	22.9	2	33 ± 1.5	2000	663
24	3	0.75	1.1	0.6	2.5	33 ± 1.5	0.4	36.2	2.2	39 ± 1.5	2630	909
24	3	0.75	1.1	0.6	2.5	33 ± 1.5	0.4	36.2	2.2	39 ± 1.5	2630	909
1	2	1.5	1.6	0.7	1.1	9 ± 0.5	0.2	4.5	1.2	12 ± 0.8	260	79
1	2	1.5	1.6	0.7	1.1	9 ± 0.5	0.2	4.5	1.2	12 ± 0.8	260	79
2	2	1.5	1.6	0.7	1.1	13 ± 0.8	0.3	11.9	1.4	17 ± 0.8	470	184
2	2	1.5	1.6	0.7	1.1	13 ± 0.8	0.3	11.9	1.4	17 ± 0.8	470	184
4	2	1.5	1.6	0.7	1.1	15.5 ± 0.8	0.3	13.6	1.5	19.5 ± 0.8	670	269
4	2	1.5	1.6	0.7	1.1	15.5 ± 0.8	0.3	13.6	1.5	19.5 ± 0.8	670	269
8	2	1.5	1.6	0.7	1.1	21 ± 1	0.3	17.8	1.7	25.5 ± 1	1090	446
8	2	1.5	1.6	0.7	1.1	21 ± 1	0.3	17.8	1.7	25.5 ± 1	1090	446
12	2	1.5	1.6	0.7	1.4	25.5 ± 1	0.3	20.4	1.9	30.5 ± 1	1530	606

Number of elements	No of cores in element	Cross section core, mm ²	Conductor Diameter, mm	Insulation Thickness, mm	Thickness Inner covering, mm	Diameter inner covering, mm	Diameter Braid Wire, mm	Mechanical cross-section of the braid, mm ²	Thickness Outer Sheath, mm	Diameter outer sheath, mm	Weight of Cable Approx. (Kg/Km)	Copper content Approx. (kg/km)
										1.5		
12	2	1.5	1.6	0.7	1.4	25.5 ± 1	0.3	20.4	1.9	30.5 ± 1.5	1530	606
16	2	1.5	1.6	0.7	2.1	30 ± 1.5	0.3	22.9	2	35 ± 1.5	2060	766
16	2	1.5	1.6	0.7	2.1	30 ± 1.5	0.3	22.9	2	35 ± 1.5	2060	766
19	2	1.5	1.6	0.7	2.1	31 ± 1.5	0.4	36.2	2.1	36.5 ± 1.5	2440	998
24	2	1.5	1.6	0.7	2.3	36.5 ± 1.5	0.4	40.7	2.3	43 ± 2	3080	1211
24	2	1.5	1.6	0.7	2.3	36.5 ± 1.5	0.4	40.7	2.3	43 ± 2	3080	1211
1	3	1.5	1.6	0.7	1.1	9.5 ± 0.5	0.2	4.5	1.2	12.5 ± 0.8	290	93
1	3	1.5	1.6	0.7	1.1	9.5 ± 0.5	0.2	4.5	1.2	12.5 ± 0.8	290	93
2	3	1.5	1.6	0.7	1.1	14.5 ± 0.8	0.3	11.9	1.5	18.5 ± 0.8	550	213
2	3	1.5	1.6	0.7	1.1	14.5 ± 0.8	0.3	11.9	1.5	18.5 ± 0.8	550	213
4	3	1.5	1.6	0.7	1.1	17 ± 0.8	0.3	15.3	1.6	21 ± 1	820	342
4	3	1.5	1.6	0.7	1.1	17 ± 0.8	0.3	15.3	1.6	21 ± 1	820	342
8	3	1.5	1.6	0.7	1.1	22.5 ± 1	0.3	20.4	1.8	27 ± 1	1370	584
8	3	1.5	1.6	0.7	1.1	22.5 ± 1	0.3	20.4	1.8	27 ± 1	1370	584
12	3	1.5	1.6	0.7	1.6	28.5 ± 1	0.3	22.9	2	33.5 ± 1.5	1970	802
12	3	1.5	1.6	0.7	1.6	28.5 ± 1	0.3	22.9	2	33.5 ± 1.5	1970	802
16	3	1.5	1.6	0.9	2.3	36.5 ± 1.5	0.4	36.2	2.2	42.5 ± 2	3060	1125
16	3	1.5	1.6	0.9	2.3	36.5 ± 1.5	0.4	36.2	2.2	42.5 ± 2	3060	1125
24	3	1.5	1.6	0.9	2.7	45.5 ± 2	0.4	45.2	2.5	52 ± 2.5	4400	1598
24	3	1.5	1.6	0.9	2.7	45.5 ± 2	0.4	45.2	2.5	52 ± 2.5	4400	1598
1	2	2.5	2	0.7	1.1	9.5 ± 0.5	0.2	4.5	1.2	13 ± 0.8	300	99
1	2	2.5	2	0.7	1.1	9.5 ± 0.5	0.2	4.5	1.2	13 ± 0.8	300	99
2	2	2.5	2	0.7	1.1	14.5 ± 0.8	0.3	11.9	1.5	18.5 ± 0.8	560	225
4	2	2.5	2	0.7	1.1	17 ± 0.8	0.3	15.3	1.6	21.5 ± 1	830	367
8	2	2.5	2	0.7	1.1	23.5 ± 1	0.3	20.4	1.8	28 ± 1	1390	633
12	2	2.5	2	0.7	2.3	30 ± 1.5	0.3	22.9	2	35.5 ± 1.5	2170	874
16	2	2.5	2	0.9	2.3	36.5 ± 1.5	0.4	36.2	2.2	42.5 ± 2	3040	1222
1	3	2.5	2	0.7	1.1	10.5 ± 0.8	0.2	5.3	1.2	13.5 ± 0.8	350	129
8	3	2.5	2	0.7	1.3	25.5 ± 1	0.3	22.9	2	30.5 ± 1.5	1820	844
12	3	2.5	2	0.7	2.6	33.5 ± 1.5	0.4	36.2	2.2	39.5 ± 1.5	2940	1284

Electrical values instrumentation cables

Type	Capacitance, approx. (nF/km)	Inductance, approx. (mH/km)	Resistance at 20°C, max. (Ohm/km)	L/R ratio, (microH/Ohm)
Shielded pair 0,75 mm ²	110	0,67	26,3	12,7
Shielded triple 0,75 mm ²	110	0,67	26,3	12,7
Shielded pair 1,5 mm ²	125	0,63	12,9	24,4
Shielded triple 1,5 mm ²	125	0,63	12,9	24,4
Shielded pair 2,5 mm ²	145	0,59	8,02	36,8
Shielded triple 2,5 mm ²	145	0,59	8,02	36,8
Shielded 16 and 24 triple 1,5 mm ²	105	0,71	12,9	24,4
Shielded 16 pair 2,5 mm ²	110	0,66	8,02	41,1

Ordering information

New Part number	Old Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
20110623		BFOU(I) 1PAIR 0.75mm ² S3/S7	GREY	Yes	7021528932003	1043820
20110624		BFOU(I) 1PAIR 0.75mm ² S3/S7	BLUE	Yes	7021528932010	1043819
20110625		BFOU(I) 1QUAD 0.75mm ² S3/S7	GREY	-	7021528932034	-
20110626		BFOU(I) 2PAIR 0.75mm ² S3/S7	GREY	Yes	7021528932065	1044020
20104969		BFOU(I) 2PAIR 0.75mm ² S3/S7	BLUE	Yes	7021528932072	1044019
20110627		BFOU(I) 4PAIR 0.75mm ² S3/S7	GREY	Yes	7021528932188	1044021
20110628		BFOU(I) 4PAIR 0.75mm ² S3/S7	BLUE	-	7021528932195	1044022
20109496		BFOU(I) 8PAIR 0.75mm ² S3/S7	GREY	Yes	7021528932300	1044028
20110773		BFOU(I) 8PAIR 0.75mm ² S3/S7	BLUE	-	7021528932317	1044029
20110629		BFOU(I) 12PAIR 0.75mm ² S3/S7	GREY	-	7021528932362	1044030
20110630		BFOU(I) 12PAIR 0.75mm ² S3/S7	BLUE	-	7021528932379	1044031
20110631		BFOU(I) 16PAIR 0.75mm ² S3/S7	GREY	Yes	7021528932423	1044033
20110632		BFOU(I) 16PAIR 0.75mm ² S3/S7	BLUE	-	7021528932430	1044034
	893245	BFOU(I) 19PAIR 0.75mm ² S3/S7	GREY	-	7021528932454	-
	893246	BFOU(I) 19PAIR 0.75mm ² S3/S7	BLUE	-	7021528932461	-
20110633		BFOU(I) 24PAIR 0.75mm ² S3/S7	GREY	-	7021528932485	1044036
	893249	BFOU(I) 24PAIR 0.75mm ² S3/S7	BLUE	-	7021528932492	1044037
20110634		BFOU(I) 1TRIP 0.75mm ² S3/S7	GREY	Yes	7021528932607	1043920
20110635		BFOU(I) 1TRIP 0.75mm ² S3/S7	BLUE	-	7021528932614	1043919
20110636		BFOU(I) 2TRIP 0.75mm ² S3/S7	GREY	-	7021528932669	1044121
20110864		BFOU(I) 2TRIP 0.75mm ² S3/S7	BLUE	-	7021528932676	1044122
20111212		BFOU(I) 4TRIP 0.75mm ² S3/S7	GREY	-	7021528932782	1044123
20110865		BFOU(I) 4TRIP 0.75mm ² S3/S7	BLUE	-	7021528932799	1044124
20110637		BFOU(I) 8TRIP 0.75mm ² S3/S7	GREY	-	7021528932904	1044128
20112240		BFOU(I) 8TRIP 0.75mm ² S3/S7	BLUE	-	7021528932911	1044129
20110878		BFOU(I) 12TRIP 0.75mm ² S3/S7	GREY	-	7021528932966	1044130
	893297	BFOU(I) 12TRIP 0.75mm ² S3/S7	BLUE	-	7021528932973	1044131
20110774		BFOU(I) 16TRIP 0.75mm ² S3/S7	GREY	-	7021528933024	1044132
	893303	BFOU(I) 16TRIP 0.75mm ² S3/S7	BLUE	-	7021528933031	-
	893305	BFOU(I) 19TRIP 0.75mm ² S3/S7	GREY	-	7021528933055	-
20131938		BFOU(I) 24TRIP 0.75mm ² S3/S7	GREY	-	7021528933086	1044138
	893309	BFOU(I) 24TRIP 0.75mm ² S3/S7	BLUE	-	7021528933093	1044139
20110638		BFOU(I) 1PAIR 1.5mm ² S3/S7	GREY	Yes	7021528934007	1043860
20110639		BFOU(I) 1PAIR 1.5mm ² S3/S7	BLUE	Yes	7021528934014	1043859
20110640		BFOU(I) 2PAIR 1.5mm ² S3/S7	GREY	Yes	7021528934069	1044060
20111213		BFOU(I) 2PAIR 1.5mm ² S3/S7	BLUE	-	7021528934076	1044061
20110641		BFOU(I) 4PAIR 1.5mm ² S3/S7	GREY	Yes	7021528934182	1044063
20110642		BFOU(I) 4PAIR 1.5mm ² S3/S7	BLUE	-	7021528934199	1044064
20110643		BFOU(I) 8PAIR 1.5mm ² S3/S7	GREY	Yes	7021528934304	1044068
20110644		BFOU(I) 8PAIR 1.5mm ² S3/S7	BLUE	-	7021528934311	1044069
20110645		BFOU(I) 12PAIR 1.5mm ² S3/S7	GREY	Yes	7021528934366	1044070
20110646		BFOU(I) 12PAIR 1.5mm ² S3/S7	BLUE	-	7021528934373	1044071
20109497		BFOU(I) 16PAIR 1.5mm ² S3/S7	GREY	Yes	7021528934427	1044073
20109498		BFOU(I) 16PAIR 1.5mm ² S3/S7	BLUE	-	7021528934434	1044074
	893445	BFOU(I) 19PAIR 1.5mm ² S3/S7	GREY	-	7021528934458	-
20109499		BFOU(I) 24PAIR 1.5mm ² S3/S7	GREY	Yes	7021528934489	1044076
20109500		BFOU(I) 24PAIR 1.5mm ² S3/S7	BLUE	-	7021528934496	-
20110647		BFOU(I) 1TRIP 1.5mm ² S3/S7	GREY	Yes	7021528934601	1044170
20110648		BFOU(I) 1TRIP 1.5mm ² S3/S7	BLUE	-	7021528934618	1044169
20110866		BFOU(I) 2TRIP 1.5mm ² S3/S7	GREY	-	7021528934663	1044171
	893467	BFOU(I) 2TRIP 1.5mm ² S3/S7	BLUE	-	7021528934670	-
20109501		BFOU(I) 4TRIP 1.5mm ² S3/S7	GREY	-	7021528934786	1044173
20117428		BFOU(I) 4TRIP 1.5mm ² S3/S7	BLUE	-	7021528934793	1044174
20110649		BFOU(I) 8TRIP 1.5mm ² S3/S7	GREY	-	7021528934908	1044177
20117424		BFOU(I) 8TRIP 1.5mm ² S3/S7	BLUE	-	7021528934915	1044178
20109502		BFOU(I) 12TRIP 1.5mm ² S3/S7	GREY	-	7021528934960	1044179
	893497	BFOU(I) 12TRIP 1.5mm ² S3/S7	BLUE	-	7021528934977	1044180
20109503		BFOU(I) 16TRIP 1.5mm ² S3/S7	GREY	-	7021528935028	1044181
	893503	BFOU(I) 16TRIP 1.5mm ² S3/S7	BLUE	-	7021528935035	1044182
	893508	BFOU(I) 24TRIP 1.5mm ² S3/S7	GREY	-	7021528935080	1044193
	893509	BFOU(I) 24TRIP 1.5mm ² S3/S7	BLUE	-	7021528935097	1044194
20110650		BFOU(I) 1PAIR 2.5mm ² S3/S7	GREY	Yes	7021528936001	1044140
20110867		BFOU(I) 1PAIR 2.5mm ² S3/S7	BLUE	-	7021528936018	-
	893606	BFOU(I) 2PAIR 2.5mm ² S3/S7	GREY	-	7021528936063	-
20110868		BFOU(I) 4PAIR 2.5mm ² S3/S7	GREY	-	7021528936186	-

New Part number	Old Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
	893630	BFOU(I) 8PAIR 2.5mm ² S3/S7	GREY	-	7021528936308	-
	893636	BFOU(I) 12PAIR 2.5mm ² S3/S7	GREY	-	7021528936360	-
20109504		BFOU(I) 16PAIR 2.5mm ² S3/S7	GREY	-	7021528936421	-
20110869		BFOU(I) 1TRIP 2.5mm ² S3/S7	GREY	-	7021528936605	-
	893690	BFOU(I) 8TRIP 2.5mm ² S3/S7	GREY	-	7021528936902	-
	893696	BFOU(I) 12TRIP 2.5mm ² S3/S7	GREY	-	7021528936964	-

Installation recommendations

Minimum Bending Radius during Installation	Minimum Bending Radius Fixed Installed	Maximum Tensile Load During Installation	Minimum Installation Temperature
8 x D	6 x D	50 N /mm ²	-20°C

Halogen-free, mud resistant, fire resistant instrumentation cable BFOU(c)
150/250(300)V, S4/S8

Fire resistant, flame retardant halogen-free
instrumentation cable. Mud resistant

BFOU(c) 150/250(300)V

MGT/EPR/EPR/TCWB/EVA

NEK TS 606 CodeS4/S8



Operating temperature
Operating Voltage

: 90°C
: 150/250(300)V

Standards applied

Application

Fixed installation for instrumentation, communication, control and alarm systems in both EX (Zone 0, 1 & 2)- and safe areas, emergency and critical systems where requirement for fire resistance exists. Meets the mud resistant requirements in NEK TS 606:2009.

IEC 60092-376 (2003-05)
IEC 60228 class 2
IEC 60092-360
IEC 60092-360
IEC 60332-1-2
IEC 60332-3-22
IEC 60331-1, -2, -21
IEC 60754-1,2
IEC 61034-1,2

- Design
- Conductor
- Insulation
- Sheath
- Flame Retardant
- Flame Retardant
- Fire Resistant
- Halogen Free
- Low Smoke

Construction

	Code Letter	
Conductor		Tinned annealed stranded circular copper (STCC), IEC 60228 class 2
Insulation	B	Mica-tape + EP-rubber, IEC 60092-360 (EPR)
Pair / Triple / Quad twisting		Color coded cores twisted together and wrapped with polyester tape. Pairs/Triples are laid up collectively and screened by copper backed polyester tape with tinned copper drain wire. Pairs/triples are identified by numbered tape or by numbers printed directly on the insulated conductors.
Inner covering	F	Flame retardant and halogen-free thermoplastic compound
Tape over inner covering		PET tape
Armour/screen	O	Tinned annealed copper wire braid
Tape over armour/screen		PET tape
Outer sheath	U	Flame retardant, halogen-free and mud resistant thermoset compound, SHF2 (IEC 60092-360)
Marking text		Eg. "meter" "year" DRAKA 01 BFOU(c) 250V S4/S8 4 PAIR 0,75 mm ² FLEX - FLAME IEC 60092-376 IEC 60331-1*) or IEC 60331-2*) IEC 60331-21**) IEC 60332-3-22
Manufacturing unit		DRAKA 01 = Draka Norsk Kabel
Outer sheath colour		Grey or Blue

*) IEC 60331-1 for cables with an overall diameter exceeding 20 mm and IEC 60331-2 for cables with an overall diameter not exceeding 20 mm

**) IEC 60331-21 also at enhanced temperature 1000°C for 180 minutes

Core identification instrumentation cables

Pair - Black - Light Blue

Triple - Black - Light Blue - Brown

Quad - Black - Light Blue - Brown - Grey

Range and dimensions

Number of elements	No of cores in element	Cross section core, mm ²	Conductor Diameter, mm	Insulation Thickness, mm	Thickness Inner covering, mm	Diameter inner covering, mm	Diameter Braid Wire, mm	Mechanical cross-section of the braid, mm ²	Thickness Outer Sheath, mm	Diameter outer sheath, mm	Weight of Cable Approx. (Kg/Km)	Copper content Approx. (kg/km)
2	2	0.75	1.1	0.6	1.1	10.5 ± 0.8	0.3	8.5	1.3	14.5 ± 0.8	340	113
2	2	0.75	1.1	0.6	1.1	10.5 ± 0.8	0.3	8.5	1.3	14.5 ± 0.8	340	113
4	2	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	10.2	1.4	16 ± 0.8	440	155
4	2	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	10.2	1.4	16 ± 0.8	440	155
8	2	0.75	1.1	0.6	1.1	16.5 ± 0.8	0.3	13.6	1.5	20.5 ± 1	680	240
8	2	0.75	1.1	0.6	1.1	16.5 ± 0.8	0.3	13.6	1.5	20.5 ± 1	680	240
12	2	0.75	1.1	0.6	1.4	19.5 ± 0.8	0.3	15.3	1.6	24 ± 1	910	307
12	2	0.75	1.1	0.6	1.4	19.5 ± 0.8	0.3	15.3	1.6	24 ± 1	910	307
16	2	0.75	1.1	0.6	1.9	22 ± 1	0.3	17.8	1.7	26.5 ± 1	1180	383
16	2	0.75	1.1	0.6	1.9	22 ± 1	0.3	17.8	1.7	26.5 ± 1	1180	383
19	2	0.75	1.1	0.6	1.9	23 ± 1	0.3	20.4	1.8	28 ± 1	1330	447
24	2	0.75	1.1	0.6	2.3	27.5 ± 1	0.3	22.9	2	32.5 ± 1.5	1700	536
24	2	0.75	1.1	0.6	2.3	27.5 ± 1	0.3	22.9	2	32.5 ± 1.5	1700	536
2	3	0.75	1.1	0.6	1.1	12 ± 0.8	0.3	10.2	1.3	15.5 ± 0.8	400	142
2	3	0.75	1.1	0.6	1.1	12 ± 0.8	0.3	10.2	1.3	15.5 ± 0.8	400	142
4	3	0.75	1.1	0.6	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	540	197
4	3	0.75	1.1	0.6	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	540	197
8	3	0.75	1.1	0.6	1.1	18.5 ± 0.8	0.3	15.3	1.6	23 ± 1	870	308
8	3	0.75	1.1	0.6	1.1	18.5 ± 0.8	0.3	15.3	1.6	23 ± 1	870	308
12	3	0.75	1.1	0.6	1.4	22 ± 1	0.3	17.8	1.8	27 ± 1	1180	410
12	3	0.75	1.1	0.6	1.4	22 ± 1	0.3	17.8	1.8	27 ± 1	1180	410
16	3	0.75	1.1	0.6	2.1	25.5 ± 1	0.3	20.4	1.9	30.5 ± 1.5	1580	513
16	3	0.75	1.1	0.6	2.1	25.5 ± 1	0.3	20.4	1.9	30.5 ± 1.5	1580	513
24	3	0.75	1.1	0.6	2.5	31.5 ± 1.5	0.4	36.2	2.1	37 ± 1.5	2350	820
2	2	1.5	1.6	0.7	1.1	13 ± 0.8	0.3	10.2	1.4	16.5 ± 0.8	440	162
2	2	1.5	1.6	0.7	1.1	13 ± 0.8	0.3	10.2	1.4	16.5 ± 0.8	440	162
4	2	1.5	1.6	0.7	1.1	15 ± 0.8	0.3	11.9	1.4	19 ± 0.8	600	234
4	2	1.5	1.6	0.7	1.1	15 ± 0.8	0.3	11.9	1.4	19 ± 0.8	600	234
8	2	1.5	1.6	0.7	1.1	20 ± 1	0.3	17.8	1.7	24.5 ± 1	990	404
8	2	1.5	1.6	0.7	1.1	20 ± 1	0.3	17.8	1.7	24.5 ± 1	990	404
12	2	1.5	1.6	0.7	1.4	24 ± 1	0.3	20.4	1.8	28.5 ± 1	1350	540
12	2	1.5	1.6	0.7	1.4	24 ± 1	0.3	20.4	1.8	28.5 ± 1	1350	540
16	2	1.5	1.6	0.7	1.9	27 ± 1	0.3	22.9	1.9	31.5 ± 1.5	1750	677
16	2	1.5	1.6	0.7	1.9	27 ± 1	0.3	22.9	1.9	31.5 ± 1.5	1750	677
24	2	1.5	1.6	0.7	2.3	33.5 ± 1.5	0.4	36.2	2.2	39.5 ± 1.5	2620	1030
24	2	1.5	1.6	0.7	2.3	33.5 ± 1.5	0.4	36.2	2.2	39.5 ± 1.5	2620	1030
2	3	1.5	1.6	0.7	1.1	14.5 ± 1	0.3	11.9	1.4	18.5 ± 1	540	207

Number of elements	No of cores in element	Cross section core, mm ²	Conductor Diameter, mm	Insulation Thickness, mm	Thickness Inner covering, mm	Diameter inner covering, mm	Diameter Braid Wire, mm	Mechanical cross-section of the braid, mm ²	Thickness Outer Sheath, mm	Diameter outer sheath, mm	Weight of Cable Approx. (Kg/Km)	Copper content Approx. (kg/km)
						0.8				0.8		
2	3	1.5	1.6	0.7	1.1	14.5 ± 0.8	0.3	11.9	1.4	18.5 ± 0.8	540	207
4	3	1.5	1.6	0.7	1.1	17 ± 0.8	0.3	13.6	1.5	21 ± 1	760	307
4	3	1.5	1.6	0.7	1.1	17 ± 0.8	0.3	13.6	1.5	21 ± 1	760	307
8	3	1.5	1.6	0.7	1.1	22.5 ± 1	0.3	17.8	1.8	27 ± 1	1270	516
8	3	1.5	1.6	0.7	1.1	22.5 ± 1	0.3	17.8	1.8	27 ± 1	1270	516
12	3	1.5	1.6	0.7	1.4	27 ± 1	0.3	22.9	1.9	32 ± 1.5	1750	734
12	3	1.5	1.6	0.7	1.4	27 ± 1	0.3	22.9	1.9	32 ± 1.5	1750	734
16	3	1.5	1.6	0.7	2.3	31.5 ± 1.5	0.4	36.2	2.1	37 ± 1.5	2540	1032
16	3	1.5	1.6	0.7	2.3	31.5 ± 1.5	0.4	36.2	2.1	37 ± 1.5	2540	1032
24	3	1.5	1.6	0.7	2.7	38.5 ± 1.5	0.4	40.7	2.4	45 ± 2	3580	1417
2	2	2.5	2	0.7	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	530	217
4	2	2.5	2	0.7	1.1	16.5 ± 0.8	0.3	13.6	1.5	20.5 ± 1	740	325
8	2	2.5	2	0.7	1.1	22 ± 1	0.3	17.8	1.8	27 ± 1	1230	551
12	2	2.5	2	0.7	2.1	28 ± 1	0.3	22.9	1.9	32.5 ± 1.5	1860	784
16	2	2.5	2	0.9	2.3	33 ± 1.5	0.4	31.7	2.1	39 ± 1.5	2600	1054
24	2	2.5	2	0.9	2.7	41 ± 2	0.4	40.7	2.4	47.5 ± 2	3780	1511
4	3	2.5	2	0.7	1.1	18.5 ± 0.8	0.3	15.3	1.6	23 ± 1	950	435
8	3	2.5	2	0.7	1.1	25 ± 1	0.3	20.4	1.9	30 ± 1.5	1620	761
16	3	2.5	2	0.9	2.6	38.5 ± 1.5	0.4	36.2	2.3	44.5 ± 2	3570	1473

Electrical values instrumentation cables

Type	Capacitance, approx. (nF/km)	Inductance, approx. (mH/km)	Resistance at 20°C, max. (Ohm/km)	L/R ratio, (microH/Ohm)
Unshielded pair 0,75 mm ²	100	0,67	26,3	12,7
Unshielded triple 0,75 mm ²	100	0,67	26,3	12,7
Unshielded pair 1,5 mm ²	110	0,63	12,9	24,4
Unshielded triple 1,5 mm ²	110	0,63	12,9	24,4
Unshielded pair 2,5 mm ²	125	0,59	8,02	36,8
Unshielded triple 2,5 mm ²	125	0,59	8,02	36,8
Unshielded 16 and 24 pair 2,5 mm ²	95	0,66	8,02	41,1
Unshielded 16 triple 2,5 mm ²	95	0,66	8,02	41,1

Ordering information

New Part number	Old Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
20110651		BFOU(C) 2PAIR 0.75mm ² S4/S8	GREY	Yes	7021528938067	1043821
20110652		BFOU(C) 2PAIR 0.75mm ² S4/S8	BLUE	Yes	7021528938074	1043822
20110653		BFOU(C) 4PAIR 0.75mm ² S4/S8	GREY	Yes	7021528938180	1043823
20110654		BFOU(C) 4PAIR 0.75mm ² S4/S8	BLUE	Yes	7021528938197	1043824
20110655		BFOU(C) 8PAIR 0.75mm ² S4/S8	GREY	Yes	7021528938302	1043828
20110656		BFOU(C) 8PAIR 0.75mm ² S4/S8	BLUE	Yes	7021528938319	1043829
20110657		BFOU(C) 12PAIR 0.75mm ² S4/S8	GREY	Yes	7021528938364	1043830
20110658		BFOU(C) 12PAIR 0.75mm ² S4/S8	BLUE	-	7021528938371	1043831
20110659		BFOU(C) 16PAIR 0.75mm ² S4/S8	GREY	Yes	7021528938425	1043833
20110660		BFOU(C) 16PAIR 0.75mm ² S4/S8	BLUE	-	7021528938432	1043834
	893845	BFOU(C) 19PAIR 0.75mm ² S4/S8	GREY	-	7021528938456	-
20109505		BFOU(C) 24PAIR 0.75mm ² S4/S8	GREY	Yes	7021528938487	1043836
20118235		BFOU(C) 24PAIR 0.75mm ² S4/S8	BLUE	-	7021528938494	1043837
20110661		BFOU(C) 2TRIP 0.75mm ² S4/S8	GREY	-	7021528938661	1043921
	893867	BFOU(C) 2TRIP 0.75mm ² S4/S8	BLUE	-	7021528938678	1043922
20110662		BFOU(C) 4TRIP 0.75mm ² S4/S8	GREY	-	7021528938784	1043924
20118161		BFOU(C) 4TRIP 0.75mm ² S4/S8	BLUE	-	7021528938791	1043925
20110663		BFOU(C) 8TRIP 0.75mm ² S4/S8	GREY	-	7021528938906	1043928

New Part number	Old Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
20113359		BFOU(C) 8TRIP 0.75mm ² S4/S8	BLUE	Yes	7021528938913	1043929
20110664		BFOU(C) 12TRIP 0.75mm ² S4/S8	GREY	-	7021528938968	1043930
	893897	BFOU(C) 12TRIP 0.75mm ² S4/S8	BLUE	-	7021528938975	1043931
20110665		BFOU(C) 16TRIP 0.75mm ² S4/S8	GREY	-	7021528939026	1043933
	893903	BFOU(C) 16TRIP 0.75mm ² S4/S8	BLUE	-	7021528939033	1043934
	893908	BFOU(C) 24TRIP 0.75mm ² S4/S8	GREY	-	7021528939088	1043936
20110666		BFOU(C) 2PAIR 1.5mm ² S4/S8	GREY	Yes	7021528940060	1043862
20110667		BFOU(C) 2PAIR 1.5mm ² S4/S8	BLUE	-	7021528940077	1043861
20110668		BFOU(C) 4PAIR 1.5mm ² S4/S8	GREY	Yes	7021528940183	1043863
20110669		BFOU(C) 4PAIR 1.5mm ² S4/S8	BLUE	-	7021528940190	1043864
20110670		BFOU(C) 8PAIR 1.5mm ² S4/S8	GREY	Yes	7021528940305	1043868
20110671		BFOU(C) 8PAIR 1.5mm ² S4/S8	BLUE	-	7021528940312	1043869
20110672		BFOU(C) 12PAIR 1.5mm ² S4/S8	GREY	Yes	7021528940367	1043870
20110673		BFOU(C) 12PAIR 1.5mm ² S4/S8	BLUE	-	7021528940374	1043871
20109506		BFOU(C) 16PAIR 1.5mm ² S4/S8	GREY	Yes	7021528940428	1043873
20109507		BFOU(C) 16PAIR 1.5mm ² S4/S8	BLUE	-	7021528940435	1043874
20109508		BFOU(C) 24PAIR 1.5mm ² S4/S8	GREY	Yes	7021528940480	1043876
20109509		BFOU(C) 24PAIR 1.5mm ² S4/S8	BLUE	-	7021528940497	1043877
20110775		BFOU(C) 2TRIP 1.5mm ² S4/S8	GREY	-	7021528940664	1043971
	894067	BFOU(C) 2TRIP 1.5mm ² S4/S8	BLUE	-	7021528940671	1043972
20110674		BFOU(C) 4TRIP 1.5mm ² S4/S8	GREY	-	7021528940787	1043973
	894079	BFOU(C) 4TRIP 1.5mm ² S4/S8	BLUE	-	7021528940794	1043974
20110675		BFOU(C) 8TRIP 1.5mm ² S4/S8	GREY	Yes	7021528940909	1043977
	894091	BFOU(C) 8TRIP 1.5mm ² S4/S8	BLUE	-	7021528940916	1043978
20109510		BFOU(C) 12TRIP 1.5mm ² S4/S8	GREY	-	7021528940961	1043979
	894097	BFOU(C) 12TRIP 1.5mm ² S4/S8	BLUE	-	7021528940978	-
20109511		BFOU(C) 16TRIP 1.5mm ² S4/S8	GREY	Yes	7021528941029	1043981
	894103	BFOU(C) 16TRIP 1.5mm ² S4/S8	BLUE	-	7021528941036	1043982
20110776		BFOU(C) 24TRIP 1.5mm ² S4/S8	GREY	-	7021528941081	1043987
20110676		BFOU(C) 2PAIR 2.5mm ² S4/S8	GREY	-	7021528942064	-
20110677		BFOU(C) 4PAIR 2.5mm ² S4/S8	GREY	-	7021528942187	-
20110678		BFOU(C) 8PAIR 2.5mm ² S4/S8	GREY	-	7021528942309	-
	894231	BFOU(C) 8PAIR 2.5mm ² S4/S8	BLUE	-	7021528942316	-
20122326		BFOU(C) 12PAIR 2.5mm ² S4/S8	GREY	-	7021528942361	-
20110777		BFOU(C) 16PAIR 2.5mm ² S4/S8	GREY	-	7021528942422	-
	894248	BFOU(C) 24PAIR 2.5mm ² S4/S8	GREY	-	7021528942484	-
	894278	BFOU(C) 4TRIP 2.5mm ² S4/S8	GREY	-	7021528942781	-
	894290	BFOU(C) 8TRIP 2.5mm ² S4/S8	GREY	-	7021528942903	-
	894302	BFOU(C) 16TRIP 2.5mm ² S4/S8	GREY	-	7021528943023	-

Installation recommendations

Minimum Bending Radius during Installation	Minimum Bending Radius Fixed Installed	Maximum Tensile Load During Installation	Minimum Installation Temperature
8 x D	6 x D	50 N /mm ²	-20°C