

a1_4

October 3, 2025

```
[1]: # ---
# jupyter:
#   jupyter:
#     text_representation:
#       extension: .py
#       format_name: percent
#       format_version: '1.3'
#       jupyter_text_version: 1.16.7
#   kernelspec:
#     display_name: Python (ML25_assignments)
#     language: python
#     name: ml25
# ---

# %% [markdown]
# # 4 Model Selection (optional)

# %%
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import KFold
from sklearn.metrics import accuracy_score
from sklearn.model_selection import KFold
# %load_ext autoreload
# %autoreload 2

from a01_helper import *
from a01_functions import nb_train, nb_predict
```

```
[2]: # %%
# To create folds, you can use:
K = 5
Kf = KFold(n_splits=K, shuffle=True)
for i_train, i_test in Kf.split(X):
    # code here is executed K times, once per test fold
    # i_train has the row indexes of X to be used for training
    # i_test has the row indexes of X to be used for testing
    print(
```

```

        "Fold has {:d} training points and {:d} test points".format(
            len(i_train), len(i_test)
        )
    )
)

```

```

Fold has 48000 training points and 12000 test points
Fold has 48000 training points and 12000 test points
Fold has 48000 training points and 12000 test points
Fold has 48000 training points and 12000 test points
Fold has 48000 training points and 12000 test points

```

```

[3]: # %%
# Use cross-validation to find a good value of alpha. Also plot the obtained
# accuracy estimate (estimated from CV, i.e., without touching test data) as a
# function of alpha.
# YOUR CODE HERE

# Choose whether to run CV on the small sample (fast) or full MNIST (slow).
# For initial experimentation use use_sample=True. For final run set False.
use_sample = True

if use_sample:
    X_cv = X_s.copy()
    y_cv = y_s.copy()
    print("Using sampled data (fast).")
else:
    X_cv = X.copy()
    y_cv = y.copy()
    print("Using full data (slow).")

```

Using sampled data (fast).

```

[4]: # K-Fold setup (you already declared K above; reuse or set here)
K = 5
kf = KFold(n_splits=K, shuffle=True, random_state=0)

# Alphas to try: include small integers and a few larger values.
# You can change or extend this list.
alphas = [1, 2, 5, 10, 50, 100]

# Storage for results
mean_acc = []
std_acc = []
all_fold_acc = np.zeros((len(alphas), K))

# CV loop
for ia, alpha in enumerate(alphas):
    fold_idx = 0

```

```

print(f"\nAlpha = {alpha}:")
for train_idx, test_idx in kf.split(X_cv):
    Xtr, ytr = X_cv[train_idx], y_cv[train_idx]
    Xte, yte = X_cv[test_idx], y_cv[test_idx]

    # Train and predict
    model = nb_train(Xtr, ytr, alpha=alpha)
    pred = nb_predict(model, Xte)
    yhat = pred["yhat"]

    acc = accuracy_score(yte, yhat)
    all_fold_acc[ia, fold_idx] = acc
    print(f"  Fold {fold_idx+1}/{K} accuracy: {acc:.4f}")
    fold_idx += 1

mean_acc.append(all_fold_acc[ia].mean())
std_acc.append(all_fold_acc[ia].std())
print(f"  -> mean acc: {mean_acc[-1]:.4f}, std: {std_acc[-1]:.4f}")

mean_acc = np.array(mean_acc)
std_acc = np.array(std_acc)

```

Alpha = 1:

```

Fold 1/5 accuracy: 0.0750
Fold 2/5 accuracy: 0.1350
Fold 3/5 accuracy: 0.0800
Fold 4/5 accuracy: 0.0800
Fold 5/5 accuracy: 0.1300
-> mean acc: 0.1000, std: 0.0266

```

Alpha = 2:

```

Fold 1/5 accuracy: 0.2600
Fold 2/5 accuracy: 0.5750
Fold 3/5 accuracy: 0.4300

```

/Users/marmee/Desktop/Data Science/Semester 5/Machine Learning/Assignment/a01-nb/a01_functions.py:77: RuntimeWarning: divide by zero encountered in log

```

    return dict(logpriors=np.log(priors), logcls=np.log(cls))

```

/Users/marmee/Desktop/Data Science/Semester 5/Machine Learning/Assignment/a01-nb/a01_helper.py:136: RuntimeWarning: invalid value encountered in subtract

```

    return offset + np.log(np.sum(np.exp(x - offset), axis=0))

```

/Users/marmee/Desktop/Data Science/Semester 5/Machine Learning/Assignment/a01-nb/a01_functions.py:77: RuntimeWarning: divide by zero encountered in log

```

    return dict(logpriors=np.log(priors), logcls=np.log(cls))

```

```

/Users/marmee/Desktop/Data Science/Semester 5/Machine
Learning/Assignment/a01-nb/a01_helper.py:136: RuntimeWarning: invalid value
encountered in subtract
    return offset + np.log(np.sum(np.exp(x - offset), axis=0))
/Users/marmee/Desktop/Data Science/Semester 5/Machine
Learning/Assignment/a01-nb/a01_functions.py:77: RuntimeWarning: divide by zero
encountered in log
    return dict(logpriors=np.log(priors), logcls=np.log(cls))
/Users/marmee/Desktop/Data Science/Semester 5/Machine
Learning/Assignment/a01-nb/a01_helper.py:136: RuntimeWarning: invalid value
encountered in subtract
    return offset + np.log(np.sum(np.exp(x - offset), axis=0))
/Users/marmee/Desktop/Data Science/Semester 5/Machine
Learning/Assignment/a01-nb/a01_functions.py:77: RuntimeWarning: divide by zero
encountered in log
    return dict(logpriors=np.log(priors), logcls=np.log(cls))
/Users/marmee/Desktop/Data Science/Semester 5/Machine
Learning/Assignment/a01-nb/a01_helper.py:136: RuntimeWarning: invalid value
encountered in subtract
    return offset + np.log(np.sum(np.exp(x - offset), axis=0))
/Users/marmee/Desktop/Data Science/Semester 5/Machine
Learning/Assignment/a01-nb/a01_functions.py:77: RuntimeWarning: divide by zero
encountered in log
    return dict(logpriors=np.log(priors), logcls=np.log(cls))
/Users/marmee/Desktop/Data Science/Semester 5/Machine
Learning/Assignment/a01-nb/a01_helper.py:136: RuntimeWarning: invalid value
encountered in subtract
    return offset + np.log(np.sum(np.exp(x - offset), axis=0))

Fold 4/5 accuracy: 0.6100
Fold 5/5 accuracy: 0.5400
-> mean acc: 0.4830, std: 0.1268

```

Alpha = 5:

```

Fold 1/5 accuracy: 0.1250
Fold 2/5 accuracy: 0.4550
Fold 3/5 accuracy: 0.3350
Fold 4/5 accuracy: 0.5450
Fold 5/5 accuracy: 0.3650
-> mean acc: 0.3650, std: 0.1407

```

Alpha = 10:

```

Fold 1/5 accuracy: 0.1000
Fold 2/5 accuracy: 0.3550
Fold 3/5 accuracy: 0.3000
Fold 4/5 accuracy: 0.5100
Fold 5/5 accuracy: 0.2700
-> mean acc: 0.3070, std: 0.1325

```


Alpha = 50:

```
Fold 1/5 accuracy: 0.0600
Fold 2/5 accuracy: 0.2850
Fold 3/5 accuracy: 0.1850
Fold 4/5 accuracy: 0.4550
Fold 5/5 accuracy: 0.1950
-> mean acc: 0.2360, std: 0.1309
```

Alpha = 100:

```
Fold 1/5 accuracy: 0.0550
Fold 2/5 accuracy: 0.2700
Fold 3/5 accuracy: 0.1350
Fold 4/5 accuracy: 0.4600
Fold 5/5 accuracy: 0.1800
-> mean acc: 0.2200, std: 0.1387
```

```
[5]: # Plot results
plt.figure(figsize=(7,4))
plt.errorbar(alphas, mean_acc, yerr=std_acc, marker='o', linestyle='-')
plt.xscale('log') # alpha is a hyperparameter spanning multiple scales; log
                 ↪ scale helps
plt.xlabel('alpha (Dirichlet prior)')
plt.ylabel('CV accuracy (mean ± std)')
plt.title(f'{K}-fold CV accuracy vs alpha {"(sampled)" if use_sample else'
          ↪ "(full)"}')
plt.grid(True, which='both', ls='--', alpha=0.6)
plt.show()
```



```
[6]: # Print best alpha (highest mean CV accuracy)
best_idx = np.argmax(mean_acc)
print(f"Best alpha (by mean CV acc): {alphas[best_idx]} with mean acc_
↪{mean_acc[best_idx]:.4f} ± {std_acc[best_idx]:.4f}")
```

Best alpha (by mean CV acc): 2 with mean acc 0.4830 ± 0.1268