


# MI1206K601R-10

**UNCONTROLLED  
DOCUMENT**

## PHYSICAL DIMENSIONS:

A	3.20 [.126]	+ 0.20 [.008]
B	1.60 [.063]	+ 0.20 [.008]
C	1.10 [.043]	+ 0.20 [.008]
D	0.51 [.020]	+ 0.25 [.010]




## ELECTRICAL CHARACTERISTICS:


Z @ 100MHz ( $\Omega$ )	DCR ( $\Omega$ )	Rated Current
Nominal	600	
Minimum	450	
Maximum	750	0.080 1500 mA

NOTES: UNLESS OTHERWISE SPECIFIED

1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 3000 PCS/REEL.
2. TERMINATION FINISH IS 100% TIN.
3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.





## LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762  
(.030) to this dimension)

## RECOMMENDED SOLDERING CONDITIONS



DIMENSIONS ARE IN mm [INCHES].

This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.



PROJECT/PART NUMBER:  
**MI1206K601R-10**

REV **C** PART TYPE: **CO-FIRE** DRAWN BY: **TMB**

C	UPDATE COMPANY LOGO	08/22/08	JRK
B	ADD ROHS SYMBOL CHANGE CURRENT RATING	06/24/05	JRK
A	ORIGINAL DRAFT	03/26/04	TMB
REV	DESCRIPTION	DATE	INT

DATE: 03/26/04

SCALE: NTS

SHEET: 2 of 2

