iLab Info

When implementing part 3, you will need at least 2 machines to test on. All iLab machines are connected to each other over LAN. When you use the rpc.Dial method, you will need to pick a random high number port that the server is listening on along with its ip address. To find the ip address, you can use the `ip a` command and look for the inet label on the ethernet interface e.g

```
ddl73@kill:~$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
       valid_lft forever preferred_lft forever
2: enp128s31f6: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qle
    link/ether 84:5c:31:11:12:ad brd ff:ff:ff:ff:ff:ff
    inet 128.6.13.175/25 brd 128.6.13.255 scope global dynamic noprefixroute enp128s31f6   <-
       valid_lft 395730sec preferred_lft 395730sec
    inet6 2620:0:d60:ac0e::af/64 scope global dynamic noprefixroute
       valid_lft 2591911sec preferred_lft 604711sec
    inet6 fe80::865c:31ff:fe11:12ad/64 scope link noprefixroute
       valid_lft forever preferred_lft forever
```

The ip address is 128.6.13.175, and your rpc.Dial method may look like

```
client, err := rpc.Dial("tcp", "128.6.13.175:52251")
```