

Spring Integration Introduction

Spring Integration

- Spring integration is technology widely used in different parts of Mercury and Quicksilver
- ?


Spring integration allows you to :

- 1) Let application components exchange data through in-memory messaging
- 2) Integrate with external applications in a variety of ways through adapters

- Builds on Enterprise Integration Patterns for both

Ground rules

- Simple core API:
- A **Message** is sent by an endpoint
- **Endpoints** are connected to each other using **MessageChannles**
- An **endpoint** can receive **Messages** from a **MessageChannels**
 - by subscribing (passive) or pooling (active)



Message


- A **Message** consists of **MessageHeaders** and a **payload**
 - Some headers are pre defined
 - payload is just Java object
- A message is immutable
 - Let framework wrap payload for you or use a **MessageBuilder** to create it
- Each Message is created with unique ID

MessageChannels


- Connect message endpoints (loose coupling)
- Optional buffering, Interception
- Just spring beans
 - No broker needed
 - No persistence by default

MessageChannel Types

- **Point-to-point**
- Only one receiver by message
- **DirectChannel**
 - Message passed to receiver in senders's thread (return, exceptions), synchronous
 - passive subscriber
- **QueueChannel**
 - Message is queued, sending doesn't block
 - Active receiver polls from different thread





Direct vs Queue Channel




MessageChannel Types

- **Publish-subscribe**
- Multiple receivers per message
- **PublishSubscribeChannel**
 - Receivers invoked one by one in senders thread
 - Or invoked in parallel on different threads using TaskExecutor



Publish Subscribe



Defining Channels

- **DirectChannel** (sync)
 <channel id="incoming">
- **QueueChannel** (async)
 <channel id="orderedNotifications">
 <queue capacity="10"/>
 </channel>

Defining Channels

- **PublishSubscribeChannel** (sync)

```
<publish-subscribe-channel id="statistics" />
```

- **PublishSubscribeChannel** (async)

```
<publish-subscribe-channel id="appEvents"  
    task-executor="pubSubExecutor" />
```


```
<task-executor id="pubSubExecutor" pool-size="10" />
```

Message Endpoints

- **Channel Adapter:** One way integration
 - message enters or leaves application
 - Called 'inbound' or 'outbound'
- **Gateway:** Two way integration
 - Bring message into application and wait for response (inbound) or invoke external system and feed response back into application (outbound)
- **Service Activator**
 - Call method and wrap message into response channel

Adapters

- Connect your application to the outside world
 - Remoting, REST, WS, File & FTP, SMTP, Twitter, ...
 - Also Mirrorlake, PCS, Jupiter, ION, ...
 - For accepting input or producing output



Adapters

- External events produce incoming message
 - Incoming emails, new file (in folder), SOAP request
- Internal message can trigger external event
 - Calling a service, sending JMS message or email

Gateways and Adapters

- Remember the difference:
 - Channel adapter is one way (in or out)
 - Inbound Gateway awaits internal reply and returns it in-band
 - Outbound Gateway awaits external response and puts it on a channel in invoking thread
- Often use or add message headers
 - inbound HTTP: copies request header to SI headers
 - outbound JMS: copies SI headers to JMS headers

Service Activator

```
<service-activator ref="orderProcessor"
```

```
    input-channel="orders" output-channel="confirmations" />
```

```
<beans:bean id="orderProcessor" class="broker.OrderProcessor" />
```

- Invoke bean method for incoming message
- Take message from channel execute business logic and put returned object to new channel

Integration Namespaces


- Spring integration has dedicated namespaces for different integration types
- For example :
 - file, http, xml, jms, ip, twitter
- In Mercury we have own namespaces
 - pcs, jupiter, ml

```
<jupiter:publisher id="publisher" inputChannel="channelName"  
serverUrl="${host}" userName="${username}"  
userPassword="${password}" />
```

Sample : Inbound File Adapter

- It is triggered on new files in directory


```
<int-file:inbound-channel-adapter id="filesIn"  
  channel="incomingFiles"  
  directory="file:C:/inputResource" />
```



Sample: Outbound JMS Adapter

Adapter translate to jms message

```
<int-jms:outbound-channel-adapter id="jmsOut"  
  channel="toJms" destination="jmsQueue" />
```




Sample : Inbound Web Service Gateway

```
<int-ws:inbound-gateway id="wsGateway" channel="fromWS"  
marshaller="jaxb2" unmarshaller="jaxb2" />
```


```
<oxm:jaxb2-marshaller id="jaxb2"  
contextPath="com.example.xml" />
```

- In com.example.xml we can find xsd



STS Visual Editor

- SpringSource Tool Suite includes a visual editor for Spring Integration flows
- Select 'integration-graph' tab on open Spring Integration configuration file



Sample: Combining Components - call

@Controller

```
public class OrderController {
```

```
    @Autowired OrderService orderService;
```

```
    @PostMapping("/orders")
```

```
    @ResponseStatus(CREATED)
```

```
    public void placeOrder(@RequestBody Order order)
```

```
        Confirmation conf = orderService.submitOrder(order)
```

```
        ...
```

```
}
```


Sample: Combining Components

Message is processed by service adapter and additionally send to jms queue :

```
<gateway default-request-channel="new-orders"  
    service-interface="com.example.OrderService" />
```

```
<publish-subscribe-channel id="new-orders"/>
```

```
<service-activator input-channel="new-orders" requires-  
reply="true" ref="orderProcessor"  
method="processOrder" />
```

```
<int-jms:outbound-channel-adapter channel="new-  
orders" destination-name="queue.orders" />
```


Benefits

- Loose coupling between components
 - Small focused components
 - Eases testing, reuse
- Event-driven architecture
 - No hard-coded process flow
 - Easy to change or expand
- Separates integration and processing logic
 - Framework handle routing, transformation ...
 - Easily switch between sync & async processing

Benefits

- Loose coupling between components
 - Small focused components
 - Eases testing, reuse
- Event-driven architecture
 - No hard-coded process flow
 - Easy to change or expand
- Separates integration and processing logic
 - Framework handle routing, transformation ...
 - Easily switch between sync & async processing

Next time

- More Endpoint types (bridge, transformer, router, filter)
- Error handling
- Chains
- Using SpEL

LAB