



 @AndrzejWasowski

Andrzej Wąsowski

Advanced Programming

State Monad

IT UNIVERSITY OF COPENHAGEN

S SOFTWARE
Q QUALITY
R RESEARCH

Does FP Eliminate State?

Picture: you after four weeks of ADPRO

- **Variables** and fields are state
- Program **stack&heap** are state
- **Databases** are state
- **Program counter** is state!
- Variable **assignments** set state
- Variable **accesses** read state
- **Loops** must change state
- **Exceptions** modify program counter and stack
- We have **disallowed** almost all of these?

- In FP we often make **state explicit**:
 - Converted loops to **recursive functions**
 - A function is a **state transform**
 - **Arguments** are the state explicitly
 - **No other implicit**, hidden state that can be **changed** by others
- Today, a pure **pattern** for state transforms:
 - A more **recipe-like** way to encode state
 - Allows to hide the state, make it **implicit** like in imperative programming
 - Still the state is **encapsulated** in a well defined value
 - Still **no other** encapsulated state that can be **changed** by others



- RNG: a random **integer generator**; we maintain the state
- Rand[A]: a random **A generator**; we hide the RNG in the state
- State[S,A]: a general pattern for **stateful computations** producing A, where the state is of type S



AGENDA

A Typical Stateful Imperative API

```
var rng = new scala.Util.Random  
  
// returns a random number form 0 to 5  
def rollDie: Int = rng.nextInt(6)
```

- We call `rollDie` and observe a value 5 the first time, and 0 the second time
- What does it tell us about referential transparency of `rollDie`?
- `rng` is an external, implicit state, that can be changed by others
- To make `rollDie` referentially transparent, make the state explicit

Converting RNG to explicit state


- We had: `RNG.nextInt: () => Int`
- Lets **return new state explicitly**, instead of modifying old (RT)

```
trait RNG {  
  def nextInt: (Int, RNG)  
}  
object RNG {  
  def nextInt (rng: RNG): (Int, RNG) =  
    rng.nextInt  
}
```

- **In general** a function: `State => (Output, State)`
- **Wrap** this as `case class State[S, +A] (run: S => (A, S))`
- So RNG becomes `State[RNG, Int] { run = RNG.nextInt }`
- **Intuition 1:** Automaton or Transition would be better names than State
- **Intuition 2:** step would be a better name than run

Consider a Simple Automaton

Stateful by definition



```
var state = 1
while (true)
  state match {
    case 1 => print ("a"); state = 2
    case 2 => print ("b"); state = 3
    case 3 => print ("c"); state = 1
  }
```

```
def step (state: Int): (String, Int) =
  state match {
    case 1 => ("a", 2)
    case 2 => ("b", 3)
    case 3 => ("c", 1)
  }
```

```
def loop (state: Int = 1) =
  loop (step (state)._2)
```

- We need a simple **recursive loop** to run the step like above
- **One general general loop** for the State type
- This automaton as an **instance of State**: `State[Int,String] (step)`

Exercise

Use 5 minutes to write down an instance of State implementing this imperative code

```
x=0
while (true) {
  println (x)
  x+=1
}
```

Anything stateful maps to the state pattern


Recap

- Random number generators (state: RNG seed)
- Websites with modality (session state)
- Database backed applications (DB state)
- Communication protocols (protocol state)
- etc.

Random Number Generator as an Instance of State

```
type Rand[A] = State[RNG,A]
```

- RNG is the state of the random generator (usually some large number encapsulated)
- The textbook gives a simple implementation of RNG based on multiplication with large primes module 64 bits
- Rand[A] is a **computation** that we can run, then it will produce a random A and a new state RNG
- Another useful intuition: Rand[A] is a **generator of random A's**
- Or even just a **"random A"**
- **Question:**
What stream can we unfold from State[RNG,Int] (`_.nextInt`)?



How do I use this generator of random numbers?

```
type Rand[A] = State[RNG,A]  
val r : Rand[Int] = SimpleRNG (42)  
val (r1,i) = r.run
```

- SimpleRNG is the book's concrete implementation of the RNG trait
- 42 is the initial seed (state)
- (r1,i) is a new state and a random number
- **Question:** How do I get the next random number?
- **Question:** What happens if I call `r.run` again?

What can we do with Automata/State?

State is a monad, similar key operations as for List, Option, and Stream

```
def map[S,A,B] (s: State[S,A]) (f: A =>B): State[S,B]
```

Can use this to generate even numbers:

```
val even: Rand[Int] =map[Int] (r) (n =>n * 2)
```

Automata can be composed [1/2]

flatMap can be used to compose generators:

```
def flatMap[S,A,B] (s: State[S,A]) (f: A => State[S,B]): State[S,B]
```

In our context of generators:

```
def flatMap[A,B] (r: Rand[A]) (f: A => Rand[B]): Rand[B] =  
  flatMap[A,B] (r: State[RNG,A]) (f: State[RNG,B]): State[RNG,B]
```

flatMap can compose generators (compute a random size list of random even integers):

```
val int: Rand[Int] = ... (assume you have it)  
val ints: Int => Rand[List[Int]] = ... (assume creates a random list of given length)  
val ns: Rand[List[Int]] = int.flatMap ( n => ints (n) )
```

the state RNG passed **implicitly**; size generated with different state than each number

Automata can be composed [2/2]

The `map2` function can compute a zipping of two automata over the same state space for us:

```
map2 [S,A,B,C] (sa: State[S,A]) (sb: State[S,B]) (f: (A,B) =>C): State[S,C]
```

Could be used to create a product automaton

- interleaving computations, then `C` is `Either[A,B]`
- synchronizing two computations, then `C` is `(A,B)`

More fun in exercises :)

Next Week

- Next week we will design a parallel computation library, in purely functional style
- In two weeks, we will use the generators of random numbers to implement a modern testing framework
- So: keep reading the chapters and solve the exercises!