

Abort behaviors

What should you do when the glider aborts?

1. Make sure your phone is getting glider abort texts
 - User (top right) -> glider event subscriptions
 - Select glider of interest
 - Add email, phone, and abort message
 - For ATT: ex `phonenumber@txt.att.net`
 - For Tmobile: `phonenumber@tmomail.net`
2. Glider will send abort message
3. As quickly as possible while it is connected to Iridium:
 - In SFMC Terminal: Pause Script
 - **Ctrl C** (multiple times if necessary)
 - o Glider will go to GliderDOS
 - o If you don't catch the glider with **ctrl C**, it will try diving again if in 'sequence' or otherwise go to `lastgasp.mi` if in 'run'
 - o Ex sequence `nhg2test.mi(5)`
 - Once caught, you will have ~5-10 minutes at the surface to talk to the glider
 - o You can extend this with **ctrl E**
4. Review Abort messages
 - Behavior abort: something wrong with yo, surface, waypoints ma files
 - Device abort: something wrong with hardware
 - Critical abort: something seriously wrong with glider (contact everyone)
5. If a non-critical abort message:
 - **send *.sbd *.tbd *.vem *.azf** (it will take a while to send files over Iridium)
 - **get m_vacuum** (at surface should be ~8.5)
 - **use** (confirm all devices are in use that are supposed to be)
 - **sequence mission_name.mi(5)** (run the mission)
 - o Sequence runs the mission up to 5 times, and after that will run `lastgasp.mi`
6. After glider has dived, activate Script again
 - Ex. `vemaz_dp.xml`