

# A ALE Finite Element Method for Vorticity-Streamfunction Formulation with Species Transport Equation

Student Researcher: Leandro Marques

Advisors: Gustavo Anjos and Jose Pontes

State University of Rio de Janeiro

June, 22th 2020

# Outline

1. Introduction
2. Mathematical Model
3. Validation
4. Results
5. Conclusion

# Introduction

## Motivation:

- Ischaemic heart disease and stroke have remained the leading death causes globally in the last 15 years [1]

## Aims:

- To develop a Finite Element code for stream-vorticity formulation with species transport equation using the Arbitrary Lagrangian-Eulerian (ALE) approach
- To create new drug-eluting design patent



1. Introduction
2. Mathematical Model
3. Validation
4. Results
5. Conclusion

# Arbitrary Lagrangian-Eulerian (ALE)




The Arbitrary Lagrangian-Eulerian combines the classical motion descriptions, while it provides [2]:

Advantages:

- Simulations in fluid-structure and moving boundary problems

Disadvantages:

- The computational mesh requires an extensive topological treatment



[2] Donea, J., Huerta, A., Ponthot, J.-P. and Rodríguez-Ferran, A. (2004). Arbitrary Lagrangian-Eulerian Methods. In Encyclopedia of Computational Mechanics *doi:10.1002/0470091355.ecm009*

# Governing Equations

Assumptions [3]:

1. Continuum hypothesis
2. Homogeneous and Isotropic
3. Incompressible
4. Newtonian
5. Constant Mass Difusivity
6. Single-phase Flow
7. Two-dimensional flow

$$\frac{\partial \omega}{\partial t} + (\mathbf{v} - \hat{\mathbf{v}}) \cdot \nabla \omega = \frac{1}{Re} \nabla^2 \omega$$

$$\nabla^2 \psi = -\omega$$

$$\frac{\partial c}{\partial t} + (\mathbf{v} - \hat{\mathbf{v}}) \cdot \nabla c = \frac{1}{ReSc} \nabla^2 c$$

The material velocity field  $\mathbf{v} = (v_x, v_y)$  is calculated by:  $v_x = \partial \psi / \partial y$  and  $v_y = -\partial \psi / \partial x$

The mesh velocity field  $\hat{\mathbf{v}} \neq \mathbf{v}$  (*Lagrangian*) or 0 (*Eulerian*)

# Semi-Lagrangian Method


The convective term was replaced by material derivative of  $\omega$  and  $c$  in the direction of characteristic trajectory

$$\frac{D\omega}{Dt} = \frac{1}{Re} \nabla^2 \omega$$

$$\nabla^2 \psi = -\omega$$

$$\frac{Dc}{Dt} = \frac{1}{ReSc} \nabla^2 c$$

The departure node is calculated by  $x_d^n = x_i^{n+1} - (\mathbf{v} - \hat{\mathbf{v}}) \Delta t$ . Then, a searching procedure is required to find  $x_d^n$  using barycentric coordinates



# Semi-Lagrangian Method

The implicit semi-Lagrangian time discretization provides [4]:

Advantages:

- Symmetric linear systems
- Unconditionnal stability


Disadvantages:

- Numerical Diffusion
- Searching procedure may lead to excessive computational cost if it is not well designed



$$\frac{\omega_i^{n+1} - \omega_d^n}{\Delta t} = \frac{1}{Re} \nabla^2 \omega^{n+1}$$

$$\nabla^2 \psi = -\omega$$

$$\frac{c_i^{n+1} - c_d^n}{\Delta t} = \frac{1}{ReSc} \nabla^2 c^{n+1}$$







$$\left[ \frac{\mathbf{M}}{\Delta t} + \frac{\mathbf{K}}{Re} \right] \omega_i^{n+1} = \frac{\mathbf{M}}{\Delta t} \omega_d^n$$

$$\mathbf{K}\psi = \mathbf{M}\omega$$

$$\left[ \frac{\mathbf{M}}{\Delta t} + \frac{\mathbf{K}}{ReSc} \right] c_i^{n+1} = \frac{\mathbf{M}}{\Delta t} c_d^n$$

The material velocity field is calculated by:  $\mathbf{M}v_x = \mathbf{G}_y\psi$  and  $\mathbf{M}v_y = -\mathbf{G}_x\psi$


# Laplacian Smoothing

To avoid the fast degradation of the computational elements due to ALE description, it was used the Laplacian Smoothing Method [5]


The new node position  $\hat{\mathbf{x}}_i$  can be approximated by:

$$\hat{\mathbf{x}}_i = \sum_{j \in N_1} e_{ij}^{-1} (\mathbf{x}_j - \mathbf{x}_i)$$

where,  $e_{ij}^{-1}$  is the distance between the node and each neighbor in 1-ring  $N_1$




with Laplacian Smoothing



no Laplacian Smoothing

[5] Desbrun, M. Meyer, P. Schröder, A. Barr, Implicit fairing of irregular meshes using diffusion and curvature flow, in: Proceedings of Siggraph, 1999, pp. 317–324

# Solution Algorithm



1. Introduction
2. Mathematical Model
3. Validation
4. Results
5. Conclusion

# Validation - Poiseuille Flow




Boundaries Conditions:

Inflow condition:  $u = 1$ ,  $v = 0$  e  $\psi = y$

Outflow condition:  $\psi = y$

Top plate:  $u = 0$ ,  $v = 0$ ,  $\psi = 1$

Bottom plate:  $u = 0$ ,  $v = 0$ ,  $\psi = 0$






# Validation - Lid Driven Cavity Flow

Boundaries Conditions:

Bottom and side plates:  $u = 0$ ,  $v = 0$  e  $\psi = 0$

Top plate:  $u = 1$ ,  $v = 0$  e  $\psi = 0$



Coming Soon

Coming Soon



1. Introduction
2. Mathematical Model
3. Validation
4. Results
5. Conclusion

Coming Soon

1. Introduction
2. Mathematical Model
3. Validation
4. Results
5. Conclusion

1. Was observed that the species transport in blood flow is directly influenced by drug used in stent production
2. The streamfunction-vorticity formulation showed an useful approach for to calculate the velocity and concentration fields since the variables are scalars allowing a smooth implementation
3. Due to generalized construction of the code, the simulator is able to describe drug-eluting stent problem in coronary artery as well as flows of Newtonian fluids with scalar transport (concentration or temperature)

# Thank you!

marquesleandro67@gmail.com  
gustavo.rabello@mecanica.coppe.ufrj.br  
jose.pontes@uerj.br

The authors thank the FAPERJ (Research Support Foundation of the State of Rio de Janeiro) for its financial support

