BLOG-DOC-15

Complete API Contract & HTTP Specification

Canonical Wave-2 HTTP reconciliation; OpenAPI companion is executable authority

Revision	v1.0-RC8
Date	11 September 2026
Status	OWNER-AUTHORIZED WAVE-2 RECONCILIATION
Supersedes	v1.0-RC7 only where this reconciliation explicitly says so
Authority rule	This revision resolves existing contradictions only; it creates no new product scope.

Normative reconciliation decisions

CB-W2-01 Autosave transport

AutosaveInput now requires editor_instance_id (opaque non-empty text, max 128). AutosaveResponse returns editor_instance_id. API15-S-015 requires the same editor_instance_id as query input. AUTOSAVE Preview handoff carries editor_instance_id so the chosen tab-specific autosave is deterministic.

CB-W2-02 structured_data_inputs

Post create/update schemas transport the canonical DOC-07 RC2 object representation losslessly. The array-form representation is removed.

CB-W2-03 STATIC transport

AdminLinkDestination, AdminNavDestination and InternalLinkCandidate use static_page_key for STATIC targets. Entity targets continue to use target_id. STATIC targets never require fake UUID rows and internal links never become arbitrary URL strings.

CB-W2-05 Site Settings value

SettingEntry.value uses an explicit JSON-compatible SettingJsonValue. Structured Site Settings may carry objects whose child values are JSON scalars or scalar arrays. Undocumented stringification is not part of the contract.

CB-W2-07 Active Website selector

Adds API15-AUTH-012 GET /api/v1/auth/selectable-sites. It requires an authenticated Admin session and returns only ACTIVE Sites the caller may legitimately attempt to enter (all ACTIVE Sites for the designated Super Admin; assigned ACTIVE Sites for ordinary Admins). It grants no authority; every later SITE request still resolves and authorizes CTX-ADMIN-SITE.

API15-S-002 completion note

GET /api/v1/admin/sites/{site_key}/dashboard remains the existing canonical SITE operation; reconciliation requires the integrated backend to register and implement it exactly rather than modifying or removing the operation.

Invariant / count effect

Canonical executable companion: contracts/http/BLOG-DOC-15_openapi_v1.0-RC8.yaml. SHA-256 bf577a463b4c5d8fdceddc2087f53216426ef88d67d8e1a0d22ccf819751cd00. Final contract: 113 operations / 86 unique paths / 221 schemas+helpers / 1,311 resolved internal $refs. Scope subtotals: AUTH 12, PUBLIC+PREVIEW 2, SITE 63, GLOBAL 36. No new permission, Page ID, Post state, service or database table is introduced.

Incorporation rule

Supersedes only affected transport/schema clauses in Sections 5-7, 17, 20, 22, 27, 30 and the operation/schema appendices of RC7. All unaffected RC7 HTTP behavior remains incorporated unchanged.

Source inclusion note

The following pages are the complete inherited v1.0-RC7 source document. They remain normative except where a clause is explicitly superseded by the reconciliation pages above. This packaging avoids silently rewriting historical source pages while issuing the controlling v1.0-RC8 contract.

BLOG-DOC-15

Complete API Contract & HTTP Specification

Canonical HTTP transport authority for public and Central Admin APIs across the 14-site blogging platform - methods, paths, SiteContext, authorization, schemas, validation, errors, pagination, idempotency, concurrency and rate limiting.

112	85	217	1
HTTP operations	unique route paths	OpenAPI schemas/helpers	executable openapi.yaml

CORE HTTP AUTHORITY RULE

Every API operation has one explicit scope. Ordinary public requests derive tenant context from the trusted effective Host before site-owned route/data lookup. SITE Admin endpoints request a site through /admin/sites/{site_key} but the server validates assignment, permission and target ownership before constructing CTX-ADMIN-SITE. GLOBAL endpoints require explicit GLOBAL authority. Missing site scope never means all sites.

Document control	Value
Status	REVIEW CANDIDATE - RC7 controlled authentication HTTP reconciliation; built against finalized/frozen BLOG-DOC-01 through BLOG-DOC-14 and constrained by BLOG-DOC-19 RC1 security mechanics; freeze after approval
Version	1.0-RC7
Date	10 September 2026
Upstream authorities	BLOG-DOC-01 through BLOG-DOC-14 remain source-of-truth. RC7 additionally consumes BLOG-DOC-19 RC1 only for already-defined authentication/session/MFA security semantics while DOC-15 remains sole HTTP method/path/schema/status authority.
Primary authority	HTTP methods/paths, route/query/header parameters, logical auth context, permission mapping, request/response wire schemas, status/errors, pagination transport, idempotency, concurrency tokens, rate-limit ceilings and examples
Machine-readable companion	openapi.yaml (versioned copy: BLOG-DOC-15_openapi_v1.0-RC7.yaml) - executable contract audited against this PDF
Explicit non-authority	SEO/search ranking/XML sitemap algorithms (PDF-16), media processing/storage/CDN (PDF-17), workers/cache implementation (PDF-18), credential/session/MFA/CSRF/CORS mechanics (PDF-19), performance/DR (PDF-20), exhaustive QA (PDF-21), repository/deployment/visual authorities (PDFs 23-27)

DEVELOPER LOCK TARGET

A competent API developer must not choose endpoint scope, construct tenant authority from client data, invent response fields, expose internal site_id, create a generic page API, silently broaden permissions, retry a non-idempotent mutation ambiguously, overwrite a stale Post, or choose ad hoc status/error behavior. The PDF and openapi.yaml together lock the v1 HTTP contract.

Table of Contents / Document Map

Section	Subject
1	Purpose, authority and one-source-of-truth rules
2	Frozen upstream contract and cross-document locks
3	API topology, versioning and naming
4	Common request execution pipeline
5	SiteContext and scope resolution
6	Authentication and authorization transport boundary
7	Headers, media types and correlation
8	HTTP status and error model
9	Validation and field error rules
10	Pagination transport
11	Idempotency contract
12	Optimistic concurrency and stale-context behavior
13	Rate-limit classes and 429 behavior
14	Public API contract
15	Public PageData transport and routing outcomes
16	Central Admin SITE API contract
17	Posts, editor, workflow, autosave, revision and Preview endpoints
18	Taxonomy and Authors endpoints
19	Media endpoints and PDF-17 boundary
20	Navigation/Home controls endpoints
21	SEO and Redirect endpoints
22	Search, Calendar and Site Settings endpoints
23	Central Admin GLOBAL API contract
24	Sites, Domains and lifecycle endpoints
25	Admin Users, Roles and Permission Registry endpoints
26	Audit and Platform Settings endpoints
27	Request/response schema architecture
28	Security/non-disclosure boundaries
29	Canonical examples
30	OpenAPI executable-contract rules
31	DOC-01 through DOC-14 consistency audit
32	Traceability
33	Comprehensive acceptance criteria
34	Downstream dependencies and handoff
Appendix A	Canonical 112-operation endpoint registry with exact success status
Appendix B	Schema registry
Appendix C	Error/status matrix
Appendix D	Rate-limit registry
Appendix E	One-page developer execution reference

AUTHORITY BOUNDARY

DOC-15 owns HTTP transport. It does not rename or broaden DOC-13 public objects, does not change DOC-02 permission semantics, does not alter DOC-07 lifecycle rules, does not change DOC-09 public route identity, and does not define PDF-19 credential/session mechanics. If implementation needs a semantic field/capability that upstream does not authorize, the upstream authority is reopened first.

1. Purpose, Authority and One-Source-of-Truth Rules

BLOG-DOC-15 is the canonical HTTP boundary between the shared platform core and its consumers: fourteen isolated public frontend applications plus the single Central Admin. It maps frozen semantic dependencies into exact HTTP operations without creating new product behavior.

1.1 Conflict rule

CONFLICT RULE	A later implementation cannot add a path, response field, permission shortcut or tenant fallback that changes an upstream decision. Conversely, DOC-15 may define transport details that earlier documents intentionally deferred. Any requested API operation that would create a new page, capability, permission, lifecycle state, persistence object or cross-site sharing model is rejected pending controlled upstream revision.

1.2 Single authority per decision

Decision	Authority
Product/site topology	DOC-01
Roles/permissions/authorization semantics	DOC-02
Feature/capability existence	DOC-03
Trusted SiteContext/isolation	DOC-04
Public/Admin page estate	DOC-05 / DOC-06
Content/lifecycle/concurrency semantics	DOC-07
Persistence/RLS	DOC-08
Public routes/redirect/404/410	DOC-09
Admin/public execution behavior	DOC-10 / DOC-11
Public component anatomy	DOC-12
Canonical public PageData fields	DOC-13
14-frontend integration boundary	DOC-14
HTTP transport	DOC-15
Credential/session/MFA/CSRF/CORS mechanics	PDF-19 security-mechanics authority; DOC-15 owns their HTTP transport homes

2. Frozen Upstream Contract and Cross-Document Locks

DOC-15 consumes the existing platform as a transport problem, not a redesign opportunity.

Frozen fact	Transport consequence
14 public applications + one shared API core	Public HTTP contract is common; site context stays isolated.
19 Admin modules / 36 operational Admin pages	Endpoint groups serve the existing page/action estate; no extra Admin module is implied.
161 capabilities / 69 fixed permission keys	Every protected mutation/read maps to existing permission semantics; no hidden API permission exists.
33 PostgreSQL tables / RLS on 20 site-owned tables	HTTP IDs do not bypass repository scope or RLS; site_id is not accepted as ownership authority.
5 Post states / 12 body block types	API schemas and commands preserve exact lifecycle/body semantics.
14 public Page IDs / DOC-09 route families	Public transport resolves existing Page IDs only; no generic Pages endpoint.
48 DOC-13 public objects	Successful public PageData uses those field semantics exactly; transport errors are separate.
14 independent frontend apps	All can use the same API contract without site-to-site frontend imports.

3. API Topology, Versioning and Naming

3.1 Version namespace

All v1 operations are under /api/v1. The path version is the HTTP compatibility boundary. Changing a canonical field or product semantic still requires revision of its owning upstream document; a new path version does not grant permission to silently fork semantics.

3.2 Scope namespaces

Namespace	Scope	Rule
/api/v1/public/*	PUBLIC/PREVIEW	Ordinary public context derives from effective trusted Host. Preview requires separate preview authority.

Namespace	Scope	Rule
/api/v1/auth/*	AUTH ACCESS	Authentication/invitation/reset/MFA/session/step-up transport. It constructs no DOC-04 SiteContext and grants no business permission.
/api/v1/admin/sites/{site_key}/*	SITE	site_key is a requested context identifier only; server validates it before constructing CTX-ADMIN-SITE.
/api/v1/admin/*	GLOBAL	Explicit GLOBAL permissions; absence of site context never implies network authority.

3.3 Naming rules

- Path segments are lowercase kebab-case; identifiers are UUID path parameters where resource identity is required.
- Wire field names use lower_snake_case. DOC-13 public keys are preserved exactly.
- Operation IDs are stable API15-PUB-*, API15-AUTH-*, API15-S-* and API15-G-* traceability keys and appear identically in openapi.yaml.

4. Common Request Execution Pipeline



Security/scope decisions precede business convenience. For SITE requests, authorization and object ownership are repeated at mutation time. Stale responses belonging to a superseded site/target context are discarded by consumers according to DOC-10/11; a server success is never proof that a later client context should display it.

5. SiteContext and Scope Resolution

Scope	Requested input	Trusted authority construction
PUBLIC	Effective request Host + public path	DOC-09 host normalization/resolution creates one ACTIVE CTX-PUBLIC-SITE before site-owned lookup. No client site_id query/header is accepted.
PREVIEW	Effective Host + post_id + valid preview authority	Creates CTX-PREVIEW-SITE bound to owning site/target after PDF-19 credential validation.
AUTH access	Credential/token/challenge/session proof per operation	No DOC-04 SiteContext is created. Successful authentication only establishes security authority for later SITE/GLOBAL requests, which still construct their own trusted context.
SITE Admin	site_key path parameter	Resolve site registry + lifecycle, authenticate ACTIVE Admin, verify assignment (unless designated Super Admin), calculate SITE permissions, then construct CTX-ADMIN-SITE.
GLOBAL Admin	GLOBAL endpoint path	Authenticate ACTIVE Admin and verify exact GLOBAL permission. Missing SiteContext is not a shortcut to GLOBAL.

WRONG-SITE RULE A syntactically valid UUID belonging to another site is treated as unavailable in the current SITE context. The API does not return title, count, metadata, timing detail or an alternate-site hint that confirms existence.

6. Authentication and Authorization Transport Boundary

DOC-15 owns the HTTP transport homes for authentication/security access surfaces while PDF-19 owns credential, session, MFA, token, CSRF/CORS and step-up mechanics. RC7 closes GAP19-API-01 without creating a business capability, permission or tenant context.

Logical auth context	DOC-15 behavior
NONE	Ordinary public read or enumeration-safe security request with no established Admin authority.
ADMIN_SESSION	Protected Admin operation or authenticated self-service security request requires current Admin session.
INVITE_SETUP_TOKEN / RESET_TOKEN	One-time security authority validated and consumed only according to PDF-19; never becomes a business permission.
MFA_CHALLENGE	Short-lived pre-auth/enrollment challenge; not an Admin session.
PREVIEW_AUTHORITY	Private Preview operation requires valid target/site-bound preview authority before PageData construction.

6.1 Permission evaluation

- UI button/menu visibility is never authorization. Direct API invocation repeats exact server-side checks.
- AUTH access operations grant no SITE/GLOBAL permission and construct no DOC-04 SiteContext.
- SITE assignment is membership, not functional permission.

- Roles combine only under DOC-02 rules; wildcard permissions do not exist.
- GLOBAL roles do not automatically grant SITE content access.
- Bulk security validation is all-or-nothing before per-target business/version outcomes are evaluated.

6.2 Authentication / security access-surface operations - RC7 reconciliation

GAP19-API-01 was genuine: RC6 had logical ADMIN_SESSION/PREVIEW contexts but no canonical HTTP method/path/schema/status for the authentication lifecycle itself. RC7 adds exactly 11 AUTH operations. AUTH is a transport namespace only; it is not a fifth DOC-04 SiteContext and none of these operations grants a business permission.

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-AUTH-001	POST	/api/v1/auth/login	200	AUTH | NONE - credential verification only	LoginInput -> LoginResponse	AUTH_LOGIN | NO | NONE
API15-AUTH-002	POST	/api/v1/auth/logout	204	AUTH | ADMIN_SESSION	- -> EmptyResponse	AUTH_SESSION | NO | NONE
API15-AUTH-003	POST	/api/v1/auth/invitations/accept	200	AUTH | INVITE_SETUP_TOKEN	InvitationAcceptanceInput -> InvitationAcceptanceResponse	AUTH_TOKEN | NO | NONE
API15-AUTH-004	POST	/api/v1/auth/password/setup	200	AUTH | INVITE_SETUP_TOKEN OR ADMIN_SESSION	PasswordSetupInput -> PasswordSetupResponse	AUTH_TOKEN | NO | NONE
API15-AUTH-005	POST	/api/v1/auth/password-reset/request	202	AUTH | NONE	PasswordResetRequestInput -> AcceptedCommand	AUTH_RESET_REQUEST | NO | NONE
API15-AUTH-006	POST	/api/v1/auth/password-reset/complete	204	AUTH | RESET_TOKEN	PasswordResetCompleteInput -> EmptyResponse	AUTH_TOKEN | NO | NONE
API15-AUTH-007	POST	/api/v1/auth/mfa/enrollment	200	AUTH | ADMIN_SESSION OR INVITE_SETUP_TOKEN	MfaEnrollmentInput -> MfaEnrollmentResponse	AUTH_SESSION | NO | NONE
API15-AUTH-008	POST	/api/v1/auth/mfa/verify	200	AUTH | MFA_CHALLENGE	MfaVerificationInput -> MfaVerificationResponse	AUTH_TOKEN | NO | NONE
API15-AUTH-009	POST	/api/v1/auth/mfa/recovery	200	AUTH | MFA_CHALLENGE	MfaRecoveryInput -> MfaVerificationResponse	AUTH_TOKEN | NO | NONE
API15-AUTH-010	POST	/api/v1/auth/sessions/terminate	204	AUTH | ADMIN_SESSION	SessionTerminationInput -> EmptyResponse	AUTH_SESSION | NO | NONE
API15-AUTH-011	POST	/api/v1/auth/step-up	200	AUTH | ADMIN_SESSION	StepUpInput -> StepUpResponse	AUTH_SESSION | NO | NONE

6.3 Security transport invariants

- Every AUTH response is Cache-Control: no-store. Raw password, invite/reset token, MFA factor/recovery code and provisioning secret fields are marked sensitive/write-only or one-time output in OpenAPI and must not enter logs/audit details.
- API15-AUTH-005 returns the same 202 AcceptedCommand whether or not an eligible ACTIVE account exists; account enumeration is forbidden.
- API15-AUTH-004 covers both initial invitation password setup and authenticated password change so PDF-19 Section 8.1 has an explicit HTTP home without adding another product capability.
- MFA verification and recovery operate only on a server-bound challenge. A successful MFA result may establish/upgrade security state but still does not grant SITE/GLOBAL authorization.
- API15-AUTH-011 creates reusable browser step-up state only for L1/L2. L3 stays PDF-19 controlled recovery/transfer and is intentionally not represented as a reusable API proof.

NO NEW TENANT CONTEXT

/api/v1/auth/* executes before or beside tenant authorization. It never accepts site_id/site_key as authority and never treats successful authentication as authorization. Every later SITE/GLOBAL API call still resolves current account state, assignment, permission and trusted context.

7. Headers, Media Types and Correlation

Header / media type	Rule
X-Request-ID	Optional request correlation value, maximum 128 characters. Server returns the accepted/generated request ID.
Idempotency-Key	Required only where the operation registry marks REQUIRED; 16-200 characters.
RateLimit-Limit / Remaining / Reset	Returned for quota-aware operations. Reset is seconds to current window reset.
Retry-After	Required on 429.
Location	Required on public 301/302/308 redirect outcomes.
Cache-Control: no-store	Required for AUTH, Admin and Preview success responses. Ordinary public cache TTL/invalidations remain later cache/performance authority.
application/json	Default structured request/response media type.

Header / media type	Rule
multipart/form-data	Used only for Media upload/replace binary transport; PDF-17 owns accepted types/sizes and processing.

8. HTTP Status and Error Model

Status	Meaning
200	Successful read/update/command with response body.
201	Resource/handoff created.
202	Long-running system request accepted; no worker/cache internals exposed.
204	Successful deletion with no response body.
301 / 302	Manual redirect outcome allowed by DOC-09.
308	Canonical scheme/host/path normalization redirect owned by DOC-09.
400	Malformed request/unsupported media/parameter shape.
401	Protected operation has no valid logical authentication authority.
403	Authenticated but denied by scope/permission/step-up policy.
404	Authorized-context target unavailable or deliberately non-disclosed; public page API returns safe NotFoundPageData.
409	State/version/idempotency conflict; no conflicting mutation committed.
410	Public page API only: DOC-09 terminal historical locator, safe GonePageData.
422	Field/business validation failure.
429	DOC-15 transport quota exceeded.
503	Required service dependency temporarily unavailable.

8.1 Admin error envelope

```
{
  "error": {
    "code": "VERSION_CONFLICT",
    "message": "The resource changed before this mutation was committed.",
    "request_id": "req_...",
    "details": [{"field":"expected_version","code":"STALE_VERSION","message":"Reload current state."}]
  }
}
```

Validation details disclose only fields/resources the caller is authorized to know. Public 404/410 PageData are system page roots, not ApiError bodies.

9. Validation and Field Error Rules

- Parse and validate path/query/header syntax before service execution; reject ambiguous or malformed identifiers.
- Validate request JSON against the OpenAPI schema with unknown properties rejected unless a schema explicitly permits validated structured data.
- Re-resolve every site-owned related resource in the same trusted SiteContext before commit.
- Apply DOC-07 publish/schedule/body/link/embed/relationship rules before state transitions.
- Field-level Post relationship edits retain frozen prerequisite view permissions; Post SEO field mutation additionally requires seo.view + seo.edit.
- Validation failure returns 422 VALIDATION_FAILED when the request is syntactically well-formed but semantically invalid.
- Authorization/non-disclosure takes precedence over field validation that could reveal a protected target.

10. Pagination Transport

Surface	page	page_size	Maximum	Body semantics
Public collection/search	Default 1	Default 20	50	DOC-13 PageData pagination object remains canonical; page_size/total are not added to the public PageData object.
Admin list/search/audit	Default 1	Default 50	100	Admin list response includes PageRequestMeta with current page_size and has_more.

- page is 1-based.
- Invalid page/page_size values return 400.
- Changing public search query resets to page=1.
- Collection destinations remain same-site; responsive clients preserve DOC-13 result order.
- A blank public search query returns DOC-13 NO_QUERY + [] and never becomes all Posts.

11. Idempotency Contract

Retryable create/command operations marked REQUIRED must supply Idempotency-Key. The server stores an outcome fingerprint for 24 hours.

Case	Required behavior
First key use	Execute after normal authorization/validation and persist response status/body association.
Same key + same actor/scope/method/path/body fingerprint	Replay the original accepted outcome; do not duplicate side effects.
Same key + different fingerprint	409 IDEMPOTENCY_KEY_REUSE; execute nothing.
Authorization changed before replay	Current security policy still applies; never use stored success to bypass revoked authority.
Expired key after 24 hours	May execute as a new request if all current guards pass.

Idempotency is a transport replay guarantee, not an authorization or lifecycle shortcut. GET operations do not require Idempotency-Key. RC7 AUTH operations intentionally do not use the generic 24-hour Idempotency-Key replay contract: one-time invite/reset/MFA security authorities follow PDF-19 consume/supersession semantics and must not be replayed from a stored transport outcome.

12. Optimistic Concurrency and Stale-Context Behavior

- Durable Post mutations defined by DOC-07 carry expected_version in the JSON body. The API does not introduce an alternative If-Match concurrency model in v1.
- A version mismatch returns 409 VERSION_CONFLICT and performs no durable mutation, revision creation, public effect or downstream scheduling side effect.
- Autosave carries base_version and remains private recovery state; autosave success is not durable revision/publish success.
- Revision restore is atomic against current expected_version and all field-level authorization.
- Bulk requests carry per-target expected_version where the chosen action is versioned. Security validation completes first; business/version outcomes may then be per-item.
- Global identity/role/settings mutations reauthorize and revalidate current server state immediately before commit even where no general version field is frozen upstream.

13. Rate-Limit Classes and 429 Behavior

DOC-15 freezes endpoint transport quota ceilings. These are not platform-capacity targets. PDF-19 may impose stricter credential-abuse or risk-based throttles but may not silently raise these API ceilings. RC7 adds AUTH_LOGIN, AUTH_TOKEN, AUTH_RESET_REQUEST and AUTH_SESSION ceilings for the new security access-surface HTTP operations; PDF-19 failure/cooldown rules remain stricter overlays.

Class	Limit	Window	Key
PUBLIC_READ	120	60s	effective client + trusted public site
PREVIEW_READ	30	60s	preview authority + trusted preview site
AUTH_LOGIN	30	60s	source IP + normalized login-identifier hash
AUTH_TOKEN	30	60s	source IP + security token-family hash
AUTH_RESET_REQUEST	10	3600s	source IP; PDF-19 additionally limits matched normalized account
AUTH_SESSION	30	60s	authenticated Admin session + admin_id
ADMIN_READ	120	60s	authenticated Admin account
ADMIN_WRITE	60	60s	Admin account + trusted target scope
ADMIN_SENSITIVE	30	60s	Admin account + trusted target scope
ADMIN_DESTRUCTIVE	10	60s	Admin account + trusted target scope
MEDIA_UPLOAD	20	60s	Admin account + trusted site
REINDEX	2	3600s	Admin account + trusted site
AUDIT_EXPORT	4	3600s	Admin account

- 429 responses include Retry-After plus RateLimit-* headers.
- Rate-limit identity never substitutes for SiteContext or permission checks.
- A quota key must not collapse different tenants into shared authorization state; it may intentionally share a transport budget only as explicitly described by the class key.

14. Public API Contract

Ordinary public transport uses one canonical resolver endpoint so all fourteen frontend applications consume identical host/routing/PageData semantics without duplicating server route lookup. This does not change the public page URLs

themselves; DOC-09 remains the browser-route authority.

14.1 Public operations

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-PUB-001	GET	/api/v1/public/page	200	PUBLIC | NONE	- -> PublicPageResponse	PUBLIC_READ | NO | NONE
API15-PUB-002	GET	/api/v1/public/preview/posts/{post_id}	200	PREVIEW | PREVIEW_AUTHORITY	- -> PreviewPageData	PREVIEW_READ | NO | NONE

14.2 Public request pipeline

```
GET /api/v1/public/page?path=/article/example-slug
Host: WhatsYourRashi.in

1. Normalize trusted effective Host + path under DOC-09.
2. Emit 308/301/302 if routing resolves a redirect.
3. Construct one ACTIVE CTX-PUBLIC-SITE.
4. Enforce public eligibility and same-site lookup.
5. Return exactly one successful DOC-13 PageData root, or safe 404/410 system PageData.
```

15. Public PageData Transport and Routing Outcomes

Outcome	HTTP body
Home / Article / Category / Tag / Author / Search / five static routes	200; one canonical DOC-13 PageData root matching the resolved Page ID.
Canonicalization	308 + Location; no destination page body under source route.
Manual redirect	301 or 302 + Location; redirect table semantics remain DOC-09.
No eligible current resource	404 NotFoundPageData; no private/wrong-site disclosure.
Terminal deleted historical locator	410 GonePageData; no deleted title/author/media metadata.
Recoverable service failure	503 ApiError; client maps to DOC-11 retry/error state without inventing PageData flags.

NO PUBLIC ENVELOPE DRIFT DOC-13 PageData roots remain direct successful response bodies. DOC-15 does not wrap them in {data: ...}, add site_id, add transport status flags inside PageData, or serialize optional values as implicit null.

16. Central Admin SITE API Contract

Every SITE operation is nested under /api/v1/admin/sites/{site_key}. The path site_key is only a requested working context. The server constructs CTX-ADMIN-SITE only after current account, site lifecycle, assignment and permission checks.

NO TENANT-BLIND SITE ENDPOINT There is no v1 /api/v1/admin/posts/{id} endpoint that can load a site-owned object before site context. Site-owned resource IDs are always resolved inside the validated site namespace.

16.1 Context and Dashboard

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-001	GET	/api/v1/admin/sites/{site_key}/context	200	SITE | authenticated + active assignment	- -> AdminSiteContext	ADMIN_READ | NO | NONE
API15-S-002	GET	/api/v1/admin/sites/{site_key}/dashboard	200	SITE | dashboard.view	- -> DashboardResponse	ADMIN_READ | NO | NONE

17. Posts, Editor, Workflow, Autosave, Revision and Preview Endpoints

17.1 Complete Post endpoint family

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-010	GET	/api/v1/admin/sites/{site_key}/posts	200	SITE | posts.view	- -> PostListResponse	ADMIN_READ | NO | NONE
API15-S-011	POST	/api/v1/admin/sites/{site_key}/posts	201	SITE | posts.view + posts.create	PostCreateInput -> PostResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-012	GET	/api/v1/admin/sites/{site_key}/posts/{post_id}	200	SITE | posts.view	- -> PostResponse	ADMIN_READ | NO | NONE
API15-S-013	PATCH	/api/v1/admin/sites/{site_key}/posts/{post_id}	200	SITE | posts.view + posts.edit	PostUpdateInput -> PostResponse	ADMIN_WRITE | REQUIRED | expected_version
API15-S-014	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/autosaves	201	SITE | posts.view + posts.edit	AutosaveInput -> AutosaveResponse	ADMIN_WRITE | REQUIRED | base_version

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-015	GET	/api/v1/admin/sites/{site_key}/posts/{post_id}/autosaves/latest	200	SITE | posts.view + posts.edit	- -> AutosaveResponse	ADMIN_READ | NO | NONE
API15-S-016	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/preview-handoff	201	SITE | posts.view + posts.preview	PreviewHandoffInput -> PreviewHandoffResponse	ADMIN_SENSITIVE | REQUIRED | base_version
API15-S-017	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/schedule	200	SITE | posts.view + posts.edit + posts.schedule	SchedulePostInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-018	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/unschedule	200	SITE | posts.view + posts.edit + posts.schedule	VersionCommandInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-019	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/publish	200	SITE | posts.view + posts.edit + posts.publish	VersionCommandInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-020	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/archive	200	SITE | posts.view + posts.archive	VersionCommandInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-021	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/trash	200	SITE | posts.view + posts.trash	VersionCommandInput -> PostResponse	ADMIN_DESTRUCTIVE | REQUIRED | expected_version
API15-S-022	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/restore	200	SITE | posts.view + posts.restore	VersionCommandInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-023	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/permanent-delete	204	SITE | posts.view + posts.delete	VersionCommandInput -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | expected_version
API15-S-024	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/duplicate	201	SITE | posts.view + posts.duplicate	DuplicatePostInput -> PostResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-025	POST	/api/v1/admin/sites/{site_key}/posts/bulk	200	SITE | action-specific Post permission; security prevalidation for all targets	BulkPostInput -> BulkPostResponse	ADMIN_SENSITIVE | REQUIRED | per-target expected_version where applicable
API15-S-026	GET	/api/v1/admin/sites/{site_key}/posts/{post_id}/revisions	200	SITE | posts.view + posts.revisions.view	- -> RevisionListResponse	ADMIN_READ | NO | NONE
API15-S-027	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/revisions/{revision_id}/restore	200	SITE | posts.view + posts.edit + posts.revisions.view + posts.revisions.restore	RestoreRevisionInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-028	GET	/api/v1/admin/sites/{site_key}/posts/{post_id}/url-history	200	SITE | posts.view	- -> UrlHistoryResponse	ADMIN_READ | NO | NONE

17.2 Post command invariants

- Create always creates a Draft inside current CTX-ADMIN-SITE; request body cannot set site ownership.
- Preview does not publish and private Preview authority is not returned inside PreviewPageData.
- Restore from Trash returns to the upstream-approved non-public state and never silently republishes.
- Duplicate creates a new same-site Post identity; cross-site duplicate/move is not exposed.
- URL history is read-only transport here; history alone does not create a redirect.
- Permanent delete is an explicit POST command with expected_version so concurrency state is in the body; successful response is 204.

18. Taxonomy and Authors Endpoints

18.1 Categories

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-030	GET	/api/v1/admin/sites/{site_key}/categories	200	SITE | categories.view	- -> CategoryListResponse	ADMIN_READ | NO | NONE
API15-S-031	POST	/api/v1/admin/sites/{site_key}/categories	201	SITE | categories.view + categories.create	CategoryInput -> CategoryResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-032	GET	/api/v1/admin/sites/{site_key}/categories/{category_id}	200	SITE | categories.view	- -> CategoryResponse	ADMIN_READ | NO | NONE
API15-S-033	PATCH	/api/v1/admin/sites/{site_key}/categories/{category_id}	200	SITE | categories.view + categories.edit	CategoryUpdateInput -> CategoryResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-034	DELETE	/api/v1/admin/sites/{site_key}/categories/{category_id}	204	SITE | categories.view + categories.delete	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE

18.2 Tags

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-040	GET	/api/v1/admin/sites/{site_key}/tags	200	SITE | tags.view	- -> TagListResponse	ADMIN_READ | NO | NONE
API15-S-041	POST	/api/v1/admin/sites/{site_key}/tags	201	SITE | tags.view + tags.create	TagInput -> TagResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-042	GET	/api/v1/admin/sites/{site_key}/tags/{tag_id}	200	SITE | tags.view	- -> TagResponse	ADMIN_READ | NO | NONE

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-043	PATCH	/api/v1/admin/sites/{site_key}/tags/{tag_id}	200	SITE | tags.view + tags.edit	TagUpdateInput -> TagResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-044	DELETE	/api/v1/admin/sites/{site_key}/tags/{tag_id}	204	SITE | tags.view + tags.delete	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-S-045	POST	/api/v1/admin/sites/{site_key}/tags/{tag_id}/merge	200	SITE | tags.view + tags.edit + tags.delete	TagMergeInput -> TagResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE

18.3 Authors

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-050	GET	/api/v1/admin/sites/{site_key}/authors	200	SITE | authors.view	- -> AuthorListResponse	ADMIN_READ | NO | NONE
API15-S-051	POST	/api/v1/admin/sites/{site_key}/authors	201	SITE | authors.view + authors.create	AuthorInput -> AuthorResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-052	GET	/api/v1/admin/sites/{site_key}/authors/{author_id}	200	SITE | authors.view	- -> AuthorResponse	ADMIN_READ | NO | NONE
API15-S-053	PATCH	/api/v1/admin/sites/{site_key}/authors/{author_id}	200	SITE | authors.view + authors.edit	AuthorUpdateInput -> AuthorResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-054	POST	/api/v1/admin/sites/{site_key}/authors/{author_id}/retire	200	SITE | authors.view + authors.retire	SimpleCommandInput -> AuthorResponse	ADMIN_SENSITIVE | REQUIRED | NONE

Every relationship and merge/retire/delete command resolves same-site ownership before mutation. API transport does not invent cross-site taxonomy/author sharing.

18.4 Category/Author SEO Field Transport - RC4 Authorization Reconciliation

DOC-03/DOC-08 require the existing Category/Author SEO fields, while DOC-02 prerequisite rules and DOC-10 SEO action contracts require seo.view + seo.edit for SEO mutation. RC4 preserves the RC3 transport fields and reconciles their conditional write authorization; no endpoint, capability, permission key, schema field or product feature is added.

Entity/schema	SEO fields exposed	Read visibility	Write requirement
CategoryInput / CategoryUpdateInput / CategoryResource	seo_title; meta_description; canonical_override; index_policy	SEO fields in Resource are emitted only with seo.view	Base categories.create/edit permission plus seo.view + seo.edit when any SEO field is supplied
AuthorInput / AuthorUpdateInput / AuthorResource	seo_title; meta_description; canonical_override; index_policy	SEO fields in Resource are emitted only with seo.view	Base authors.create/edit permission plus seo.view + seo.edit when any SEO field is supplied

- index_policy is exactly INHERIT | INDEX | NOINDEX.
- canonical_override is URI-shaped transport data; final canonical-selection validity remains PDF-16 authority.
- If any SEO field is supplied, both seo.view and seo.edit are required in addition to the base entity create/edit permission. If either SEO permission is absent, the request fails atomically; the server must not persist ordinary fields while silently discarding protected SEO fields.
- Omission of SEO fields from a Resource because seo.view is absent is authorization-aware omission, not null and not evidence that the stored value is absent.

19. Media Endpoints and PDF-17 Boundary

19.1 Media family

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-060	GET	/api/v1/admin/sites/{site_key}/media	200	SITE | media.view	- -> MediaListResponse	ADMIN_READ | NO | NONE
API15-S-061	POST	/api/v1/admin/sites/{site_key}/media	201	SITE | media.view + media.upload	MediaUploadInput -> MediaResponse	MEDIA_UPLOAD | REQUIRED | NONE
API15-S-062	GET	/api/v1/admin/sites/{site_key}/media/{media_id}	200	SITE | media.view	- -> MediaResponse	ADMIN_READ | NO | NONE
API15-S-063	PATCH	/api/v1/admin/sites/{site_key}/media/{media_id}	200	SITE | media.view + media.edit	MediaUpdateInput -> MediaResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-064	POST	/api/v1/admin/sites/{site_key}/media/{media_id}/replace	200	SITE | media.view + media.replace	MediaUploadInput -> MediaResponse	MEDIA_UPLOAD | REQUIRED | NONE
API15-S-065	DELETE	/api/v1/admin/sites/{site_key}/media/{media_id}	204	SITE | media.view + media.delete	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-S-066	GET	/api/v1/admin/sites/{site_key}/media/{media_id}/usage	200	SITE | media.view	- -> MediaUsageResponse	ADMIN_READ | NO | NONE

19.2 Media Library search/filter/pagination/sort - RC6 reconciliation

FC-MED-03 and ADM-S-MEDIA-01 require a server-backed site-scoped Media Library search/filter surface. RC6 closes that existing-capability transport gap without adding an endpoint.

Query	Type/default	Locked behavior
search	string, optional, max 200	Case-insensitive search across original filename, editorial title, alt text, caption and credit within the current trusted site only. Trim surrounding whitespace; blank behaves as omitted.
mime_type	string, optional	Exact validated MIME filter. Upload allowlist remains PDF-17 authority.
usage	ALL | USED | UNUSED; default ALL	USED means usage_count > 0; UNUSED means usage_count = 0.
page	integer >=1; default 1	1-based Admin pagination.
page_size	integer 1..100; default 50	Uses the frozen Admin pagination ceiling.
sort	CREATED_DESC default; CREATED_ASC; UPDATED_DESC; UPDATED_ASC; TITLE_ASC/DESC; FILENAME_ASC/DESC	All sort modes use media_id ASC as final deterministic tie-breaker.

- Filtering/search execute server-side after CTX-ADMIN-SITE resolution; the API never returns all-site/all-library data for browser filtering.
- MediaListResponse.items remain MediaResource objects and therefore include usage_count as the required list usage indicator; the detailed usage references remain API15-S-066.

19.3 MediaResource variant/dimension and metadata transport

Concern	RC6 transport rule
variants	MediaResource.variants is a required array; [] is valid when no verified derivative exists. Each item declares variant_key, mime_type, byte_size and optional width/height. No object_key/checksum/bucket/private credential is exposed.
usage_count	Required non-negative derived current usage count. It is an indicator only; exact references are read from API15-S-066.
title	Existing DOC-08 editorial media title is transported in MediaUploadInput, MediaUpdateInput and MediaResource.
source_url	Existing DOC-08 editorial provenance/source URL is transported in the same schemas; it is not fetched automatically and is not public PageData by default.

19.4 Replace-versus-metadata authorization

API15-S-064 continues to require media.view + media.replace for the binary generation switch. Because its multipart body reuses MediaUploadInput, supplying alt_text, title, caption, credit or source_url is a separate metadata mutation and additionally requires media.edit. If media.edit is absent, the entire replace request fails atomically; the server must not switch the binary while silently dropping unauthorized metadata.

MEDIA BOUNDARY DOC-15 freezes Media HTTP transport: query parameters, multipart body shape, MediaResource fields, response schemas and permission metadata. PDF-17 owns accepted MIME/size limits, private object-storage keying, derivative catalog/processing, public-safe fallback selection, CDN and replacement/deletion storage mechanics. API bodies never expose storage bucket, object_key, checksum or private signed credential.

20. Navigation and Home Controls Endpoints

20.1 Navigation/Home family

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-070	GET	/api/v1/admin/sites/{site_key}/navigation/menus	200	SITE | navigation.view	- -> NavigationAdminResponse	ADMIN_READ | NO | NONE
API15-S-071	PUT	/api/v1/admin/sites/{site_key}/navigation/menus/{menu_key}	200	SITE | navigation.view + navigation.manage	NavigationMenuInput -> NavigationAdminResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-072	GET	/api/v1/admin/sites/{site_key}/homepage	200	SITE | navigation.view	- -> HomepageAdminResponse	ADMIN_READ | NO | NONE
API15-S-073	PUT	/api/v1/admin/sites/{site_key}/homepage	200	SITE | navigation.view + navigation.manage	HomepageInput -> HomepageAdminResponse	ADMIN_WRITE | REQUIRED | NONE

Only HEADER/FOOTER menu identities and predefined Home controls are transported. No generic page builder, arbitrary component registry or editable public-page route is introduced.

21. SEO and Redirect Endpoints

21.1 SEO

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-080	GET	/api/v1/admin/sites/{site_key}/seo	200	SITE | seo.view	- -> SiteSeoResponse	ADMIN_READ | NO | NONE
API15-S-081	PATCH	/api/v1/admin/sites/{site_key}/seo	200	SITE | seo.view + seo.edit	SiteSeoInput -> SiteSeoResponse	ADMIN_WRITE | REQUIRED | NONE

21.2 Redirects

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-082	GET	/api/v1/admin/sites/{site_key}/redirects	200	SITE | redirects.view	- -> RedirectListResponse	ADMIN_READ | NO | NONE
API15-S-083	POST	/api/v1/admin/sites/{site_key}/redirects	201	SITE | redirects.view + redirects.create	RedirectInput -> RedirectResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-084	GET	/api/v1/admin/sites/{site_key}/redirects/{redirect_id}	200	SITE | redirects.view	- -> RedirectResponse	ADMIN_READ | NO | NONE
API15-S-085	PATCH	/api/v1/admin/sites/{site_key}/redirects/{redirect_id}	200	SITE | redirects.view + redirects.edit	RedirectUpdateInput -> RedirectResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-086	DELETE	/api/v1/admin/sites/{site_key}/redirects/{redirect_id}	204	SITE | redirects.view + redirects.delete	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE

SEO endpoints transport approved inputs/diagnostics only; PDF-16 owns fallback, ranking, schema.org and sitemap/search algorithms. Manual redirect status_code is restricted to 301 or 302. System canonicalization remains DOC-09 308 behavior.

22. Search, Calendar and Site Settings Endpoints

22.1 Search/Indexing

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-090	GET	/api/v1/admin/sites/{site_key}/search/posts	200	SITE | search.view	- -> AdminSearchResponse	ADMIN_READ | NO | NONE
API15-S-091	GET	/api/v1/admin/sites/{site_key}/search/internal-links	200	SITE | search.view	- -> InternalLinkSearchResponse	ADMIN_READ | NO | NONE
API15-S-092	GET	/api/v1/admin/sites/{site_key}/search/related-posts	200	SITE | search.view	- -> RelatedCandidateResponse	ADMIN_READ | NO | NONE
API15-S-093	GET	/api/v1/admin/sites/{site_key}/search/status	200	SITE | search.view	- -> SearchStatusResponse	ADMIN_READ | NO | NONE
API15-S-094	POST	/api/v1/admin/sites/{site_key}/search/reindex	202	SITE | search.view + search.reindex	SimpleCommandInput -> AcceptedCommand	REINDEX | REQUIRED | NONE

22.2 Calendar and Site Settings

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-095	GET	/api/v1/admin/sites/{site_key}/calendar	200	SITE | calendar.view	- -> CalendarResponse	ADMIN_READ | NO | NONE
API15-S-096	GET	/api/v1/admin/sites/{site_key}/settings	200	SITE | site_settings.view	- -> SiteSettingsResponse	ADMIN_READ | NO | NONE
API15-S-097	PATCH	/api/v1/admin/sites/{site_key}/settings	200	SITE | site_settings.view + site_settings.edit	SiteSettingsInput -> SiteSettingsResponse	ADMIN_WRITE | REQUIRED | NONE

Reindex returns 202 AcceptedCommand and deliberately does not expose worker/job/cache IDs; PDF-18 owns background processing mechanics. Settings transport is allowlisted and may not become a raw environment/configuration dump.

23. Central Admin GLOBAL API Contract

GLOBAL endpoints operate on platform/global resources or explicitly authorized aggregate projections. Active Website selector state does not grant GLOBAL authority and does not retarget explicit global forms.

23.1 Global Context and Network

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-G-001	GET	/api/v1/admin/context	200	GLOBAL | authenticated ACTIVE Admin with at least one explicit GLOBAL permission	- -> AdminGlobalContext	ADMIN_READ | NO | NONE
API15-G-002	GET	/api/v1/admin/network/dashboard	200	GLOBAL | network_dashboard.view	- -> NetworkDashboardResponse	ADMIN_READ | NO | NONE
API15-G-003	GET	/api/v1/admin/network/posts	200	GLOBAL | network_dashboard.view + per-row site assignment + posts.view	- -> NetworkPostListResponse	ADMIN_READ | NO | NONE

The network/posts projection may aggregate authorized site-owned rows, but every row remains labelled by its site and drilldown/mutation establishes a new target CTX-ADMIN-SITE. Global summary authority is not universal site-content authority.

24. Sites, Domains and Lifecycle Endpoints

24.1 Site/Domain family

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-G-010	GET	/api/v1/admin/sites	200	GLOBAL | sites.view	- -> SiteListResponse	ADMIN_READ | NO | NONE

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-G-011	POST	/api/v1/admin/sites	201	GLOBAL | sites.view + sites.create	SiteCreateInput -> SiteAdminResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-012	GET	/api/v1/admin/sites/{site_key}	200	GLOBAL | sites.view	- -> SiteAdminResponse	ADMIN_READ | NO | NONE
API15-G-013	PATCH	/api/v1/admin/sites/{site_key}	200	GLOBAL | sites.view + sites.edit	SiteUpdateInput -> SiteAdminResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-014	POST	/api/v1/admin/sites/{site_key}/enable	200	GLOBAL | sites.view + sites.enable	SimpleCommandInput -> SiteAdminResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-015	POST	/api/v1/admin/sites/{site_key}/disable	200	GLOBAL | sites.view + sites.disable	SimpleCommandInput -> SiteAdminResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-016	POST	/api/v1/admin/sites/{site_key}/archive	200	GLOBAL | sites.view + sites.archive	SimpleCommandInput -> SiteAdminResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-017	POST	/api/v1/admin/sites/{site_key}/deletion-requests	201	GLOBAL | sites.view + sites.deletion_request	SiteDeletionRequestInput -> SiteDeletionRequestResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-018	GET	/api/v1/admin/sites/{site_key}/domains	200	GLOBAL | sites.view + sites.manage_domains	- -> DomainListResponse	ADMIN_READ | NO | NONE
API15-G-019	POST	/api/v1/admin/sites/{site_key}/domains	201	GLOBAL | sites.view + sites.manage_domains	DomainInput -> DomainResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-020	PATCH	/api/v1/admin/sites/{site_key}/domains/{domain_id}	200	GLOBAL | sites.view + sites.manage_domains	DomainUpdateInput -> DomainResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-021	DELETE	/api/v1/admin/sites/{site_key}/domains/{domain_id}	204	GLOBAL | sites.view + sites.manage_domains	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-022	POST	/api/v1/admin/sites/{site_key}/domains/{domain_id}/make-canonical	200	GLOBAL | sites.view + sites.manage_domains	SimpleCommandInput -> DomainResponse	ADMIN_SENSITIVE | REQUIRED | NONE

- Domain aliases are explicit records only; no implicit www alias operation exists.
- Domain management does not change immutable site ownership of existing site-owned records.
- Enable/disable/archive/deletion request preserve upstream lifecycle and safety rules; the API does not invent an immediate hard-delete site operation.

25. Admin Users, Roles and Permission Registry Endpoints

25.1 Admin Users

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-G-030	GET	/api/v1/admin/admin-users	200	GLOBAL | admin_users.view	- -> AdminUserListResponse	ADMIN_READ | NO | NONE
API15-G-031	POST	/api/v1/admin/admin-users/invitations	201	GLOBAL | admin_users.view + admin_users.invite	AdminInvitationInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-032	GET	/api/v1/admin/admin-users/{admin_user_id}	200	GLOBAL | admin_users.view	- -> AdminUserResponse	ADMIN_READ | NO | NONE
API15-G-033	PATCH	/api/v1/admin/admin-users/{admin_user_id}	200	GLOBAL | admin_users.view + admin_users.edit	AdminUserUpdateInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-034	POST	/api/v1/admin/admin-users/{admin_user_id}/enable	200	GLOBAL | admin_users.view + admin_users.enable	SimpleCommandInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-035	POST	/api/v1/admin/admin-users/{admin_user_id}/disable	200	GLOBAL | admin_users.view + admin_users.disable	SimpleCommandInput -> AdminUserResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-036	PUT	/api/v1/admin/admin-users/{admin_user_id}/site-assignments	200	GLOBAL | admin_users.view + admin_users.manage_site_assignments	SiteAssignmentInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-037	PUT	/api/v1/admin/admin-users/{admin_user_id}/role-assignments	200	GLOBAL | admin_users.view + roles.view + roles.assign	RoleAssignmentInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE

25.2 Roles and Permission Registry

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-G-040	GET	/api/v1/admin/roles	200	GLOBAL | roles.view	- -> RoleListResponse	ADMIN_READ | NO | NONE
API15-G-041	POST	/api/v1/admin/roles	201	GLOBAL | roles.view + roles.create	RoleInput -> RoleResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-042	GET	/api/v1/admin/roles/{role_id}	200	GLOBAL | roles.view	- -> RoleResponse	ADMIN_READ | NO | NONE
API15-G-043	PATCH	/api/v1/admin/roles/{role_id}	200	GLOBAL | roles.view + roles.edit	RoleUpdateInput -> RoleResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-044	POST	/api/v1/admin/roles/{role_id}/retire	200	GLOBAL | roles.view + roles.retire	SimpleCommandInput -> RoleResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-045	POST	/api/v1/admin/roles/{role_id}/duplicate	201	GLOBAL | roles.view + roles.create	RoleDuplicateInput -> RoleResponse	ADMIN_SENSITIVE | REQUIRED | NONE

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-G-046	GET	/api/v1/admin/permissions	200	GLOBAL | permissions.view	- -> PermissionRegistryResponse	ADMIN_READ | NO | NONE

- Invitation credential/setup token format and delivery remain PDF-19 authority.
- Role scope is SITE or GLOBAL and cannot mix permission registries.
- Role assignment is still subject to actor privilege ceiling; API acceptance never permits self-escalation.
- Permission Registry is read-only and returns exactly 69 fixed keys; there is no create/edit/delete permission endpoint.

26. Audit and Platform Settings Endpoints

26.1 Audit

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-G-050	GET	/api/v1/admin/audit	200	GLOBAL | audit.view	- -> AuditListResponse	ADMIN_READ | NO | NONE
API15-G-051	GET	/api/v1/admin/audit/{audit_id}	200	GLOBAL | audit.view	- -> AuditResponse	ADMIN_READ | NO | NONE
API15-G-052	POST	/api/v1/admin/audit/export	202	GLOBAL | audit.view + audit.export	AuditExportInput -> AcceptedCommand	AUDIT_EXPORT | REQUIRED | NONE

26.2 Platform Settings

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-G-060	GET	/api/v1/admin/platform-settings	200	GLOBAL | platform_settings.view	- -> PlatformSettingsResponse	ADMIN_READ | NO | NONE
API15-G-061	PATCH	/api/v1/admin/platform-settings	200	GLOBAL | platform_settings.view + platform_settings.edit	PlatformSettingsInput -> PlatformSettingsResponse	ADMIN_SENSITIVE | REQUIRED | NONE

Audit export is accepted asynchronously without exposing downstream worker identifiers. Platform Settings remains a controlled approved settings surface, not a secrets/environment console.

27. Request/Response Schema Architecture

27.1 Canonical public schemas

The openapi.yaml includes DOC-13-compatible public contracts and PageData roots. Public keys remain lower_snake_case; optional fields are omitted rather than serialized as implicit null; required collections are [] when honestly empty; array order remains authoritative.

27.2 Admin schemas

Admin request/response types expose only fields needed by frozen Admin capabilities. Resource IDs are opaque; site ownership is derived from trusted scope, never from an editable site_id field. Unknown top-level properties are rejected by default.

27.3 Schema evolution

- A required public field change first reopens DOC-13.
- A new operation requiring a new capability/permission first reopens its upstream authority.
- Backward-compatible HTTP additions still require versioned DOC-15/OpenAPI change control and traceability.
- An implementation may generate language bindings from openapi.yaml but generated types must not rename wire keys or weaken constraints.

28. Security and Non-Disclosure Boundaries

Concern	Locked transport behavior
Tenant authority	No public site_id header/query/body. SITE Admin site_key is requested context only and revalidated server-side.
Wrong-site objects	404-equivalent non-disclosure within current authorized SITE context.
Admin authorization	Every protected operation rechecks session/account/scope/permission/ownership at execution.
Preview	Private auth required; PageData contains no preview credential; no-store.
Sensitive internal fields	No DB technical roles/RLS context, secrets, storage keys, private signed URLs, worker/cache/job identifiers in public bodies.
CSRF/CORS/session carrier	PDF-19 owns exact mechanism; DOC-15 declares logical authentication only.
Rate limiting	DOC-15 endpoint ceilings; PDF-19 may add stricter credential/risk throttles.

29. Canonical Examples

29.1 Public Article request

```
GET /api/v1/public/page?path=/article/example-slug HTTP/1.1
Host: WhatsYourRashi.in
X-Request-ID: web-4f2...

HTTP/1.1 200 OK
Content-Type: application/json
X-Request-ID: web-4f2...
RateLimit-Limit: 120
RateLimit-Remaining: 119

{ "context": {"page_id":"PUB-ARTICLE-01","page_kind":"CONTENT","render_mode":"PUBLIC"}, ... }
```

29.2 Durable Post edit with idempotency + version

```
PATCH /api/v1/admin/sites/SITE-01/posts/11111111-1111-1111-1111-111111111111
Idempotency-Key: 0d7179c8-2c6d-4af1-bdf9-c9f1f40b3223
Content-Type: application/json

{
  "expected_version": 12,
  "title": "Updated title"
}

# If current version is 13:
HTTP/1.1 409 Conflict
{ "error": {"code":"VERSION_CONFLICT", ...} }
```

29.3 Public canonical redirect

```
GET /api/v1/public/page?path=/article/example-slug
Host: alias.example

HTTP/1.1 308 Permanent Redirect
Location: https://canonical.example/article/example-slug
```

29.4 Login requiring MFA

```
POST /api/v1/auth/login
Content-Type: application/json

{
  "email": "admin@example.invalid",
  "password": "<redacted>"
}

HTTP/1.1 200 OK
Cache-Control: no-store
{
  "state": "MFA_REQUIRED",
  "mfa_challenge_id": "opaque-challenge",
  "challenge_expires_at": "2026-09-10T11:35:00Z"
}
```

The challenge is not an Admin session. API15-AUTH-008/009 must complete the bound MFA challenge before a session can exist.

30. OpenAPI Executable-Contract Rules

The accompanying openapi.yaml is the executable contract for server/client generation, schema validation and API contract testing. The PDF endpoint registry is generated from the same canonical operation inventory, while Appendix B is loaded directly from the delivered YAML schema registry so field names and required-field declarations cannot drift silently.

Synchronization measure	Value
OpenAPI version	3.1.0
Document/API version	1.0-RC7
Operation count	112 = 2 PUBLIC/PREVIEW + 11 AUTH + 63 SITE + 36 GLOBAL
Unique operation IDs	112
Unique method/path pairs	112
Unique route paths	85
Success status distribution	200 x 85 | 201 x 15 | 202 x 3 | 204 x 9
Schema/helper count	217
Resolved internal schema references	1,297 / 1,297
SHA-256 of delivered openapi.yaml	3376444e141fd16bbf0a440f2828de0e97d04b5f60a49e106b2d07013f8397b2

SYNC RULE	Any mismatch in operation ID, method, path, exact success status, request schema, response schema, permission mapping, SiteContext scope, idempotency, concurrency or rate-limit class is release-blocking. YAML field constraints are executable; this PDF explains authority and human-readable registry semantics.

30.1 RC7 reconciliation audit

Audit item	Result	Disposition
Claimed operation count vs canonical inventory	PASS - 112 claimed; 112 unique operation IDs; 112 unique method/path pairs	RC7 controlled addition is explicitly subtotaled 2 PUBLIC/PREVIEW + 11 AUTH + 63 SITE + 36 GLOBAL.
Exact success status per operation	PASS	Every registry row states 200/201/202/204 and YAML carries the same response code + x-success-status.
PDF <-> YAML operation contract	PASS after RC4 regeneration	Method/path/status/request/response/scope/permission/rate/idempotency/concurrency audited operation-by-operation.
DOC-13 public field schemas	PASS	RC2 corrections remain intact: MediaVariant, PublicMedia.credit_text, OpenGraph and all 12 ArticleBlock wrapper/payload contracts remain aligned.
Category SEO transport	RC2 gap confirmed	PASS after RC4 - Category SEO fields remain present; conditional mutation authorization now explicitly requires seo.view + seo.edit plus the base Category create/edit permission.
Author SEO transport	RC2 gap confirmed	PASS after RC4 - Author SEO fields remain present; conditional mutation authorization now explicitly requires seo.view + seo.edit plus the base Author create/edit permission.
Category/Author SEO mutation permission pair	RC3 mismatch confirmed	FIXED in RC4 - DOC-02 prerequisite rules and DOC-10 FC-SEO actions are now mirrored explicitly: any Category/Author SEO-field write requires seo.view + seo.edit, in addition to the base entity create/edit permission; failure is atomic.
OpenAPI internal references	PASS	1,297 references resolve; zero unresolved schema references.
Appendix B schema-registry representation	RC4 ambiguity confirmed	FIXED in RC5 - Appendix B now distinguishes required fields from the complete declared top-level property set and is generated directly from the delivered OpenAPI schemas.
Media Library search/filter transport	DOC-17 RC1 gap confirmed	FIXED in RC6 - API15-S-060 now declares search, mime_type, usage, page, page_size and deterministic sort query parameters; all filtering remains same-site/server-side.
Media variants/dimensions transport	DOC-17 RC1 gap confirmed	FIXED in RC6 - MediaResource now carries required variants[] with variant_key/MIME/byte_size and optional dimensions; no storage internals are exposed.
Media title/source metadata transport	DOC-17 RC1 gap confirmed	FIXED in RC6 - title and source_url are present in MediaUploadInput, MediaUpdateInput and MediaResource.
Media List usage indicator	Potential N+1 ambiguity confirmed	FIXED in RC6 - MediaResource carries required usage_count; API15-S-066 remains the exact-reference detail operation.
Replace metadata authorization	Additional cross-check issue confirmed	FIXED in RC6 - media.replace alone cannot mutate metadata; metadata in API15-S-064 additionally requires media.edit and failure is atomic.
Authentication/security HTTP access surface	GAP19-API-01 confirmed	FIXED in RC7 - exactly 11 API15-AUTH-* operations now own method/path/schema/status/rate transport for login/logout, invitation acceptance, password setup/change, reset request/complete, MFA enrollment/verification/recovery, session termination and L1/L2 step-up. PDF-19 still owns security mechanics; no new product permission/context is created.

31. DOC-01 through DOC-14 + PDF-19 RC1 Controlled Consistency Audit

Authority	Result	DOC-15 compatibility outcome
DOC-01	PASS	One shared API/backend + 14 isolated public applications preserved; no per-site backend fork.
DOC-02	PASS after RC4	Exactly existing permission semantics used; Category/Author SEO writes now explicitly require seo.view + seo.edit in addition to base entity permission; no wildcard/hidden permission; SITE/GLOBAL boundary preserved.
DOC-03	PASS after RC6	No new module/capability introduced; required Category/Author SEO editing remains transported and FC-MED-01/03/04/07/09 now have complete existing-operation media list/metadata/usage-indicator/variant transport.
DOC-04	PASS	Trusted SiteContext before site-owned access; missing scope fails closed; public all-site filtering prohibited.
DOC-05/06	PASS	14 public Page IDs and 36 Admin pages remain unchanged; endpoints implement rather than expand the estate.
DOC-07	PASS	Five Post states, 12 blocks, Preview/autosave/revision/concurrency semantics preserved.
DOC-08	PASS after RC6	No HTTP contract weakens site ownership/RLS; Category/Author SEO fields remain transported and existing media.title/source_url plus media_variants dimensions/byte metadata are exposed without object_key/checksum.
DOC-09	PASS	Browser route families, 308 canonicalization, 301/302 manual redirect and 404/410 semantics preserved.
DOC-10	PASS after RC6	All semantic Admin dependency families receive explicit HTTP homes; Media Library search/filter/usage indicators and Media Detail variants/dimensions can now be transported without new pages.
DOC-11	PASS	Public runtime states map to transport outcomes without embedding transport errors into successful PageData.
DOC-12	PASS	API carries data only; no public visual/component authority pulled into DOC-15.
DOC-13	PASS	Canonical public objects are transported directly; no site_id/internal fields or nullability/order drift.

Authority	Result	DOC-15 compatibility outcome
DOC-14	PASS	Shared API client can consume this common contract; no site-to-site frontend dependency or site-specific API fork.
PDF-19 RC1	PASS after RC7	GAP19-API-01 closed at DOC-15 HTTP authority. Security token/session/MFA/CSRF/CORS/step-up mechanics remain PDF-19; AUTH access operations create no new business permission or tenant context.

AUDIT RESULT

No genuine contradiction or blocking missing upstream requirement was found. One intentional boundary overlap was reconciled: DOC-15 owns endpoint transport quota classes/numeric ceilings/429 headers; later PDF-19 may add stricter credential-abuse/security-risk throttling but cannot silently relax or raise DOC-15 ceilings. Authentication credential/session/MFA/CSRF/CORS mechanics remain PDF-19 authority, but their HTTP access surfaces are now explicitly transported by API15-AUTH-* as required by the DOC-15 method/path/schema/status authority.

32. Traceability

Trace ID	Upstream	Locked DOC-15 requirement
TR15-001	DOC-01	One common v1 HTTP contract serves 14 isolated public apps + Central Admin.
TR15-002	DOC-02	Exact SITE/GLOBAL permissions and server-side authorization are declared per protected operation.
TR15-003	DOC-04	PUBLIC/SITE/PREVIEW/GLOBAL SiteContext construction is explicit and fail-closed; AUTH access constructs none.
TR15-004	DOC-07	Post expected_version/autosave/Preview/lifecycle commands preserve editorial semantics.
TR15-005	DOC-08	Opaque IDs + same-site service/RLS boundary; site_id is not request authority.
TR15-006	DOC-09	Public transport preserves canonical route/redirect/404/410 outcomes.
TR15-007	DOC-10	DEP10 service families map to exact HTTP endpoints.
TR15-008	DOC-11	Transport outcomes support public state/error behavior without schema drift.
TR15-009	DOC-13	PageData schemas/field semantics are transported without redefinition.
TR15-010	DOC-14	Shared frontend API client may generate bindings from this contract without site-to-site imports.
TR15-011	PDF-19 handoff	Logical auth contexts and no-store boundary -> later concrete session/token/cookie/CSRF/CORS mechanics.
TR15-012	PDF-21/22 handoff	Operation IDs/schema IDs become executable QA and end-to-end traceability anchors.
TR15-013	PDF-19 RC1 / GAP19-API-01	Authentication lifecycle receives exact API15-AUTH-* HTTP homes while PDF-19 retains credential/session/MFA/CSRF/CORS/step-up mechanics.

33. Comprehensive Acceptance Criteria

These DOC-15 checks are release-blocking contract assertions. PDF-21 may expand them into executable security/integration/load suites but may not weaken their expected outcomes.

ID	Release assertion
AC15-001	PDF and openapi.yaml contain exactly 112 identical operation IDs = 2 PUBLIC/PREVIEW + 11 AUTH + 63 SITE + 36 GLOBAL, with 112 unique method/path pairs.
AC15-002	Every v1 operation is under /api/v1 and has one explicit PUBLIC, PREVIEW, AUTH ACCESS, SITE or GLOBAL transport scope; AUTH ACCESS creates no DOC-04 SiteContext.
AC15-003	Ordinary public requests derive tenant from trusted effective Host; no site_id query/header/body is accepted as authority.
AC15-004	Every SITE Admin path includes {site_key}; backend validates lifecycle, assignment and permission before site-owned data access.
AC15-005	Missing/invalid SITE scope fails closed and never returns all sites.
AC15-006	GLOBAL endpoints require explicit GLOBAL permission and do not inherit Active Website selector authority.
AC15-007	Wrong-site resource IDs return non-disclosing 404-equivalent behavior in authorized context.
AC15-008	Public successful PageData responses never expose site_id, Admin auth state, storage internals, preview credential, search debug or worker/cache IDs.
AC15-009	DOC-13 optional field omission, required [] collection and authoritative ordering rules survive JSON serialization.
AC15-010	Public blank search query produces NO_QUERY + [] and never an all-Posts result.
AC15-011	Public canonicalization returns 308 + Location; manual redirects use only 301/302.
AC15-012	Public 404 returns safe NotFoundPageData and neutral unknown-host 404 contains no guessed tenant shell.
AC15-013	Public 410 is emitted only for DOC-09 terminal historical-locator rule and discloses no deleted content metadata.
AC15-014	Preview endpoint requires preview authority, is no-store/noindex by data contract, and returns no credential in PageData.
AC15-015	Admin button visibility is never accepted as authorization; direct unauthorized invocation fails server-side.
AC15-016	Permission Registry endpoint returns exactly 69 fixed keys and no permission mutation endpoint exists.
AC15-017	SITE role/permission semantics never cross to another site; GLOBAL role never implies site-content permission.
AC15-018	Post create creates a same-site Draft and request cannot set or change owning site_id.

ID	Release assertion
AC15-019	Post durable edits require expected_version where declared and version conflict performs zero durable side effects.
AC15-020	Autosave uses base_version and never creates a formal revision or publication event by itself.
AC15-021	Preview handoff never publishes and never leaks preview authority through ordinary PublicDestination.
AC15-022	Restore from Trash does not silently republish.
AC15-023	Duplicate creates same-site Draft only; no cross-site duplicate/move endpoint exists.
AC15-024	Revision restore is atomic against current version and required field-level authorization.
AC15-025	Bulk security checks cover all targets before any per-item business/version result is committed.
AC15-026	Taxonomy, author, media and related-post references are re-resolved inside current SiteContext.
AC15-027	Tag merge requires tags.view + tags.edit + tags.delete and same-site target.
AC15-028	Post SEO field mutation additionally requires frozen SEO permissions; ordinary posts.edit does not silently grant SEO authority.
AC15-029	Media multipart endpoints expose no storage bucket/object key/private signed credential; PDF-17 validation/processing remains downstream.
AC15-030	Navigation/Home APIs expose only approved menus/predefined Home controls and no generic page builder.
AC15-031	Manual redirect schema accepts only 301/302 and DOC-09 validation/loop/precedence rules remain authoritative.
AC15-032	Reindex/audit export 202 bodies do not expose worker/job/cache IDs.
AC15-033	Idempotency-Key is required exactly where registry marks REQUIRED; same key+same fingerprint replays original outcome for 24 hours.
AC15-034	Same idempotency key with different fingerprint returns 409 and executes no side effect.
AC15-035	Idempotency replay never bypasses current revoked/changed authorization.
AC15-036	Public pagination default=1/20/max50; Admin default=1/50/max100; invalid bounds return 400.
AC15-037	429 includes Retry-After and RateLimit-Limit/Remaining/Reset; quota class matches operation registry.
AC15-038	Admin and Preview success responses include Cache-Control: no-store.
AC15-039	All success/error responses return X-Request-ID correlation identity.
AC15-040	422 validation details reveal only fields/resources authorized for current caller/context.
AC15-041	401 vs 403 vs 404 behavior does not disclose wrong-site/private target existence.
AC15-042	OpenAPI rejects undeclared top-level properties by default except explicitly validated structured-data subobjects.
AC15-043	Every $ref in delivered OpenAPI resolves; all 217 schemas/helpers are structurally complete and all operation request/response schema references exist.
AC15-044	Every endpoint declares rate class, logical auth context, SiteContext scope, permission mapping, idempotency and concurrency metadata.
AC15-045	No new public Page ID, Admin page, module, permission key, Post state or Article block type appears in DOC-15.
AC15-046	Network all-posts view returns only site rows the caller may see and mutations re-enter explicit target CTX-ADMIN-SITE.
AC15-047	Domain API never creates implicit www alias and canonical-host changes do not move tenant ownership.
AC15-048	Admin invitation endpoint does not define credential/setup token format; PDF-19 boundary is preserved.
AC15-049	openapi.yaml SHA-256, 112-operation count, 85-path count, 217-schema count and 1,297 resolved-ref count in the PDF match the delivered artifact at generation time.
AC15-050	Contract tests generated from openapi.yaml can validate every method/path, exact success status, request/response schema and declared field constraint without consulting undocumented implementation behavior.
AC15-051	CategoryInput, CategoryUpdateInput and CategoryResource expose seo_title, meta_description, canonical_override and index_policy; Resource SEO fields require seo.view, and supplying any SEO field for create/update requires seo.view + seo.edit in addition to the base Category permission; absence of either SEO permission rejects the entire mutation atomically.
AC15-052	AuthorInput, AuthorUpdateInput and AuthorResource expose seo_title, meta_description, canonical_override and index_policy; Resource SEO fields require seo.view, and supplying any SEO field for create/update requires seo.view + seo.edit in addition to the base Author permission; absence of either SEO permission rejects the entire mutation atomically.
AC15-053	OpenAPI Category/Author create/update operations encode the conditional SEO permission pair as executable metadata; x-field-write-permission on all Category/Author SEO properties is seo.view + seo.edit and contract audit rejects drift.
AC15-054	Appendix B distinguishes required fields from the complete declared top-level property set; Category/Author schema rows explicitly show seo_title, meta_description, canonical_override and index_policy, and the registry is generated from the delivered OpenAPI schema objects.
AC15-055	API15-S-060 exposes search, mime_type, usage, page, page_size and sort parameters; execution is same-site/server-side and page_size never exceeds 100.
AC15-056	MediaResource always exposes usage_count >= 0 and variants as an array; Media Library can show usage indicators without per-row usage-reference requests.
AC15-057	Each MediaResource variant item exposes only variant_key, mime_type, byte_size and optional width/height; object_key, checksum, bucket and private credentials remain absent.
AC15-058	MediaUploadInput, MediaUpdateInput and MediaResource expose the existing title and source_url metadata fields; MediaUpdate requires media.view + media.edit.
AC15-059	API15-S-064 binary replace requires media.view + media.replace; if alt_text/title/caption/credit/source_url is supplied, media.edit is additionally required and authorization failure rejects the whole replace atomically.
AC15-060	Exactly 11 API15-AUTH-* operations exist and no AUTH operation creates a DOC-04 SiteContext, business permission, Admin page or new account lifecycle state.

ID	Release assertion
AC15-061	API15-AUTH-001 returns 200 AUTHENTICATED or MFA_REQUIRED only after PDF-19 credential checks; invalid/unknown/INVITED/DISABLED/wrong-password cases use enumeration-safe failure and disclose no account/site/role detail.
AC15-062	API15-AUTH-002 revokes the current Admin session before 204 and applies PDF-19 CSRF/Origin checks for the cookie-authenticated unsafe request.
AC15-063	Invitation acceptance validates current one-time setup authority without account activation; password setup/change has an explicit HTTP home and never returns password/hash/token material.
AC15-064	Password-reset request returns identical 202 acknowledgement whether or not an eligible ACTIVE account exists; completion consumes valid reset authority and returns 204 after PDF-19 session/step-up revocation effects.
AC15-065	MFA enrollment response is no-store and exposes provisioning material only as one-time sensitive output; MFA is not enabled until the bound verification succeeds.
AC15-066	MFA verify/recovery operate only on the bound challenge, recovery-code consumption is one-time, and successful factor proof never substitutes for SITE/GLOBAL authorization.
AC15-067	Session termination can affect only the authenticated admin_id; it cannot target another Admin account and ALL_SESSIONS clears current authority.
AC15-068	Step-up API represents L1/L2 only, returns no reusable bearer proof, remains session/admin-bound and grants no permission; L3 is intentionally outside reusable browser transport.
AC15-069	AUTH access-surface bodies mark passwords/tokens/factors/provisioning secrets as sensitive/write-only or one-time output and every AUTH success/error response is no-store.
AC15-070	AUTH_LOGIN/AUTH_TOKEN/AUTH_RESET_REQUEST/AUTH_SESSION transport ceilings are enforced while PDF-19 may impose stricter failure/cooldown limits but cannot raise them.

34. Downstream Dependencies and Handoff

Later authority	Receives from DOC-15 / must not redefine
PDF-16 SEO/Search	Consume exact HTTP shapes while owning ranking, SEO fallback, XML sitemap and search algorithms.
PDF-17 Media/CDN	Implement MIME/size/storage/variant/processing/CDN behavior behind frozen Media HTTP surface.
PDF-18 Workers/Cache	Implement accepted async commands, cache invalidation and background work without changing API bodies/status semantics.
PDF-19 Security	Consumes exact API15-AUTH-* HTTP homes while owning password/token/session/cookie/MFA/CSRF/CORS/step-up/recovery mechanics; may add stricter security throttles but may not change method/path/schema/status without DOC-15 revision.
PDF-20 Scale/Operations	Capacity, latency, replicas, DR/observability targets; cannot change endpoint semantics.
PDF-21 QA	Generate contract/integration/security tests from operation IDs/schemas/acceptance criteria.
PDF-22 Traceability	Map requirements -> operations/schemas -> implementation -> QA.
PDF-23/24 Engineering/Deployment	Implement server/client code, folders, dependencies, gateway/proxy and deployment without changing API authority.

Appendix A. Canonical 112-Operation Endpoint Registry

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-PUB-001	GET	/api/v1/public/page	200	PUBLIC | NONE	- -> PublicPageResponse	PUBLIC_READ | NO | NONE
API15-PUB-002	GET	/api/v1/public/preview/posts/{post_id}	200	PREVIEW | PREVIEW_AUTHORITY	- -> PreviewPageData	PREVIEW_READ | NO | NONE
API15-AUTH-001	POST	/api/v1/auth/login	200	AUTH | NONE - credential verification only	LoginInput -> LoginResponse	AUTH_LOGIN | NO | NONE
API15-AUTH-002	POST	/api/v1/auth/logout	204	AUTH | ADMIN_SESSION	- -> EmptyResponse	AUTH_SESSION | NO | NONE
API15-AUTH-003	POST	/api/v1/auth/invitations/accept	200	AUTH | INVITE_SETUP_TOKEN	InvitationAcceptanceInput -> InvitationAcceptanceResponse	AUTH_TOKEN | NO | NONE
API15-AUTH-004	POST	/api/v1/auth/password/setup	200	AUTH | INVITE_SETUP_TOKEN OR ADMIN_SESSION	PasswordSetupInput -> PasswordSetupResponse	AUTH_TOKEN | NO | NONE
API15-AUTH-005	POST	/api/v1/auth/password-reset/request	202	AUTH | NONE	PasswordResetRequestInput -> AcceptedCommand	AUTH_RESET_REQUEST | NO | NONE
API15-AUTH-006	POST	/api/v1/auth/password-reset/complete	204	AUTH | RESET_TOKEN	PasswordResetCompleteInput -> EmptyResponse	AUTH_TOKEN | NO | NONE
API15-AUTH-007	POST	/api/v1/auth/mfa/enrollment	200	AUTH | ADMIN_SESSION OR INVITE_SETUP_TOKEN	MfaEnrollmentInput -> MfaEnrollmentResponse	AUTH_SESSION | NO | NONE
API15-AUTH-008	POST	/api/v1/auth/mfa/verify	200	AUTH | MFA_CHALLENGE	MfaVerificationInput -> MfaVerificationResponse	AUTH_TOKEN | NO | NONE
API15-AUTH-009	POST	/api/v1/auth/mfa/recovery	200	AUTH | MFA_CHALLENGE	MfaRecoveryInput -> MfaVerificationResponse	AUTH_TOKEN | NO | NONE

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-AUTH-010	POST	/api/v1/auth/sessions/terminate	204	AUTH | ADMIN_SESSION	SessionTerminationInput -> EmptyResponse	AUTH_SESSION | NO | NONE
API15-AUTH-011	POST	/api/v1/auth/step-up	200	AUTH | ADMIN_SESSION	StepUpInput -> StepUpResponse	AUTH_SESSION | NO | NONE
API15-S-001	GET	/api/v1/admin/sites/{site_key}/context	200	SITE | authenticated + active assignment	- -> AdminSiteContext	ADMIN_READ | NO | NONE
API15-S-002	GET	/api/v1/admin/sites/{site_key}/dashboard	200	SITE | dashboard.view	- -> DashboardResponse	ADMIN_READ | NO | NONE
API15-S-010	GET	/api/v1/admin/sites/{site_key}/posts	200	SITE | posts.view	- -> PostListResponse	ADMIN_READ | NO | NONE
API15-S-011	POST	/api/v1/admin/sites/{site_key}/posts	201	SITE | posts.view + posts.create	PostCreateInput -> PostResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-012	GET	/api/v1/admin/sites/{site_key}/posts/{post_id}	200	SITE | posts.view	- -> PostResponse	ADMIN_READ | NO | NONE
API15-S-013	PATCH	/api/v1/admin/sites/{site_key}/posts/{post_id}	200	SITE | posts.view + posts.edit	PostUpdateInput -> PostResponse	ADMIN_WRITE | REQUIRED | expected_version
API15-S-014	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/autosaves	201	SITE | posts.view + posts.edit	AutosaveInput -> AutosaveResponse	ADMIN_WRITE | REQUIRED | base_version
API15-S-015	GET	/api/v1/admin/sites/{site_key}/posts/{post_id}/autosaves/latest	200	SITE | posts.view + posts.edit	- -> AutosaveResponse	ADMIN_READ | NO | NONE
API15-S-016	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/preview-handoff	201	SITE | posts.view + posts.preview	PreviewHandoffInput -> PreviewHandoffResponse	ADMIN_SENSITIVE | REQUIRED | base_version
API15-S-017	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/schedule	200	SITE | posts.view + posts.edit + posts.schedule	SchedulePostInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-018	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/unschedule	200	SITE | posts.view + posts.edit + posts.schedule	VersionCommandInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-019	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/publish	200	SITE | posts.view + posts.edit + posts.publish	VersionCommandInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-020	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/archive	200	SITE | posts.view + posts.archive	VersionCommandInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-021	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/trash	200	SITE | posts.view + posts.trash	VersionCommandInput -> PostResponse	ADMIN_DESTRUCTIVE | REQUIRED | expected_version
API15-S-022	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/restore	200	SITE | posts.view + posts.restore	VersionCommandInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-023	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/permanent-delete	204	SITE | posts.view + posts.delete	VersionCommandInput -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | expected_version
API15-S-024	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/duplicate	201	SITE | posts.view + posts.duplicate	DuplicatePostInput -> PostResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-025	POST	/api/v1/admin/sites/{site_key}/posts/bulk	200	SITE | action-specific Post permission; security prevalidation for all targets	BulkPostInput -> BulkPostResponse	ADMIN_SENSITIVE | REQUIRED | per-target expected_version where applicable
API15-S-026	GET	/api/v1/admin/sites/{site_key}/posts/{post_id}/revisions	200	SITE | posts.view + posts.revisions.view	- -> RevisionListResponse	ADMIN_READ | NO | NONE
API15-S-027	POST	/api/v1/admin/sites/{site_key}/posts/{post_id}/revisions/{revision_id}/restore	200	SITE | posts.view + posts.edit + posts.revisions.view + posts.revisions.restore	RestoreRevisionInput -> PostResponse	ADMIN_SENSITIVE | REQUIRED | expected_version
API15-S-028	GET	/api/v1/admin/sites/{site_key}/posts/{post_id}/url-history	200	SITE | posts.view	- -> UrlHistoryResponse	ADMIN_READ | NO | NONE
API15-S-030	GET	/api/v1/admin/sites/{site_key}/categories	200	SITE | categories.view	- -> CategoryListResponse	ADMIN_READ | NO | NONE
API15-S-031	POST	/api/v1/admin/sites/{site_key}/categories	201	SITE | categories.view + categories.create	CategoryInput -> CategoryResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-032	GET	/api/v1/admin/sites/{site_key}/categories/{category_id}	200	SITE | categories.view	- -> CategoryResponse	ADMIN_READ | NO | NONE
API15-S-033	PATCH	/api/v1/admin/sites/{site_key}/categories/{category_id}	200	SITE | categories.view + categories.edit	CategoryUpdateInput -> CategoryResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-034	DELETE	/api/v1/admin/sites/{site_key}/categories/{category_id}	204	SITE | categories.view + categories.delete	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-S-040	GET	/api/v1/admin/sites/{site_key}/tags	200	SITE | tags.view	- -> TagListResponse	ADMIN_READ | NO | NONE
API15-S-041	POST	/api/v1/admin/sites/{site_key}/tags	201	SITE | tags.view + tags.create	TagInput -> TagResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-042	GET	/api/v1/admin/sites/{site_key}/tags/{tag_id}	200	SITE | tags.view	- -> TagResponse	ADMIN_READ | NO | NONE
API15-S-043	PATCH	/api/v1/admin/sites/{site_key}/tags/{tag_id}	200	SITE | tags.view + tags.edit	TagUpdateInput -> TagResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-044	DELETE	/api/v1/admin/sites/{site_key}/tags/{tag_id}	204	SITE | tags.view + tags.delete	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-S-045	POST	/api/v1/admin/sites/{site_key}/tags/{tag_id}/merge	200	SITE | tags.view + tags.edit + tags.delete	TagMergeInput -> TagResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-S-050	GET	/api/v1/admin/sites/{site_key}/authors	200	SITE | authors.view	- -> AuthorListResponse	ADMIN_READ | NO | NONE
API15-S-051	POST	/api/v1/admin/sites/{site_key}/authors	201	SITE | authors.view + authors.create	AuthorInput -> AuthorResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-052	GET	/api/v1/admin/sites/{site_key}/authors/{author_id}	200	SITE | authors.view	- -> AuthorResponse	ADMIN_READ | NO | NONE
API15-S-053	PATCH	/api/v1/admin/sites/{site_key}/authors/{author_id}	200	SITE | authors.view + authors.edit	AuthorUpdateInput -> AuthorResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-054	POST	/api/v1/admin/sites/{site_key}/authors/{author_id}/retire	200	SITE | authors.view + authors.retire	SimpleCommandInput -> AuthorResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-S-060	GET	/api/v1/admin/sites/{site_key}/media	200	SITE | media.view	- -> MediaListResponse	ADMIN_READ | NO | NONE
API15-S-061	POST	/api/v1/admin/sites/{site_key}/media	201	SITE | media.view + media.upload	MediaUploadInput -> MediaResponse	MEDIA_UPLOAD | REQUIRED | NONE
API15-S-062	GET	/api/v1/admin/sites/{site_key}/media/{media_id}	200	SITE | media.view	- -> MediaResponse	ADMIN_READ | NO | NONE
API15-S-063	PATCH	/api/v1/admin/sites/{site_key}/media/{media_id}	200	SITE | media.view + media.edit	MediaUpdateInput -> MediaResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-064	POST	/api/v1/admin/sites/{site_key}/media/{media_id}/replace	200	SITE | media.view + media.replace	MediaUploadInput -> MediaResponse	MEDIA_UPLOAD | REQUIRED | NONE
API15-S-065	DELETE	/api/v1/admin/sites/{site_key}/media/{media_id}	204	SITE | media.view + media.delete	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-S-066	GET	/api/v1/admin/sites/{site_key}/media/{media_id}/usage	200	SITE | media.view	- -> MediaUsageResponse	ADMIN_READ | NO | NONE
API15-S-070	GET	/api/v1/admin/sites/{site_key}/navigation/menus	200	SITE | navigation.view	- -> NavigationAdminResponse	ADMIN_READ | NO | NONE
API15-S-071	PUT	/api/v1/admin/sites/{site_key}/navigation/menus/{menu_key}	200	SITE | navigation.view + navigation.manage	NavigationMenuInput -> NavigationAdminResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-072	GET	/api/v1/admin/sites/{site_key}/homepage	200	SITE | navigation.view	- -> HomepageAdminResponse	ADMIN_READ | NO | NONE
API15-S-073	PUT	/api/v1/admin/sites/{site_key}/homepage	200	SITE | navigation.view + navigation.manage	HomepageInput -> HomepageAdminResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-080	GET	/api/v1/admin/sites/{site_key}/seo	200	SITE | seo.view	- -> SiteSeoResponse	ADMIN_READ | NO | NONE
API15-S-081	PATCH	/api/v1/admin/sites/{site_key}/seo	200	SITE | seo.view + seo.edit	SiteSeoInput -> SiteSeoResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-082	GET	/api/v1/admin/sites/{site_key}/redirects	200	SITE | redirects.view	- -> RedirectListResponse	ADMIN_READ | NO | NONE
API15-S-083	POST	/api/v1/admin/sites/{site_key}/redirects	201	SITE | redirects.view + redirects.create	RedirectInput -> RedirectResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-084	GET	/api/v1/admin/sites/{site_key}/redirects/{redirect_id}	200	SITE | redirects.view	- -> RedirectResponse	ADMIN_READ | NO | NONE
API15-S-085	PATCH	/api/v1/admin/sites/{site_key}/redirects/{redirect_id}	200	SITE | redirects.view + redirects.edit	RedirectUpdateInput -> RedirectResponse	ADMIN_WRITE | REQUIRED | NONE
API15-S-086	DELETE	/api/v1/admin/sites/{site_key}/redirects/{redirect_id}	204	SITE | redirects.view + redirects.delete	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-S-090	GET	/api/v1/admin/sites/{site_key}/search/posts	200	SITE | search.view	- -> AdminSearchResponse	ADMIN_READ | NO | NONE
API15-S-091	GET	/api/v1/admin/sites/{site_key}/search/internal-links	200	SITE | search.view	- -> InternalLinkSearchResponse	ADMIN_READ | NO | NONE
API15-S-092	GET	/api/v1/admin/sites/{site_key}/search/related-posts	200	SITE | search.view	- -> RelatedCandidateResponse	ADMIN_READ | NO | NONE
API15-S-093	GET	/api/v1/admin/sites/{site_key}/search/status	200	SITE | search.view	- -> SearchStatusResponse	ADMIN_READ | NO | NONE
API15-S-094	POST	/api/v1/admin/sites/{site_key}/search/reindex	202	SITE | search.view + search.reindex	SimpleCommandInput -> AcceptedCommand	REINDEX | REQUIRED | NONE
API15-S-095	GET	/api/v1/admin/sites/{site_key}/calendar	200	SITE | calendar.view	- -> CalendarResponse	ADMIN_READ | NO | NONE
API15-S-096	GET	/api/v1/admin/sites/{site_key}/settings	200	SITE | site_settings.view	- -> SiteSettingsResponse	ADMIN_READ | NO | NONE
API15-S-097	PATCH	/api/v1/admin/sites/{site_key}/settings	200	SITE | site_settings.view + site_settings.edit	SiteSettingsInput -> SiteSettingsResponse	ADMIN_WRITE | REQUIRED | NONE
API15-G-001	GET	/api/v1/admin/context	200	GLOBAL | authenticated ACTIVE Admin with at least one explicit GLOBAL permission	- -> AdminGlobalContext	ADMIN_READ | NO | NONE
API15-G-002	GET	/api/v1/admin/network/dashboard	200	GLOBAL | network_dashboard.view	- -> NetworkDashboardResponse	ADMIN_READ | NO | NONE
API15-G-003	GET	/api/v1/admin/network/posts	200	GLOBAL | network_dashboard.view + per-row site assignment + posts.view	- -> NetworkPostListResponse	ADMIN_READ | NO | NONE
API15-G-010	GET	/api/v1/admin/sites	200	GLOBAL | sites.view	- -> SiteListResponse	ADMIN_READ | NO | NONE

ID	Method	Path	Success	Scope / permission	Req -> Resp	Rate / idem / concurrency
API15-G-011	POST	/api/v1/admin/sites	201	GLOBAL | sites.view + sites.create	SiteCreateInput -> SiteAdminResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-012	GET	/api/v1/admin/sites/{site_key}	200	GLOBAL | sites.view	- -> SiteAdminResponse	ADMIN_READ | NO | NONE
API15-G-013	PATCH	/api/v1/admin/sites/{site_key}	200	GLOBAL | sites.view + sites.edit	SiteUpdateInput -> SiteAdminResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-014	POST	/api/v1/admin/sites/{site_key}/enable	200	GLOBAL | sites.view + sites.enable	SimpleCommandInput -> SiteAdminResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-015	POST	/api/v1/admin/sites/{site_key}/disable	200	GLOBAL | sites.view + sites.disable	SimpleCommandInput -> SiteAdminResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-016	POST	/api/v1/admin/sites/{site_key}/archive	200	GLOBAL | sites.view + sites.archive	SimpleCommandInput -> SiteAdminResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-017	POST	/api/v1/admin/sites/{site_key}/deletion-requests	201	GLOBAL | sites.view + sites.deletion_request	SiteDeletionRequestInput -> SiteDeletionRequestResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-018	GET	/api/v1/admin/sites/{site_key}/domains	200	GLOBAL | sites.view + sites.manage_domains	- -> DomainListResponse	ADMIN_READ | NO | NONE
API15-G-019	POST	/api/v1/admin/sites/{site_key}/domains	201	GLOBAL | sites.view + sites.manage_domains	DomainInput -> DomainResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-020	PATCH	/api/v1/admin/sites/{site_key}/domains/{domain_id}	200	GLOBAL | sites.view + sites.manage_domains	DomainUpdateInput -> DomainResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-021	DELETE	/api/v1/admin/sites/{site_key}/domains/{domain_id}	204	GLOBAL | sites.view + sites.manage_domains	- -> EmptyResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-022	POST	/api/v1/admin/sites/{site_key}/domains/{domain_id}/make-canonical	200	GLOBAL | sites.view + sites.manage_domains	SimpleCommandInput -> DomainResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-030	GET	/api/v1/admin/admin-users	200	GLOBAL | admin_users.view	- -> AdminUserListResponse	ADMIN_READ | NO | NONE
API15-G-031	POST	/api/v1/admin/admin-users/invitations	201	GLOBAL | admin_users.view + admin_users.invite	AdminInvitationInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-032	GET	/api/v1/admin/admin-users/{admin_user_id}	200	GLOBAL | admin_users.view	- -> AdminUserResponse	ADMIN_READ | NO | NONE
API15-G-033	PATCH	/api/v1/admin/admin-users/{admin_user_id}	200	GLOBAL | admin_users.view + admin_users.edit	AdminUserUpdateInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-034	POST	/api/v1/admin/admin-users/{admin_user_id}/enable	200	GLOBAL | admin_users.view + admin_users.enable	SimpleCommandInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-035	POST	/api/v1/admin/admin-users/{admin_user_id}/disable	200	GLOBAL | admin_users.view + admin_users.disable	SimpleCommandInput -> AdminUserResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-036	PUT	/api/v1/admin/admin-users/{admin_user_id}/site-assignments	200	GLOBAL | admin_users.view + admin_users.manage_site_assignments	SiteAssignmentInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-037	PUT	/api/v1/admin/admin-users/{admin_user_id}/role-assignments	200	GLOBAL | admin_users.view + roles.view + roles.assign	RoleAssignmentInput -> AdminUserResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-040	GET	/api/v1/admin/roles	200	GLOBAL | roles.view	- -> RoleListResponse	ADMIN_READ | NO | NONE
API15-G-041	POST	/api/v1/admin/roles	201	GLOBAL | roles.view + roles.create	RoleInput -> RoleResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-042	GET	/api/v1/admin/roles/{role_id}	200	GLOBAL | roles.view	- -> RoleResponse	ADMIN_READ | NO | NONE
API15-G-043	PATCH	/api/v1/admin/roles/{role_id}	200	GLOBAL | roles.view + roles.edit	RoleUpdateInput -> RoleResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-044	POST	/api/v1/admin/roles/{role_id}/retire	200	GLOBAL | roles.view + roles.retire	SimpleCommandInput -> RoleResponse	ADMIN_DESTRUCTIVE | REQUIRED | NONE
API15-G-045	POST	/api/v1/admin/roles/{role_id}/duplicate	201	GLOBAL | roles.view + roles.create	RoleDuplicateInput -> RoleResponse	ADMIN_SENSITIVE | REQUIRED | NONE
API15-G-046	GET	/api/v1/admin/permissions	200	GLOBAL | permissions.view	- -> PermissionRegistryResponse	ADMIN_READ | NO | NONE
API15-G-050	GET	/api/v1/admin/audit	200	GLOBAL | audit.view	- -> AuditListResponse	ADMIN_READ | NO | NONE
API15-G-051	GET	/api/v1/admin/audit/{audit_id}	200	GLOBAL | audit.view	- -> AuditResponse	ADMIN_READ | NO | NONE
API15-G-052	POST	/api/v1/admin/audit/export	202	GLOBAL | audit.view + audit.export	AuditExportInput -> AcceptedCommand	AUDIT_EXPORT | REQUIRED | NONE
API15-G-060	GET	/api/v1/admin/platform-settings	200	GLOBAL | platform_settings.view	- -> PlatformSettingsResponse	ADMIN_READ | NO | NONE
API15-G-061	PATCH	/api/v1/admin/platform-settings	200	GLOBAL | platform_settings.view + platform_settings.edit	PlatformSettingsInput -> PlatformSettingsResponse	ADMIN_SENSITIVE | REQUIRED | NONE

Appendix B. Schema Registry

This registry is generated directly from the delivered OpenAPI schema objects. Required fields are shown separately from the complete declared top-level property set. A dash in Required means the object has no always-required top-level property; it does NOT mean the schema has no optional properties. For oneOf schemas, composition is shown instead of properties. Nested

constraints and property-level permission metadata remain executable in openapi.yaml.

Schema	Kind	Required fields / composition	All declared top-level properties
EmptyResponse	object	-	-
ApiErrorDetail	object	code, message	field, code, message
ApiError	object	error	error
PageRequestMeta	object	page, page_size, has_more	page, page_size, has_more
AcceptedCommand	object	accepted, request_id	accepted, request_id
SimpleCommandInput	object	-	reason
VersionCommandInput	object	expected_version	expected_version, reason
PageContext	object	page_id, page_kind, render_mode	page_id, page_kind, render_mode, locale_code
PageIntro	object	h1	h1, intro_text
PublicDestination	object	kind, url, is_external	kind, url, page_id, is_external
SocialProfile	object	platform, url	platform, label, url
ContactItem	object	kind, label, display_value	kind, label, display_value, destination
ContactInfo	object	items	items
MediaVariant	object	variant_key, url, mime_type	variant_key, url, mime_type, width, height
PublicMedia	object	media_id, url, mime_type, variants	media_id, url, mime_type, width, height, alt_text, caption, variants, credit_text
SiteIdentity	object	site_key, display_name, canonical_domain, home_destination, timezone_id	site_key, display_name, canonical_domain, home_destination, logo_media, favicon_media, default_language, locale_code, timezone_id
PublicSettings	object	social_profiles	copyright_text, social_profiles, default_social_image
NavigationItem	object	label, destination, children	label, destination, children
NavigationMenu	object	menu_key, items	menu_key, items
NavigationBundle	object	header, footer	header, footer
BreadcrumbItem	object	label, is_current	label, destination, is_current
BreadcrumbTrail	object	items	items
TaxonomySummary	object	kind, name, destination	kind, name, destination
AuthorSummary	object	author_id, display_name	author_id, display_name, destination, avatar_media, short_bio
AuthorDetail	object	author_id, display_name, destination, expertise, social_profiles	author_id, display_name, destination, avatar_media, bio, designation, expertise, social_profiles
CategoryDetail	object	category_id, name, destination	category_id, name, description, destination
TagDetail	object	tag_id, name, destination	tag_id, name, description, destination
PaginationLink	object	page_number, destination, is_current	page_number, destination, is_current
Pagination	object	current_page, links	current_page, links, previous, next
RobotsDirective	object	index, follow	index, follow
OpenGraph	object	title, type	title, description, url, type, image
SeoProjection	object	baseline_indexability, title, robots, structured_data	baseline_indexability, title, meta_description, canonical_url, open_graph, robots, structured_data
InlineMark	object	kind	kind, destination
InlineRun	object	text, marks	text, marks, link
RichText	object	runs	runs
ParagraphBlock	object	block_id, type, payload	block_id, type, payload
HeadingBlock	object	block_id, type, payload	block_id, type, payload
ListBlock	object	block_id, type, payload	block_id, type, payload
QuoteBlock	object	block_id, type, payload	block_id, type, payload
SeparatorBlock	object	block_id, type, payload	block_id, type, payload
MediaBlock	object	block_id, type, payload	block_id, type, payload
TableBlock	object	block_id, type, payload	block_id, type, payload
EmbedBlock	object	block_id, type, payload	block_id, type, payload
CalloutBlock	object	block_id, type, payload	block_id, type, payload
CtaBlock	object	block_id, type, payload	block_id, type, payload
DisclaimerBlock	object	block_id, type, payload	block_id, type, payload
SourceReferenceEntry	object	title	title, url, publisher, note
SourcesReferencesBlock	object	block_id, type, payload	block_id, type, payload
ArticleBlock	oneOf	union of 12 alternatives	-
ArticleBody	object	content_schema_version, blocks	content_schema_version, blocks
ArticleSummary	object	article_id, destination, title, published_at	article_id, destination, title, excerpt, featured_media, author, published_at, updated_at, taxonomy_label

Schema	Kind	Required fields / composition	All declared top-level properties
ArticleDetail	object	article_id, destination, title, body, author, categories, tags, published_at	article_id, destination, title, excerpt, body, featured_media, author, categories, tags, published_at, updated_at
PreviewArticle	object	article_id, title, body, categories, tags	article_id, public_destination, title, excerpt, body, author, categories, tags, featured_media, published_at, updated_at
RelatedContent	object	articles	articles
HomeSection	object	section_key, section_kind	section_key, section_kind, label, posts, categories
StaticSection	object	paragraphs, list_items	heading, paragraphs, list_items
StaticContent	object	static_key, title, sections	static_key, title, intro_text, sections
PreviewMeta	object	lifecycle_status, source_kind, notice_text	lifecycle_status, source_kind, notice_text, return_url
SystemMessage	object	code, title, body	code, title, body
RecoveryActions	object	-	home, search
HomePageData	object	context, site, settings, navigation, intro, sections, latest_articles, seo	context, site, settings, navigation, intro, lead_article, sections, latest_articles, seo
ArticlePageData	object	context, site, settings, navigation, article, seo	context, site, settings, navigation, breadcrumbs, article, related_content, seo
CategoryPageData	object	context, site, settings, navigation, category, articles, seo	context, site, settings, navigation, breadcrumbs, category, articles, pagination, seo
TagPageData	object	context, site, settings, navigation, tag, articles, seo	context, site, settings, navigation, breadcrumbs, tag, articles, pagination, seo
AuthorPageData	object	context, site, settings, navigation, author, articles, seo	context, site, settings, navigation, breadcrumbs, author, articles, pagination, seo
SearchPageData	object	context, site, settings, navigation, intro, query, search_state, articles, result_summary, seo	context, site, settings, navigation, intro, query, search_state, articles, result_summary, pagination, seo
StaticPageData	object	context, site, settings, navigation, content, seo	context, site, settings, navigation, breadcrumbs, content, contact_info, seo
PreviewPageData	object	context, site, settings, navigation, preview, article, seo	context, site, settings, navigation, preview, article, related_content, seo
NotFoundPageData	object	context, message, seo	context, site, settings, navigation, message, recovery, seo
GonePageData	object	context, message, recovery, seo	context, site, settings, navigation, message, recovery, seo
PublicPageResponse	oneOf	union of 7 alternatives	-
AdminSiteContext	object	site_key, display_name, lifecycle_state, effective_permissions	site_key, display_name, lifecycle_state, effective_permissions
AdminGlobalContext	object	effective_permissions	effective_permissions
DashboardMetric	object	key, label, value	key, label, value
DashboardResponse	object	metrics, attention_items	metrics, attention_items
AdminLinkDestination	object	kind	kind, target_type, target_id, url
AdminInlineRun	object	text, marks	text, marks, link
AdminRichText	object	runs	runs
AdminParagraphBlock	object	block_id, type, content	block_id, type, content
AdminHeadingBlock	object	block_id, type, level, content	block_id, type, level, content
AdminListBlock	object	block_id, type, style, items	block_id, type, style, items
AdminQuoteBlock	object	block_id, type, quote	block_id, type, quote, attribution, source
AdminSeparatorBlock	object	block_id, type	block_id, type
AdminMediaBlock	object	block_id, type, media_id	block_id, type, media_id, alt_override, caption
AdminTableBlock	object	block_id, type, header_row, rows	block_id, type, header_row, rows
AdminEmbedBlock	object	block_id, type, provider_key, source_url_or_id	block_id, type, provider_key, source_url_or_id, caption
AdminCalloutBlock	object	block_id, type, body	block_id, type, label, body
AdminCtaBlock	object	block_id, type, label, destination	block_id, type, label, supporting_text, destination
AdminDisclaimerBlock	object	block_id, type, body	block_id, type, label, body
AdminSourceReferenceEntry	object	title	title, url, publisher, note
AdminSourcesReferencesBlock	object	block_id, type, entries	block_id, type, entries
AdminArticleBlock	oneOf	union of 12 alternatives	-
AdminArticleBody	object	content_schema_version, blocks	content_schema_version, blocks
PostResource	object	post_id, status, version, body, category_ids, tag_ids, manual_related_post_ids, updated_at, created_at	post_id, status, version, title, excerpt, body, category_ids, tag_ids, featured_media_id, manual_related_post_ids, slug, seo_title, meta_description, canonical_override, index_policy, link_robots_policy, og_title, og_description, published_at, updated_at, author_site_profile_id, og_image_media_id, structured_data_inputs, breadcrumb_label, scheduled_for_utc, schedule_local_input, schedule_timezone_id, first_published_at, archived_at, trashed_at, created_at
PostCreateInput	object	body	title, excerpt, body, category_ids, tag_ids, featured_media_id, manual_related_post_ids, slug, seo_title, meta_description, canonical_override, index_policy, link_robots_policy, og_title, og_description, author_site_profile_id, og_image_media_id, structured_data_inputs, breadcrumb_label

Schema	Kind	Required fields / composition	All declared top-level properties
PostUpdateInput	object	expected_version	title, excerpt, body, category_ids, tag_ids, featured_media_id, manual_related_post_ids, slug, seo_title, meta_description, canonical_override, index_policy, link_robots_policy, og_title, og_description, expected_version, author_site_profile_id, og_image_media_id, structured_data_inputs, breadcrumb_label
PostResponse	object	post	post
PostListResponse	object	items, page	items, page
AutosaveInput	object	base_version, working_copy	base_version, working_copy
AutosaveResponse	object	autosave_id, post_id, base_version, saved_at, working_copy	autosave_id, post_id, base_version, saved_at, working_copy
PreviewHandoffInput	object	source_kind	source_kind, base_version, working_copy
PreviewHandoffResponse	object	preview_url, expires_at	preview_url, expires_at
SchedulePostInput	object	expected_version, schedule_local_input, schedule_timezone_id	expected_version, schedule_local_input, schedule_timezone_id
DuplicatePostInput	object	-	title_override
BulkPostTarget	object	post_id, expected_version	post_id, expected_version
BulkPostInput	object	action, targets	action, targets, schedule_local_input, schedule_timezone_id
BulkPostOutcome	object	post_id, status	post_id, status, error_code
BulkPostResponse	object	outcomes	outcomes
RevisionSummary	object	revision_id, post_id, version, created_at	revision_id, post_id, version, created_at, created_by_admin_id
RevisionListResponse	object	items, page	items, page
RestoreRevisionInput	object	expected_version	expected_version
UrlHistoryItem	object	slug, became_current_at	slug, became_current_at, ceased_current_at
UrlHistoryResponse	object	items	items
CategoryResource	object	category_id, name, slug, status, created_at, updated_at	category_id, name, description, slug, parent_category_id, status, created_at, updated_at, seo_title, meta_description, canonical_override, index_policy
CategoryInput	object	name	name, description, slug, parent_category_id, seo_title, meta_description, canonical_override, index_policy
CategoryUpdateInput	object	-	name, description, slug, parent_category_id, seo_title, meta_description, canonical_override, index_policy
CategoryResponse	object	category	category
CategoryListResponse	object	items	items
TagResource	object	tag_id, name, slug, status, created_at, updated_at	tag_id, name, description, slug, status, created_at, updated_at
TagInput	object	name	name, description, slug
TagUpdateInput	object	-	name, description, slug
TagResponse	object	tag	tag
TagListResponse	object	items	items
TagMergeInput	object	target_tag_id	target_tag_id
AuthorResource	object	author_id, display_name, expertise, social_profiles, status, created_at, updated_at	author_id, display_name, slug, bio, designation, expertise, social_profiles, avatar_media_id, status, created_at, updated_at, seo_title, meta_description, canonical_override, index_policy
AuthorInput	object	display_name, expertise, social_profiles	display_name, slug, bio, designation, expertise, social_profiles, avatar_media_id, seo_title, meta_description, canonical_override, index_policy
AuthorUpdateInput	object	-	display_name, slug, bio, designation, expertise, social_profiles, avatar_media_id, seo_title, meta_description, canonical_override, index_policy
AuthorResponse	object	author	author
AuthorListResponse	object	items	items
MediaResource	object	media_id, filename, mime_type, size_bytes, status, created_at, updated_at, usage_count, variants	media_id, filename, mime_type, size_bytes, width, height, alt_text, caption, credit, status, public_url, created_at, updated_at, title, source_url, usage_count, variants
MediaUploadInput	object	file	file, alt_text, caption, credit, title, source_url
MediaUpdateInput	object	-	alt_text, caption, credit, title, source_url
MediaResponse	object	media	media
MediaListResponse	object	items, page	items, page
MediaUsageItem	object	resource_type, resource_id, label	resource_type, resource_id, label
MediaUsageResponse	object	items	items
AdminNavDestination	object	kind	kind, target_id, url
AdminNavItem	object	label, destination, children	label, destination, children
NavigationMenuInput	object	items	items
NavigationAdminResponse	object	header, footer	header, footer

Schema	Kind	Required fields / composition	All declared top-level properties
HomepageSectionAdmin	object	section_key, section_kind, enabled	section_key, section_kind, enabled, display_label, post_ids, category_ids
HomepageInput	object	sections	lead_post_id, sections
HomepageAdminResponse	object	homepage	homepage
SiteSeoInput	object	-	seo_title, meta_description, index_policy, link_robots_policy, default_social_image_media_id, structured_data_inputs
SiteSeoResponse	object	seo	seo
RedirectResource	object	redirect_id, source_path, destination_url, status_code, is_active, created_at, updated_at	redirect_id, source_path, destination_url, status_code, is_active, created_at, updated_at
RedirectInput	object	source_path, destination_url, status_code	source_path, destination_url, status_code, is_active
RedirectUpdateInput	object	-	source_path, destination_url, status_code, is_active
RedirectResponse	object	redirect	redirect
RedirectListResponse	object	items, page	items, page
AdminSearchHit	object	post_id, title, status, updated_at	post_id, title, status, updated_at
AdminSearchResponse	object	items, page	items, page
InternalLinkCandidate	object	kind, label, destination_url	kind, label, destination_url, resource_id
InternalLinkSearchResponse	object	items, page	items, page
RelatedCandidateResponse	object	items, page	items, page
SearchStatusResponse	object	state	state, last_indexed_at, message
CalendarItem	object	post_id, title, status	post_id, title, status, scheduled_for, published_at
CalendarResponse	object	items, from, to	items, from, to
SettingEntry	object	key, value	key, value
SiteSettingsInput	object	settings	settings
SiteSettingsResponse	object	settings	settings
PlatformSettingsInput	object	settings	settings
PlatformSettingsResponse	object	settings	settings
SiteAdminResource	object	site_key, display_name, lifecycle_state, timezone_id, created_at, updated_at	site_key, display_name, lifecycle_state, canonical_domain, default_language, locale_code, timezone_id, created_at, updated_at
SiteCreateInput	object	site_key, display_name, timezone_id	site_key, display_name, default_language, locale_code, timezone_id
SiteUpdateInput	object	-	display_name, default_language, locale_code, timezone_id
SiteAdminResponse	object	site	site
SiteListResponse	object	items, page	items, page
SiteDeletionRequestInput	object	reason, confirmation_text	reason, confirmation_text
SiteDeletionRequestResponse	object	request_id, site_key, state, created_at	request_id, site_key, state, created_at
DomainResource	object	domain_id, hostname, is_canonical, is_active, created_at, updated_at	domain_id, hostname, is_canonical, is_active, created_at, updated_at
DomainInput	object	hostname	hostname, is_canonical, is_active
DomainUpdateInput	object	-	is_active
DomainResponse	object	domain	domain
DomainListResponse	object	items	items
RoleAssignment	object	role_id, scope	role_id, scope, site_key
AdminUserResource	object	admin_user_id, email, state, site_assignments, role_assignments, created_at, updated_at	admin_user_id, email, display_name, state, site_assignments, role_assignments, created_at, updated_at
AdminInvitationInput	object	email	email, display_name, site_assignments, role_assignments
AdminUserUpdateInput	object	-	display_name, email
SiteAssignmentInput	object	site_keys	site_keys
RoleAssignmentInput	object	assignments	assignments
AdminUserResponse	object	admin_user	admin_user
AdminUserListResponse	object	items, page	items, page
RoleResource	object	role_id, name, scope, permission_keys, state, created_at, updated_at	role_id, name, description, scope, permission_keys, state, created_at, updated_at
RoleInput	object	name, scope, permission_keys	name, description, scope, permission_keys
RoleUpdateInput	object	-	name, description, permission_keys
RoleDuplicateInput	object	name	name
RoleResponse	object	role	role
RoleListResponse	object	items	items
PermissionEntry	object	permission_key, scope, description, prerequisite_keys	permission_key, scope, description, prerequisite_keys
PermissionRegistryResponse	object	items, count	items, count

Schema	Kind	Required fields / composition	All declared top-level properties
NetworkDashboardResponse	object	site_count, aggregates, site_summaries	site_count, aggregates, site_summaries
NetworkPostItem	object	site_key, site_display_name, post	site_key, site_display_name, post
NetworkPostListResponse	object	items, page	items, page
AuditResource	object	audit_id, occurred_at, scope, event_type, summary, request_id	audit_id, occurred_at, actor_admin_user_id, scope, site_key, event_type, resource_type, resource_id, summary, request_id
AuditResponse	object	audit	audit
AuditListResponse	object	items, page	items, page
AuditExportInput	object	format	actor_id, site_key, event_type, from, to, format
LoginInput	object	email, password	email, password
LoginResponse	object	state	state, session_expires_at, mfa_challenge_id, challenge_expires_at
InvitationAcceptanceInput	object	invite_token	invite_token
InvitationAcceptanceResponse	object	accepted, next_step, expires_at	accepted, next_step, expires_at
InvitationPasswordSetupInput	object	mode, invite_token, new_password	mode, invite_token, new_password
AuthenticatedPasswordChangeInput	object	mode, current_password, new_password	mode, current_password, new_password
PasswordSetupInput	oneOf	union of 2 alternatives	-
PasswordSetupResponse	object	completed, next_step	completed, next_step
PasswordResetRequestInput	object	email	email
PasswordResetCompleteInput	object	reset_token, new_password	reset_token, new_password
MfaEnrollmentInput	object	mode	mode, current_password, invite_token
MfaEnrollmentResponse	object	enrollment_id, secret_base32, provisioning_uri, expires_at	enrollment_id, secret_base32, provisioning_uri, expires_at
MfaVerificationInput	object	challenge_id, code	challenge_id, code
MfaVerificationResponse	object	result	result, session_expires_at, step_up_expires_at, recovery_codes
MfaRecoveryInput	object	challenge_id, recovery_code	challenge_id, recovery_code
SessionTerminationInput	object	scope	scope
StepUpFactor	object	kind, value	kind, value
StepUpInput	object	level, current_password	level, current_password, factor
StepUpResponse	object	level, expires_at	level, expires_at

Appendix C. Error / Status Matrix

Code	HTTP	Meaning
BAD_REQUEST	400	Malformed path/query/header/body or unsupported media type.
UNAUTHENTICATED	401	Protected operation lacks a valid authenticated/preview authority.
DENIED	403	Authenticated principal lacks required scope/permission/step-up condition; no protected payload returned.
NOT_FOUND	404	Target unavailable in authorized context, including non-disclosed wrong-site targets.
CONFLICT	409	Current state conflicts with requested mutation.
VERSION_CONFLICT	409	expected_version does not equal current durable version; no mutation performed.
STATE_CONFLICT	409	Lifecycle/state transition is not legal for current resource state.
IDEMPOTENCY_KEY_REUSE	409	Same Idempotency-Key reused with a materially different request fingerprint.
VALIDATION_FAILED	422	Syntactically valid request violates field/business validation.
RATE_LIMITED	429	Transport quota exceeded; Retry-After supplied.
SERVICE_UNAVAILABLE	503	Required service dependency is temporarily unavailable.

Appendix D. Rate-Limit Registry

Class	Limit	Window seconds	Quota identity
PUBLIC_READ	120	60	effective client + trusted public site
PREVIEW_READ	30	60	preview authority + trusted preview site
AUTH_LOGIN	30	60	source IP + normalized login-identifier hash
AUTH_TOKEN	30	60	source IP + security token-family hash
AUTH_RESET_REQUEST	10	3600	source IP; PDF-19 additionally limits matched normalized account
AUTH_SESSION	30	60	authenticated Admin session + admin_id
ADMIN_READ	120	60	authenticated Admin account
ADMIN_WRITE	60	60	Admin account + trusted target scope

Class	Limit	Window seconds	Quota identity
ADMIN_SENSITIVE	30	60	Admin account + trusted target scope
ADMIN_DESTRUCTIVE	10	60	Admin account + trusted target scope
MEDIA_UPLOAD	20	60	Admin account + trusted site
REINDEX	2	3600	Admin account + trusted site
AUDIT_EXPORT	4	3600	Admin account

Appendix E. One-Page Developer Execution Reference

PUBLIC	Host -> DOC-09 route resolution -> one ACTIVE CTX-PUBLIC-SITE -> public eligibility -> direct DOC-13 PageData. 308 canonicalization; 301/302 manual redirects; safe 404/410.
SECURITY ACCESS	/auth/* -> no SiteContext -> validate current PDF-19 credential/token/challenge/session proof -> establish/revoke/upgrade security state only. Authentication never grants SITE/GLOBAL permission.
SITE ADMIN	/admin/sites/{site_key} -> authenticate ACTIVE Admin -> validate site/lifecycle + assignment -> exact SITE permission -> CTX-ADMIN-SITE -> same-site object -> state/version validation -> mutation/read.
GLOBAL ADMIN	/admin/* -> authenticated ACTIVE Admin -> exact GLOBAL permission -> global resource/authorized aggregate only. Site-owned drilldown/mutation re-enters target CTX-ADMIN-SITE.
MUTATION SAFETY	Idempotency-Key where REQUIRED; 24h replay window; expected_version for versioned Post mutations; no silent merge/overwrite; 409 on conflicts; current authorization always rechecked.
CONTRACT SYNC	PDF rationale + endpoint registry and openapi.yaml executable schemas are generated from one source. Any mismatch is release-blocking.