What supports the M6-to-corner observation?

The shift toward M1–M2 during the slow precursor remains in both November runs and in the comparison checks.

Comparison	Paired events	M6 first	Then M1–M2	Share of M6-first
Run 32731	320	59	43 / 59	73%
Run 32739	213	27	17 / 27	63%
Both runs + one July record	533	86	60 / 86	70%
Exclude events 33 and 52	531	85	59 / 85	69%
Use a 4.096 µs window	544	93	73 / 93	78%
Raise the signal cut to 50 ADC	428	70	53 / 70	76%
Exclude header-only baselines	462	76	55 / 76	72%
Require pulse before TPC precursor	355	69	47 / 69	68%

Coverage of the saved sample

1,531 saved records were checked; 1,527 contain PDS data.

1,377 have both APA2 endpoint 109 and a main-shake time: 714 in run 32731, 662 in run 32739, and one in run 27938.

15 records have no main-shake time. Another 139 aligned records have no APA2 endpoint 109.

The October files contain other PDS endpoints. Applying the APA2 M6/corner layout to them would give the wrong physical comparison.

After the shake, only 13 records pass the snapshot coverage rule; only 4 support a main-to-after paired comparison.

The counts describe this saved sample, not the frequency of this behaviour during detector operation.

M6 has the largest first pulse in 99 / 602 assessable events. The M6-to-corner sequence recurs, but M6 is not the usual starting maximum.

“Largest” is an amplitude comparison. It is not the same as “first to start”; channel timing is checked separately in the linked leading-channel study.