

ISLR | Chapter 8 Exercises

Marshall McQuillen

10/10/2018

Conceptual

1

(sketch on following page)

2

Consider the regression setting; when each tree has depth one (meaning there is only one split), each tree will only consist of one split on one attribute, and the predicted response for those two groups will be the mean response (of the training data) of those two groups. Therefore, the base model will take the form $f_j(x_j) = \beta_j I(x_{ji} \leq t) + \beta'_j I(x_{ji} > t)$, where t is the value in the range of x_j that dictates the split (in order to minimize the RSS). Knowing this, one can outline algorithm 8.2, as shown below:

$$f(\hat{x}) = 0 \tag{1}$$

$$f_1(x_1) = \beta_1 I(x_{1i} \leq t) + \beta'_1 I(x_{1i} > t) \tag{2}$$

$$f(\hat{x}) = f(\hat{x}) + \lambda f_1(x_1) \tag{3}$$

$$r_i = r_i - \lambda f_1(x_i) \tag{4}$$

$$f_2(x_2) = \beta_2 I(x_{2i} \leq t) + \beta'_2 I(x_{2i} > t) \tag{5}$$

$$f(\hat{x}) = f(\hat{x}) + \lambda f_2(x_2) \tag{6}$$

$$r_i = r_i - \lambda f_2(x_i) \tag{7}$$

$$\vdots \tag{8}$$

$$f_j(x_j) = \beta_j I(x_{ji} \leq t) + \beta'_j I(x_{ji} > t) \tag{9}$$

$$f(\hat{x}) = f(\hat{x}) + \lambda f_j(x_j) \tag{10}$$

$$r_i = r_i - \lambda f_j(x_i) \tag{11}$$

$$\vdots \tag{12}$$

$$f(x) = \sum_{j=1}^P f_j(X_j) \quad \text{where} \quad f_j(X_j) = \beta_j I(x_{ji} \leq t) + \beta'_j I(x_{ji} > t) \tag{13}$$

$$\tag{14}$$

Note that β_j is the mean of the response for all values of x_j that are less than or equal to t , and β'_j is the mean response for all values of x_j that are greater than t .





Figure 1: "Conceptual Exercise 1"