TableOS — Complete Test Plan

Every feature, role, limit and API, in 32 modules you can test one by one

Plan 1.0 · for TableOS 0.16.2 · generated 2026-10-21
279 test cases: P1 134 · P2 106 · P3 39

Record results and screenshots in **TableOS-Test-Workbook.html**, then use **Export for developer**.

How to test

1. Work module by module (M00 first). Each module is independent once M00 is done.
2. For every case: follow the steps, compare with Expected, then mark Pass, Fail, Blocked (can't run it because something else is broken) or N/A (feature not used).
3. For a failure: pick a severity, write what actually happened (and what you expected), and attach screenshots (paste with Ctrl+V, drag in, or choose files).
4. Priority: P1 must work (blocker if broken), P2 important, P3 polish.
5. Use the interactive workbook (TableOS-Test-Workbook.html): it saves automatically in your browser. When done (or at any point), click "Export for developer" and send that one file; it contains every result, note and screenshot.
6. Found a problem no case covers? Add it under "Other findings" at the end of the workbook.

Severity

Severity	Meaning
Critical	Data loss, security hole, or nobody can work.
High	A main feature is broken with no workaround.
Medium	Broken but there is a workaround, or a secondary feature fails.
Low	Cosmetic, wording, small inconvenience.

Test accounts

Name	Account	How to set it up
OWNER	Owner	ai.deptbcc@bluecascade.org (the account from the fresh start)
OWNER2	Second Owner	A second Owner, invited by OWNER as Owner
ADMIN	Admin	Invited by OWNER as Admin; give it Creator on workspace WS-A only
CREATOR	Member, base Creator	Invited to base BASE-1 as Creator
EDITOR	Member, base Editor	Invited to base BASE-1 as Editor
COMMENTER	Member, base Commenter	Invited to base BASE-1 as Commenter
VIEWER	Member, workspace Viewer	Invited to workspace WS-A as Viewer (all its bases)
DOMAIN	Member via allowed domain	Signs up with an @bluecascade.org (or allowed) email without an invitation
OUTSIDER	No account	An email that is not invited and not on an allowed domain

Test data

Name	What
WS-A	Workspace "Sales" created by OWNER
WS-B	Workspace "Finance" created by OWNER
BASE-1	Base "CRM" in WS-A with tables Contacts, Companies, Deals
BASE-2	Base "Budget" in WS-B
CSV-S	A small CSV (20 rows, 6 columns: text, number, date, email, select-like, checkbox)
CSV-L	A large CSV (5,000+ rows) for background import
XLSX	An Excel file with two sheets
CSV-BAD	A CSV with invalid emails, phone numbers and dates mixed in

IMG	A few images (PNG/JPG, one larger than 5 MB) and a PDF

Modules

Module	Goal	Cases	P1
M00 Environment and test accounts	Get everything the other modules need, and record what you test against.	6	5
M01 Sign-up and invitations	Only invited people (or allowed email domains) can create accounts; nobody gets a personal organization.	9	4
M02 Sign-in, two-factor and sessions	Sign-in always needs the password and a two-factor code; sessions end after 30 idle days.	9	2
M03 Sign-in security: wrong passwords and alerts	Five wrong passwords lock an account for 15 minutes; Owners are alerted with email and IP.	6	3
M04 Account types: Owner, Admin, Member	Only Owners change account types; several Owners; transfer; at least one Owner always remains.	9	6
M05 Members & access: invites, roles, end dates	One invite form everywhere; roles per workspace or base; Admins only within their reach.	15	10
M06 Device approval	With device approval on, every non-Owner needs each browser approved.	8	3
M07 Security settings and Activity log	Allowed sign-up domains and the audit trail.	6	3
M08 Workspaces	Only Owners and Admins create workspaces; rename and delete with a warning.	8	4
M09 Bases	Create, rename, duplicate, move, delete and restore bases.	9	5
M10 Tables	Add, rename, duplicate, hide, delete and restore tables.	6	3
M11 Fields and field types	Every field type stores, shows and converts values correctly.	19	10
M12 Editing records in the grid	Fast, correct editing with mouse and keyboard.	10	5
M13 Comments, mentions and history	Discuss records and see who changed what.	6	4
M14 Undo, redo and trash	Mistakes can be reversed.	4	3
M15 Views	Every view type and the view toolbar; the default Grid view can never be deleted.	18	7
M16 Links, lookups, rollups and counts	Relationships between tables, including across bases.	7	4
M17 Formulas	Formula fields compute correctly and report errors clearly.	8	4
M18 Synced tables from another base	Read-only copies that stay up to date.	8	3
M19 Connectors: Airtable, HubSpot, Gmail, Slack	External data and messaging.	7	0
M20 Import and export	Files in and out; export is for Owners and Admins only.	10	6
M21 Attachments	Upload, preview, download, limits.	5	2
M22 Forms	Collect records from anyone with the link.	5	3
M23 Interfaces	Dashboards and app pages on top of the data.	6	2
M24 Automations	Triggers, actions, tests, run history, Runs as and limits.	15	5
M25 Public share links	Read-only links for people outside TableOS, Creators and up only.	9	6
M26 Search, notifications and contacts	Find things and stay informed.	6	2
M27 Live collaboration (realtime)	Changes appear for everyone without refreshing.	7	2
M28 API and access tokens	The public record API, token scopes and errors.	17	9
M29 Limits and performance	TableOS behaves well at its limits and with real amounts of data.	7	1

M30 Permission matrix spot checks	One pass through the roles to make sure each sees exactly what it should.	8	8
M31 Help, UI and browsers	Everything is understandable and works across browsers and screen sizes.	6	0

M00 — Environment and test accounts

Goal: Get everything the other modules need, and record what you test against.

Before you start

- Use a desktop browser (Chrome or Edge, latest) for OWNER, and a second browser or a private window for every other account.
- Install an authenticator app on your phone (Google Authenticator, Microsoft Authenticator, Authy…). Every account needs two-factor.

`M00-01` **Record the version under test** P1 UI

1. Open Help → Release notes.
2. Open <API>/v1/version in a browser tab.

> **Expected:** Both show the same version (e.g. 0.16.2). Note it at the top of this workbook.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M00-02` **OWNER signs in for the first time** P1 Security

1. Sign in as OWNER with the agreed password.

> **Expected:** You are taken to “Set up two-factor sign-in” and nothing else opens until it is done.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M00-03` **OWNER sets up two-factor** P1 Security

1. Click Set up two-factor authentication.
2. Scan the QR code with the authenticator app.
3. Enter the 6-digit code and Turn on.

> **Expected:** Two-factor turns on and TableOS opens Home. Account → Two-factor shows On and has no “Turn off” option.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M00-04` **Create the test workspaces and base** P1 Data

1. As OWNER create WS-A and WS-B on Home.
2. In WS-A create BASE-1 with tables Contacts, Companies, Deals; in WS-B create BASE-2.

> **Expected:** All appear on Home under the right workspace.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M00-05 **Invite the test accounts** P1 UI

1. Members & access → People → invite each account from the Accounts table with the stated account type and access.
2. Each person opens the invitation email (or the copied link), creates an account and sets up two-factor.

> **Expected:** Every account can sign in and sees only what it was given.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M00-06 **Prepare the test files** P2 Data

1. Create CSV-S, CSV-L, XLSX, CSV-BAD and IMG on your computer.

> **Expected:** Files ready for M20–M22.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M01 — Sign-up and invitations

Goal: Only invited people (or allowed email domains) can create accounts; nobody gets a personal organization.

Before you start

- OUTSIDER and DOMAIN are not signed in. Allowed domains are set in M07 first if you test DOMAIN here.

`M01-01` **Sign-up page explains invitations** P3 UI

1. Open /signup while signed out.

> **Expected:** The page says TableOS accounts are by invitation.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M01-02` **Stranger can't sign up** P1 Security

1. Sign up with the OUTSIDER email.

> **Expected:** Refused: “TableOS accounts are by invitation only…”. No account is created.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M01-03` **Invited person signs up from the link** P1 UI

1. Invite a new email to BASE-1 as Viewer.
2. Open the invitation link signed out → Sign up with that email.

> **Expected:** Account created, invitation accepted, the person lands on two-factor setup, then sees only BASE-1.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M01-04` **Invitation for the wrong account** P2 Security

1. While signed in as EDITOR, open an invitation sent to another email.

> **Expected:** TableOS says the invitation was sent to another address and asks to sign in with it.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M01-05` **Expired or cancelled invitation** P2 Security

1. Cancel a pending invitation in Members & access, then open its link.

> **Expected:** The link shows “expired or revoked”.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M01-06` **Allowed-domain sign-up** P1 Security

1. With @bluecascade.org in allowed domains (M07), sign up as DOMAIN without an invitation.

> **Expected:** Account created as Member with no access. OWNER and Admins get a bell notification “New member: …”.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M01-07` **No personal organization** P1 Security

1. After any sign-up above, open the account menu → Members & access, and Home.

> **Expected:** No organization or “Home” workspace of their own was created.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M01-08` **Invitation with an account type** P2 UI

1. As OWNER invite an email as Admin with “No workspace or base yet”. Open the link signed out.

> **Expected:** The invitation page says “You’ll join as Admin”. After accepting, the person is Admin.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M01-09` **Re-invite never lowers an account type** P2 Security

1. Invite ADMIN again as a Member to a base and accept it.

> **Expected:** ADMIN is still Admin, with the extra base access.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M02 — Sign-in, two-factor and sessions

Goal: Sign-in always needs the password and a two-factor code; sessions end after 30 idle days.

`M02-01` **Sign in with code** P1 Security

1. Sign out, sign in as EDITOR with password, enter the authenticator code.

> **Expected:** Signed in. A wrong code shows “Invalid authentication code”.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M02-02` **Too many wrong codes** P2 Security

1. Enter a wrong two-factor code 5 times.

> **Expected:** The sign-in attempt expires and you must enter the password again.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M02-03` **Two-factor can't be turned off** P1 Security

1. Account → Two-factor authentication.

> **Expected:** Shows On and a note that it can't be turned off. No turn-off form.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M02-04` **Show password** P3 UI

1. On sign-in, sign-up and Change password click the eye icon.

> **Expected:** The password becomes visible and hides again.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M02-05` **Change password** P2 Security

1. Account → Password → change it.

> **Expected:** Saved. Other sessions of that account are signed out; the current one stays.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M02-06` **Sessions list** P2 Security

1. Account → Sessions: sign in from a second browser, then “Sign out other sessions”.

> **Expected:** Both sessions listed with browser and IP; the other browser is signed out on its next action.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M02-07 **Session ends after 30 idle days** P3 Security

1. (Optional, needs database access) Ask the developer to age a session past 30 days, then use it.

> **Expected:** You are sent to the sign-in page. Activity within 30 days keeps you signed in.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M02-08 **Back after signing in** P2 UI

1. Signed out, open a deep link (a base URL). Sign in.

> **Expected:** After sign-in (and two-factor) you land on that base.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M02-09 **Google sign-in (if enabled)** P3 Security

1. Click Sign in with Google with an invited Google account.

> **Expected:** Signs in; two-factor is still required.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M03 — Sign-in security: wrong passwords and alerts

Goal: Five wrong passwords lock an account for 15 minutes; Owners are alerted with email and IP.

Before you start

- Use the EDITOR account. Have OWNER signed in elsewhere to watch the bell.

M03-01 **Attempts 1–2: no warning** P2 Security

1. Enter a wrong password twice for EDITOR.

Expected: Plain “Incorrect email or password”.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M03-02 **Attempts 3–4: warning** P1 Security

1. Enter a wrong password a 3rd and 4th time.

Expected: A warning with attempts left (e.g. “2 attempts left”).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M03-03 **Attempt 5: locked 15 minutes** P1 Security

1. Enter a wrong password a 5th time, then the right one.

Expected: Account locked with a countdown; the right password is refused while locked.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M03-04 **Owner alerts** P1 Security

1. Check OWNER’s bell and email.

Expected: One alert per wrong attempt with the email tried, IP, browser, time and “Wrong password n of 5”, plus a lock alert.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M03-05 **Owner is never locked** P2 Security

1. Enter OWNER’s password wrong 6 times (in a private window).

Expected: OWNER is not locked (the general rate limit of 10 tries per 15 minutes per IP still applies).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M03-06 **Unlock after 15 minutes** P2 Security

1. Wait 15 minutes, sign in as EDITOR with the right password.

> **Expected:** Works and resets the count.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M04 — Account types: Owner, Admin, Member

Goal: Only Owners change account types; several Owners; transfer; at least one Owner always remains.

`M04-01` **Account types offered** P1 UI

1. As OWNER open Members & access → People → Invite.

> **Expected:** Account type list is exactly Member, Admin, Owner.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M04-02` **Owner changes an account type** P1 UI

1. Change EDITOR to Admin and back to Member with the Account type select.

> **Expected:** Confirmation, then the badge changes; Activity log records it.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M04-03` **Admin can't change account types** P1 Security

1. As ADMIN open People.

> **Expected:** No Account type selects and no Transfer ownership.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M04-04` **Second Owner** P1 Security

1. Invite OWNER2 as Owner; accept.

> **Expected:** OWNER2 sees every workspace and base, and Members & access.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M04-05` **Owner steps down (two Owners)** P2 UI

1. As OWNER2 set your own account type to Admin.

> **Expected:** Allowed while another active Owner exists.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M04-06` **Last Owner can't step down** P1 Security

1. With a single Owner, try to make yourself Admin.

> **Expected:** Refused: the organization needs at least one Owner.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M04-07 **Transfer ownership** P2 UI

1. As OWNER click Transfer ownership on OWNER2 (or a Member) and confirm.

> **Expected:** They become Owner and you become Admin. (Restore afterwards.)

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M04-08 **Admin data access is only what is given** P1 Security

1. As ADMIN (Creator on WS-A only) open Home.

> **Expected:** ADMIN opens WS-A's bases but not WS-B's; WS-B is listed by name (rename/delete only).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M04-09 **Billing is Owner-only** P3 Security

1. As ADMIN look for plan/billing options or call the billing endpoint.

> **Expected:** Not available to Admins.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05 — Members & access: invites, roles, end dates

Goal: One invite form everywhere; roles per workspace or base; Admins only within their reach.

M05-01 **Invite to selected bases** P1 UI

1. Invite with “Selected bases only”, tick two bases, role Editor.

> **Expected:** The person sees exactly those two bases, as Editor.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-02 **Invite to a whole workspace** P1 UI

1. Invite with “Workspace · WS-A (all its bases)”, role Viewer.

> **Expected:** The person sees every base in WS-A, read-only.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-03 **Workspace Owner role** P2 Security

1. Give CREATOR the Workspace Owner role on WS-B.
2. As CREATOR: rename WS-B, edit a base’s fields in WS-B, try Create a base in WS-B.

> **Expected:** Rename (and delete) WS-B works and CREATOR is Creator on every base in it; creating bases still needs Owner or Admin.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-04 **Home Share uses the same form** P2 UI

1. On Home click Share on WS-A.

> **Expected:** The same invite form, starting with the whole workspace; the member list below.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-05 **Change a role** P1 Security

1. Edit access → change a base role from Editor to Viewer.

> **Expected:** The person can no longer edit (refresh their page).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-06 **Base role overrides workspace role** P1 Security

1. VIEWER has Viewer on WS-A. Set BASE-1 to Editor for VIEWER, and another base to “No access to this base”.

> **Expected:** VIEWER edits BASE-1, can't see the blocked base, still reads the others.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-07 **Access end date** P2 Security

1. Set “Access until” to tomorrow on a grant.

> **Expected:** Shown as time-limited; after the date the access disappears.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-08 **Bulk change** P2 UI

1. Tick several rows in Edit access and Apply a role to selected.

> **Expected:** All selected rows change.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-09 **Suspend and reactivate** P1 Security

1. Suspend EDITOR, try to open BASE-1 as EDITOR, then reactivate.

> **Expected:** Suspended: nothing opens. Reactivated: access back with the same roles.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-10 **Remove from organization** P1 Security

1. Remove a test Member.

> **Expected:** All their access and devices here are gone.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-11 **Admin manages Members within reach** P1 Security

1. As ADMIN invite a Member to WS-A; change their role; suspend them.

> **Expected:** All allowed.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-12 **Admin limits** P1 Security

1. As ADMIN try: invite to WS-B, give a role above Creator, change OWNER’s or another Admin’s access, change your own access, invite an Admin.

> **Expected:** Each is refused with a clear message.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-13 **Admin sees only what they manage** P1 Security

1. As ADMIN open Members & access.

> **Expected:** Only WS-A (and its bases) appear in the invite form and access matrix.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-14 **Member can't open Members & access** P1 Security

1. As EDITOR open the account menu → Members & access.

> **Expected:** "Only Owners and Admins can manage access."

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M05-15 **Pending invitations** P2 UI

1. Check the invitations list; cancel one.

> **Expected:** Listed with role and expiry; cancelled invitation link stops working.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M06 — Device approval

Goal: With device approval on, every non-Owner needs each browser approved.

Before you start

- Security → Require device approval is on (default).

`M06-01` **New device waits** P1 Security

1. Sign in as EDITOR in a new browser.

> **Expected:** A “waiting for approval” banner; no data opens.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M06-02` **Owner/Admin notified** P2 UI

1. Check OWNER’s and ADMIN’s bell.

> **Expected:** “Device approval needed” with browser and IP.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M06-03` **Approve** P1 Security

1. Members & access → Devices → Approve.

> **Expected:** EDITOR’s page unlocks by itself.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M06-04` **Revoke and forget** P2 Security

1. Revoke the device, then Forget it.

> **Expected:** Revoked device is blocked again; forgotten device asks for approval next time.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M06-05` **Admin limits on devices** P1 Security

1. As ADMIN try to approve your own device or OWNER’s.

> **Expected:** Refused. ADMIN can approve Members’ devices.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M06-06` **Owner is exempt** P2 Security

1. Sign in as OWNER in a new browser.

> **Expected:** No approval needed.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M06-07 **Device log** P3 UI

1. Open Devices and expand a person.

> **Expected:** Waiting/approved/revoked devices, active and ended sessions, history of approvals with who decided.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M06-08 **Turn approval off** P2 Security

1. Security → untick Require device approval; sign in from a new browser as EDITOR.

> **Expected:** No approval needed. Turn it back on afterwards.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M07 — Security settings and Activity log

Goal: Allowed sign-up domains and the audit trail.

`M07-01` **Add and remove allowed domains** P1 UI

1. Security → add "@example.org", then remove it.

> **Expected:** Chip appears and disappears; invalid input like "not a domain" is refused.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M07-02` **Admins can change security** P2 Security

1. As ADMIN change allowed domains.

> **Expected:** Allowed.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M07-03` **Activity log lists events** P1 UI

1. Members & access → Activity.

> **Expected:** Recent sign-ins, invitations, role changes, devices, tokens, moves… with who, what, when and IP.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M07-04` **Activity filter** P2 UI

1. Choose each filter (Invitations, Devices…).

> **Expected:** Only that kind of event is listed.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M07-05` **Show older** P3 UI

1. With more than 100 events, click Show older.

> **Expected:** Older events load below.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M07-06` **Members can't see Activity** P1 Security

1. As EDITOR try /admin?tab=activity.

> **Expected:** Refused.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M08 — Workspaces

Goal: Only Owners and Admins create workspaces; rename and delete with a warning.

`M08-01` **Owner creates a workspace** P1 UI

1. Home → + Create workspace.

> **Expected:** Created and listed in the sidebar.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M08-02` **Members can't create workspaces** P1 Security

1. As EDITOR look for + Create workspace.

> **Expected:** Not shown; the API refuses it too.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M08-03` **Organization picker** P3 UI

1. As an account that is Owner/Admin of two organizations, create a workspace.

> **Expected:** The dialog asks which organization.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M08-04` **Rename workspace** P2 UI

1. Workspace ⋯ → Rename.

> **Expected:** Name changes everywhere.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M08-05` **Delete workspace with warning** P1 UI

1. Workspace ⋯ → Delete workspace…
2. Try to confirm before typing the name, then type it and delete.

> **Expected:** Delete stays disabled until the exact name is typed; then the workspace and its bases disappear for everyone.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M08-06` **Who can delete** P1 Security

1. As EDITOR and as VIEWER open the workspace ⋯ menu.

> **Expected:** No Delete or Rename for them.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M08-07 **Contacts directory** P2 UI

1. Workspace ⋯ → Contacts: add, edit, search, delete a contact.

> **Expected:** Works for people with a workspace role; base-only people don’t get Contacts.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M08-08 **Empty Home for people without access** P3 UI

1. Sign in as DOMAIN (no access yet).

> **Expected:** “Nothing has been shared with you yet” with an explanation.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M09 — Bases

Goal: Create, rename, duplicate, move, delete and restore bases.

`M09-01` **Create a base** P1 UI

1. In WS-A click Create a base → Start from scratch.

> **Expected:** Opens with Table 1, a default Grid view and 3 empty rows.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M09-02` **Create from a CSV** P2 UI

1. Create a base → Import a CSV.

> **Expected:** Base created with the file's columns and rows.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M09-03` **Rename a base** P2 UI

1. Base ⋯ (Home card or base title menu) → Rename.

> **Expected:** Name updated in Home, title and search.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M09-04` **Duplicate a base (Owner/Admin)** P1 UI

1. Base card ⋯ → Duplicate.

> **Expected:** A copy with tables, fields, views and records appears in the same workspace.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M09-05` **Members can't duplicate** P1 Security

1. As CREATOR look for Duplicate.

> **Expected:** Not shown; API refuses.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M09-06` **Move to another workspace** P1 UI

1. Base card ⋯ → Move to workspace… → WS-B.

> **Expected:** Base listed in WS-B with all data, automations and share links working; people who had access only through WS-A lose it; base-level roles stay.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M09-07 **Move limits** P2 Security

1. As CREATOR (not Owner/Admin/Workspace Owner of both) try to move.

> **Expected:** Refused.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M09-08 **Delete a base** P1 UI

1. Base ⋯ → Delete → confirm.

> **Expected:** Removed for everyone.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M09-09 **Base IDs** P3 UI

1. Table tab menu → IDs & API…

> **Expected:** Shows bas_… and tbl_… IDs with copy buttons.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M10 — Tables

Goal: Add, rename, duplicate, hide, delete and restore tables.

`M10-01` **Add a blank table** P1 UI

1. + next to the table tabs → Blank table.

> **Expected:** New tab with a default Grid view.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M10-02` **Rename, duplicate, hide** P2 UI

1. Table tab menu → Rename / Duplicate / Hide.

> **Expected:** Each works; hidden tables can be shown again.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M10-03` **Reorder tables** P3 UI

1. Drag a table tab.

> **Expected:** Order is kept after refresh.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M10-04` **Delete and restore** P1 Data

1. Delete a table, then Tools → Trash → restore.

> **Expected:** Table and data come back.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M10-05` **Table limit** P3 Limit

1. (Free plan: 50 tables per base.) Create tables until refused, or ask the developer to check.

> **Expected:** A clear plan-limit message at the limit.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M10-06` **Viewer can't change tables** P1 Security

1. As VIEWER open the table tab menu.

> **Expected:** No create/rename/delete.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11 — Fields and field types

Goal: Every field type stores, shows and converts values correctly.

Before you start

- Use a scratch table in BASE-1. For each type: create the field, enter 3 values (normal, empty, edge), refresh, then convert to Single line text and back where it makes sense.

`M11-01` **Single line text and Long text** P1 UI

1. Create both; type short, empty and very long (2,000+ chars) values; multi-line in Long text.

> **Expected:** Values saved; long text wraps in tall rows and the expanded record.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M11-02` **Number, Currency, Percent** P1 UI

1. Set decimals, currency symbol; enter 0, negative, large and decimal values.

> **Expected:** Shown with the chosen format; invalid text refused or converted.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M11-03` **Duration and Rating** P2 UI

1. Enter 1:30 in Duration; set Rating by click and keys 1–9.

> **Expected:** Stored and shown correctly.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M11-04` **Checkbox** P2 UI

1. Toggle by click and Enter.

> **Expected:** Toggles; counts in summaries.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M11-05` **Single and Multiple select** P1 UI

1. Add options with colors, rename an option, delete one, pick values, type a new option.

> **Expected:** Options and colors kept; renaming updates every record.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-06 **User (collaborator)** P2 UI

1. Assign collaborators; allow multiple on/off.

> **Expected:** Only base collaborators listed; avatars shown.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-07 **Date and Date and time** P1 UI

1. Set formats and time zone; enter dates via picker and typing.

> **Expected:** Shown in the chosen format and time zone; sorting by date works.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-08 **Email, URL, Phone** P2 UI

1. Enter valid and invalid values; click the links.

> **Expected:** Valid ones become links (mailto:, tel:, web); invalid ones are flagged/refused.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-09 **Attachment** P1 UI

1. Upload images and a PDF (see M21).

> **Expected:** Thumbnails in the cell; preview and download work.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-10 **Link to another record** P1 UI

1. Link Deals → Companies; allow multiple off/on (see M16).

> **Expected:** Chips shown; the other table gets a matching link field.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-11 **Barcode, Button, JSON** P3 UI

1. Enter a barcode value; configure a Button with a URL and click it; enter valid and invalid JSON.

> **Expected:** Barcode stored; button opens the URL; invalid JSON refused.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-12 **Formula, Lookup, Rollup, Count** P1 UI

1. Create each (see M16, M17).

> **Expected:** Read-only computed values that update when inputs change.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-13 **Autonumber, Record ID, Created/modified time, Created/modified by** P2 UI

1. Add each; create and edit records.

> **Expected:** Filled automatically, read-only; modified fields update on edit.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-14 **Primary field** P2 UI

1. Try to hide/delete the primary field; Set as primary on another field.

> **Expected:** Primary can't be hidden or deleted; another field can become primary.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-15 **Change field type** P1 Data

1. Convert number → text → number, text → single select, date → text.

> **Expected:** Values converted where possible; Ctrl+Z undoes the change.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-16 **Field description and menu** P2 UI

1. Add a description; use header ▾: duplicate, insert left/right, sort, filter, group, freeze, hide.

> **Expected:** Description shows as a tooltip; each menu action works.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-17 **Reorder and resize columns** P3 UI

1. Drag a header; drag its edge.

> **Expected:** Kept after refresh (per view).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-18 **Field permissions** P1 Security

1. Field ▾ → Edit permissions → Creators and up; then Specific users; then Nobody but Creators and Owners. Test with EDITOR and CREATOR.

> **Expected:** EDITOR is blocked as configured; Owners and Creators can always edit.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M11-19 **Delete a field and restore** P1 Data

1. Delete a field, then restore it from Trash.

> **Expected:** Field and its values come back.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M12 — Editing records in the grid

Goal: Fast, correct editing with mouse and keyboard.

`M12-01` **Type into cells** P1 UI

1. Click a cell and type; press Enter to edit; Esc to cancel.

> **Expected:** Values saved; Esc restores the old value.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M12-02` **Keyboard navigation** P2 UI

1. Use arrows, Ctrl+arrows, Tab/Shift+Tab, Enter, Space (expand), Shift+Space (select row), Delete (clear).

> **Expected:** Each shortcut does what Help → Keyboard shortcuts says.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M12-03` **Copy and paste** P1 UI

1. Copy a range in TableOS and paste elsewhere; paste a range from Excel/Google Sheets.

> **Expected:** Values pasted into the right cells with type conversion.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M12-04` **Fill handle** P2 UI

1. Select a cell and drag the fill handle down.

> **Expected:** Values copied down.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M12-05` **Add, insert, duplicate, delete rows** P1 UI

1. + row at the bottom; right-click a row → insert above/below, duplicate, delete.

> **Expected:** Each works; deleted rows can be restored from Trash.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M12-06` **Multi-select actions** P2 UI

1. Tick several row checkboxes; delete them.

> **Expected:** All selected rows deleted (and restorable).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M12-07 **Expanded record** P1 UI

1. Open a record (⤢ or Space); edit hidden fields; move with ↑/↓ or K/J; copy record URL; Esc.

> **Expected:** Everything editable; URL contains rec_...; navigation works.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M12-08 **Record URL** P2 UI

1. Copy a record URL, open it in another tab.

> **Expected:** Opens the same table, view and record.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M12-09 **Viewer and Commenter can't edit** P1 Security

1. As VIEWER and COMMENTER try to edit cells, add/delete rows.

> **Expected:** Not possible in the UI; API refuses.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M12-10 **Large table scrolling** P2 Limit

1. Open a table with 5,000+ rows (after CSV-L import) and scroll.

> **Expected:** Smooth; rows load as you scroll; row count in the footer is right.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M13 — Comments, mentions and history

Goal: Discuss records and see who changed what.

`M13-01` **Comment on a record** P1 UI

1. Expanded record → write a comment.

> **Expected:** Comment shown with author and time.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M13-02` **@mention** P1 UI

1. Mention EDITOR in a comment.

> **Expected:** EDITOR gets a bell notification that opens the record.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M13-03` **Edit and delete own comment** P2 Security

1. Edit then delete your comment.

> **Expected:** Allowed for your own; others' comments can't be changed.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M13-04` **Commenter can comment** P1 Security

1. As COMMENTER comment on a record.

> **Expected:** Allowed; editing cells is not.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M13-05` **Revision history** P1 UI

1. Change several fields; open the record's history; group by person / by field.

> **Expected:** Every change listed with old → new value, who and when.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M13-06` **Activity filters** P3 UI

1. Use the record activity filter (all activity, revision history, comments, resolved).

> **Expected:** Lists filter correctly.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M14 — Undo, redo and trash

Goal: Mistakes can be reversed.

`M14-01` **Undo/redo cell edits** P1 UI

1. Edit cells, press Ctrl+Z several times, then Ctrl+Shift+Z / Ctrl+Y.

> **Expected:** Edits undone and redone in order.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M14-02` **Undo a deletion** P1 Data

1. Delete rows, press Ctrl+Z.

> **Expected:** Rows come back with their values and links.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M14-03` **Undo a field type change** P2 Data

1. Change a field type, press Ctrl+Z.

> **Expected:** Type and values restored.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M14-04` **Trash** P1 Data

1. Tools → Trash: restore a deleted record, field and table.

> **Expected:** Each restored.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15 — Views

Goal: Every view type and the view toolbar; the default Grid view can never be deleted.

`M15-01` **Default Grid view** P1 Security

1. On any table open the default Grid view's ⋯ menu.

> **Expected:** No "Delete view" and no "Make personal"; a note "Default view: every table keeps it." Rename still works.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M15-02` **Grid view** P1 UI

1. Create a collaborative Grid view.

> **Expected:** Works like the default grid.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M15-03` **Gallery view** P2 UI

1. Create a Gallery with an attachment as cover.

> **Expected:** Cards with covers; click opens the record.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M15-04` **Kanban view** P1 UI

1. Kanban by a single select (and by a user field); drag cards between columns.

> **Expected:** Dragging changes the field value.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M15-05` **Calendar view** P2 UI

1. Calendar on a date field; drag a record to another day.

> **Expected:** Records on their dates; dragging changes the date.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M15-06` **Timeline and Gantt** P2 UI

1. Set start and end dates; drag/resize bars.

> **Expected:** Bars match the dates; changes saved.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-07 **List view** P3 UI

1. Create a List view.

> **Expected:** Compact readable list.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-08 **Form view** P1 UI

1. Create a Form view (see M22).

> **Expected:** Form editor opens.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-09 **Hide fields** P1 UI

1. Hide and show fields; drag their order.

> **Expected:** Only this view changes.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-10 **Filter** P1 UI

1. Add conditions for text, number, date, select, checkbox, empty/not empty; nest an OR group.

> **Expected:** Only matching records shown; the filter is saved with the view.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-11 **Sort and group** P1 UI

1. Sort by two fields; group by up to three fields with group summaries.

> **Expected:** Correct order and groups.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-12 **Color and row height** P3 UI

1. Color rows by a select field and by conditions; change row height.

> **Expected:** Applied and saved.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-13 **Search in view** P2 UI

1. Use 🔍 in the toolbar.

> **Expected:** Matches highlighted; moves between matches.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-14 **Summary footer** P2 UI

1. Choose count, sum, average, min, max, filled, empty per column.

> **Expected:** Correct numbers for the visible records.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-15 **Personal, collaborative, locked views** P2 Security

1. Create a personal view (only you see it); lock a collaborative view; try editing it as EDITOR.

> **Expected:** Personal views are private; locked views can't be changed except by their creator/base Creators.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-16 **Favorites, duplicate, rename, delete** P2 UI

1. Favorite a view; duplicate; rename; delete a non-default view.

> **Expected:** Each works; favorites appear in My favorites.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-17 **Views sidebar** P3 UI

1. Hide the views list with ☰ and show it again; refresh.

> **Expected:** Choice remembered.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M15-18 **View URL** P3 UI

1. Copy the URL of a view and open it in a new tab.

> **Expected:** Opens the same view.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M16 — Links, lookups, rollups and counts

Goal: Relationships between tables, including across bases.

`M16-01` **Create a link** P1 UI

1. Deals: Link to Companies. Pick records; type to search.

> **Expected:** Chips in Deals; Companies gets a matching link field showing the deals.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M16-02` **Single vs multiple** P2 UI

1. Turn off “allow multiple” and try to add a second record.

> **Expected:** Only one allowed.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M16-03` **Lookup** P1 Data

1. Companies → lookup Deals.Amount.

> **Expected:** Shows the linked values; updates when Deals change.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M16-04` **Rollup** P1 Data

1. Companies → rollup SUM(Deals.Amount), then AVERAGE, MAX, COUNT, ARRAYJOIN.

> **Expected:** Correct results; update live.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M16-05` **Count** P2 Data

1. Companies → count of Deals.

> **Expected:** Correct counts.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M16-06` **Unlinking and deleting** P1 Data

1. Remove a link chip; delete a linked record.

> **Expected:** Lookups/rollups/counts update; no orphan errors.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M16-07 **Link to another base** P2 UI

1. Create a link field → + Link to a table in another base → BASE-2.

> **Expected:** A synced copy of that table is added and linked; lookups work.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M17 — Formulas

Goal: Formula fields compute correctly and report errors clearly.

`M17-01` **Arithmetic and text** P1 Data

1. {Price} * {Quantity}; {First} & " " & {Last}; UPPER/LOWER/LEFT/MID.

> **Expected:** Correct values.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M17-02` **Logic** P1 Data

1. IF, SWITCH, AND/OR, ISBLANK, IFERROR.

> **Expected:** Correct values.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M17-03` **Dates** P1 Data

1. DATEADD, DATETIME_DIFF, DATETIME_FORMAT, TODAY, NOW, WORKDAY, IS_BEFORE, SET_TIMEZONE.

> **Expected:** Correct values in the base time zone.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M17-04` **Lists and regex** P2 Data

1. ARRAYJOIN/ARRAYUNIQUE on a lookup; REGEX_MATCH/EXTRACT/REPLACE.

> **Expected:** Correct values.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M17-05` **Record functions** P2 Data

1. RECORD_ID(), CREATED_TIME(), ROW_NUMBER(), CREATED_BY().

> **Expected:** Correct values.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M17-06` **Editor help** P3 UI

1. Type in the formula editor.

> **Expected:** Field and function suggestions appear.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M17-07 **Errors** P2 UI

1. Write an invalid formula (unknown field, wrong arguments, division by zero).

> **Expected:** Clear error message; the field isn't saved broken / shows #ERROR in cells as designed.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M17-08 **Updates** P1 Realtime

1. Change an input field.

> **Expected:** Formula value updates immediately (and for other users live).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M18 — Synced tables from another base

Goal: Read-only copies that stay up to date.

`M18-01` **Add a synced table** P1 UI

1. + → Sync from another base → pick BASE-2's table.

> **Expected:** Table with ⇄ badge, fields and records copied.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M18-02` **Changes flow** P1 Data

1. Edit/add/delete in the source; wait a few seconds.

> **Expected:** Changes appear in the synced table (full check also every ~5 minutes).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M18-03` **Schema changes flow** P2 Data

1. Rename, add and delete a field in the source.

> **Expected:** Reflected in the synced table.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M18-04` **Read-only** P1 Security

1. Try to edit or add records in the synced table.

> **Expected:** Not allowed; your own extra fields stay editable.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M18-05` **Sync bar controls** P2 UI

1. Sync now, Stop, Pause, Resume.

> **Expected:** Progress shown; each control works.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M18-06` **Values that don't fit** P2 Data

1. Put an invalid phone in a source field mapped to Phone; sync.

> **Expected:** Rest syncs; "values couldn't be synced — review" lets you keep as text or leave empty.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M18-07 **Stop syncing** P2 UI

1. Tab menu → Stop syncing.

> **Expected:** Becomes a normal editable table.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M18-08 **Access of the creator** P3 Security

1. Remove the sync creator's access to the source base.

> **Expected:** Sync stops with an error until someone with access sets it up again.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M19 — Connectors: Airtable, HubSpot, Gmail, Slack

Goal: External data and messaging.

Before you start

- Needs real accounts/tokens for each service. Skip (mark N/A) any service you don't use.

`M19-01` **Connect Airtable** P2 UI

1. Account menu → Connectors → Airtable → paste a personal access token.

> **Expected:** Connected; listed under Connectors.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M19-02` **Sync from Airtable** P2 Data

1. + → Sync from Airtable → base, table, fields.

> **Expected:** Records and fields arrive; linked records show names; attachments show names/links.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M19-03` **Connect HubSpot and sync** P2 Data

1. Connect a private-app token; Sync from HubSpot → contacts with chosen properties.

> **Expected:** Records arrive with types kept; refresh every 15 minutes; Sync now works.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M19-04` **HubSpot two-way** P3 Data

1. Tick Two-way; edit a synced field.

> **Expected:** The change appears in HubSpot within seconds; rejected values explained on the bar.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M19-05` **Gmail** P3 Data

1. Sign in with Google; Sync from Gmail with in:inbox; automation step Send email via Gmail.

> **Expected:** Messages arrive in a table; the email is sent from your address.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M19-06` **Slack** P3 Data

1. Connect a bot token in the Send Slack message step; run the automation.

> **Expected:** Message posted in the channel.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M19-07 **Disconnect** P3 UI

1. Remove a connection.

> **Expected:** Removed; syncs using it show an error instead of silently failing.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M20 — Import and export

Goal: Files in and out; export is for Owners and Admins only.

`M20-01` **Import CSV as a new table** P1 Data

1. + → Import a file → CSV-S; check suggested types; import.

> **Expected:** Table created with the right types and 20 rows.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M20-02` **Import Excel** P2 Data

1. Import XLSX; pick the second sheet.

> **Expected:** That sheet imported.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M20-03` **Import TSV/TXT** P3 Data

1. Import a .tsv and .txt file.

> **Expected:** Imported correctly.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M20-04` **Import into an existing table** P1 Data

1. Table menu → Import into the table; check column matching, + New field, Import all / Don't import any.

> **Expected:** Columns matched by name; new fields created where chosen.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M20-05` **Large import in the background** P1 Limit

1. Import CSV-L.

> **Expected:** Progress shown; you can keep working; all rows arrive.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M20-06` **Stop an import** P2 UI

1. Start CSV-L and press Stop.

> **Expected:** Stops at once with a summary.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M20-07 **Invalid entries** P1 Data

1. Import CSV-BAD.

> **Expected:** Invalid values listed per row; fix them, import them empty or skip them.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M20-08 **Name clashes** P3 UI

1. Import a file whose table name already exists.

> **Expected:** A sensible new name or a prompt.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M20-09 **Export CSV/Excel/JSON** P1 Data

1. As OWNER: Tools → Export CSV (or view menu Download) as CSV, Excel and JSON.

> **Expected:** Only visible fields and filtered records, in view order.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M20-10 **Members can't export** P1 Security

1. As CREATOR and EDITOR look for Export / Download.

> **Expected:** Not shown; API refuses (copy and paste in the grid still works).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M21 — Attachments

Goal: Upload, preview, download, limits.

`M21-01` **Upload in a cell** P1 UI

1. Drop images and a PDF into an Attachment cell.

> **Expected:** Uploads with progress; thumbnails shown.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M21-02` **Preview and download** P1 UI

1. Open the expanded attachment view; download a file.

> **Expected:** Preview for images/PDF; download saves the original file.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M21-03` **Remove and reorder** P2 UI

1. Remove one attachment; reorder.

> **Expected:** Saved.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M21-04` **File size limit** P2 Limit

1. Upload a file over 100 MB.

> **Expected:** Refused with a clear message (per-file limit 100 MB; base limit 1 GB on the Free plan).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M21-05` **Attachments in share links** P2 Security

1. See M25 (allow copy off).

> **Expected:** No download links when copy is off.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M22 — Forms

Goal: Collect records from anyone with the link.

`M22-01` **Build a form** P1 UI

1. Create a Form view; choose fields, mark required ones, add help text.

> **Expected:** Saved.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M22-02` **Share and submit** P1 Data

1. Share the form link; submit it signed out.

> **Expected:** A new record is created with the values.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M22-03` **Required fields and validation** P1 Data

1. Submit with a required field empty or an invalid email.

> **Expected:** Refused with a message.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M22-04` **Attachments in a form** P2 Data

1. Upload a file in the form.

> **Expected:** File attached to the new record.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M22-05` **Form-submitted automation** P2 Data

1. See M24 trigger “When a form is submitted”.

> **Expected:** Automation runs.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M23 — Interfaces

Goal: Dashboards and app pages on top of the data.

`M23-01` **Create an interface** P1 UI

1. Base → Interfaces → create one.

> **Expected:** Designer opens.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M23-02` **Each element** P1 UI

1. Add Number, Chart, Date filter, Grid, List, Gallery, Record details, Form, Button, Text, Divider; connect each to a table/view.

> **Expected:** Each element renders the right data.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M23-03` **Charts** P2 Data

1. Bar, horizontal bar, line, area, pie, donut; group dates by day/week/month/quarter/year; up to four values; sort; limit; labels and legend.

> **Expected:** Correct totals; empty periods shown as zero.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M23-04` **Date filter** P2 Data

1. Add a Date filter; try each period and a custom range.

> **Expected:** Every element using the same table follows the filter.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M23-05` **Record details and Form** P2 UI

1. Select a record in a List; Record details shows it; submit the Form element.

> **Expected:** Correct record; new record created.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M23-06` **Publish/view as others** P2 Security

1. Open the interface as EDITOR and VIEWER.

> **Expected:** They see the page according to their role.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24 — Automations

Goal: Triggers, actions, tests, run history, Runs as and limits.

M24-01 **Record created → Update record** P1 Data

1. Create the automation, turn it on, add a record.

> **Expected:** Runs and updates the record; run history shows success.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-02 **Record updated (specific fields)** P1 Data

1. Trigger on one field; edit that field and another.

> **Expected:** Runs only for the chosen field.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-03 **Record matches conditions / enters a view** P2 Data

1. Set conditions; change a record to match.

> **Expected:** Runs once when it starts matching.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-04 **Form submitted** P2 Data

1. Trigger on a form; submit it.

> **Expected:** Runs.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-05 **Scheduled** P2 Data

1. Every N minutes / daily at a time.

> **Expected:** Runs on time (check run history).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-06 **Button clicked** P2 Data

1. Button field with Run automation; click it.

> **Expected:** Runs for that record.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-07 **Webhook received** P2 API

1. Copy the webhook URL; POST JSON to it (e.g. with curl or Postman).

> **Expected:** Runs with the payload available as tokens; too many calls in a burst return 429.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-08 **Actions** P1 Data

1. Use each: Update, Create, Find, Delete record; In-app notification; Send email; Send webhook; Conditional group.

> **Expected:** Each action does what it says; tokens {} filled from the trigger.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-09 **Run a script** P2 Limit

1. Script using input.config(), base.findRecords, base.updateRecord, fetch to a public URL, output.set.

> **Expected:** Works; limits: 30 s total, 2 s CPU, 20 fetches, 100 calls per run; errors shown in history.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-10 **Test and run history** P1 UI

1. Use Test with a chosen record; open run history and a failed run.

> **Expected:** Step-by-step results and clear error messages.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-11 **Runs as** P2 Security

1. Header “Runs as …”: as a Creator pick another Creator; try an Editor.

> **Expected:** Saved for Creators; refused for Editors; editing no longer changes it.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-12 **Permissions** P1 Security

1. As EDITOR open Automations.

> **Expected:** Can view, can’t create or edit (Creators only).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-13 **Loops are stopped** P2 Limit

1. Make automation A update a record that triggers B that triggers A.

> **Expected:** Stops after the chain limit (8) without running forever.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-14 **Limit per base** P3 Limit

1. (150 automations per base.)

> **Expected:** A plan-limit message at the limit (optional to test).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M24-15 **Duplicate, rename, delete, turn off** P2 UI

1. Use the automation ⋯ menu.

> **Expected:** Each works; turned-off automations don’t run.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M25 — Public share links

Goal: Read-only links for people outside TableOS, Creators and up only.

M25-01 **Creator creates a view link** P1 UI

1. As CREATOR: Share view → Create shareable link.

> **Expected:** Link created; opens signed out in a private window.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M25-02 **Editor can't create or change links** P1 Security

1. As EDITOR open Share view.

> **Expected:** Message "Only Creators and Owners…"; controls disabled.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M25-03 **Shared page content** P1 Security

1. Open the link signed out.

> **Expected:** Only the view's visible fields and filtered records; search and sort work; table tabs for base links.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M25-04 **Allow copy off (default)** P1 Security

1. On the shared page try copy, cut, right-click, drag; check attachments; load more records.

> **Expected:** Copy/cut/right-click/drag blocked; attachments have no download; records load 50 at a time.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M25-05 **Allow copy on** P2 UI

1. Turn on Allow copying data; reload the page.

> **Expected:** Copying works; attachments downloadable.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M25-06 **Password** P1 Security

1. Add a password; open the link; wrong password 5 times.

> **Expected:** Password asked; warnings on attempts 3–4; locked 15 minutes on the 5th; Owner alerted.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M25-07 **Expiry** P2 Security

1. Set an expiry a few minutes ahead; wait.

> **Expected:** Link stops working after it.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M25-08 **Generate new link / Disable** P1 Security

1. Generate a new link, then Disable.

> **Expected:** Old link stops at once; disabled link shows not found.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M25-09 **Share entire base** P2 UI

1. Share view → Entire base.

> **Expected:** All tables readable via the link.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M26 — Search, notifications and contacts

Goal: Find things and stay informed.

M26-01 **Search palette** P1 UI

1. Ctrl+K: search a base, a table, a record value.

> **Expected:** Results grouped; Enter opens the right place; only things you can open are listed.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M26-02 **Search after moving a base** P3 Data

1. Move a base (M09) then search its records.

> **Expected:** Still found.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M26-03 **Notification bell** P1 UI

1. Trigger a mention, a comment on your record, an automation notification.

> **Expected:** Each appears with unread count; clicking opens the record; mark read/unread; mark all read.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M26-04 **Desktop notifications** P3 UI

1. Allow browser notifications when asked.

> **Expected:** New notifications pop up on the desktop.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M26-05 **Hidden after losing access** P2 Security

1. Notify EDITOR about BASE-1, then remove EDITOR's access.

> **Expected:** That notification disappears and isn't counted.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M26-06 **Member emails are private** P2 Security

1. As EDITOR open Share/member lists and @mention list.

> **Expected:** Names only (your own email visible); Owners/Admins/Workspace Owners see emails.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M27 — Live collaboration (realtime)

Goal: Changes appear for everyone without refreshing.

Before you start

- Open BASE-1 as OWNER in one browser and as EDITOR (and ADMIN) in another, side by side.

`M27-01` **Live cell edits** P1 Realtime

1. OWNER edits a cell.

> **Expected:** EDITOR sees it within about a second, without refreshing. And the other way round.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M27-02` **Live rows** P1 Realtime

1. Add and delete rows in one browser.

> **Expected:** Appear/disappear in the other.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M27-03` **Live schema** P2 Realtime

1. Add, rename, delete a field; create a view.

> **Expected:** Other browser updates.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M27-04` **Presence** P2 Realtime

1. Both open the same table.

> **Expected:** Avatars of who is here at the top.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M27-05` **Same cell at once** P2 Realtime

1. Both edit the same cell at the same time.

> **Expected:** Last write wins without errors; both end with the same value.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M27-06` **Reconnect** P2 Realtime

1. Turn Wi-Fi off for 30 seconds in one browser, make changes in the other, turn it on.

> **Expected:** The first browser catches up automatically.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M27-07 **Different roles** P2 Realtime

1. VIEWER watches while EDITOR edits.

> **Expected:** VIEWER sees live changes but can’t edit.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28 — API and access tokens

Goal: The public record API, token scopes and errors.

Before you start

- Use curl, Postman or similar. Token from Members & access → API tokens. Base URL = the API address.

M28-01 **Create a token** P1 API

1. Create tokens: Read only; Read+Write; Read+Write+Delete; one limited to BASE-1; one with an expiry.

Expected: Token shown once; listed with types, bases, expiry.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-02 **List bases** P1 API

1. GET /v1/api/bases with the token.

Expected: Only reachable bases with tables and IDs.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-03 **Schema** P2 API

1. GET /v1/bases/{baseId} and GET /v1/tables/{tableId}.

Expected: Tables and fields.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-04 **Query records** P1 API

1. POST …/records/query with pageSize, sort, filter (eq, contains, gt, empty, and/or), search, fields, viewId; follow nextCursor.

Expected: Correct records and paging; nextCursor null on the last page.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-05 **Read one record** P2 API

1. GET …/records/{recordId}?fields=fld_a,fld_b.

Expected: That record with the asked fields.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-06 **Group** P3 API

1. POST …/records/group.

> **Expected:** Grouped counts/aggregates.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-07 **Create, update, delete** P1 API

1. POST …/records; PATCH …/records/{id}; DELETE …/records/{id}; use field names and IDs; typecast true for a select option name.

> **Expected:** Works; changes appear live in the UI and in record history as “via API”.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-08 **Batches of 500** P1 Limit

1. POST …/records/batch with 500 records, then 501; PATCH …/records/batch; POST …/records/batch-delete.

> **Expected:** 500 works; 501 refused with a clear error.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-09 **Token types enforced** P1 Security

1. Use the Read-only token to create; the Write token to delete.

> **Expected:** 403 with the missing type named.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-10 **Base limits enforced** P1 Security

1. Use the BASE-1-only token on BASE-2.

> **Expected:** 404/403.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-11 **Revoked/expired tokens** P1 Security

1. Revoke a token and call the API; wait for an expired one.

> **Expected:** 401 immediately.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-12 **Admin tokens** P1 Security

1. As ADMIN create a token; read WS-B data with it.

> **Expected:** Refused: an Admin's token only reaches what the Admin was given. Admin sees only their own tokens.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-13 **Non-record APIs refused** P2 Security

1. Call e.g. /v1/workspaces with a token.

> **Expected:** 403 "API tokens can only call the record API".

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-14 **Synced tables are read-only** P2 API

1. Write to a synced table via API.

> **Expected:** 403.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-15 **Errors** P2 API

1. Send invalid JSON, an unknown field, a stale version, a missing token.

> **Expected:** 400/422 listing the problem; 409 for version conflicts; 401 without token.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-16 **Version** P3 API

1. GET /v1/version without a token; check the x-tableos-version header on any response.

> **Expected:** Both show the running version.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M28-17 **Rate per token** P2 Limit

1. Send 30 requests in one second with one token (plan: Free 5/s, Team 20/s).

> **Expected:** Record what happens (429 with retry-after, or all succeed). Report either way.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M29 — Limits and performance

Goal: TableOS behaves well at its limits and with real amounts of data.

M29-01 **Sign-in rate limit** P2 Limit

1. From one IP try 11 wrong sign-ins for an Owner within 15 minutes.

> **Expected:** 429 “Too many attempts” after 10.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M29-02 **Sign-up rate limit** P3 Limit

1. (Production: 30 sign-ups per IP per hour.)

> **Expected:** 429 after the limit (optional).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M29-03 **Import request size** P2 Limit

1. Import a file with 2,000+ rows.

> **Expected:** Sent in chunks; all rows imported.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M29-04 **Big base** P1 Limit

1. A table with 30,000 records and 30 fields: scroll, filter, sort, group, search.

> **Expected:** Usable (record times; anything over ~3 s is worth reporting).

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M29-05 **Many people at once** P2 Limit

1. 5+ people edit the same base for 10 minutes.

> **Expected:** No lost edits, no errors, realtime keeps up.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M29-06 **Text and name lengths** P3 Limit

1. Names over 200 characters (workspace/base/automation), comments over 10,000 characters.

> **Expected:** Refused with a clear message.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M29-07 **Server stays healthy** P2 Limit

1. During heavy use ask the developer to watch logs (no out-of-memory or Redis errors).

> **Expected:** No errors.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M30 — Permission matrix spot checks

Goal: One pass through the roles to make sure each sees exactly what it should.

Before you start

- For each row, sign in as that account and try the action in BASE-1 (and WS-B where noted).

`M30-01` **OWNER** P1 Security

1. Open every workspace/base; Members & access; export; duplicate; move; delete.

Expected: Everything allowed.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M30-02` **ADMIN** P1 Security

1. WS-A bases; WS-B bases; Members & access (Members only); billing.

Expected: WS-A yes; WS-B no data; Members yes; billing no.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M30-03` **CREATOR (base)** P1 Security

1. Schema changes, automations, share links, interfaces; export; duplicate base.

Expected: Schema/automations/share/interfaces yes; export and duplicate no.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M30-04` **EDITOR (base)** P1 Security

1. Edit records, shared views, import; fields/tables; share links; automations.

Expected: Records, views, import yes; fields/tables, share links, automations no.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M30-05` **COMMENTER (base)** P1 Security

1. Comment; personal views; edit cells.

Expected: Comment and personal views yes; editing no.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M30-06` **VIEWER (workspace)** P1 Security

1. Read every base in WS-A; edit; comment.

Expected: Read yes; edit/comment no.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M30-07` **DOMAIN (no access)** P1 Security

1. Home; any base URL.

> **Expected:** Nothing opens until given access.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M30-08` **Direct URLs and API** P1 Security

1. Paste URLs of things you shouldn't see; call the API with a session (browser dev tools) for forbidden actions.

> **Expected:** 404/403 everywhere; no data leaks in responses.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

M31 — Help, UI and browsers

Goal: Everything is understandable and works across browsers and screen sizes.

`M31-01` **Help pages** P3 UI

1. Open every Help topic; follow links between them.

> **Expected:** Content matches what TableOS does; no broken links.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M31-02` **Release notes** P3 UI

1. Help → Release notes.

> **Expected:** Current version listed first.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M31-03` **Browsers** P2 UI

1. Repeat a short smoke test (sign in, edit a cell, open a record, create a view) in Chrome, Edge, Firefox and Safari.

> **Expected:** Works the same.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M31-04` **Small screens** P3 UI

1. Use a 1366×768 laptop screen and a tablet/phone width.

> **Expected:** Nothing important cut off; dialogs scroll.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M31-05` **Error messages** P3 UI

1. Throughout testing, note any message that is unclear, technical or in the wrong place.

> **Expected:** Messages are clear and say what to do.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

`M31-06` **Slow network** P3 UI

1. Chrome dev tools → Network → Slow 3G; use the app.

> **Expected:** Loading states shown; no duplicate actions.

☐ Pass ☐ Fail ☐ Blocked ☐ N/A | Severity: ☐ Critical ☐ High ☐ Medium ☐ Low

Notes / what happened / screenshot file names:

Other findings

Anything not covered above: what, where, steps, expected, actual, severity, screenshots.