

# Análisis de Datos y Aprendizaje Máquina con Tensorflow 2.0: Redes neuronales recurrentes

2019/09/30

## 1 Deep Bidirectional RNN

Objetivo: Comprender las RNN Bidireccionales y sus efectos en el aprendizaje del modelo. Conocer el comportamiento de los optimizadores y aplicar regularización a modelos recurrentes.

```
In [17]: from tensorflow.keras.models import Model
         from tensorflow.keras.layers import LSTM, Embedding, Dense, SimpleRNN, Bidirectional
         from tensorflow.keras.datasets import imdb
         from tensorflow.keras.models import Sequential

         from tensorflow.keras.preprocessing.sequence import pad_sequences
         import matplotlib.pyplot as plt
```

## 2 Reseñas de películas de IMDB

- Conjunto de datos de 25,000 críticas de películas de IMDB, etiquetadas por sentimiento (positivo / negativo).

```
In [18]: # numero de palabras
         num_words = 4000


         max_len = 100

         #dimensión embedding
         emb_dim = 64

         (x_train, y_train), (x_test, y_test) = imdb.load_data(num_words=num_words)

         x_train = pad_sequences(x_train, maxlen=max_len, padding = 'post')
         x_test = pad_sequences(x_test, maxlen=max_len, padding = 'post')

         print(x_train.shape)
         print(x_test.shape)
```



RNN

```
print(y_train.shape)
print(y_test.shape)
```

```
(25000, 100)
(25000, 100)
(25000,)
(25000,)
```

```
In [19]: epoch = 4
         verbose = 1
         batch = 128
```

## 2.1 Cada palabra de la review esta identificada por un número

```
In [20]: print('Reseña')
         print(x_train[0])
         print('Etiqueta')
         print(y_train[0])
```

Reseña

[1415	33	6	22	12	215	28	77	52	5	14	407	16	82
2	8	4	107	117	2	15	256	4	2	7	3766	5	723
36	71	43	530	476	26	400	317	46	7	4	2	1029	13
104	88	4	381	15	297	98	32	2071	56	26	141	6	194

```

    2   18   4  226   22   21  134  476   26  480   5  144   30   2
    18   51   36   28  224   92   25  104   4  226   65   16   38 1334
    88   12   16  283   5   16   2  113  103   32   15   16   2   19
    178  32]
Etiqueta
1

```

## 2.2 Palabras de reseña

```

In [21]: wordDict = {y:x for x,y in imdb.get_word_index().items()}
         res = []
         for index in x_train[0]:
             res.append(wordDict.get(index - 3))
         print('Reseña: ',res,'Longitud reseña: ', len(res))

```

Reseña: ['cry', 'at', 'a', 'film', 'it', 'must', 'have', 'been', 'good', 'and', 'this', 'definit

## 2.3 Deep RNN

- Se comparará el modelo con y sin regularización

```

In [22]: def deep_lstm():
         model = Sequential()
         model.add(Embedding(num_words, emb_dim))
         model.add(LSTM(64, return_sequences = True))
         model.add(LSTM(64, return_sequences = False))
         model.add(Dense(1, activation='sigmoid'))
         model.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])

         return model

```

```

In [23]: model = deep_lstm()
         model.summary()

```

Model: "sequential\_2"

Layer (type)	Output Shape	Param #
embedding_2 (Embedding)	(None, None, 64)	256000
lstm_4 (LSTM)	(None, None, 64)	33024
lstm_5 (LSTM)	(None, 64)	33024
dense_2 (Dense)	(None, 1)	65

Total params: 322,113

Trainable params: 322,113

Non-trainable params: 0

```
-----  
In [24]: history = model.fit(x_train, y_train, batch_size = batch, validation_split = 0.3,  
                             epochs = epoch, verbose = verbose)
```

Epoch 1/4

137/137 [=====] - 39s 283ms/step - loss: 0.5071 - accuracy: 0.7265 - val

Epoch 2/4

137/137 [=====] - 38s 278ms/step - loss: 0.3156 - accuracy: 0.8702 - val

Epoch 3/4

137/137 [=====] - 38s 277ms/step - loss: 0.2711 - accuracy: 0.8920 - val

Epoch 4/4

137/137 [=====] - 39s 287ms/step - loss: 0.2351 - accuracy: 0.9093 - val

```
In [25]: test_loss, test_acc = model.evaluate(x_test, y_test, verbose=2)
```


```
        print('\nTest accuracy:', test_acc)
```

782/782 - 21s - loss: 0.3869 - accuracy: 0.8348

Test accuracy: 0.8347600102424622

```
In [26]: plt.figure(figsize=(10,9))
```

```
    plt.subplot(211)  
    plt.plot(history.history['accuracy'])  
    plt.plot(history.history['val_accuracy'])  
    plt.title('accuracy')  
    plt.legend(['train', 'test'])  
    plt.grid()  
    plt.subplot(212)  
    plt.plot(history.history['loss'])  
    plt.plot(history.history['val_loss'])  
    plt.title('loss')  
    plt.legend(['train', 'test'])  
    plt.grid()
```



## 2.4 Bidirectional RNN

- Bidirectional RNNs lee las secuencias en ambas direcciones

```
In [27]: def bidirectional_lstm():
        model = Sequential()
        model.add(Embedding(num_words, emb_dim))
        model.add(Bidirectional(LSTM(64, return_sequences = False)))
        model.add(Dense(1, activation='sigmoid'))
        model.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])

        return model
```

```
In [28]: model = bidirectional_lstm()
        model.summary()
```

Model: "sequential\_3"

-----

Layer (type)	Output Shape	Param #
embedding_3 (Embedding)	(None, None, 64)	256000
bidirectional (Bidirectional)	(None, 128)	66048
dense_3 (Dense)	(None, 1)	129

Total params: 322,177  
 Trainable params: 322,177  
 Non-trainable params: 0

```
In [29]: history = model.fit(x_train, y_train, batch_size = batch, validation_split = 0.3,
                             epochs = epoch, verbose = verbose)
```

```
Epoch 1/4
137/137 [=====] - 35s 253ms/step - loss: 0.5087 - accuracy: 0.7275 - val
Epoch 2/4
137/137 [=====] - 34s 250ms/step - loss: 0.3207 - accuracy: 0.8661 - val
Epoch 3/4
137/137 [=====] - 34s 250ms/step - loss: 0.2763 - accuracy: 0.8904 - val
Epoch 4/4
137/137 [=====] - 35s 252ms/step - loss: 0.2447 - accuracy: 0.9049 - val
```

```
In [30]: test_loss, test_acc = model.evaluate(x_test, y_test, verbose=2)
```

```
print('\nTest accuracy:', test_acc)
```


```
782/782 - 17s - loss: 0.3747 - accuracy: 0.8414
```

```
Test accuracy: 0.8414400219917297
```

```
In [31]: plt.figure(figsize=(10,9))
```

```

plt.subplot(211)
plt.plot(history.history['accuracy'])
plt.plot(history.history['val_accuracy'])
plt.title('accuracy')
plt.legend(['train', 'test'])
plt.grid()
plt.subplot(212)
plt.plot(history.history['loss'])
plt.plot(history.history['val_loss'])
plt.title('loss')
plt.legend(['train', 'test'])
plt.grid()
```



## 2.5 Deep Bidirectional RNN

- Observar el efecto de la profundidad de la red en el entrenamiento

```
In [89]: def deep_bidirectional_lstm():
        model = Sequential()
        model.add(Embedding(num_words, emb_dim))
        model.add(Bidirectional(LSTM(64, return_sequences = True)))
        model.add(Bidirectional(LSTM(64, return_sequences = False)))
        model.add(Dense(1, activation='sigmoid'))
        model.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])

        return model
```

```
In [91]: model = deep_bidirectional_lstm()
        model.summary()
```

Model: "sequential\_16"

-----

Layer (type)	Output Shape	Param #
embedding_16 (Embedding)	(None, None, 64)	256000
bidirectional_25 (Bidirectio	(None, None, 128)	66048
bidirectional_26 (Bidirectio	(None, 128)	98816
dense_17 (Dense)	(None, 1)	129

Total params: 420,993  
 Trainable params: 420,993  
 Non-trainable params: 0

```
In [92]: history1 = model.fit(x_train, y_train, batch_size = batch, validation_split = 0.3,
                             epochs = epoch, verbose = verbose)
```

```
Epoch 1/4
137/137 [=====] - 86s 625ms/step - loss: 0.4784 - accuracy: 0.7574 - val
Epoch 2/4
137/137 [=====] - 85s 624ms/step - loss: 0.3031 - accuracy: 0.8726 - val
Epoch 3/4
137/137 [=====] - 84s 616ms/step - loss: 0.2608 - accuracy: 0.8967 - val
Epoch 4/4
137/137 [=====] - 85s 618ms/step - loss: 0.2204 - accuracy: 0.9151 - val
```

```
In [93]: test_loss, test_acc = model.evaluate(x_test, y_test, verbose=2)
```

```
print('\nTest accuracy:', test_acc)
```

```
782/782 - 37s - loss: 0.3867 - accuracy: 0.8279
```


```
Test accuracy: 0.8279200196266174
```

```
In [94]: plt.figure(figsize=(10,9))
```

```
plt.subplot(211)
plt.plot(history.history['accuracy'])
plt.plot(history.history['val_accuracy'])
plt.title('accuracy')
plt.legend(['train', 'test'])
plt.grid()
plt.subplot(212)
plt.plot(history.history['loss'])
plt.plot(history.history['val_loss'])
plt.title('loss')
```



```
plt.legend(['train', 'test'])
plt.grid()
```



## 2.6 Optimización en Bidirectional RNN con regularización

- Los optimizadores tienen comportamientos diferentes en las distintas arquitecturas de redes
- La regularización como dropout se agrega con 'recurrent\_dropout'

```
In [59]: recurrent_dropout = 0.2
```

```
In [67]: def deep_bidirectional_lstm():
    model = Sequential()
    model.add(Embedding(num_words, emb_dim))
    model.add(Bidirectional(LSTM(64, return_sequences = True,
                                recurrent_initializer='glorot_uniform',
                                recurrent_dropout=recurrent_dropout)))
    model.add(Bidirectional(LSTM(64, return_sequences = False,
                                recurrent_initializer='glorot_uniform',
```

```

                                recurrent_dropout=recurrent_dropout)))
model.add(Dense(1, activation='sigmoid'))
model.compile(loss='binary_crossentropy', optimizer='rmsprop', metrics=['accuracy'])

return model

```

```

In [68]: model = deep_bidirectional_lstm()
         model.summary()

```

Model: "sequential\_12"

Layer (type)	Output Shape	Param #
embedding_12 (Embedding)	(None, None, 64)	256000
bidirectional_17 (BidirectionalLSTM)	(None, None, 128)	66048
bidirectional_18 (BidirectionalLSTM)	(None, 128)	98816
dense_13 (Dense)	(None, 1)	129

Total params: 420,993  
 Trainable params: 420,993  
 Non-trainable params: 0

```

In [69]: history2 = model.fit(x_train, y_train, batch_size = batch, validation_split = 0.3,
                             epochs = epoch, verbose = verbose)

```

```

Epoch 1/4
137/137 [=====] - 126s 921ms/step - loss: 0.4895 - accuracy: 0.7605 - va
Epoch 2/4
137/137 [=====] - 131s 959ms/step - loss: 0.3334 - accuracy: 0.8597 - va
Epoch 3/4
137/137 [=====] - 126s 922ms/step - loss: 0.2902 - accuracy: 0.8829 - va
Epoch 4/4
137/137 [=====] - 125s 911ms/step - loss: 0.2667 - accuracy: 0.8931 - va

```

```

In [70]: test_loss, test_acc = model.evaluate(x_test, y_test, verbose=2)

```

```

print('\nTest accuracy:', test_acc)

```

```

782/782 - 47s - loss: 0.3590 - accuracy: 0.8500

```

```

Test accuracy: 0.8500000238418579

```

- RMSProp con regularización supera a las redes anteriores con Adam
- Averiguar si quitando la regularización se llega a el mismo resultado

```
In [71]: def deep_bidirectional_lstm():
        model = Sequential()
        model.add(Embedding(num_words, emb_dim))
        model.add(Bidirectional(LSTM(64, return_sequences = True,
                                     recurrent_initializer='glorot_uniform',
                                     recurrent_dropout=recurrent_dropout)))
        model.add(Bidirectional(LSTM(64, return_sequences = False,
                                     recurrent_initializer='glorot_uniform',
                                     recurrent_dropout=recurrent_dropout)))
        model.add(Dense(1, activation='sigmoid'))
        model.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])

        return model
```

```
In [72]: model = deep_bidirectional_lstm()
        model.summary()
```

Model: "sequential\_13"

Layer (type)	Output Shape	Param #
embedding_13 (Embedding)	(None, None, 64)	256000
bidirectional_19 (Bidirectional)	(None, None, 128)	66048
bidirectional_20 (Bidirectional)	(None, 128)	98816
dense_14 (Dense)	(None, 1)	129

Total params: 420,993  
 Trainable params: 420,993  
 Non-trainable params: 0

```
In [73]: history3 = model.fit(x_train, y_train, batch_size = batch, validation_split = 0.3,
                             epochs = epoch, verbose = verbose)
```

```
Epoch 1/4
137/137 [=====] - 126s 916ms/step - loss: 0.4711 - accuracy: 0.7595 - va
Epoch 2/4
137/137 [=====] - 129s 941ms/step - loss: 0.3026 - accuracy: 0.8779 - va
Epoch 3/4
137/137 [=====] - 125s 914ms/step - loss: 0.2541 - accuracy: 0.9001 - va
Epoch 4/4
137/137 [=====] - 125s 912ms/step - loss: 0.2019 - accuracy: 0.9245 - va
```

```
In [74]: test_loss, test_acc = model.evaluate(x_test, y_test, verbose=2)

        print('\nTest accuracy:', test_acc)
```

782/782 - 47s - loss: 0.4126 - accuracy: 0.8361

Test accuracy: 0.836080014705658

```
In [95]: #plot
plt.figure(figsize=(10,9))
plt.subplot(211)

plt.plot(history1.history['accuracy'])
plt.plot(history2.history['accuracy'])
plt.plot(history3.history['accuracy'])


plt.legend(['Adam simple',
            'RMSProp dropout 0.2',
            'Adam dropout 0.2'])

plt.title('Test')
plt.ylabel('accuracy')
plt.xlabel('epoch')

plt.subplot(212)
plt.plot(history1.history['loss'])
plt.plot(history2.history['loss'])
plt.plot(history3.history['loss'])

plt.legend(['Adam simple',
            'RMSProp dropout 0.2',
            'Adam dropout 0.2'])

plt.ylabel('loss')
plt.xlabel('epoch')
plt.show()
```



```
In [96]: #plot
plt.figure(figsize=(10,9))
plt.subplot(211)

plt.plot(history1.history['val_accuracy'])
plt.plot(history2.history['val_accuracy'])
plt.plot(history3.history['val_accuracy'])

plt.legend(['Adam simple',
            'RMSProp dropout 0.2',
            'Adam dropout 0.2'])

plt.title('Test')
plt.ylabel('accuracy')
plt.xlabel('epoch')

plt.subplot(212)
```


```

plt.plot(history1.history['val_loss'])
plt.plot(history2.history['val_loss'])
plt.plot(history3.history['val_loss'])

plt.legend(['Adam simple',
            'RMSProp dropout 0.2',
            'Adam dropout 0.2'])

plt.ylabel('loss')
plt.xlabel('epoch')
plt.show()

```



- Mejorar el accuracy de la red
- Probar Deep-Bidirectional-RNN con otro dataset
- Probar con otros optimizadores y diferentes valores de 'recurrent\_dropout' y 'recurrent\_initializer'