INTERTANKO CHARTERING QUESTIONNAIRE 88 – OIL/CHEMICAL

Version 6

1.	**GENERAL INFORMATION**	
1.1	Date updated:	Dec 31, 2025
1.2	Vessel's name (IMO number):	MTM North Sound (9360946)
1.2b	Is the vessel owner/manager a member of INTERTANKO? If yes, please provide IMO number of the Member organization	No,
1.3	Vessel's previous name(s) and date(s) of change:	GOLDEN FLORENCE (Aug 22, 2011)
1.4	Date delivered/Builder (where built):	Nov 28, 2006/Fukuoka Shipbuilding Co. Ltd. (Nagasaki Yard)
1.5	Flag/Port of Registry:	Singapore/Singapore
1.6	Call sign/MMSI:	9V9576/566203000
1.7	Vessel's contact details (satcom/fax/email etc.)	Tel: +1 90 4900 6112 (Bridge/CCR) / +1 90 4900 6598 (Master Office) / (Iridium) : + 8816 7775 4601 (Bridge) Fax: N/A Email: master@northsound.cruisecontrolemail.com
1.8	Type of vessel (as described in Form A or Form B Q1.11 of the IOPPC):	Other
1.8a	If other type of vessel, please specify:	Product Carrier
1.9	Type of hull:	Double Hull

Ownership and Operation		
1.10	Registered owner - Full style: IMO Number	MTM North Sound Pte. Ltd. 78 Shenton Way, #13-01, Singapore 079120 Singapore Tel: +65 6304 1770 Email: marine@mtmsm.com IMO: 5627908
1.11	Technical operator - Full style:	M.T.M. Ship Management Pte. Ltd. 78, Shenton Way, #13-01, Singapore 079120 Singapore Tel: +65 6304 1770 Fax: +65 6220 7988 Email: marine@mtmsm.com Company IMO#: 1314037
1.12	Commercial operator - Full style:	M.T. Maritime Pte Ltd. 78 Shenton Way, #29-02, Singapore 079120 Singapore Tel: +65 6221 2255 Fax: +65 6221 2277 Email: operations@mtmm.sg
1.13	Disponent owner - Full style:	N/A

Insurance			
1.14	P & I Club - Full Style:	NorthStandard Limited 100 The Quayside, Newcastle upon Tyne, NE1 3DU UK Tel: +44 191 232 5221 Fax: +44 191 261 0540 Email: pandi.singapore@north-standard.com Web: https://north-standard.com If other P&I - specify:	
1.15	P & I Club pollution liability coverage/expiration date:	1,000,000,000 US$	Feb 20, 2026
1.16	Hull & Machinery insured by - Full Style: (Specify broker or leading underwriter)	Sompo Japan Nipponkoa Insurance Inc. 26-1, Nishi - Shinyuku 1-Chome, Shinjuku - Ku,	

		Tokyo, Japan 160-8338		
1.17	Hull & Machinery insured value/expiration date:		21,900,000 US$	Feb 01, 2026
Classification				
1.18	Classification society:		Nippon Kaiji Kyokai	
1.18a	Is Classification Society an IACS member?		Yes	
1.19	Class notation:		NS* (TOB/CT II&III)(ESP) (IHM) MNS*	
1.20	Does the vessel have any open conditions of Class? If yes List all open conditions No			
	Open Conditions of Class		**Due Date**	
1.20a	Does the vessel have any Memoranda of Class? If yes, list details No			
1.21	If classification society changed, name of previous and date of change:		, Not Applicable	
1.22	Does the vessel have ice class? If yes, state what level:		N/A,	
1.23	Date/place of last dry-dock:		Dec 25, 2024 / Chengxi Shipyard, Jiang Yin, China	
1.24	Date next dry dock due/next annual survey due:		Dec 24, 2027	Feb 28, 2026
1.25	Date of last special survey/next special survey due:		Dec 25, 2024	Nov 30, 2029
1.26	If ship has Condition Assessment Program (CAP), what is the latest overall rating:		Yes, 2	
Dimensions				
1.27	Length overall (LOA):			144.03 Metres
1.28	Length between perpendiculars (LBP):			136.00 Metres
1.29	Extreme breadth (Beam):			24.23 Metres
1.30	Moulded depth:			12.80 Metres
1.31	Keel to masthead (KTM)/ Keel to masthead (KTM) in collapsed condition, if applicable:		37.20 Metres	0 Metres
1.32	Distance bridge front to center of manifold:			44.50 Metres
1.33	Bow to center manifold (BCM)/Stern to center manifold (SCM):		71.93 Metres	72.10 Metres
1.34	Parallel body distances	Lightship	Normal Ballast	Summer Dwt
	Forward to mid-point manifold:	24.07 Metres	30.99 Metres	34.24 Metres
	Aft to mid-point manifold:	23.74 Metres	29.41 Metres	35.57 Metres
	Parallel body length:	47.81 Metres	60.40 Metres	69.81 Metres
Tonnages				
1.35	Net Tonnage:			6,365.00
1.36	Gross Tonnage/Reduced Gross Tonnage (if applicable):		11,641.00	
1.37	Suez Canal Tonnage - Gross (SCGT)/Net (SCNT):		12,126.72	10,549.61

1.38	Is vessel fitted for transit of Panama canal? Panama Canal Net Tonnage (PCNT):				Yes, 9,795.36
Loadline Information					
1.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	3.21 Metres	9.63 Metres	19,874.00 Metric Tonnes	25,289.46 Metric Tonnes
	Winter:	3.41 Metres	9.43 Metres	19,279.53 Metric Tonnes	24,694.99 Metric Tonnes
	Tropical:	3.01 Metres	9.83 Metres	20,471.55 Metric Tonnes	25,887.01 Metric Tonnes
	Normal loaded condition:	3.21 Metres	9.63 Metres	19,874.00 Metric Tonnes	25,289.46 Metric Tonnes
	Lightship:	10.48 Metres	2.35 Metres	-	5,415.46 Metric Tonnes
	Normal Ballast Condition:	7.13 Metres	5.71 Metres	8,624.33 Metric Tonnes	14,039.79 Metric Tonnes
	Segregated Ballast Condition:	7.52 Metres	5.31 Metres	7,720.60 Metric Tonnes	13,136.10 Metric Tonnes
1.40	FWA/TPC at summer draft:			212.00 Millimetres	29.807 Metric Tonnes
1.41	Have multiple deadweights been assigned? If yes, list all assigned deadweights:			Yes Assigned DWT 1: 19,874.00 Assigned DWT 2: 19,600.14 Assigned DWT 3: Assigned DWT 4: Assigned DWT 5:	
1.42	Constant (excluding fresh water):				NA
1.43	What is the company guidelines for Under Keel Clearance (UKC) for this vessel?			Minimum UKC Deep Sea—5D Coastal Passage – 2D Approaches—15% of draft Port limits—10% of draft Berth- 60 CM	
1.44	What is the max height of mast above waterline (air draft)			Full Mast	Collapsed Mast
	Summer deadweight:			27.57 Metres	0 Metres
	Normal ballast:			31.49 Metres	0 Metres
	Lightship:			34.85 Metres	0 Metres

2.	**CERTIFICATES**	**Issued**	**Last Annual**	**Last Intermediate**	**Expires**
2.1	Safety Equipment Certificate (SEC):	Dec 25, 2024	Not Applicable		Nov 30, 2029
2.2	Safety Radio Certificate (SRC):	Dec 25, 2024	Not Applicable		Nov 30, 2029
2.3	Safety Construction Certificate (SCC):	Dec 25, 2024	Not Applicable		Nov 30, 2029
2.4	International Loadline Certificate (ILC):	Dec 25, 2024	Not Applicable	Not Applicable	Nov 30, 2029
2.5	International Oil Pollution Prevention Certificate (IOPPC):	Dec 25, 2024	Not Applicable		Nov 30, 2029
2.6	International Ship Security Certificate (ISSC):	Aug 31, 2021	Not Applicable	May 26, 2024	Sep 06, 2026
2.7	Maritime Labour Certificate (MLC):	May 04, 2023	N/A	Not Applicable	Jun 27, 2028
2.8	Minimum Safe Manning Certificate (MSM)	Nov 06, 2023	Not Applicable	N/A	Not Applicable
2.9	ISM Safety Management Certificate (SMC):	Aug 31, 2021	Not Applicable	May 26, 2024	Sep 06, 2026
2.10	Document of Compliance (DOC):	Aug 28, 2025	Aug 28, 2025		Sep 16, 2026
2.11	USCG Certificate of Compliance(USCGCOC):	Aug 02, 2025	Not Applicable	Not Applicable	Aug 02, 2027
2.12	Civil Liability Convention (CLC) 1992 Certificate:	Feb 20, 2025	N/A	N/A	Feb 20, 2026
2.13	Civil Liability for Bunker Oil Pollution Damage Convention (CLBC) Certificate:	Feb 20, 2025	N/A	N/A	Feb 20, 2026

2.14	Liability for the Removal of Wrecks Certificate (WRC):	Feb 20, 2025	N/A	N/A	Feb 20, 2026
2.15	U.S. Certificate of Financial Responsibility (COFR):	Apr 25, 2023	N/A	N/A	Apr 25, 2026
2.16	Certificate of Class (COC):	Dec 25, 2024	Not Applicable	Not Applicable	Nov 30, 2029
2.17	Certificate of Registry (COR)	May 15, 2024	N/A	N/A	Permanent
2.18	International Sewage Pollution Prevention Certificate (ISPPC):	Dec 25, 2024	N/A	N/A	Nov 30, 2029
2.19	Certificate of Fitness (COF) (Chemical):	May 20, 2025	Not Applicable	Not Applicable	Nov 30, 2029
2.20	Certificate of Fitness (COF) (Gas):	Not Applicable	Not Applicable	Not Applicable	Not Applicable
2.21	International Energy Efficiency Certificate (IEEC):	Nov 19, 2023	N/A	N/A	N/A
2.22	International Air Pollution Prevention Certificate (IAPPC):	Dec 25, 2024	Not Applicable	Not Applicable	Nov 30, 2029
2.23	Ship Sanitation Control (SSCC)/Ship Sanitation Control Exemption (SSCE)	Aug 21, 2025	N/A	N/A	Feb 21, 2026
2.24	Does the vessel have an International Ballast Water Management Certificate? If no, then describe how ship complies with the "International Convention for the Control and Management of Ships' Ballast Water and Sediments"?:			Yes, N/A	
Documentation					
2.25	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:			Yes	
2.26	Does vessel have in place a Drug and Alcohol Policy complying with OCIMF guidelines for Control of Drugs and Alcohol Onboard Ship?			Yes	
2.27	Is the ITF Special Agreement on board (if applicable)?			No	
2.28	ITF Blue Card expiry date (if applicable):			Dec 31, 2026	

3.	**CREW**		
3.1	Nationality of Master:		Myanmar
3.2	Number and nationality of Officers:	9	Myanmar
3.3	Number and nationality of Crew:	**Nationality**	**Count**
		Myanmar	14
3.4	What is the common working language onboard:		ENGLISH
3.5	Do officers speak and understand English?		Yes

3.6 If Officers/ratings employed by a manning agency - Full style:

Officers:

Company Name	Address	Phone	Fax	Email
M.T.M. Ship Management Pte. Ltd.	78 Shenton Way, #13-01, Singapore 079120	+65 6304 1770	+65 6220 7988	mtmns.crew@mtmsm.com

Ratings:

Company Name	Address	Phone	Fax	Email
M.T.M. Ship Management Pte. Ltd.	78 Shenton Way, #13-01, Singapore 079120	+65 6304 1770	+65 6220 7988	mtmns.crew@mtmsm.com

4.	**FOR USA CALLS**	
4.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter?	Yes
4.2	Qualified individual (QI) - Full style:	Gallagher Marine Systems Inc 1 Selleck Street, 5th Floor, Suite 511 Norwalk, CT 06855, USA. Tel: +1 856 642 2091/+1 703 683 4700 Email: ecmvrp@gallaghermarine.com Web: www.gallaghermarine.com

4.3	Oil Spill Response Organization (OSRO) - Full style:	National Response Corporation 3500 Sunrise Highway Suite 103, Great River, NY11739, USA. Tel: +1 800 899 4672 Fax: +1 631 224 9086 Email: iocdo@nrcc.com
4.4	Salvage and Marine Firefighting Services (SMFF) - Full Style:	Resolve Marine Group, Inc. 1510 SE 17th Street, Suite 400, Ft. Lauderdale, FL 33316, USA Tel: +1 954 764 8700 Email: opa90@resolvemarine.com

5.	**SAFETY/HELICOPTER**	
5.1	Is the vessel operated under a Quality Management System? If Yes, what type of system? (ISO9001 or IMO Resolution A.741(18) as amended):	Yes ISO 9001:2015 and ISO 14001:2015
5.2	Can the ship comply with the ICS Helicopter Guidelines?	No
5.2.1	If Yes, state whether winching or landing area provided:	Not applicable
5.2.2	If Yes, what is the diameter of the circle provided:	

6. COATING/ANODES

6.1 Cargo tanks:

Tank ID	Tank PSC	Tank Type	Constr	Coated Y/N	Coating Type	Extent	Condition	Date	Insp date	Insp Freq
1	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
1	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
2	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
2	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
3	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-06	Biannual
3	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-06	Biannual
4	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
4	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
5	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
5	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
6	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
6	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
7	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
7	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
8	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
8	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
9	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-06	Biannual
9	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
10	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-06	Biannual
10	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-06	Biannual
11	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
11	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-01	Biannual
12	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-06	Biannual
12	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-06	Biannual
13	P	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-06	Biannual
13	S	2g	SS	no	SS	Full Tank	Good	2023-02-02	2025-11-06	Biannual

Anodes Fitted : No

Ballast tanks:

ID	Coated?	Type	Extent	Condition	Coating date	Insp date	Insp freq
FPT	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-04	Biannual

1P	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-04	Biannual
1S	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-04	Biannual
2P	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-05	Biannual
2S	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-05	Biannual
3P	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-05	Biannual
3S	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-07	Biannual
4P	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-05	Biannual
4S	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-07	Biannual
5P	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-04	Biannual
5S	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-04	Biannual
6P	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-04	Biannual
6S	yes	Epoxy	Full Tank	Good	2006-08-30	2025-07-07	Biannual

Anodes Fitted: Yes

7.	**BALLAST**	
7.1	Ballast Handling Data	

Number	Type	Prime mover type	Capacity (m3/hr)	Head (bar)
1	Horizontal Centrifugal	Electric	400.00	25.00

Ballast Water Management Systems (BWMS)		
7.2	Does the vessel comply with D1 or D2 performance standards?	D2
7.3	Does the vessel have a Ballast Water Treatment System (BWTS) fitted?	Yes
7.4	What type of BWTS fitted? If other system fitted, please advise:	PureBallast 3.1 Ex, Filter & UV
7.5	Name of manufacturer of BWTS:	ALFA LAVAL Tumba AB
7.6	Does the BWTS have IMO type approval?	Yes
7.7	Is the BWTS of a USCG approved type?	Yes

8.	**CARGO –Oil/ Chem**	
Double Hull Vessels		
8.1	Is vessel fitted with centerline bulkhead in all cargo tanks? If Yes, solid or perforated:	Yes, Solid
Tank Capacities		
8.2	Cargo Tank Capacities at 98% Full - Centre:	

Total Centre: 0 Cu. Metres

Cargo Tank Capacities at 98% Full - Wing:

Tank Number	Capacity (m3)	P/S
1	399.01	Port
1	411.54	Stbd
2	469.32	Port
2	480.47	Stbd
3	337.98	Port
3	352.34	Stbd
4	1171.41	Port
4	1171.47	Stbd
5	1141.69	Port
5	1156.03	Stbd
6	732.33	Port
6	745.30	Stbd

7	1062.27	Port
7	1075.89	Stbd
8	1390.30	Port
8	1403.27	Stbd
9	1144.41	Port
9	1159.06	Stbd
10	1142.63	Port
10	1157.03	Stbd
11	319.35	Port
11	330.30	Stbd
12	700.69	Port
12	714.34	Stbd
13	741.35	Port
13	741.78	Stbd

Total Wing: 21,651.65 Cu. Metres

Deck Tank Capacities at 98% Full:

Deck Tank Number	Port/Centre/Stbd	Capacity @ 98%
1 FWD	Stbd	26.29
1 AFT	Stbd	26.29

Total Deck: 52.58 Cu. Metres

8.2a	Grand Total Cubic Capacity (98%) (centre + wing tanks)	21,651.65 Cu. Metres
8.2.1	Capacity (98%) of each natural segregation with double valve (specify tanks):	Seg#1: 399.017 m3 (COT 1P) Seg#2: 411.541 m3 (COT 1S) Seg#3: 469.322 m3 (COT 2P) Seg#4: 480.474 m3 (COT 2S) Seg#5: 337.982 m3 (COT 3P) Seg#6: 352.349 m3 (COT 3S) Seg#7: 1171.414 m3 (COT 4P) Seg#8: 1171.472 m3 (COT 4S) Seg#9: 1141.690 m3 (COT 5P) Seg#10: 1156.037 m3 (COT 5S) Seg#11: 732.334 m3 (COT 6P) Seg#12: 745.300 m3 (COT 6S) Seg#13: 1062.271 m3 (COT 7P) Seg#14: 1075.893 m3 (COT 7S) Seg#15: 1390.306 m3 (COT 8P) Seg#16: 1403.273 m3 (COT 8S) Seg#17: 1144.415 m3 (COT 9P) Seg#18: 1159.066 m3 (COT 9S) Seg#19: 1142.631 m3 (COT 10P) Seg#20: 1157.037 m3 (COT 10S) Seg#21: 319.353 m3 (COT 11P) Seg#22: 330.309 m3 (COT 11S) Seg#23: 700.690 m3 (COT 12P) Seg#24: 714.342 m3 (COT 12S) Seg#25: 741.350 m3 (COT 13P) Seg#26: 741.782 m3 (COT 13S) (Total 26 tanks of each natural segregation with double valve.)
8.2.2	IMO class (Oil/Chemical Ship Type 1, 2 or 3):	IMO 2 (2, 3)
8.3	Slops tank capacities (98%):	

Tank Number	Capacity (m3)	P/S
N/A		

Total:

8.3.1	Specify segregations which slops tanks belong to and their capacity with double valve:	11P, 11S	
8.3.2	Residual/retention oil tank(s) capacity (98%), if applicable:	52.586 Cu. Metres	
Cargo Handling and Pumping Systems			
8.4	How many grades/products can vessel load/discharge with double valve segregation:	26	
8.4.1	State type of cargo containment (integral, independent, gravity or pressure tanks):	1G (Independent Gravity)	
8.5	Are there any cargo tank filling restrictions? If yes, specify number of slack tanks, max s.g., ullage restrictions etc.:	Yes Design Specific Gravity : 1.50	
8.6	Max loading rate for homogenous cargo	With VECS	Without VECS
	Loaded per manifold connection:	476 Cu. Metres/Hour	476 Cu. Metres/Hour
	Loaded simultaneously through all manifolds:	1,200 Cu. Metres/Hour	476.00 Cu. Metres/Hour
Cargo Control Room			
8.7	Is ship fitted with a Cargo Control Room (CCR)?	Yes	
8.8	Can tank innage/ullage be read from the CCR?	Yes	
Gauging and Sampling			
8.9	Is gauging system certified and calibrated? If no, specify which ones are not calibrated:	Yes,	
	What type of gauging system as per IBC 13.1 is fitted (Open/Restricted/Closed)?	CLOSED	
	Is a tank overflow control system fitted? If yes, then state if system includes automatic closing of valves?	No, No	
	Are high level alarms fitted to the cargo tanks? If high level alarms are fitted, are the high level alarms fitted to all cargo tanks?	Yes, Yes	
8.9.1	Are cargo tanks fitted with multipoint gauging? If yes, specify type and locations:	Yes, FLOAT TYPE, EACH TANK.	
8.10	Number of portable gauging units (example- MMC) on board:	3	
Vapor Emission Control System (VECS)			
8.11	Is a vapour return system (VRS) fitted?	Yes	
	If fitted, is vapour line return manifold in compliance with OCIMF Guidelines?	Yes	
	If fitted, how many vapor return segregations can the vessel maintain simultaneously?	3	
	Does the ship possess Vapour Emission Control (VEC) Certification? If yes, state the issuing authority	Yes, NKK	
8.12	Number/size of VECS manifolds (per side):	3	150 Millimetres
8.13	Number/size/type of VECS reducers:	2x150x125mm(6”x5”)/ 2x150x100mm(6”x4”)/ 1x150x250mm(6”x10”)	
Venting			
8.14	State what type of venting system is fitted:	High Velocity	
Cargo Manifolds and Reducers			

8.15 Total number/size of cargo manifold connections on each side:
No.: 26

Size:

Manifold	PCS	Size	Unit	Pressure Rating	Unit PR	Standard
1	P	150	mm	7	KG/Cm2	ANSI
1	S	150	mm	7	KG/Cm2	ANSI
2	P	150	mm	7	KG/Cm2	ANSI
2	S	150	mm	7	KG/Cm2	ANSI
3	P	150	mm	7	KG/Cm2	ANSI
3	S	150	mm	7	KG/Cm2	ANSI
4	P	150	mm	7	KG/Cm2	ANSI

4	S	150	mm	7	KG/Cm2	ANSI
5	P	150	mm	7	KG/Cm2	ANSI
5	S	150	mm	7	KG/Cm2	ANSI
6	P	150	mm	7	KG/Cm2	ANSI
6	S	150	mm	7	KG/Cm2	ANSI
7	P	150	mm	7	KG/Cm2	ANSI
7	S	150	mm	7	KG/Cm2	ANSI
8	P	150	mm	7	KG/Cm2	ANSI
8	S	150	mm	7	KG/Cm2	ANSI
9	P	150	mm	7	KG/Cm2	ANSI
9	S	150	mm	7	KG/Cm2	ANSI
10	P	150	mm	7	KG/Cm2	ANSI
10	S	150	mm	7	KG/Cm2	ANSI
11	P	150	mm	7	KG/Cm2	ANSI
11	S	150	mm	7	KG/Cm2	ANSI
12	P	150	mm	7	KG/Cm2	ANSI
12	S	150	mm	7	KG/Cm2	ANSI
13	P	150	mm	7	KG/Cm2	ANSI
13	S	150	mm	7	KG/Cm2	ANSI

8.15.1	Is the vessel fitted with a fixed common line ?	Yes	
	What is the number of common cargo connections per side?	1	
	What is the size of common cargo connections?	300 Millimetres	
8.16	What type of valves are fitted at manifold? If other, specify:	Butterfly,	
8.17	What is the material/rating of the manifold:	Stainless Steel SUS316L/26	
8.17.1	Does the cargo manifold arrangement comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment'?	Yes	
8.18	Distance between cargo manifold centers:	400.00 Millimetres	
8.19	Distance ships rail to manifold:	4,350.00 Millimetres	
8.20	Distance manifold to ships side:	4,560.00 Millimetres	
8.21	Top of rail to center of manifold:	600.00 Millimetres	
8.22	Distance main deck to center of manifold:	2,750.00 Millimetres	
8.23	Spill tank grating to center of manifold:	1,050.00 Millimetres	
8.24	Manifold height above the waterline in normal ballast/at SDWT condition:	9.88 Metres	5.98 Metres
8.25	Number/size/type of reducers:	2 x 150/150mm (6/6") 2 x 150/100mm (6/4") 2 x 150/125mm (6/5") 2 x 150/200mm (6/8") 1 x 150/300mm (6/12") (1 x 200/300mm (8/12") 1 x 250/300mm (10/12")) ANSI	
8.26	Is vessel fitted with a stern manifold? If yes, state size:	No, 0 Millimetres	

Heating

8.27 Provide details of Heating Coils/Heat Exchangers

Tank ID	P/C/S/ Decktank/ Other	Heat exchanger	Internal/External	External ducts	Heating coils	Heating coil sets	Height of the heating coils above tank bottom (mm)	total heating surface (m2)	Ratio of the heating surface	Welded or coupled	Material

1	P	no	Internal	no	yes	2	150.00	12.30	0.03	Welded	SS
2	P	no	Internal	no	yes	2	150.00	14.25	0.03	Welded	SS
1	S	no	Internal	no	yes	2	150.00	12.30	0.03	Welded	SS
2	S	no	Internal	no	yes	2	150.00	14.25	0.03	Welded	SS
3	P	no	Internal	no	yes	2	150.00	11.04	0.03	Welded	SS
3	S	no	Internal	no	yes	2	150.00	11.04	0.03	Welded	SS
4	P	no	Internal	no	yes	2	150.00	30.12	0.03	Welded	SS
4	S	no	Internal	no	yes	2	150.00	30.13	0.03	Welded	SS
5	P	no	Internal	no	yes	2	150.00	29.25	0.03	Welded	SS
5	S	no	Internal	no	yes	2	150.00	29.25	0.03	Welded	SS
6	P	no	Internal	no	yes	2	150.00	22.65	0.03	Welded	SS
6	S	no	Internal	no	yes	2	150.00	22.65	0.03	Welded	SS
7	P	no	Internal	no	yes	2	150.00	27.25	0.03	Welded	SS
7	S	no	Internal	no	yes	2	150.00	27.25	0.03	Welded	SS
8	P	no	Internal	no	yes	2	150.00	35.63	0.03	Welded	SS
8	S	no	Internal	no	yes	2	150.00	35.63	0.03	Welded	SS
9	P	no	Internal	no	yes	2	150.00	29.25	0.03	Welded	SS
9	S	no	Internal	no	yes	2	150.00	29.25	0.03	Welded	SS
10	P	no	Internal	no	yes	2	150.00	29.25	0.03	Welded	SS
11	P	no	Internal	no	yes	2	150.00	10.89	0.03	Welded	SS
11	S	no	Internal	no	yes	2	150.00	10.89	0.03	Welded	SS
10	S	no	Internal	no	yes	2	150.00	29.25	0.03	Welded	SS
12	P	no	Internal	no	yes	2	150.00	21.60	0.03	Welded	SS
12	S	no	Internal	no	yes	2	150.00	21.60	0.03	Welded	SS
13	P	no	Internal	no	yes	2	150.00	22.65	0.03	Welded	SS
13	S	no	Internal	no	yes	2	150.00	22.65	0.03	Welded	SS

8.27.1	Is a Thermal Oil Heating system fitted? If yes, identify tanks?	Yes, 12 W, 13W	
8.28	Maximum temperature cargo can be loaded/maintained:	80.0 °C / 176.0 °F	65 °C / 149 °F
8.28.1	Minimum temperature cargo can be loaded/maintained:	Ambient	80.0 °C / 176.0 °F
Inert Gas			
8.29	Is an Inert Gas System (IGS) fitted/operational?	No/Yes	
8.30	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:	Nitrogen Generator	
8.30.1	If nitrogen generator, specify the applicable flow rate for each of the designed purity modes:	1000 Nm3/hr (95%) 130 Nm3/hr(99.9%)	
Cargo Pumps			
8.31	How many cargo pumps can be run simultaneously at full capacity:	5	

8.32 Cargo Pump Data:

Pump Identity	Pump Location	Type	Type of prime mover	Capacity	At what head?
1P	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
1S	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
2P	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
2S	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
3P	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
3S	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
6P	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
6S	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
11P	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
11S	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
12P	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
12S	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
13P	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00

	13S	Cargo Tank	Centrifugal	Hydraulic	200.00	115.00
	4P	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	4S	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	5P	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	5S	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	7P	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	7S	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	8P	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	8S	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	9P	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	9S	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	10P	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00
	10S	Cargo Tank	Centrifugal	Hydraulic	300.00	115.00

8.33	Is at least one emergency portable cargo pump provided?	Yes
Tank Cleaning Systems		
8.34	Is tank cleaning equipment fixed in cargo tanks?	Yes
8.35	Is portable tank cleaning equipment provided?	Yes
8.36	Tank washing pump capacity:	150.00 Cu. Metres/Hour
8.37	Is a washing water heater fitted? If yes is it operational and state max washing water temperature:	Yes, Yes 80.00 Degrees Celsius
8.38	What is the maximum number of machines that can be operated at their designed max pressure?	10
Other Deck Equipment		
8.39	Is vessel fitted with a remote cargo tank temperature monitoring system. If yes, is it operational?	Yes, Yes
8.40	Is vessel fitted with a remote cargo tank pressure monitoring system. If yes, is it operational?	Yes, Yes
8.41	Is vessel fitted with a cargo tank drier. If yes is it operational and state capacity:	Yes, Yes 9,000.00 Cu. Metres/Hour
8.42	Is vessel fitted with a cargo cooling system. If yes is it operational and state tanks applicable:	No, N/A N/A
8.43	Is steam available on deck?	Yes

9.	
9.1	Provide details for Mooring Ropes, Wires, Tails and Shackles

Type	Location and Identity	Material	Diameter/size	Length	LDBF(100-105 % of SDMBL (Tonnes))	TDBF(125-130 % of SDMBL (Tonnes)	SWL (tonnes)	WLL (tonnes) (50-55% of Max LDBF)	Certificate No.	Installed Date	Reversed Date	Renewal2 Date	Status of line/tail	Condition of line/tail
Ropes	AFT Station	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	7ed0ed0d	2021-04-22	2023-10-22	2026-04-21	In Use	Suitable
Ropes	FWD Port Inner	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	9522cf0f	2025-02-15	2027-08-15	2030-02-14	In Use	Suitable
Ropes	AFT Station	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	3a011aca	2024-07-29	2027-01-29	2029-07-28	In Use	Suitable
Rope	FWD	Mixed	51.00	220.00	42.00	0.00	0.00	21.00	632acee6	2023-01-	2025-07-	2028-01-29	In Use	Suitable

s	Station	Polyolefins (B5 yarn) and HT PES								30	30			
Ropes	FWD Station	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	d08c24f2	2023-01-30	2025-07-30	2028-01-29	In Use	Suitable
Ropes	Rope store	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	2e339742	2025-05-29	2027-11-29	2030-05-28	Spare	Suitable
Ropes	FWD Port Outer	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	0f65275b	2025-02-15	2027-08-15	2030-02-14	In Use	Suitable
Ropes	FWD STBD Inner	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	c88ec0c6	2025-01-01	2027-06-30	2029-12-31	In Use	Suitable
Ropes	Rope Store	Mixed Polyolefins (B5 yarn) and HT PES	48.00	220.00	42.00	0.00	0.00	21.00	1630120377	2020-11-21	2023-05-21	2025-11-20	In Use	Suitable
Ropes	AFT Port Outer	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	25c7fe28	2025-02-15	2027-08-15	2030-02-14	In Use	Suitable
Ropes	AFT STBD Inner	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	99ea6774	2022-11-25	2025-02-15	2027-11-24	In Use	Suitable
Ropes	Rope store	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	fcc5c597	2025-05-29	2027-11-29	2030-05-28	Spare	Suitable
Ropes	AFT Station	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	b8decbc4	2021-04-22	2023-10-22	2026-04-21	In Use	Suitable
Ropes	FWD Station	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	83233921	2023-01-30	2025-07-30	2028-01-29	In Use	Suitable
Ropes	AFT STBD Outer	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	e07f0007	2022-11-25	2025-02-15	2027-11-24	In Use	Suitable
Ropes	FWD Station	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	b0e26e83	2023-01-30	2025-07-30	2028-01-29	In Use	Suitable
Ropes	FWD STBD Outer	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	ca75458d	2025-01-01	2027-06-30	2029-12-31	In Use	Suitable
Ropes	AFT Port Inner	Mixed Polyolefins (B5 yarn) and HT PES	51.00	220.00	42.00	0.00	0.00	21.00	33859808	2024-07-29	2028-01-29	2029-07-28	In Use	Suitable

Ropes	Rope Store	Mixed Polyolefins (B5 yarn) and HT PES	48.00	220.00	42.00	0.00	0.00	21.00	1730120002	2020-11-21	2023-05-21	2025-11-20	In Use	Suitable

9.2 Details of winches and brake testing including rendering loads

Mooring winch Location	Split Drum	Motive Power	Remote Operational controls	Heaving power	Hauling Speed	Type of Brake	Designed Brake Max holding load (ISO) (80% of SDMB	Operational brake holding load (60% of SDMBL)	Date of last brake test	Brake Rendering load	Frequency of testing brakes
1	no	Hydraulic	no	10.00	0.25	Hydraulic	32.00	24.00	2025-12-10	24.00	Annual
2	no	Hydraulic	no	10.00	0.25	Hydraulic	32.00	24.00	2025-12-10	24.00	Annual
3	no	Hydraulic	no	10.00	0.25	Hydraulic	32.00	24.00	2025-12-10	24.00	Annual
4	no	Hydraulic	no	10.00	0.25	Hydraulic	32.00	24.00	2025-12-10	24.00	Annual
5	no	Hydraulic	no	10.00	0.25	Hydraulic	32.00	24.00	2025-12-10	24.00	Annual
6	no	Hydraulic	no	10.00	0.25	Hydraulic	32.00	24.00	2025-12-10	24.00	Annual
7	no	Hydraulic	no	10.00	0.25	Hydraulic	32.00	24.00	2025-12-10	24.00	Annual
8	no	Hydraulic	no	10.00	0.25	Hydraulic	32.00	24.00	2025-12-10	24.00	Annual

9.3 Provide Details of Mooring bollards and bitts

Location	Identity No	Certificate Number	Size (mm)	SWL (tonnes)
Forecastle	4	-	400	70
Forecastle	2	-	355	56
Maindeck Forward (Port)	1	-	355	56
Maindeck Forward (Stbd)	1	-	355	56
Poop Deck (Port)	2	-	355	56
Poop Deck (Port)	2	-	400	70
Poop Deck (Stbd)	2	-	355	56
Poop Deck (Stbd)	2	-	400	70

9.4 **Provide details of Mooring Fairleads/Chocks**

Type	Location	Identity No	Certificate	Size (mm)	SWL (tonnes)	Modifications	If yes, are modifications class approved?
Panama type	Forecastle	3	-	360	62	no	no
Roller fairlead protected by bulwark	Forecastle	6	-	300	82	no	no
Panama type	Maindeck Forward (Port)	1	-	350	56	no	no
Panama type	Maindeck Forward (Stbd)	1	-	350	56	no	no

Panama type	Poop Deck (Port)	3	-	360	62	no	no
Panama type	Poop Deck (Stbd)	2	-	360	62	no	no
Roller fairlead protected by bulwark	Poop Deck (Port)	2	-	300	82	no	no
Roller fairlead protected by bulwark	Poop Deck (Stbd)	2	-	300	62	no	no

Anchors/Emergency Towing System			
9.5	Number of shackles on port/starboard cable:	10.50/10.50	
9.6	Type/SWL of Emergency Towing system forward:	N/A	
9.7	Type/SWL of Emergency Towing system aft:	N/A	
9.8	What is size of closed chock and/or fairleads of enclosed type on stern		
Escort Tug			
9.9	What is SWL of closed chock and/or fairleads of enclosed type on stern:	70.80 Metric Tonnes	
9.10	What is SWL of bollard on poop deck suitable for escort tug:	56.70 Metric Tonnes	
Lifting Equipment/Gangway			
9.11	Derrick/Crane description (Number, SWL and location):	Cranes: 1 x 5 Tonnes MIDSHIP	
9.12	Accommodation ladder direction:	Aft	
9.13	Does vessel have a portable gangway? If yes, state length:	Yes, 12 Metres	
Single Point Mooring (SPM) Equipment			
9.14	Does the vessel meet the recommendations in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings (SPM)':?	No	
9.15	If fitted, how many chain stoppers:	0	
9.16	Details of Bow chain stoppers:		
9.17	Distance between the bow fairlead and chain stopper/bracket:	0 Metres	
9.18	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:	No 360mm x 260mm	

10.	**PROPULSION**		
10.1	Speed	Maximum	Economical
	Ballast speed:	12.20 Knots (WSNP) (NA)	11.50 Knots (WSNP) (NA)
	Laden speed:	12.20 Knots (WSNP) (NA)	11.50 Knots (WSNP) (NA)
10.2	What type of fuel is used for main propulsion? If other, then specify	HFO (380CST), VLSFO	
	What type of fuel is used for generating plant	Diesel	
10.3	Bunker Tank Capacities:		

Tank Name	Bunker Type	Tank Type	Capacity	Max Pressure
No.1 FO (P) tank	HFO	Main Bunker Tank	111.63	5.00
No.3 FO (S)	MDO	Main Bunker Tank	85.00	5.00
No.1 FO (S)	HFO	Main Bunker Tank	92.92	5.00
No.2 FO (P)	HFO	Main Bunker Tank	384.62	5.00
No.2 FO (S)	HFO	Main Bunker Tank	393.88	5.00
FO settling tank	HFO	Settling Tank	10.00	5.00
FO service tank	HFO	Service Tank	12.00	5.00
DO (P)	MDO	Main Bunker Tank	68.45	5.00
DO (S)	MDO	Main Bunker Tank	57.68	5.00
No.3 FO (P)	MDO	Main Bunker Tank	85.00	5.00

	If other, then specify			
10.4	Is vessel fitted with fixed or controllable pitch propeller(s):			
10.5	Engines	No	Capacity	Make/Type
	Main engine:	1	6,230 Kilowatt	AKASAKA-MITSUBISHI 7UEC45LA
	Aux engine:	3	500 Kilowatt	YANMAR, 6N18AL-DV
	Power packs:	3	1,200 Cu. Metres/Hour	Frank Mohn AS
	Boilers:	1	18.00 Metric Tonnes/Hour	TORTOISE ENGINEERING Co, Ltd/ MVW-180
Bow/Stern Thruster				
10.6	What is brake horse power of bow thruster (if fitted):		Yes, 864 bhp	
10.7	What is brake horse power of stern thruster (if fitted):		No, 0 bhp	
Environmental/Emissions				
10.8	Does the vessel have an EEDI Rating number? If yes then provide EEDI rating:		No, NA	
	If No then provide reason:		Not Applicable	
	Is the EEDI rating verified by Class, 3rd Party or Owner?			
10.9	Does the vessel have an EEXI Rating number? If yes then provide EEXI rating		Yes, 7.77	
	If No then provide reason:			
	Is the EEXI rating verified by Class, 3rd Party or Owner?		Class	
10.10	Does the vessel have a CII Rating number? If yes then provide CII rating:		Yes, B	
	If No then provide reason			
	Is the CII rating verified by Class, 3rd Party or Owner?		Class	
10.11	Does the vessel have an EIV Rating number? If yes then provide EIV rating		No,	
	If No then provide reason		Not Applicable	
	Is the EIV rating verified by Class, 3rd Party or Owner?			
10.12	What is the ships NOx control level (Tier I, Tier II, and Tier III)?		Tier I	
	List of equipment fitted for NOx Tier III achievement for all engines (LP Selective catalytic reduction, HP Selective catalytic reduction, Exhaust gas recirculation, Alternative fuel etc...)			
	If other, then specify			
Exhaust Gas Cleaning System/Scrubber				
10.13	Does the vessel use an Exhaust Gas Cleaning System?		No	
10.14	What is the type of scrubber fitted as part of the EGCS onboard?			

11.	**SHIP TO SHIP TRANSFER**	
11.1	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum, Chemicals or Liquified Gas, as applicable)?	Yes
11.2	What is maximum outreach of cranes/derricks outboard of the ship's side:	5.90 Metres
11.3	Date/place of last STS operation:	
11.4	Does the vessel have a ship specific STS plan:	Yes

12.	**RECENT OPERATIONAL HISTORY**	
12.1	Last three cargoes/charterers/voyages (Last/2nd Last/3rd Last):	Private and Confidential as per Charter Party. Please contact owner for detail.
12.2	Has ship been involved in a pollution, grounding, collision or allision incident during the past 12 months? If yes, provide details: No	
12.3	Date and place of last Port State Control inspection:	Oct 24, 2025, Gresik

12.4	Any outstanding deficiencies as reported by any Port State Control? If yes, provide details:	No, N/A
12.5	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: ** "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.*	ENOC, Petron, IMT, PERTAMINA, PREEM AB, SONANGOL USA CO, KOCH, Phillips 66, NESTE OIL, LUKOIL, BHP, SHELL
12.6	Date/Place last SIRE inspection:	Jul 13, 2025 / Jorf Lasfar
12.6.1	Date/Place last CDI inspection:	Sep 26, 2024 / Haldia
12.7	Additional information relating to features of the ship or operational characteristics:	

Revised 2024 (INTERTANKO/Q88.com)

Form completed on http://www.q88.com/integration.aspx Please email support@q88.com an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee