

# Natural Language Processing IN2361

Prof. Dr. Georg Groh

# Chapter 25

## Lexicons for Sentiment, Affect and Connotation

- content is based on [1] and [2]
- certain elements (e.g. equations or tables) were taken over or taken over in a modified form from [1] or [2]
- citations of [1] and [2] are omitted for legibility
- errors are fully in the responsibility of Georg Groh
- BIG thanks to Dan and James for a great book!

- Scherer **typology of affective states**:

**Emotion:** Relatively brief episode of response to the evaluation of an external or internal event as being of major significance.

*(angry, sad, joyful, fearful, ashamed, proud, elated, desperate)*

**Mood:** Diffuse affect state, most pronounced as change in subjective feeling, of low intensity but relatively long duration, often without apparent cause.

*(cheerful, gloomy, irritable, listless, depressed, buoyant)*

**Interpersonal stance:** Affective stance taken toward another person in a specific interaction, colouring the interpersonal exchange in that situation.

*(distant, cold, warm, supportive, contemptuous, friendly)*

**Attitude:** Relatively enduring, affectively colored beliefs, preferences, and pre-dispositions towards objects or persons.

*(liking, loving, hating, valuing, desiring)*

**Personality traits:** Emotionally laden, stable personality dispositions and behavior tendencies, typical for a person.

*(nervous, anxious, reckless, morose, hostile, jealous)*

e.g. Sentiment Analysis (see chapter 6) = extraction of attitudes


# Encoding Emotion

- linear combinations of **basic emotions**:

- **Ekman**: surprise, happiness, anger, fear, disgust, sadness
- **Plutchik**: joy–sadness, anger–fear, trust–disgust, and anticipation–surprise

- **vector space**: e.g. 3 dimensional:

- **valence**: the pleasantness of the stimulus
- **arousal**: the intensity of emotion provoked by the stimulus
- **dominance**: the degree of control exerted by the stimulus



# Lexicons for Emotion and Other Affective States

Assumption: words have an affective meaning (connotation)

- General Inquirer (1966): 1915 positive and 2291 negative words
- MPQA Subjectivity lexicon (2005): 2718 positive and 4912 negative words with reliability score (weakly or strongly subjective)
- polarity lexicon of (Hu and Liu, 2004): 2006 positive and 4783 negative words

**Positive** admire, amazing, assure, celebration, charm, eager, enthusiastic, excellent, fancy, fantastic, frolic, graceful, happy, joy, luck, majesty, mercy, nice, patience, perfect, proud, rejoice, relief, respect, satisfactorily, sensational, super, terrific, thank, vivid, wise, wonderful, zest

**Negative** abominable, anger, anxious, bad, catastrophe, cheap, complaint, condescending, deceit, defective, disappointment, embarrass, fake, fear, filthy, fool, guilt, hate, idiot, inflict, lazy, miserable, mourn, nervous, objection, pest, plot, reject, scream, silly, terrible, unfriendly, vile, wicked



# Lexicons for Emotion and Other Affective States

general idea: ask human study participants (questionnaires / crowdsourcing / serious games / ...):

- NRC **Word-Emotion Association Lexicon (EmoLex)** (2013): 14000 words,
  - raters first determine word sense with **association task**, then rate word sense with Plutchik's 8 emotions and 4 intensity levels;
  - post-processing: majority voting, outlier removal, reduce to 2 intensity levels

Which word is closest in meaning (most related) to **startle**?

- automobile
- shake
- honesty
- entertain

Word	anger	anticipation	disgust	fear	joy	sadness	surprise	trust	positive	negative
reward	0	1	0	0	1	0	1	1	1	0
worry	0	1	0	1	0	1	0	0	0	1
tenderness	0	0	0	0	1	0	0	0	1	0
sweetheart	0	1	0	0	1	1	0	1	1	0
suddenly	0	0	0	0	0	0	1	0	0	0
thirst	0	1	0	0	0	1	1	0	0	0
garbage	0	0	1	0	0	0	0	0	0	1

# Lexicons for Emotion and Other Affective States

- NRC **Valence, Arousal, and Dominance (VAD)** lexicon (2018) (20000 words)

<b>Valence</b>		<b>Arousal</b>		<b>Dominance</b>	
vacation	.840	enraged	.962	powerful	.991
delightful	.918	party	.840	authority	.935
whistle	.653	organized	.337	saxophone	.482
consolation	.408	effortless	.120	discouraged	.0090
torture	.115	napping	.046	weak	.045

- NRC **Emotion/Affect Intensity Lexicon** (2018) (5814 words)

<b>Anger</b>		<b>Fear</b>		<b>Joy</b>		<b>Sadness</b>	
outraged	0.964	horror	0.923	superb	0.864	sad	0.844
violence	0.742	anguish	0.703	cheered	0.773	guilt	0.750
coup	0.578	pestilence	0.625	rainbow	0.531	unkind	0.547
oust	0.484	stressed	0.531	gesture	0.387	difficulties	0.421
suspicious	0.484	failing	0.531	warms	0.391	beggar	0.422
nurture	0.059	confident	0.094	hardship	.031	sing	0.017

# Lexicons for Emotion and Other Affective States

- **Linguistic Inquiry and Word Count (LWIC)** (2007): 2300 words, **73 categories**: e.g. positive and negative emotion, anger, sadness, cognitive mechanisms, perception, tentative, inhibition, etc.

<b>Positive Emotion</b>	<b>Negative Emotion</b>	<b>Insight</b>	<b>Inhibition</b>	<b>Family</b>	<b>Negate</b>
appreciat*	anger*	aware*	avoid*	brother*	aren't
comfort*	bore*	believe	careful*	cousin*	cannot
great	cry	decid*	hesitat*	daughter*	didn't
happy	despair*	feel	limit*	family	neither
interest	fail*	figur*	oppos*	father*	never
joy*	fear	know	prevent*	grandf*	no
perfect*	griev*	knew	reluctan*	grandm*	nobod*
please*	hate*	means	safe*	husband	none
safe*	panic*	notice*	stop	mom	nor
terrific	suffers	recogni*	stubborn*	mother	nothing
value	terrify	sense	wait	niece*	nowhere
wow*	violent*	think	wary	wife	without



# Semi-supervised Induction of Sentiment Lexicons

## Semantic Axis Methods

- **step 1:** (in a genre-sensitive way) choose **positive** and **negative seed words**

Domain	Positive seeds	Negative seeds
<b>General</b>	good, lovely, excellent, fortunate, pleasant, delightful, perfect, loved, love, happy	bad, horrible, poor, unfortunate, unpleasant, disgusting, evil, hated, hate, unhappy
<b>Twitter</b>	love, loved, loves, awesome, nice, amazing, best, fantastic, correct, happy	hate, hated, hates, terrible, nasty, awful, worst, horrible, wrong, sad
<b>Finance</b>	successful, excellent, profit, beneficial, improving, improved, success, gains, positive	negligent, loss, volatile, wrong, losses, damages, bad, litigation, failure, down, negative

- **step 2:** train **new** or use **or fine-tune** existing **word-embeddings** for seed words on corpus and **compute centroids**:

$$\left. \begin{aligned} S^+ &= \{E(w_1^+), E(w_2^+), \dots, E(w_n^+)\} \\ S^- &= \{E(w_1^-), E(w_2^-), \dots, E(w_m^-)\} \end{aligned} \right\}$$

$$\mathbf{v}^+ = \frac{1}{n} \sum_1^n E(w_i^+)$$

$$\mathbf{v}^- = \frac{1}{m} \sum_1^m E(w_i^-)$$

## Semantic Axis Methods

- **step 3**: define “semantic axis” with respect to sentiment for genre and project on that axis:

$$\mathbf{V}_{axis} = \mathbf{V}^+ - \mathbf{V}_-$$

$$\begin{aligned} \text{score}(w) &= (\cos(E(w), \mathbf{V}_{axis})) \\ &= \frac{E(w) \cdot \mathbf{V}_{axis}}{\|E(w)\| \|\mathbf{V}_{axis}\|} \end{aligned}$$

the higher the score the more  $w$  is aligned with  $S^+$

# Semi-supervised Induction of Sentiment Lexicons


## Label Propagation

example: **SentProp** (2016)

- **step 1**: define **similarity graph** on word embeddings: connect word  $w_i$  to its  $k$  nearest neighbors; weight edges with angle between embeddings

$$E_{i,j} = \arccos \left( -\frac{\mathbf{w}_i^\top \mathbf{w}_j}{\|\mathbf{w}_i\| \|\mathbf{w}_j\|} \right)$$

- **step 2**: choose positive and negative **seed words**
- **step 3**: **propagate polarities**:  
random walk starting at seeds with transition probabilities  $E_{i,j}$  ;  
a word's positive / negative raw polarity score: proportional to number of visits from positive / negative seeds



**Label Propagation**      example: **SentProp** (2016)

- **step 4:** **normalize** raw scores:

$$\text{score}^+(w_i) = \frac{\text{score}^+(w_i)}{\text{score}^+(w_i) + \text{score}^-(w_i)}$$

- **step 5:** start from various seeds and compute variance of scores for each run → **confidence measure**

# Semi-supervised Induction of Sentiment Lexicons

## Other ideas / basic ideas

```
function BUILDSENTIMENTLEXICON(posseeds,negseeds) returns poslex,neglex  
  
  poslex ← posseeds  
  neglex ← negseeds  
  Until done  
    poslex ← poslex + FINDSIMILARWORDS(poslex)  
    neglex ← neglex + FINDSIMILARWORDS(neglex)  
  poslex,neglex ← POSTPROCESS(poslex,neglex)
```


example: **adjectives**: Hatzivassiloglou & McKeown algorithm (1997): use conjunction patterns as proxy for polarity:

- **step 1**: **hand-label** common adjectives (→ *posseeds*, *negseeds*)
- **step 2**: create **candidate polarity-related adjectives**:
  - coordination **and**: hint for **same** polarity:  
*fair and legitimate, corrupt and brutal* { *problem*: good and bad
  - coordination **but**: hint for **opposite** polarity:  
*fair but brutal, beautiful but mean*
  - **morphological negation** (un- , im- , -less...):  
*adequate/inadequate, thoughtful/thoughtless*




# Semi-supervised Induction of Sentiment Lexicons

- **step 3**: build a **polarity graph**:
  - **nodes**: adjectives and candidate adjectives
  - **edge weights**: “same polarity”-probabilities of a supervised 2-class(“same polarity”, “different polarity”)-classifier



- **step 4**: **cluster** the polarity graph into “positive” and “negative” clusters



# Semi-supervised Induction of Sentiment Lexicons

## Other ideas / basic ideas

Problem / Core Assumption: A single word can be labeled as simply positive or negative, which is not true! It's the way they are used in context.

- Using **WordNet Synonyms and Antonyms** (2004):
  - **intuition**: word's synonyms probably share its polarity; word's antonyms probably have the opposite polarity.
  - using seed-labels, **propagate**:

$\text{Lex}^+$  : Add synonyms of positive words (*well*) and antonyms (like *fine*) of negative words

$\text{Lex}^-$  : Add synonyms of negative words (*awful*) and antonyms (like *evil*) of positive words

- **SentiWordNet** (2010): extension of this idea:
  - using pos / neg word seeding, select positive and negative synsets;
  - train binary classifier on glosses of labeled pos / neg synsets;
  - combine classifier output with additional random walk steps to yield pos / neg score for synset.

# Semi-supervised Induction of Sentiment Lexicons

## Other ideas / basic ideas

- SentiWordNet

Synset	Pos	Neg	Obj
good#6 'agreeable or pleasing'	1	0	0
respectable#2 honorable#4 good#4 estimable#2 'deserving of esteem'	0.75	0	0.25
estimable#3 computable#1 'may be computed or estimated'	0	0	1
sting#1 burn#4 bite#2 'cause a sharp or stinging pain'	0	0.875	.125
acute#6 'of critical importance and consequence'	0.625	0.125	.250
acute#4 'of an angle; less than 90 degrees'	0	0	1
acute#1 'having or experiencing a rapid onset and short but severe course'	0	0.5	0.5

Examples from SentiWordNet 3.0 ([Baccianella et al., 2010](#)). Note the differences between senses of homonymous words: *estimable#3* is purely objective, while *estimable#2* is positive; *acute* can be positive (*acute#6*), negative (*acute#1*), or neutral (*acute #4*)

# Supervised Learning of Word Sentiment

- use e.g. 5-star scores **web reviews** of books, movies etc. as ground truth for their polarity

## **Movie review excerpts (IMDB)**

- 10** A great movie. This film is just a wonderful experience. It's surreal, zany, witty and slapstick all at the same time. And terrific performances too.
- 1** This was probably the worst movie I have ever seen. The story went nowhere even though they could have done some interesting stuff with it.

## **Restaurant review excerpts (Yelp)**

- 5** The service was impeccable. The food was cooked and seasoned perfectly... The watermelon was perfectly square ... The grilled octopus was ... mouthwatering...
- 2** ...it took a while to get our waters, we got our entree before our starter, and we never received silverware or napkins until we requested them...

## **Book review excerpts (GoodReads)**

- 1** I am going to try and stop being deceived by eye-catching titles. I so wanted to like this book and was so disappointed by it.
- 5** This book is hilarious. I would recommend it to anyone looking for a satirical read with a romantic twist and a narrator that keeps butting in

## **Product review excerpts (Amazon)**

- 5** The lid on this blender though is probably what I like the best about it... enables you to pour into something without even taking the lid off! ... the perfect pitcher! ... works fantastic.
- 1** I hate this blender... It is nearly impossible to get frozen fruit and ice to turn into a smoothie... You have to add a TON of liquid. I also wish it had a spout ...

# Supervised Learning of Word Sentiment

- Potts score of a word  $w$  with a rating class  $c$

$$P(w|c) = \frac{\text{count}(w, c)}{\sum_{w \in C} \text{count}(w, c)}$$

how often does word  $w$  occur in reviews with rating  $c$

$$\text{PottsScore}(w) = \frac{P(w|c)}{\sum_c P(w|c)}$$

all the words in all reviews with rating  $c$

$$\text{Potts}(\text{disappointing} | c) = [ \underset{c=1}{.10}, \underset{c=2}{.12}, .14, .14, .13, .11, .08, .06, .06, \underset{c=10}{.05} ]$$




# Supervised Learning of Word Sentiment


**scalar adjectives**: Potts diagrams:

## Positive scalars


good



great




excellent




## Negative scalars


disappointing



bad




terrible




Potts diagrams for emphasizing and attenuating **adverbs**

## Emphatics


totally



absolutely




utterly




## Attenuators


somewhat



fairly



pretty



# Log Odds Ratio Informative Dirichlet Prior

- regard **two classes A and B** of documents; examples:  
A = 1 star reviews, B = 5 star-reviews  
A = docs written by Republicans, B = docs written by Democrats
- question: **does a word w appear more often in A or in B?** → compare difference or **ratio of frequencies or log odds ratio** → does not work well with very frequent or very infrequent words
- **example:** does word *horrible* appear more often in corpus i or in corpus j → **log likelihood ratio**

$$\begin{aligned}\text{llr}(\text{horrible}) &= \log \frac{P^i(\text{horrible})}{P^j(\text{horrible})} \\ &= \log P^i(\text{horrible}) - \log P^j(\text{horrible}) \\ &= \log \frac{f^i(\text{horrible})}{n^i} - \log \frac{f^j(\text{horrible})}{n^j}\end{aligned}$$

$n^i$ : size of corpus i (class A)  
 $n^j$ : size of corpus j (class B)  
 $f^i(w)$ : count of w in corpus i  
 $f^j(w)$ : count of w in corpus j

# Log Odds Ratio Informative Dirichlet Prior

- log odds ratio

$$\begin{aligned}\text{lor}(\text{horrible}) &= \log \left( \frac{P^i(\text{horrible})}{1 - P^i(\text{horrible})} \right) - \log \left( \frac{P^j(\text{horrible})}{1 - P^j(\text{horrible})} \right) \\ &= \log \left( \frac{\frac{f^i(\text{horrible})}{n^i}}{1 - \frac{f^i(\text{horrible})}{n^i}} \right) - \log \left( \frac{\frac{f^j(\text{horrible})}{n^j}}{1 - \frac{f^j(\text{horrible})}{n^j}} \right) \\ &= \log \left( \frac{f^i(\text{horrible})}{n^i - f^i(\text{horrible})} \right) - \log \left( \frac{f^j(\text{horrible})}{n^j - f^j(\text{horrible})} \right)\end{aligned}$$

$n^i$ : size of corpus i (class A)  
 $n^j$ : size of corpus j (class B)  
 $f^i(w)$ : count of w in corpus i  
 $f^j(w)$ : count of w in corpus j

- now: Dirichlet intuition: use a large background corpus to get a prior estimate of what we expect the frequency of each word w to be:  
do this very simply by smoothing: adding the counts from that corpus to the numerator and denominator  $\leftrightarrow$  we're essentially shrinking the counts toward that prior.  
 $\leftrightarrow$  how large are the differences between i and j given what we would expect given their frequencies in a well-estimated large background corpus.

# Log Odds Ratio Informative Dirichlet Prior

- Dirichlet intuition →

$$\delta_w^{(i-j)} = \log \left( \frac{f_w^i + \alpha_w}{n^i + \alpha_0 - (f_w^i + \alpha_w)} \right) - \log \left( \frac{f_w^j + \alpha_w}{n^j + \alpha_0 - (f_w^j + \alpha_w)} \right)$$

$n^i$ : size of corpus i (class A)

$n^j$ : size of corpus j (class B)

$f_w^i$ : count of w in corpus i

$f_w^j$ : count of w in corpus j

$\alpha_0$ : size of background corpus

$\alpha_w$ : count of w in background corpus

- together with estimate for variance ( $\leftrightarrow$  scale for this log odds ratio (= difference))

$$\sigma^2 \left( \hat{\delta}_w^{(i-j)} \right) \approx \frac{1}{f_w^i + \alpha_w} + \frac{1}{f_w^j + \alpha_w}$$

we get final z-score:

$$\frac{\hat{\delta}_w^{(i-j)}}{\sqrt{\sigma^2 \left( \hat{\delta}_w^{(i-j)} \right)}}$$

# Log Odds Ratio Informative Dirichlet Prior

Class	Words in 1-star reviews	Class	Words in 5-star reviews
<b>Negative</b>	<i>worst, rude, terrible, horrible, bad, awful, disgusting, bland, tasteless, gross, mediocre, overpriced, worse, poor</i>	<b>Positive</b>	<i>great, best, love(d), delicious, amazing, favorite, perfect, excellent, awesome, friendly, fantastic, fresh, wonderful, incredible, sweet, yum(my)</i>
<b>Negation</b>	<i>no, not</i>	<b>Emphatics/universals</b>	<i>very, highly, perfectly, definitely, absolutely, everything, every, always</i>
<b>1Pl pro</b>	<i>we, us, our</i>	<b>2 pro</b>	<i>you</i>
<b>3 pro</b>	<i>she, he, her, him</i>	<b>Articles</b>	<i>a, the</i>
<b>Past verb</b>	<i>was, were, asked, told, said, did, charged, waited, left, took</i>	<b>Advice</b>	<i>try, recommend</i>
<b>Sequencers</b>	<i>after, then</i>	<b>Conjunct</b>	<i>also, as, well, with, and</i>
<b>Nouns</b>	<i>manager, waitress, waiter, customer, customers, attitude, waste, poisoning, money, bill, minutes</i>	<b>Nouns</b>	<i>atmosphere, dessert, chocolate, wine, course, menu</i>
<b>Irrealis modals</b>	<i>would, should</i>	<b>Auxiliaries</b>	<i>is/'s, can, 've, are</i>
<b>Comp</b>	<i>to, that</i>	<b>Prep, other</b>	<i>in, of, die, city, mouth</i>

(words with highest class difference z scores)



# Using Lexicons for Sentiment Recognition

- **sentiment lexicon**: list each word as either **positive** or **negative** or give a positiveness score  $\theta_w^+$  and a negativeness score  $\theta_w^-$
- use lexicon in a simple “**rule-based**” way:

$$\begin{aligned} f^+ &= \sum_{w \text{ s.t. } w \in \text{positivelexicon}} \theta_w^+ \text{count}(w) \\ f^- &= \sum_{w \text{ s.t. } w \in \text{negativelexicon}} \theta_w^- \text{count}(w) \\ \text{sentiment} &= \begin{cases} + & \text{if } \frac{f^+}{f^-} > \lambda \\ - & \text{if } \frac{f^-}{f^+} > \lambda \\ 0 & \text{otherwise.} \end{cases} \end{aligned}$$

- or use lexicon assessment for words as features for supervised sentiment classifier

- standard questionnaires for **Big 5 personality dimensions**:
  - Extroversion vs. Introversion:  
sociable, assertive, playful vs. aloof, reserved, shy
  - Emotional stability vs. Neuroticism:  
calm, unemotional vs. insecure, anxious
  - Agreeableness vs. Disagreeableness:  
friendly, cooperative vs. antagonistic, fault finding
  - Conscientiousness vs. Unconscientiousness:  
self-disciplined, organized vs. inefficient, careless
  - Openness to experience:  
intellectual, insightful vs. shallow, unimaginative
- **essay corpus** of Pennebaker & King (1999): 2479 essays (1.9 million words) from psychology students who took a standard personality test were asked to “write whatever comes into your mind” for 20 minutes.

- sample from neurotic individual:

One of my friends just barged in, and I jumped in my seat. This is crazy. I should tell him not to do that again. I'm not that fastidious actually. But certain things annoy me. The things that would annoy me would actually annoy any normal human being, so I know I'm not a freak.

- sample from emotionally stable individual:

I should excel in this sport because I know how to push my body harder than anyone I know, no matter what the test I always push my body harder than everyone else. I want to be the best no matter what the sport or event. I should also be good at this because I love to ride my bike.

- **speed dating corpus** (Ranganath et al) (2013): mutual rating: interpersonal stance of other participants

# Supervised Affect Recognition

- affect recognition: generalizing algorithms described before for detecting sentiment.
- supervised document classification problem: useful features + SVM or comparable classifier = very good results
- example: Schwartz (2013) Facebook dataset ( $3 \cdot 10^8$  words, 75000 users): personality, gender, age;  
features: unigrams, bigrams, trigrams with sufficiently high PMI

$$\text{pmi}(\text{phrase}) = \log \frac{p(\text{phrase})}{\prod_{w \in \text{phrase}} p(w)}$$

$$p(\text{phrase} | \text{subject}) = \frac{\text{freq}(\text{phrase}, \text{subject})}{\sum_{\text{phrase}' \in \text{vocab}(\text{subject})} \text{freq}(\text{phrase}', \text{subject})}$$

subject == person on Facebook

- if lexicon is available, use **class based features**:

$$f_{\mathcal{L}}(c, x) = \begin{cases} 1 & \text{if } \exists w : w \in \mathcal{L} \ \& \ w \in x \ \& \ class = c \\ 0 & \text{otherwise} \end{cases}$$

- or **just raw or log'd counts** of **word-tokens** in respective (part of) lexicon associated with a class

$$f_{\mathcal{L}} = \sum_{w \in \mathcal{L}} count(w)$$


if lexicon has membership degree weights, use **weighted counts**:

$$f_{\mathcal{L}} = \sum_{w \in \mathcal{L}} \theta_w^{\mathcal{L}} count(w)$$



# Affect Recognition

- **example** result: use **logistic regression** and investigate **weight vector** : which features are positively associated with a class, which are negatively associated:
  - LWIC lexicons *Family, Home* positively associated and *anger* and *swear* negatively correlated with personality dimension class *Agreeable*
  - Schwartz' Facebook dataset: Extroversion – Introversion regression: associated words + phrases



# Affect Recognition

- Schwartz' Facebook dataset: Neuroticism – Emotional Stability  
regression: associated words + phrases

words & phrases positively associated with class **Neuroticism**




words & phrases positively associated with class **Emotionally Stable**




# VAD Recognition using Embeddings & Regression

- for a word  $w$ : compute embedding: either
  - use static embedding (e.g. Word2Vec)
  - or average of dynamic embeddings (ELMo or BERT)
- look up Valence Arousal and Dominance values for  $w$  in NRC VAD lexicon and compute three linear regressions using embedding as  $x$  and V, A, and D values as  $y$  values.



**Figure 21.14** Power (dominance), sentiment (valence) and agency (arousal) for characters in the movie *The Dark Knight* computed from ELMo embeddings trained on the NRC VAD



- (1) Dan Jurafsky and James Martin: Speech and Language Processing (3<sup>rd</sup> ed. draft, version Jan 2023); Online: <https://web.stanford.edu/~jurafsky/slp3/> (URL, Oct 2023) (this slideset is especially based on chapter 25)
- (2) Powerpoint slides from Dan Jurafsky and James Martin: Speech and Language Processing (3<sup>rd</sup> ed. draft); Online: <https://web.stanford.edu/~jurafsky/slp3/> (URL, Oct 2022)



# Recommendations for Studying

- minimal approach:

work with the slides and understand their contents! Think beyond instead of merely memorizing the contents

- standard approach:

minimal approach + read the corresponding pages in Jurafsky [1]

- interested students

== standard approach