```
return response($content)
                                                                                               ->withHeaders([
                                                                                                    'Content-Type' => $type,
                                                                                                    'X-Header-One' => 'Header Value',
                                                                                                    'X-Header-Two' => 'Header Value',]);
                                                                                                            return response($content)
                                                                                                                     ->header('Content-Type', $type)
                      return response ('Hello World', 200)
                                                                                                                     ->cookie('name', 'value', $minutes);
                                 ->header('Content-Type', 'text/plain');
                                                                                                            cookie 默认情况下是encrypted 可以排除一些我们想获取的
                                                                                                            cookie内容
                                                                               ->header()->cookie()
                                                                                                            #App\Http\Middleware\EncryptCookies
                                                                                                            middleware
                                                                                                            protected $except = [
                                                                                                               'cookie_name',
                                         return redirect('home/
                                        dashboard');
                                                                             返回到之前的页面并且
                                                                             withInput 不包括password
                                         back()->withInput($request-
                                                                              Since this feature utilizes the
                                         >except('password')) 返回
                                                                              session, make sure the route
                                         使用with request
                                                                              calling the back function is using the
                                                                              web middleware group or has all of
                                                                              the session middleware applied
                                                                           假如要自定义route 里面的
                                                                          name 在Model里面一样可以办
                                                                          public function getRouteKey()
                                         to named route
                                                                             return $this->slug;
                                         redirect()->route('name',
                                         [parameters])
                                                                           // For a route with the following URI: profile/{id}
                                                                           如果profile 对应的参数是Eloquent model 的 id 可以直接 传入$user 这
                                                                           个参数就可以了 上面是用来改变 主键值
                                                                           return redirect()->route('profile', [$user]);
                                                                           $user 是user model的实例
                                                                return redirect()-
                                                               >action('HomeController@ind
                                                                ex',[parametes]);
                                                                将status 存在session 里面 值是
                                                                                                            @if (session('status'))
                                        返回controller
                                                               Profile updated!
                                                                                                              <div class="alert alert-success">
                                                               return redirect('dashboard')-
                                                                                                                {{ session('status') }}
                                                               >with('status', 'Profile updated!'); //是
                                                                                                              </div>
                                                                从session里面拿到数据
                                                                                                            @endif
Response
                                                      return response()
                                                             ->view('hello', $data,
                                                      200)
                                        view
                                                             ->header('Content-
                                                      Type', $type);
                                                                  return response()-
                                                                  >json(['name'=>"js"])
                      redirect
                                                                   with jsonp
                                        JSON Responses
                                                                   return response()
                                                                          ->json(['name' => 'Abigail', 'state' => 'CA'])
                                                                          ->withCallback($request->input('callback'));
                                                               会下载文件
                                                               return response()-
                                                               >download($pathToFile);
                                                               return response()-
                                                               >download($pathToFile,
                                                               $name, $headers);
                                        File download
                                                               return response()-
                                                               >download($pathToFile)-
                                                               >deleteFileAfterSend(true);
                                                               response file
                                                               return response()->file($pathToFile);
                                                               return response()->file($pathToFile, $headers);
                                                               demo return response()->file(base_path('demo.jpg'))
                                                                    <?php
                                                                    namespace App\Providers;
                                                                    use Illuminate\Support\ServiceProvider;
                                                                    use Illuminate\Support\Facades\Response;
                                                                    class ResponseMacroServiceProvider extends ServiceProvider
                                        macros(宏) 操作
                                                                       * Register the application's response macros.
                                                                                                                                        return response()->caps('foo');
                                                                       * @return void
                                                                       public function boot()
                                                                         Response::macro('caps', function ($value) {
                                                                           return Response::make(strtoupper($value));
                                                                         });
                                         https://laravel.com/docs/
                                         5.4/helpers
```