

Webcam analysis

First Author

Department, Generic University

Author Note

First Author  <https://orcid.org/0000-0000-0000-0001>

Correspondence concerning this article should be addressed to First Author, Department, Generic University, 1234 Capital St., New York, NY 12084-1234, USA, Email: janedoe@generic.edu

Abstract

This document is a template.

Impact Statement

This template helps you get started.

Keywords: Keyword 1, Keyword 2, Keyword 3

Webcam analysis

This is my first paragraph. Any section headings in the introduction should be in levels 2–5.

Section in Introduction

This is a reference (Cohen et al., 2003).

Experiment 1

Method

Participants

Measures

Procedure

Data analysis

We analysed the data for the frequency corpus by fitting Bayesian linear mixed models using the brms package (Bürkner, 2017, 2018, 2021) in R¹. These models included the word frequency condition (low, represented as -.5, vs. high, represented as .5) as well as the eye-tracker used (with the Eyelink represented as -.5 and the Webcam represented as .5). We included the maximum random effects structure (i.e., random intercepts and random slopes for condition, stimulus type, and their interaction over subjects and random intercepts and random slopes for

¹ The versions of R and all packages used are as follows: R (Version 4.5.2; R Core Team, 2025) and the R-packages *conflicted* (Version 1.2.0; Wickham, 2023), *dplyr* (Version 1.1.4; Wickham et al., 2023), *emmeans* (Version 2.0.0; Lenth & Piaskowski, 2025), *forcats* (Version 1.0.1; Wickham, 2025a), *ggplot2* (Version 4.0.0; Wickham, 2016), *gt* (Version 1.1.0; Iannone et al., 2025), *here* (Version 1.0.2; Müller, 2025), *knitr* (Version 1.50; Xie, 2015), *lubridate* (Version 1.9.4; Grolemund & Wickham, 2011), *modelsummary* (Version 2.5.0; Arel-Bundock, 2022), *papaja* (Version 0.1.4; Aust & Barth, 2025), *purrr* (Version 1.2.0; Wickham & Henry, 2025), *qs2* (Version 0.1.5; Ching, 2025), *readr* (Version 2.1.5; Wickham, Hester, et al., 2024), *sjPlot* (Version 2.9.0; Lüdtke, 2025), *stringr* (Version 1.6.0; Wickham, 2025b), *tibble* (Version 3.3.0; Müller & Wickham, 2025), *tidybayes* (Version 3.0.7; Kay, 2024), *tidyr* (Version 1.3.1; Wickham, Vaughan, et al., 2024), *tidyverse* (Version 2.0.0; Wickham et al., 2019), and *tinylabels* (Version 0.2.5; Barth, 2025).

condition over items, [Barr et al., 2013](#)). We used the Gaussian distribution to model fixation times, after excluding excessively short (< 80 ms) and long observations (first fixation duration and single fixation duration $> 1,000$ ms; gaze duration $> 1,800$ ms; total viewing time $> 2,000$). We used the default priors suggested by brms for the fixed effects and random effects; coefficients were given weakly informative priors to rule out implausibly large effects. Each model was fitted using four chains with 5000 iterations each with 1000 warmup iterations. The models converged successfully (all R-hats = 1.00). We report the estimates (b) and the 95% Bayesian Credible Intervals (95% CIs) based on the posterior distribution of each model parameter and indicate whether 0 is excluded from the 95% CI. Additionally, we report the proportion of the posterior on the same side of 0 ($P(b > 0)$ or $P(b < 0)$) and its ratio to the opposite-side proportion as a directional evidence ratio ($ER_{b>0}$ or $ER_{b<0}$), which can be interpreted as a Bayes factor for the directional hypothesis. Finally, we report Savage–Dickey Bayes factors for the point-null hypothesis $b = 0$ (BF_{10} , [Jeffreys, 1961](#)). It is important to note that each of these statistics is a valid way to summarize the evidence provided by the data, but, for simplicity, we will focus on the 95% CI in our verbal description of the results.

Results

Target word analysis. Table 1 shows the mean and standard deviation of first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on target words in Experiment 1 by eye-tracker and word frequency condition, while Table 2 shows the model estimates.

Overall, low-frequency words elicited longer fixation times than high-frequency words across all measures (FFD: $b = 0.06$, 95% CrI [0.02, 0.10], $P(b > 0) = 1.00$, $ER_{b>0} = 379.95$, $BF_{10} = 0.88$; SFD: $b = 0.06$, 95% CrI [0.02, 0.10], $P(b > 0) = 1.00$, $ER_{b>0} = 306.69$, $BF_{10} = 0.88$; GD: $b = 0.09$, 95% CrI [0.04, 0.13], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} = 17.87$; TVT: $b = 0.11$, 95% CrI [0.06, 0.17], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} = 42.70$). Fixation times were also longer with the Webcam than with the Eyelink (FFD: $b = 0.41$, 95% CrI [0.33, 0.49], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; SFD: $b = 0.41$,

95% CrI [0.32, 0.49], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; GD: $b = 0.43$, 95% CrI [0.35, 0.52], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; TVT: $b = 0.56$, 95% CrI [0.45, 0.67], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$). This is likely due to a systematic difference in the saccade and fixation detection algorithms. Importantly, the Frequency $\times$ Tracker interaction was not credibly different from 0 (FFD: $b = -0.04$, 95% CrI [-0.11, 0.03], $P(b < 0) = 0.85$, $ER_{b<0} = 5.73$, $BF_{10} = 0.06$; SFD: $b = -0.03$, 95% CrI [-0.11, 0.05], $P(b < 0) = 0.78$, $ER_{b<0} = 3.50$, $BF_{10} = 0.05$; GD: $b = -0.08$, 95% CrI [-0.17, 0.007], $P(b < 0) = 0.96$, $ER_{b<0} = 27.02$, $BF_{10} = 0.24$; TVT: $b = -0.06$, 95% CrI [-0.16, 0.03], $P(b < 0) = 0.91$, $ER_{b<0} = 10.31$, $BF_{10} = 0.12$), indicating that the frequency effect was comparable across devices.

The absence of an interaction between frequency and tracker is not positive evidence for a frequency effect in the Webcam data on its own. We calculated posterior distributions for the estimated marginal means of the difference between low and high frequency target words and found that the 95% credible intervals for these differences in the Webcam data included 0, while the credible intervals for the Eyelink data excluded 0 in FFD (Webcam: $M = 0.04$ 95% $CI = [-0.02, 0.10]$; Eyelink: $M = 0.08$ 95% $CI = [0.04, 0.12]$), SFD (Webcam: $M = 0.04$ 95% $CI = [-0.03, 0.11]$; Eyelink: $M = 0.07$ 95% $CI = [0.03, 0.12]$), GD (Webcam: $M = 0.04$ 95% $CI = [-0.03, 0.12]$; Eyelink: $M = 0.13$ 95% $CI = [0.08, 0.17]$), and TVT (Webcam: $M = 0.08$ 95% $CI = [-0.00, 0.16]$; Eyelink: $M = 0.14$ 95% $CI = [0.08, 0.20]$), although the CI for the latter included 0 very narrowly. This indicates that, while the webcam data is consistent with a frequency effect of a similar magnitude to that observed with the Eyelink, the evidence is not sufficiently strong to confirm the presence of frequency effect based on the Webcam data alone using the criterion of the 95% credible interval excluding 0. We assume that this is due to the higher amount of noise in the Webcam data.

Corpus-style analysis. By including all words in every sentence into the analysis, rather than only the target words, we can increase the number of observations. Of course, this comes at the cost of increased variability due to differences in word length, predictability, and other lexical

and contextual factors, but, overall, this approach is likely to have a better chance to detect the word frequency effect. Table 3 shows the results of these “corpus-analysis style” Bayesian linear mixed models with Zipf frequency as a continuous predictor, tracker as a two-level factor (as in the target-word analysis) and the interaction between the two predictors for the four fixation time measures (first fixation duration, FFD; single fixation duration, SFD; gaze duration, GD; total viewing time, TVT) on all words in the sentences (except for the first and last word in each sentence) in Experiment 1.

As expected we observed a frequency effect in that a higher Zipf frequency (i.e., more frequent words) was associated with shorter fixation times across all measures (FFD: $b = -0.04$, 95% CrI $[-0.06, -0.01]$, $P(b < 0) = 1.00$, $ER_{b<0} = 420.05$, $BF_{10} = 0.55$; SFD: $b = -0.05$, 95% CrI $[-0.07, -0.02]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} = 2.01$; GD: $b = -0.07$, 95% CrI $[-0.10, -0.04]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} > 1000$; TVT: $b = -0.06$, 95% CrI $[-0.10, -0.02]$, $P(b < 0) = 1.00$, $ER_{b<0} = 409.26$, $BF_{10} = 1.19$). We again observed longer mean fixation times with the Webcam than with the Eyelink (FFD: $b = 0.36$, 95% CrI $[0.29, 0.44]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; SFD: $b = 0.36$, 95% CrI $[0.29, 0.44]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; GD: $b = 0.42$, 95% CrI $[0.31, 0.53]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; TVT: $b = 0.39$, 95% CrI $[0.31, 0.47]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$). There were no credible Frequency $\times$ Tracker interactions (FFD: $b = 0.02$, 95% CrI $[-0.0083, 0.04]$, $P(b > 0) = 0.91$, $ER_{b>0} = 9.59$, $BF_{10} = 0.03$; SFD: $b = 0.01$, 95% CrI $[-0.02, 0.04]$, $P(b > 0) = 0.79$, $ER_{b>0} = 3.85$, $BF_{10} = 0.02$; GD: $b = 0.0078$, 95% CrI $[-0.02, 0.04]$, $P(b > 0) = 0.70$, $ER_{b>0} = 2.33$, $BF_{10} = 0.02$; TVT: $b = 0.03$, 95% CrI $[-0.0015, 0.06]$, $P(b > 0) = 0.97$, $ER_{b>0} = 30.37$, $BF_{10} = 0.08$). To present the frequency slope within each device directly, we summarized the Zipf effect (slope) by tracker using emtrends from the emmeans package. We found consistent evidence for the frequency effect in all measures for the Eyelink and the Webcam in SFD (Eyelink: $M = -0.05$ 95% CI $[-0.08, -0.02]$; Webcam: $M = -0.04$ 95% CI $[-0.07, -0.01]$), and GD (Eyelink: $M = -0.07$ 95% CI $[-0.10, -0.04]$; Webcam: $M = -0.06$ 95% CI $[-0.10, -0.02]$).

[-0.10, -0.03]). In FFD (Eyelink: $M = -0.05$ 95% $CI = [-0.07, -0.02]$; Webcam: $M = -0.03$ 95% $CI = [-0.06, 0.00]$), and TVT (Eyelink: $M = -0.07$ 95% $CI = [-0.11, -0.03]$; Webcam: $M = -0.04$ 95% $CI = [-0.09, 0.00]$), the 95% CI for the Webcam data narrowly included 0. Overall, this demonstrates that, when there is sufficient data, the frequency effect can be detected even in the noisier Webcam data.

Experiment 2

Method

Participants.

Measures.

Procedure.

Data analysis. The model specifications and data analysis were the same as in Experiment 1, except that Tracker was not included as a predictor since all data were collected remotely using the Webcam.

Results.

Target word analysis. Table 4 shows the mean and standard deviation of first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on target words in Experiment 2 by word frequency condition, while Table 5 shows the model estimates.

In Experiment 2, low-frequency target words elicited longer fixation times than high-frequency target words in SFD ($b = 0.09$, 95% CrI [0.02, 0.15], $P(b > 0) = 0.99$, $ER_{b>0} = 189.48$, $BF_{10} = 0.81$), GD ($b = 0.09$, 95% CrI [0.02, 0.16], $P(b > 0) = 1.00$, $ER_{b>0} = 245.15$, $BF_{10} = 1.21$), and TVT ($b = 0.08$, 95% CrI [0.02, 0.15], $P(b > 0) = 0.99$, $ER_{b>0} = 149.94$, $BF_{10} = 0.76$). In FFD, the CI narrowly included 0 ($b = 0.06$, 95% CrI [-0.0024, 0.12], $P(b > 0) = 0.97$, $ER_{b>0} = 32.90$, $BF_{10} = 0.17$). Overall, this demonstrates that, despite the much lower control we had over devices and experimental setup in the online study, reliable word frequency effects could be found.

Corpus-style analysis. As in Experiment 1, we also fitted Bayesian linear mixed models including all words in every sentence (both the multi-line sentences with the frequency manipulation and the single-line sentences) into the analysis. This increased the number of observations substantially compared to the target word analysis.

Table 6 shows the results of these “corpus-analysis style” Bayesian linear mixed models with Zipf frequency as a continuous predictor for the four fixation time measures (first fixation duration, FFD; single fixation duration, SFD; gaze duration, GD; total viewing time, TVT) on all words in the sentences (except for the first and last word in each sentence) in Experiment 2.

In Experiment 2, we observed a consistent effect of zipf frequency on all measures (FFD: $b = -0.03$, 95% CrI $[-0.04, -0.02]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} > 1000$; SFD: $b = -0.03$, 95% CrI $[-0.05, -0.02]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} > 1000$; GD: $b = -0.05$, 95% CrI $[-0.07, -0.04]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} > 1000$; TVT: $b = -0.08$, 95% CrI $[-0.09, -0.06]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} > 1000$). This again demonstrates that, when there is a sufficiently high number of observations, the frequency effect can be detected using online Webcam eye tracking where we do not have direct control over the experimental setup.

Experiment 3

Method

Participants.

Measures.

Procedure.

Data analysis. The model specifications and data analysis were the same as in Experiment 1.

Results

Target word analysis. Table 7 shows the means and standard deviations for the four fixation time measures on target words in Experiment 3, while Table 8 shows the corresponding model estimates.

As in Experiment 1, we observed a frequency effect in the expected direction across both devices: low-frequency words elicited longer fixations than high-frequency words (FFD: $b = 0.06$, 95% CrI [0.02, 0.10], $P(b > 0) = 1.00$, $ER_{b>0} = 499.00$, $BF_{10} = 1.53$; SFD: $b = 0.06$, 95% CrI [0.01, 0.10], $P(b > 0) = 0.99$, $ER_{b>0} = 196.53$, $BF_{10} = 0.58$; GD: $b = 0.06$, 95% CrI [0.01, 0.11], $P(b > 0) = 0.99$, $ER_{b>0} = 169.21$, $BF_{10} = 0.62$; TVT: $b = 0.07$, 95% CrI [0.01, 0.13], $P(b > 0) = 0.99$, $ER_{b>0} = 107.11$, $BF_{10} = 0.54$). Fixation times were again longer with the Webcam than with the Eyelink (FFD: $b = 0.36$, 95% CrI [0.30, 0.42], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; SFD: $b = 0.36$, 95% CrI [0.30, 0.43], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; GD: $b = 0.32$, 95% CrI [0.26, 0.37], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; TVT: $b = 0.31$, 95% CrI [0.25, 0.38], $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$). Again, we did not see a credible Frequency $\times$ Tracker interaction (FFD: $b = 0.03$, 95% CrI [-0.02, 0.08], $P(b > 0) = 0.90$, $ER_{b>0} = 8.80$, $BF_{10} = 0.06$; SFD: $b = 0.03$, 95% CrI [-0.02, 0.08], $P(b > 0) = 0.85$, $ER_{b>0} = 5.73$, $BF_{10} = 0.05$; GD: $b = 0.01$, 95% CrI [-0.04, 0.07], $P(b > 0) = 0.69$, $ER_{b>0} = 2.20$, $BF_{10} = 0.03$; TVT: $b = 0.03$, 95% CrI [-0.03, 0.09], $P(b > 0) = 0.86$, $ER_{b>0} = 6.20$, $BF_{10} = 0.05$).

Again as in Experiment 1, we summarized the low–high frequency contrast separately within each device using estimated marginal means. Interestingly, in Experiment 3, the Webcam data actually contained stronger evidence in favor of the frequency effect than the Eyelink data, with the 95% CI for the frequency effect excluding 0 for both devices in FFD (Webcam: $M = 0.08$ 95% CI = [0.03, 0.13]; Eyelink: $M = 0.04$ 95% CI = [0.00, 0.09]) and GD (Webcam: $M = 0.07$ 95% CI = [0.01, 0.12]; Eyelink: $M = 0.05$ 95% CI = [0.00, 0.11]), although the exclusion was very narrow for the Eyelink data), but only for the Webcam data in SFD (Webcam: $M = 0.07$ 95% CI = [0.02, 0.12]; Eyelink: $M = 0.04$ 95% CI = [-0.01, 0.09]) and TVT (Webcam: $M = 0.09$ 95% CI = [0.02, 0.15]; Eyelink: $M = 0.05$ 95% CI = [-0.01, 0.12]). These somewhat unexpected results show that the Webcam data, although noisier, do not necessarily always underestimate the size of an effect. In any case, our results highlight that a large number of observations are needed to detect even strong effects such as the word frequency effect reliably at a sampling rate of 30 Hz

(as suggested by Angele et al., 2025).

Corpus-style analysis. For Experiment 3, we also fit models predicting fixation times on all the words in every sentence (except for sentence-initial and sentence-final words), with Zipf frequency as a continuous predictor and tracker as a discrete factor with two levels, Eyelink and Webcam, as was done for the Experiment 1 data. Table 9 summarizes the Zipf frequency effect, the effect of the tracker used, and their interaction over all eligible words. We again observed a frequency effect, with higher frequency words being associated with shorter fixations, but this effect was much stronger in Experiment 3 (FFD: $b = -0.03$, 95% CrI $[-0.04, -0.02]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} > 1000$; SFD: $b = -0.04$, 95% CrI $[-0.05, -0.02]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} > 1000$; GD: $b = -0.06$, 95% CrI $[-0.08, -0.05]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} > 1000$; TVT: $b = -0.09$, 95% CrI $[-0.10, -0.07]$, $P(b < 0) = 1.00$, $ER_{b<0} > 1000$, $BF_{10} > 1000$). Just as we had observed in all the previous analyses, the Webcam data resulted in longer detected fixations overall (FFD: $b = 0.45$, 95% CrI $[0.39, 0.50]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; SFD: $b = 0.43$, 95% CrI $[0.38, 0.49]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; GD: $b = 0.39$, 95% CrI $[0.35, 0.44]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$; TVT: $b = 0.36$, 95% CrI $[0.32, 0.41]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$). There was no evidence for an interaction between Zipf frequency and tracker in FFD ($b = 0.0096$, 95% CrI $[-0.0026, 0.02]$, $P(b > 0) = 0.94$, $ER_{b>0} = 14.46$, $BF_{10} = 0.02$), but there was a credible interaction in SFD ($b = 0.01$, 95% CrI $[0.0015, 0.03]$, $P(b > 0) = 0.99$, $ER_{b>0} = 69.48$, $BF_{10} = 0.07$), GD ($b = 0.03$, 95% CrI $[0.02, 0.04]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$), and TVT ($b = 0.03$, 95% CrI $[0.01, 0.04]$, $P(b > 0) = 1.00$, $ER_{b>0} > 1000$, $BF_{10} > 1000$). Importantly, the direction of this interaction was opposite to those observed in Experiment 1: Just as in the target word analysis, the frequency effect was stronger in the Webcam data compared to the Eyelink data. Finally, we again report emtrends estimates and 95% CIs for Eyelink and Webcam data separately. Unlike in Experiment 1, the frequency effect was credible for both the Eyelink and the Webcam data in all measures (FFD: Eyelink: $M = -0.03$ 95% CI = $[-0.05, -0.02]$;

Webcam: $M = -0.02$ 95% $CI = [-0.04, -0.01]$; SFD: Eyelink: $M = -0.04$ 95% $CI = [-0.06, -0.03]$; Webcam: $M = -0.03$ 95% $CI = [-0.05, -0.01]$; GD: Eyelink: $M = -0.08$ 95% $CI = [-0.09, -0.06]$; Webcam: $M = -0.05$ 95% $CI = [-0.06, -0.03]$; TVT Eyelink: $M = -0.10$ 95% $CI = [-0.12, -0.08]$; Webcam: $M = -0.07$ 95% $CI = [-0.09, -0.05]$). This may be due to the higher number of observations in Experiment 3.

Discussion

Limitations and Future Directions

Conclusion

References

- Arel-Bundock, V. (2022). modelsummary: Data and model summaries in R. *Journal of Statistical Software*, 103(1), 1–23. <https://doi.org/10.18637/jss.v103.i01>
- Aust, F., & Barth, M. (2025). papaja: Prepare reproducible APA journal articles with R Markdown. <https://doi.org/10.32614/CRAN.package.papaja>
- Barr, D. J., Levy, R., Scheepers, C., & Tily, H. J. (2013). Random effects structure for confirmatory hypothesis testing: Keep it maximal. *Journal of Memory and Language*, 68(3), 255–278. <https://doi.org/10.1016/j.jml.2012.11.001>
- Barth, M. (2025). tinylabels: Lightweight variable labels. <https://doi.org/10.32614/CRAN.package.tinylabels>
- Bürkner, P.-C. (2017). brms: An R package for Bayesian multilevel models using Stan. *Journal of Statistical Software*, 80(1), 1–28. <https://doi.org/10.18637/jss.v080.i01>
- Bürkner, P.-C. (2018). Advanced Bayesian multilevel modeling with the R package brms. *The R Journal*, 10(1), 395–411. <https://doi.org/10.32614/RJ-2018-017>
- Bürkner, P.-C. (2021). Bayesian item response modeling in R with brms and Stan. *Journal of Statistical Software*, 100(5), 1–54. <https://doi.org/10.18637/jss.v100.i05>
- Ching, T. (2025). qs2: Efficient serialization of r objects. <https://github.com/qsbase/qs2>
- Cohen, J., Cohen, P., West, S. G., & Aiken, L. S. (2003). *Applied multiple regression/correlation analysis for the behavioral sciences* (3rd ed.). Lawrence Erlbaum Associates.

- Grolemund, G., & Wickham, H. (2011). Dates and times made easy with lubridate. *Journal of Statistical Software*, 40(3), 1–25. <https://www.jstatsoft.org/v40/i03/>
- Iannone, R., Cheng, J., Schloerke, B., Hughes, E., Lauer, A., Seo, J., Brevoort, K., & Roy, O. (2025). *Gt: Easily create presentation-ready display tables*. <https://gt.rstudio.com>
- Jeffreys, H. (1961). *The Theory of Probability* (3rd ed.). Oxford University Press.
- Kay, M. (2024). *tidybayes: Tidy data and geoms for Bayesian models*. <https://doi.org/10.5281/zenodo.1308151>
- Lenth, R. V., & Piaskowski, J. (2025). *Emmeans: Estimated marginal means, aka least-squares means*. <https://rvlenth.github.io/emmeans/>
- Lüdtke, D. (2025). *sjPlot: Data visualization for statistics in social science*. <https://CRAN.R-project.org/package=sjPlot>
- Müller, K. (2025). *Here: A simpler way to find your files*. <https://here.r-lib.org/>
- Müller, K., & Wickham, H. (2025). *Tibble: Simple data frames*. <https://tibble.tidyverse.org/>
- R Core Team. (2025). *R: A language and environment for statistical computing*. R Foundation for Statistical Computing. <https://www.R-project.org/>
- Wickham, H. (2016). *ggplot2: Elegant graphics for data analysis*. Springer-Verlag New York. <https://ggplot2.tidyverse.org>
- Wickham, H. (2023). *Conflicted: An alternative conflict resolution strategy*. <https://conflicted.r-lib.org/>
- Wickham, H. (2025a). *Forcats: Tools for working with categorical variables (factors)*. <https://forcats.tidyverse.org/>
- Wickham, H. (2025b). *Stringr: Simple, consistent wrappers for common string operations*. <https://stringr.tidyverse.org>
- Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L. D., François, R., Grolemund, G., Hayes, A., Henry, L., Hester, J., Kuhn, M., Pedersen, T. L., Miller, E., Bache, S. M., Müller, K., Ooms, J., Robinson, D., Seidel, D. P., Spinu, V., ... Yutani, H. (2019). Welcome to the tidyverse. *Journal of Open Source Software*, 4(43), 1686. <https://doi.org/10.21105/joss.01686>

Wickham, H., François, R., Henry, L., Müller, K., & Vaughan, D. (2023). *Dplyr: A grammar of data manipulation*. <https://dplyr.tidyverse.org>

Wickham, H., & Henry, L. (2025). *Purrr: Functional programming tools*.
<https://purrr.tidyverse.org/>

Wickham, H., Hester, J., & Bryan, J. (2024). *Readr: Read rectangular text data*.
<https://readr.tidyverse.org>

Wickham, H., Vaughan, D., & Girlich, M. (2024). *Tidyr: Tidy messy data*.
<https://tidyr.tidyverse.org>

Xie, Y. (2015). *Dynamic documents with R and knitr* (2nd ed.). Chapman; Hall/CRC.
<https://yihui.org/knitr/>

Table 1

Mean first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on target words in Experiment 1 by eye-tracker and word frequency condition.

Tracker	Frequency	FFD		SFD		GD		TVT	
		Mean	SD	Mean	SD	Mean	SD	Mean	SD
Webcam	low	281	173	287	174	352	239	559	390
Webcam	high	265	159	272	167	333	223	522	399
Eyelink	low	190	133	197	146	236	163	342	253
Eyelink	high	176	124	183	135	207	142	299	230

Note: *FFD* = first fixation duration; *SFD* = single fixation duration; *GD* = gaze duration; *TVT* = total viewing time; SD = standard deviation. All means and standard deviations are reported in milliseconds (ms).

Table 2

Coefficient estimates and 95% credible intervals (in square brackets) from Bayesian linear mixed models fitted to first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on target words in Experiment 1.

	FFD	SFD	GD	TVT
Intercept	5.299 [5.202, 5.398]	5.312 [5.207, 5.415]	5.472 [5.372, 5.572]	5.824 [5.714, 5.933]
Frequency	0.057 [0.018, 0.097]	0.056 [0.015, 0.099]	0.085 [0.040, 0.130]	0.112 [0.057, 0.165]
Tracker	0.413 [0.334, 0.492]	0.407 [0.320, 0.491]	0.434 [0.346, 0.525]	0.555 [0.447, 0.667]
Frequency × Tracker	-0.037 [-0.108, 0.032]	-0.031 [-0.107, 0.049]	-0.081 [-0.171, 0.007]	-0.063 [-0.159, 0.031]

Table 3

Coefficient estimates and 95% credible intervals (in square brackets) from Bayesian linear mixed models fitted to first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on all words (except for the first and last in each sentence) in Experiment 1.

	FFD	SFD	GD	TVT
Intercept	5.215 [5.146, 5.289]	5.221 [5.145, 5.295]	5.365 [5.280, 5.445]	5.702 [5.605, 5.800]
Zipf frequency	-0.037 [-0.062, -0.012]	-0.046 [-0.073, -0.018]	-0.068 [-0.098, -0.039]	-0.058 [-0.098, -0.018]
Tracker	0.361 [0.285, 0.438]	0.364 [0.288, 0.441]	0.420 [0.314, 0.526]	0.389 [0.305, 0.473]
Frequency × Tracker	0.017 [-0.008, 0.043]	0.012 [-0.016, 0.040]	0.008 [-0.021, 0.037]	0.029 [-0.001, 0.059]

Table 4

Mean first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on target words in Experiment 1 by eye-tracker and word frequency condition.

Frequency	FFD		SFD		GD		TVT	
	Mean	SD	Mean	SD	Mean	SD	Mean	SD
low	370	220	376	222	425	276	517	376
high	357	228	352	225	399	281	492	391

Note: *FFD* = first fixation duration; *SFD* = single fixation duration; *GD* = gaze duration; *TVT* = total viewing time; SD = standard deviation. All means and standard deviations are reported in milliseconds (ms).

Table 5

Coefficient estimates and 95% credible intervals (in square brackets) from Bayesian linear mixed models fitted to first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on target words in Experiment 2.

	FFD	SFD	GD	TVT
Intercept	5.721 [5.647, 5.794]	5.722 [5.648, 5.796]	5.819 [5.745, 5.893]	5.964 [5.887, 6.042]
Frequency	0.058 [-0.002, 0.118]	0.086 [0.019, 0.151]	0.091 [0.024, 0.156]	0.083 [0.020, 0.148]

Table 6

Coefficient estimates and 95% credible intervals (in square brackets) from Bayesian linear mixed models fitted to first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on all words (except for the first and last in each sentence) in Experiment 2.

	FFD	SFD	GD	TVT
Intercept	5.642 [5.580, 5.707]	5.640 [5.578, 5.704]	5.716 [5.651, 5.779]	5.813 [5.756, 5.870]
Zipf frequency	-0.030 [-0.042, -0.018]	-0.033 [-0.046, -0.021]	-0.053 [-0.066, -0.040]	-0.075 [-0.088, -0.062]

Table 7

Mean first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on target words in Experiment 3 by eye-tracker and word frequency condition.

Tracker	Frequency	FFD		SFD		GD		TVT	
		Mean	SD	Mean	SD	Mean	SD	Mean	SD
Webcam	low	236	119	239	120	249	125	293	173
Webcam	high	219	104	222	105	236	119	277	192
Eyelink	low	160	67	163	69	183	87	210	114
Eyelink	high	153	59	155	59	175	84	203	122

Note: *FFD* = first fixation duration; *SFD* = single fixation duration; *GD* = gaze duration; *TVT* = total viewing time; SD = standard deviation. All means and standard deviations are reported in milliseconds (ms).

Table 8

Coefficient estimates and 95% credible intervals (in square brackets) from Bayesian linear mixed models fitted to first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on target words in Experiment 3.

	FFD	SFD	GD	TVT
Intercept	5.164 [5.104, 5.222]	5.186 [5.118, 5.257]	5.245 [5.168, 5.325]	5.355 [5.259, 5.450]
Frequency	0.061 [0.022, 0.100]	0.057 [0.014, 0.100]	0.060 [0.014, 0.107]	0.070 [0.013, 0.126]
Tracker	0.359 [0.298, 0.421]	0.361 [0.299, 0.428]	0.317 [0.264, 0.372]	0.313 [0.250, 0.378]
Frequency × Tracker	0.033 [-0.018, 0.084]	0.028 [-0.024, 0.080]	0.013 [-0.039, 0.065]	0.032 [-0.026, 0.092]

Table 9

Coefficient estimates and 95% credible intervals (in square brackets) from Bayesian linear mixed models fitted to first fixation duration (FFD), single fixation duration (SFD), gaze duration (GD), and total viewing time (TVT) on all words (except for the first and last in each sentence) in Experiment 3.

	FFD	SFD	GD	TVT
Intercept	5.166 [5.111, 5.220]	5.181 [5.125, 5.239]	5.243 [5.174, 5.312]	5.344 [5.266, 5.421]
Zipf frequency	-0.029 [-0.040, -0.018]	-0.037 [-0.051, -0.023]	-0.061 [-0.077, -0.045]	-0.085 [-0.103, -0.068]
Tracker	0.445 [0.389, 0.500]	0.434 [0.383, 0.486]	0.394 [0.348, 0.441]	0.364 [0.317, 0.409]
Frequency × Tracker	0.010 [-0.003, 0.022]	0.014 [0.001, 0.026]	0.032 [0.021, 0.044]	0.026 [0.014, 0.038]

Appendix A

This Section Is an Appendix

Appendix B
Another Appendix