The byte values for each instruction in the binary format are listed at https://webassembly.github.io/spec/core/binary/instructions.html.

Values

WebAssembly has the following types of values:

Туре	Constructor	Bit width	Notes
Integer	i32	32-bit	Also used to store booleans and memory addresses.
	i64	64-bit	
Float ¹	f32	32-bit	
	f64	64-bit	
Vector	v128	128-bit	Can store floats (4 32-bit, or 2 64-bit) or integers (2 64-bit, 4 32-bit, 8 16-bit, or 16 8-bit).
References	funcref	Opaque	Pointers to functions, of any type
	externref		Pointers to other types of objects that can be passed into WebAssembly

Integers are interpreted as signed or unsigned numbers, depending on the operations applied to them.

Integer encoding

Integers n are encoded in the binary format using a variable-length integer encoding.

But the spec also says there are (1) unsigned, (2) signed, and (3) uninterpreted integers? (docs>structure>values)

Numeric Instructions

ixx and fxx represent instructions that exist for both 32-bit and 64-bit values. Instructions ending in _u are unsigned operations that have an equivalent signed operation ending in _s.

For binary instructions on the stack, the first operand is always the one that was pushed to the stack first, and th second operand is the one pushed to the stack last. For example,

```
i64.const 10 # first operand
i64.const 2 # second operand
i64.sub
```

will do the operation 10 - 2.

Const	$\begin{array}{c} {\rm ixx.const} \ n \\ {\rm fxx.const} \ z \end{array}$	Creates a constant value of specified type.
Comparison	ixx.eqz	Equal to zero (no floating-point type equivalent)
	ixx.eq	Equality
	ixx.ne	Not equal
	ixx.lt_u	Less than
	ixx.gt_u	Greater than
	ixx.le_u	Less than or equal
	ixx.ge_u	Greater than or equal

Equivalent float comparison operators exist, for f32 and f64 respectively, with the difference of not having signed/unsigned variants. For example, the less than operator f64.lt.

¹Specified by IEEE 754-2019 (https://ieeexplore.ieee.org/document/8766229)

Unary operations	ixx.clz	Count leading zeros
	ixx.ctz	Count trailing zeros
	ixx.popcnt	Count the number of bits set to 1 (population
		count)
Arithmetic operations	ixx.add	Addition
	ixx.sub	Subtraction
	ixx.mul	Multiplication
	ixx.div_u	Division
	ixx.rem_u	Remainder
Bitwise operations	ixx.and	Bitwise AND
	ixx.or	Bitwise OR
	ixx.xor	Bitwise XOR
	ixx.shl	Bitwise left-shift
	ixx.shr_u	Bitwise right-shift. This operator is signed/un-
	_	signed because of sign extension.
	ixx.rotl	Bitwise left-rotate
	ixx.rotr	Bitwise right-rotate
Floating-point specific	fxx.min	Minimum of two numbers
	fxx.max	Maximum of two numbers
	fxx.copysign	Copy the sign bit from the second operand to the
	., 0	first operand
	fxx.abs	Absolute value
	fxx.neg	Negate
	fxx.sqrt	Square root
	fxx.ceil	Ceiling function
	fxx.floor	Floor function
	fxx.trunc	Truncate (discard everything after the decimal
		point). For negative numbers, floor will round
		down whereas trunc will round up.
	fxx.nearest	Round to the nearest integer
Conversion	i32.wrap_i64	Reduce an i64 to an i32, taking just the lower 32
	. —	bits (i.e. taking it modulo 2^{32})
	i64.extend_i32_u	Sign-extend from an i32 to an i64
	ixx.trunc_fxx_u	Truncate a float to an integer. Available for
		every combination of 32/64-bit and signed/un-
		signed.
	f32.demote_f64	Convert a f64 to a f32. Unlike the integer
	- · · · · · · · <u>-</u> ·	wrap instruction, this will lose precision but not
		change the value of the number to an entirely
		different number.
	f64.promote_f32	Convert a f32 to a f64
	fxx.convert_ixx_u	Convert an integer to a floating-point. Avail-
	· · · -	able for every combination of 32/64-bit and
		signed/unsigned.
	ixx.reinterpret_fxx	Reinterpret the bits of a float as an integer.
	fxx.reinterpret_ixx	Reinterpret the bits of an integer as a float.
		T

Variable instructions

These instructions are for getting/setting local and global variables.

Local variables are declared in function definitions, and global variables are declared in module definitions.

$local.get\ x$	Get the value of the variable x and put it on the stack
local.set x	Set the value of the variable x to the value on top of the stack (and remove it
	from the stack)
local.tee x	The same as local.set, but also leaves the value on the stack
global.get \boldsymbol{x}	Same as local get for a global variable
$global.set\ x$	Same as local.set for a global variable

Control flow instructions

Here, '…' represents any sequence of instructions. Labels can also be omitted, in which case blocks/loops are implicitly labelled by their nesting depth.

labels vs implicitly referencing by depth?

block <i>\$label</i> end	Creates a block that can be branched out of using a br instruction. The label is used to identify which block to branch out
	of. This treats br like a break statement in C.
loop <i>\$label</i> end	Effectively the opposite of block. loop creates a 'block' that can be branched to the beginning of. It doesn't loop by itself, it needs a branched instruction inside the loop to go back to the
	start of the loop each iteration. This treats br like a continue
	statement in C.
if else end	
if eise end	Executes the first statement if the top value on the stack is
	true (positive), and the second statement if the top of the
	stack is false (0).
br <i>\$label</i>	Unconditionally branches. If <i>\$label</i> refers to a block, it jumps
	to the end of the block. If \$label refers to a loop, it jumps to
	the start of the loop.
br_if <i>\$label</i>	Conditional branch
return	Returns from a function. If the stack is empty, nothing is returned. If the stack contains at least as many values as the
	function's return type signature specifies, those values are re- turned from the top of the stack, and any other values below them on the stack are discarded.
II &C . 1	
call \$funcidx	Calls a function.
call_indirect \$tableidx \$typeidx	Calls a function from a table. <i>\$typeidx</i> must be funcref.
nop	Does nothing.
unreachable	Marks a point in code that should be unreachable. If this in-
	struction is executed, it unconditionally traps. (Similar to a
	failed assertion in C.)
select	Chooses between its first two operands, depending on if the
	third operand is zero (selects the second operand) or not
	(chooses the first operand).
drop	Pops the top value from the stack and immediately discards
· · · · ·	it.

Memory instructions

ixx.load fxx.load	Load an integer from memory, at the address given by the top of the stack. Load a float from memory.
ixx.load8_u ixx.load16_u	Integer loads can specify a smaller bit-width to load. Signed and unsigned instructions exist, to specify how to sign-extend the number.

i64.load32 <u>u</u>	
ixx.store	Store the second operand at the memory offset given by the first operand.
fxx.store	
ixx.store8	Integer stores can specify a smaller bit-width to store in that location.
ixx.store16	
i64.store32	
memory.grow	Grow the memory by the number of pages given by the operand.
memory.size	Get the number of pages the memory currently has.
memory.fill	Set all the bytes in the specified region to a given byte.
memory.copy	Copy data from one memory region to another (can be overlapping).
memory.init	Copy data from a passive data segment into memory.
data.drop	Prevent any further use of a passive data segment (allows the memory used by
	it to be freed).

Data segments

Initially, the program's memory is filled with zero bytes. Data segments exist to allow memory to be initialised from static bytes.

Data segments can either be passive or active. Passive data segments are loaded into memory explicitly using the memory init instruction. Active data segments are automatically copied into memory when the program loads. Active data segments specify the offset where they'll be loaded.

Tables

A table is an array of function pointers, that can be used to indirectly call functions. Tables live outside of WebAssembly's memory, so they can't be seen from the program itself. This keeps the memory addresses of functions hidden. To call a function referenced in a table, the call_indirect instruction is used.

Modules

A module is a compilation and loading unit for a WebAssembly program.