

TV Ratings Prediction with Time Weighting Based Regression

Master Thesis Defense

Student — Ting-Wei Ku (Martin)

Advisor — Prof. Shou-De Lin

Committee — Prof. Pu-Jen Cheng, Ph.D. Cheng-Te Li

National Taiwan University
Department of Computer Science & Information Engineering
Machine Discovery & Social Network Mining Lab

Feb 2, 2015

Agenda

- 1 Thesis Goal: Solve the Problem of TV Ratings Prediction
- 2 Solution: Time Weighting Based Regression (TWR)
- 3 Related Work
- 4 Experiments
- 5 Conclusion

Thesis Goal: Solve the Problem of TV Ratings Prediction

Agenda

- 1 Thesis Goal: Solve the Problem of TV Ratings Prediction
- 2 Solution: Time Weighting Based Regression (TWR)
- 3 Related Work
- 4 Experiments
- 5 Conclusion

What is TWR?

Why TWR?

How does TWR work?

Agenda

- 1 Thesis Goal: Solve the Problem of TV Ratings Prediction
- 2 Solution: Time Weighting Based Regression (TWR)
- 3 Related Work**
- 4 Experiments
- 5 Conclusion

TV Ratings Prediction

Agenda

- 1 Thesis Goal: Solve the Problem of TV Ratings Prediction
- 2 Solution: Time Weighting Based Regression (TWR)
- 3 Related Work
- 4 Experiments
- 5 Conclusion




Figure 1: Box plots of ratings

Agenda

- 1 Thesis Goal: Solve the Problem of TV Ratings Prediction
- 2 Solution: Time Weighting Based Regression (TWR)
- 3 Related Work
- 4 Experiments
- 5 Conclusion

Code example

```
if (weight_type == 'equal') {  
  # this is known as bagging  
  case_weights <- rep(1 / num_cases, num_cases)  
} else if (weight_type == 'linear') {  
  case_weights <- seq(1, num_cases)  
} else if (weight_type == 'exp') {  
  case_weights <- exp(1:num_cases)  
} else if (weight_type == 'exp3') {  
  alpha <- 3  
  case_weights <- (exp(1)^alpha)^(1:num_cases)  
} else {  
  # decide weight type automatically via validation error  
}
```