



СПЕЦИФИКАЦИЯ ЗА МАТЕРИАЛ LIST FOR TA1				Бр./No. 2			Общо/Total 4539 kg	
поз./fitting	сечение/section	дължина/length mm	Бр./No.	стъпаност/steel grade	тежест/weight kg			
P12	PL20x300	664	1	S235J2	31.27			
P15	PL20x290	290	1	S235J2	13.20			
P16	PL20x150	300	2	S235J2	14.13			
P62	PL12x308	600	1	S235J2	17.22			
P63	PL12x130	130	31	S235J2	49.35			
P69	PL12x130	425	1	S235J2	5.19			
P82	PL12x130	231	1	S235J2	2.46			
P83	PL12x280	280	5	S235J2	36.93			
P89	PL12x250	290	1	S235J2	6.83			
P94	PL12x280	430	1	S235J2	11.34			
P124	PL16x494.7	455	1	S235J2	21.29			
P125	PL16x254.7	594	2	S235J2	26.22			
P126	PL16x254.7	609	1	S235J2	13.07			
P127	PL16x254.7	407	1	S235J2	8.54			
P129	PL16x140	220	8	S235J2	30.72			
P132	PL16x290	425	1	S235J2	12.28			
P133	PL16x383.6	290	1	S235J2	7.65			
P154	PL25x190	300	1	S355J2	11.19			
TC1	CFSHS150X150X10.0	17201	1	S235J2H	709.79			
TC3	CFSHS150X150X10.0	17824	1	S235J2H	735.49			
TC4	CFRHS150X100X8.0	34.72	1	S235J2H	96.06			
TC5	CFRHS150X100X8.0	3093	1	S235J2H	85.55			
TC6	CFRHS120X80X6.0	1963	1	S235J2H	33.29			
TC7	CFRHS120X80X6.0	2956	1	S235J2H	50.12			
TC8	CFRHS120X80X6.0	3056	1	S235J2H	51.81			
TC9	CFRHS120X80X6.0	2796	1	S235J2H	47.41			
TC10	CFSHS80X80X4.0	1661	1	S235J2H	15.32			
TC11	CFSHS80X80X4.0	1736	1	S235J2H	16.91			
TC12	CFSHS80X80X4.0	1585	1	S235J2H	14.62			
TC13	CFSHS80X80X4.0	2912	1	S235J2H	26.85			
TC14	CFRHS100X60X5.0	2864	1	S235J2H	26.41			
TC15	CFRHS100X60X5.0	1812	1	S235J2H	20.42			
TC16	CFRHS100X60X5.0	1887	1	S235J2H	21.28			
Общо/Total:					2269.32			

Забележки:
1. Всички контактни зони между елементите
да се заварят с катет 5 mm и да се означат
2. Детайли за заваряване от "1" до "5" - както е
показано в Group GN.