



1. HOUSING MATERIAL: GLASS FILLED NYLON 46, BLACK
2. SHIELD MATERIAL: 0.2mm THICK COPPER ALLOY
3. CONTACT MATERIAL: 0.35mm THICK COPPER ALLOY
4. MATING AREA PLATING: min. 50µ" GOLD over min. 30µ" NICKEL
5. SOLDER TAILS PLATING: min. 90µ" TIN/LEAD over min. 30µ" NICKEL
6. LED: GREEN AND YELLOW
7. INTERNAL CIRCUIT PER PORT SEE 39K1A041

## P.C.B. HOLE DRILLINGS

|   |   |
|---|---|
| APPROVAL # FREIGABE # DEBLOCAGE # AUTOR/ZACION # APPROVAL | APPROVAL # FREIGABE # DEBLOCAGE # AUTOR/ZACION # APPROVAL |
| CUSTOMER APPROVAL DATE:                                   |   |
| NAME:   | TITLE:  |
| COMPANY NAME:   |   |
| APPROVAL # FREIGABE # DEBLOCAGE # AUTOR/ZACION # APPROVAL | APPROVAL # FREIGABE # DEBLOCAGE # AUTOR/ZACION # APPROVAL |

THIS DRAWING MAY NOT BE COPIED OR  
REPRODUCED IN ANY WAY, AND MAY NOT  
BE PASSED ON TO A THIRD PARTY WITHOUT  
WRITTEN PERMISSION.  
OWNERSHIP AND COPYRIGHT OF CONEC GmbH  
NOT ALTER CAD DRAWING BY HAND

|      |             |      |      |  |        |   |  |
|------|-------------|------|------|--|--------|---|--|
|      |             |      |      | tolerance  |        | <br>dim. in mm |  |
|      |             |      |      | 2002   | date   | name  |  |
|      |             |      |      | drawn  | 27.11. | Parei   |  |
|      |             |      |      | appd.  | 27.11. | Kühle   |  |
|      |             |      |      | norm   |        |   |  |
|      |             |      |      | d-old  |        |   |  |
|      |             |      |      |  |        |   |  |
|      |             |      |      |  |        |   |  |
|      |             |      |      |  |        |   |  |
| rev. | description | date | name |  |        |   |  |



|  |  |                 |         |
|--|--|-----------------|---------|
| scale:   |  | 2:1             |         |
| material:  |  | SEE NOTES       |         |
| title:<br>RJ 45 MAGNETIC MODULAR JACK<br>1. PORT SMT-TERMINATION<br>fully screened, with LED |  |                 |         |
| dwg no:  |  | AutoCAD 2000    | DIN-A   |
| 39K1A049   |  | 3               | sh: 1/1 |
| part no:   |  | RJ45SJS11AC010X |         |