OPEN AGENT HACKATHON 2026 · TRACK 02 · THE AGENT THAT CAN EXPLAIN WHY

x402 Adoption Investigator

A multi-agent system that answers "how real is x402 adoption?" and proves every number it says: each claim links to a URL with the hash of the bytes fetched, a Base transaction, or a line of its own log.

x402 = pay-per-call over HTTP 402 Payment Required, settled in USDC on Base.

Team Automata · Martin Pisacreta (solo, Argentina) · Zetaris · Meterless World Model, H-MEM and Nightshift · NVIDIA Nemotron · built with Claude Code and Cursor Agent

THE USER AND THE PROBLEM

One store, five sources, five answers

User: the operator of an autonomous agent that sells or buys over x402 and must decide where the real demand is. Asked how many paid endpoints one store has, three sources say 17, two say 19 and 36, and none of them says why.

SOURCE	WHAT IT MEASURES	ENDPOINTS FOR TIENDA.TEXTOKIT.STORE
CDP Bazaar search	listed resources, capped at 20 results	**17**
Store openapi.json	declared paid operations	**17**
Agent402	paid tools (of 34 tools)	**17**
vet402	resolved endpoints	**19**
x402-trust	keyword search matches	**36**

Activity disagrees too: Bazaar 30-day counters sum to 60 calls, the seller's receipts list 77 settled sales, and 56 of them were paid by the seller itself.

WHY THIS NEEDS AGENTS

A script would pick one number. This system explains all of them.

Live, conflicting sources

Bazaar, the seller's receipts, Base RPC, x402-trust, Agent402 and vet402 each measure a different thing on a different window.

On-chain verification

Settlements are checked on Base by decoding the USDC Transfer log, never trusting tx.from, which is the facilitator.

Disagreement as output

When sources differ, the answer carries a Conflict object with each value, its measurement basis and why they differ.

Failure is normal

Sources go down mid-run. They become explicit "unavailable" entries with a logged recovery, never silent zeros.

WHAT GOES IN, WHAT COMES OUT

A question in, a proof-carrying answer out

Input: one JSON question

```
{"run_id": "ex01-seller-audit",
 "input": {"question": "How real is the adoption of
   tienda.textokit.store? Who pays, how much,
   do they come back, and why do registries
   disagree about it?"}}
```

Output: one JSON envelope and a Markdown report

- **verdict** chosen by rules, never by a model
- **claims[]** each with evidence: URL + sha256, Base tx, or log line
- **conflicts[]** with per-source values and the explanation
- **rejected_claims[]** with the critique trail
- **unavailable[]** instead of zeros

ARCHITECTURE

Seven roles, bounded loops, every handoff logged

Planner
picks the playbook, sources and queries

Collector
fetches every source and hashes the bytes

Keeper
folds evidence into the World Model

Verifier
decodes settlements on Base

Analyst
computes each metric in SQL and in Python

Writer
drafts an answer that cites claims

Critic
rules C1 to C7: rejects or sends back

Computed twice

Every metric has a committed SQL query and a pure Python reducer over the same exports. A number survives only if both exist and agree (rule C2); a mismatch stays as an open Conflict.

Bounded and logged

Deadline, fetch, SQL, model-call and critic-round budgets. Every handoff, fetch, sql, generate, claim, conflict, critique, retry and recovery line goes to logs/<run_id>/run.jsonl.

> Planner, Writer and the Critic's second opinion send their prompts to Meterless Nightshift, answered by NVIDIA Nemotron (live runs of 24 Oct; sample mode replays the recorded answers). The model writes the plan's hypotheses, the drafts and extra critique issues; it never accepts a claim.

A REAL RUN, CONDENSED

What a judge sees in run.jsonl

```
guard     network disabled in sample mode (socket.connect patched)
generate  planner    nvidia/nemotron-3.5-lightning-30b-a3b (recorded answer)
handoff   planner → collector   plan (10 items, sha256 abce43a7…)
recovery  collector  fixture_miss on a Base receipt: settlement marked unverifiable
handoff   keeper → analyst      query_ids (13)
conflict  k01 endpoint_count_for_host   five sources, five measurement bases
conflict  k02 calls_30d_for_host        Bazaar 30-day counter vs seller receipts
generate  writer     writer-r1 draft (recorded answer)
critique  round 1  C1…C7 accept 19 claims · B revise: '15' maps to no claim
recovery  critic     critic-r1 reply cut at 500 tokens: 10 complete items kept
critique  round 2  C1…C7 accept 19 · C7 revise: conflict k02 not named
recovery  writer     3 flagged sentences cut · conflicts, caveats, verdict added
result    ok · 19 accepted · 0 rejected · 2 conflicts · 2 critic rounds
```

Condensed from the 168 JSON lines of example 01: 13 handoffs, 17 fetches, 13 SQL queries, 5 Nemotron requests replayed from recorded answers, 56 critiques, 9 recoveries, 2 conflicts.

CRITIQUE AND RECOVERY

The Critic says no, and the answer says why

```
claim     c07 verified_tx = 0   sql 0 · reducer 0
critique  round 1  C1 reject c07: no decoded
          settlement of 0xa1d1…1978 (1 sampled:
          unverifiable, fixture_miss)
critique  round 1  B revise: sentence 5 cites c07
critique  round 1  LLM: 9 issues from Nemotron
handoff   critic → writer   issues (20)
recovery  writer  narrative_trimmed: c07 left
          out of the answer and named
critique  round 2  C1…C7 accept 6 · B accept
result    partial · 6 accepted · 1 rejected
output    verdict insufficient_evidence (by rules)
```

Why the zero is rejected

SQL and reducer agree on 0, but nothing was decoded for this wallet. Zero verified would be a number about missing data, so the Critic reports it as unknown.

Not staged

Same question as example 03, another external payer of the same store. Live, its settlement is verified at block 52,914,075.

Condensed from the 115 JSON lines of example 04: 13 handoffs, 44 critiques (12 from Nemotron's second opinion), 9 recoveries, 2 critic rounds.

METERLESS, STRUCTURAL

World Model as shared state, H-MEM as policy

World Model

- Entities: sellers, endpoints, wallets, facilitators, registries, with bitemporal relationships
- Provenance on every row; a claim without a URL, tx or log line is refused by the engine
- Idempotent ingest, proved in every output: the second pass appends 0 events
- 8 of 8 conformance checks

H-MEM

- Seven pitfall memories ("never sum unique payers across endpoints", "receipts are self-reported") add caveats that Critic rule C3 checks
- Injected into Planner and Writer prompts when a model is mounted, logged by hash; tested offline
- Ablation committed: one memory less drops a caveat and fifteen citations, not the verdict
- 13 of 13 upstream vectors

METERLESS NIGHTSHIFT, THE AI PROVIDER · NVIDIA NEMOTRON

Nightshift answers every request with Nemotron

REQUEST (LIVE, EXAMPLE 01, 24 OCT 17:27 UTC)	ROUTED_MODEL IN THE COMPUTE RECEIPT	KIND	RECEIPT	MS
planner	`nvidia/nemotron-3.5-lightning-30b-a3b`	cloud	`rcpt_req_ikp1bnwc`	**2,807**
writer-r1	`nvidia/nemotron-3.5-lightning-30b-a3b`	cloud	`rcpt_req_14krm3ix`	**5,194**
critic-r1	`nvidia/nemotron-3.5-lightning-30b-a3b`	cloud	`rcpt_req_7wahdjag`	**8,604**
writer-r2	`nvidia/nemotron-3.5-lightning-30b-a3b`	cloud	`rcpt_req_qlxvvms9`	**10,077**
critic-r2	`nvidia/nemotron-3.5-lightning-30b-a3b`	cloud	`rcpt_req_8d1qnkxs`	**2,315**

Hosted, primary

Nemotron 3.5 Lightning 30B A3B on NVIDIA's API, reached by Nightshift with the key set in its Providers tab; the app never sees it. 5 live runs, 27 requests, all kind cloud.

Local GPU

Nemotron Nano 9B v2 (Q4_K_M), every layer on the RTX 5080 Laptop GPU. 1 live run, 5 requests, kind local, privacy local-only (first receipt rcpt_req_2j2p2eb0).

Offline

Sample mode replays 25 recorded Nemotron 3.5 answers, keyed by the sha256 of each prompt: no keys, no network. Thinking is off per request (reasoning_effort none, /no_think).

Nemotron writes the plan's hypotheses, the drafts and extra critique issues; claims and verdicts stay rules. Its drafts drop caveat codes and some of its issues are wrong. Zetaris was stopped for these runs, so their SQL ran on SQLite.

ZETARIS, THE LIVE FEDERATION LAYER

Live on Lightning SQL, offline on SQLite, same rows

- Each live run registers its exports as Lightning REST tables (receipts, Bazaar, openapi, Agent402, vet402, x402-trust, settlements) and flattens them with SchemaStore views
- The live seller audit computed all 19 claims on Zetaris 2.4.3.1
- Offline, the same SQL runs on SQLite; a test proves equal rows against the 19 result sets Zetaris recorded

Logged per query

Executor, SQL sha256, rows, time and tables with source URLs in sql.jsonl; every REST call in zetaris.jsonl. --require-zetaris turns any fallback into an error.

Not yet on Zetaris

3 of the 22 queries (q20 to q22) were added after the live session and have run on SQLite only. The Nightshift runs of 24 Oct had Zetaris stopped: recovery zetaris_unreachable, same SQL on SQLite.

RESULTS ON REAL DATA

Four questions, four honest answers

Seller audit · self_settled_mostly

77 sales, 56 paid by the seller's own wallets; 21 external sales by 4 payers, 0.044 USDC in total.

Catalog · concentrated

28,462 Bazaar resources on 2,680 hosts; the top host holds 29.5% of 824,796 calls in 30 days.

Payer dossier · adoption_thin

One purchase of 0.001 USDC, its settlement decoded and verified on Base against the receipts.


Unverifiable payer · insufficient_evidence

One purchase of 0.001 USDC; "0 verified" rejected by the Critic, balance and nonce unavailable.

The honest finding for our own store: most of its sales were paid by its own wallets. The system says so, with the proof.

SEE IT

The report viewer



Any output.json

Run header with the mounts, accepted claims with their evidence links, rejected claims with the Critic's reason, and conflicts with each source's value and explanation.

Static HTML, no build step, no CDN. Shown: example 04 in sample mode, two crops of one page (header, rejected claims).

STACK AND HOW TO TRY IT

One command, offline, from a clean clone

```
git clone https://github.com/martinPisacreta/x402-adoption-investigator
cd x402-adoption-investigator
python run.py --sample --input examples/ex4.json
```

Python 3.11, standard library | **Zetaris Lightning 2.4.3.1** | **Meterless World Model + H-MEM**

Meterless Nightshift 1.2.3: primary AI provider | **NVIDIA Nemotron 3.5 Lightning, hosted** | **NVIDIA Nemotron Nano 9B v2, RTX 5080**

Base JSON-RPC | **Docker** | **308 tests** | **Claude Code: main coding agent** | **Cursor Agent: viewer, README pitch draft**

Live runs of 24 Oct sent 27 requests to Nemotron 3.5 Lightning and 5 to Nemotron Nano 9B v2 through Nightshift, one compute receipt each (the first: rcpt_req_ikp1bnwc). The command above replays recorded Nemotron answers, offline and without keys.

Pre-existing, declared: our own Automata agent and its x402 store tienda.textokit.store (data source only, none of its code here), the Meterless conformance vectors (copied with attribution), the Zetaris platform and the Python standard library.