

# 1. Description

## 1.1. Project

Project Name	sensor_board
Board Name	custom
Generated with:	STM32CubeMX 6.6.1
Date	03/12/2023


## 1.2. MCU

MCU Series	STM32F4
MCU Line	STM32F446
MCU name	STM32F446RETx
MCU Package	LQFP64
MCU Pin number	64

## 1.3. Core(s) information

Core(s)	Arm Cortex-M4

## 2. Pinout Configuration




# 3. Pins Configuration

Pin Number	Pin Name	Pin Type	Alternate	Label
LQFP64	(function after reset)		Function(s)	
1	VBAT	Power		
2	PC13 *	I/O	GPIO_Input	SHTDWN3_GPIO_IN
3	PC14-OSC32_IN *	I/O	GPIO_Input	SHTDWN4_GPIO_IN
4	PC15-OSC32_OUT *	I/O	GPIO_Output	ADC1283IPT_nCS_GPIO_O UT
5	PH0-OSC_IN	I/O	RCC_OSC_IN	
6	PH1-OSC_OUT	I/O	RCC_OSC_OUT	
7	NRST	Reset		
8	PC0	I/O	ADC1_IN10	ANAL11_ADC_IN10
9	PC1	I/O	SPI2_MOSI	ADC1283IPT_DIN_SPI2_M OSI
10	PC2	I/O	ADC3_IN12	REF_5V_ADC_IN12
11	PC3	I/O	ADC3_IN13	REF_24V_ADC_IN13
12	VSSA	Power		
13	VDDA	Power		
14	PA0-WKUP	I/O	ADC1_IN0	ANAL1_ADC_IN0
15	PA1	I/O	ADC1_IN1	ANAL2_ADC_IN1
16	PA2	I/O	ADC1_IN2	ANAL3_ADC_IN2
17	PA3	I/O	ADC1_IN3	ANAL4_ADC_IN3
18	VSS	Power		
19	VDD	Power		
20	PA4	I/O	ADC1_IN4	ANAL5_ADC_IN4
21	PA5	I/O	ADC1_IN5	ANAL6_ADC_IN5
22	PA6	I/O	ADC1_IN6	ANAL7_ADC_IN6
23	PA7	I/O	ADC1_IN7	ANAL8_ADC_IN7
24	PC4	I/O	ADC2_IN14	POT1_ADC_IN14
25	PC5	I/O	ADC2_IN15	POT2_ADC_IN15
26	PB0	I/O	ADC1_IN8	ANAL9_ADC_IN8
27	PB1	I/O	ADC1_IN9	ANAL10_ADC_IN9
28	PB2	I/O	SPI3_MOSI	M95256_D_SPI3_MOSI
29	PB10	I/O	SPI2_SCK	ADC1283IPT_SCLK_SPI2_ SCK
30	VCAP_1	Power		
31	VSS	Power		
32	VDD	Power		
33	PB12 *	I/O	GPIO_Output	M95256_nW_GPIO_OUT

Pin Number LQFP64	Pin Name (function after	Pin Type	Alternate Function(s)	Label
34	reset) PB13 *	I/O	GPIO_Output	MOESEE NO CRIO OUT
35	PB14	1/0	SPI2_MISO	M95256_nS_GPIO_OUT  ADC1283IPT_DOUT_SPI2_  MISO
36	PB15	I/O	TIM12_CH2	NMOS_G_TIM12_PWM
37	PC6 *	I/O	GPIO_Output	LED_STAT3_GPIO_OUT
38	PC7 *	I/O	GPIO_Output	LED_STAT2_GPIO_OUT
39	PC8 *	I/O	GPIO_Output	LED_STAT1_GPIO_OUT
40	PC9 *	I/O	GPIO_Output	LED_WARN_GPIO_OUT
41	PA8 *	I/O	GPIO_Output	LED_ERR_GPIO_OUT
42	PA9	I/O	USART1_TX	T_VCP_TX_USART1_TX
43	PA10	I/O	USART1_RX	T_VCP_RX_USART1_RX
44	PA11	I/O	CAN1_RX	SN65HVD23x_R_CAN1_RX
45	PA12	I/O	CAN1_TX	SN65HVD23x_D_CAN1_TX
46	PA13	I/O	SYS_JTMS-SWDIO	
47	VSS	Power		
48	VDD	Power		
49	PA14	I/O	SYS_JTCK-SWCLK	
50	PA15	I/O	SYS_JTDI	
51	PC10	I/O	SPI3_SCK	M95256_C_SPI3_SCK
52	PC11	I/O	SPI3_MISO	M95256_Q_SPI3_MISO
53	PC12	I/O	UART5_TX	ADS112U04_RX_UART5_T X
54	PD2	I/O	UART5_RX	ADS112U04_TX_UART5_R X
55	PB3	I/O	SYS_JTDO-SWO	
57	PB5	I/O	GPIO_EXTI5	ADS112U04_nDRDY_GPIO _IN
58	PB6 *	I/O	GPIO_Input	BSPD_ERR_GPIO_IN
59	PB7 *	I/O	GPIO_Output	BRK_LGHT_GPIO_OUT
60	BOOT0	Boot		
61	PB8 *	I/O	GPIO_Input	SHTDWN1_GPIO_IN
62	PB9 *	I/O	GPIO_Input	SHTDWN2_GPIO_IN
63	VSS	Power		
64	VDD	Power		

<sup>\*</sup> The pin is affected with an I/O function

## 4. Clock Tree Configuration



Page 5

# 5. Software Project

## 5.1. Project Settings

Name	Value
Project Name	sensor_board
Project Folder	/home/simone/Documents/10.SquadraCorse/Work/sensor_board
Toolchain / IDE	Makefile
Firmware Package Name and Version	STM32Cube FW_F4 V1.27.1
Application Structure	Advanced
Generate Under Root	No
Do not generate the main()	No
Minimum Heap Size	0x200
Minimum Stack Size	0x400

## 5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy all used libraries into the project folder
Generate peripheral initialization as a pair of '.c/.h' files	Yes
Backup previously generated files when re-generating	Yes
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No
Enable Full Assert	No

### 5.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_ADC1_Init	ADC1
4	MX_CAN1_Init	CAN1
5	MX_ADC2_Init	ADC2
6	MX_SPI2_Init	SPI2
7	MX_SPI3_Init	SPI3
8	MX_UART5_Init	UART5
9	MX_USART1_UART_Init	USART1
10	MX_ADC3_Init	ADC3
11	MX_TIM12_Init	TIM12

sensor_board Project
Configuration Repor

# 6. Power Consumption Calculator report

### 6.1. Microcontroller Selection

Series	STM32F4
Line	STM32F446
MCU	STM32F446RETx
Datasheet	DS10693_Rev6

### 6.2. Parameter Selection

Temperature	25
Vdd	3.3

## 6.3. Battery Selection

Battery	Li-SOCL2(A3400)
Capacity	3400.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	100.0 mA
Max Pulse Current	200.0 mA
Cells in series	1
Cells in parallel	1


## 6.4. Sequence

Step	Step1	Step2
Mode	RUN	STOP UDM (Under Drive)
Vdd	3.3	3.3
Voltage Source	Battery	Battery
Range	Scale1-High	No Scale
Fetch Type	RAM/FLASH/REGON/ART/P REFETCH	n/a
CPU Frequency	180 MHz	0 Hz
Clock Configuration	HSE PLL	Regulator LP Flash-PwrDwn
Clock Source Frequency	4 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	46 mA	55 μA
Duration	0.1 ms	0.9 ms
DMIPS	225.0	0.0
Ta Max	98.02	104.99
Category	In DS Table	In DS Table

## 6.5. Results

Sequence Time	1 ms	Average Current	4.65 mA
Battery Life	1 month	Average DMIPS	225.0 DMIPS

### 6.6. Chart



## 7. Peripherals and Middlewares Configuration

7.1. ADC1
mode: IN0
mode: IN1
mode: IN2
mode: IN3
mode: IN4
mode: IN5
mode: IN6
mode: IN7
mode: IN8

mode: IN9 mode: IN10

7.1.1. Parameter Settings:

#### ADCs\_Common\_Settings:

Mode Independent mode

ADC\_Settings:

Clock Prescaler PCLK2 divided by 2

Resolution 12 bits (15 ADC Clock cycles)

Data AlignmentRight alignmentScan Conversion ModeDisabledContinuous Conversion ModeDisabledDiscontinuous Conversion ModeDisabledDMA Continuous RequestsDisabled

End Of Conversion Selection EOC flag at the end of single channel conversion

ADC\_Regular\_ConversionMode:

Number Of Conversion 1

External Trigger Conversion Source Regular Conversion launched by software

External Trigger Conversion Edge None
Rank 1

Channel Channel 0
Sampling Time 3 Cycles

ADC\_Injected\_ConversionMode:

Number Of Conversions 0

WatchDog:

Enable Analog WatchDog Mode false

7.2. ADC2 mode: IN14

mode: IN15

7.2.1. Parameter Settings:

ADCs\_Common\_Settings:

Mode Independent mode

ADC\_Settings:

Clock Prescaler PCLK2 divided by 2

Resolution 12 bits (15 ADC Clock cycles)

Data AlignmentRight alignmentScan Conversion ModeDisabledContinuous Conversion ModeDisabledDiscontinuous Conversion ModeDisabledDMA Continuous RequestsDisabled

End Of Conversion Selection EOC flag at the end of single channel conversion

ADC\_Regular\_ConversionMode:

Number Of Conversion 1

External Trigger Conversion Source Regular Conversion launched by software

External Trigger Conversion Edge None
Rank 1

Channel Channel 14
Sampling Time 3 Cycles

ADC\_Injected\_ConversionMode:

Number Of Conversions 0

WatchDog:

Enable Analog WatchDog Mode false

7.3. ADC3 mode: IN12 mode: IN13

7.3.1. Parameter Settings:

ADC\_Settings:

Clock Prescaler PCLK2 divided by 2

Resolution 12 bits (15 ADC Clock cycles)

Data Alignment Right alignment

Scan Conversion Mode Disabled
Continuous Conversion Mode Disabled
Discontinuous Conversion Mode Disabled
DMA Continuous Requests Disabled

End Of Conversion Selection EOC flag at the end of single channel conversion

ADC\_Regular\_ConversionMode:

Number Of Conversion

External Trigger Conversion Source Regular Conversion launched by software

External Trigger Conversion Edge None
Rank 1

Channel 12 Sampling Time 3 Cycles

ADC\_Injected\_ConversionMode:

Number Of Conversions 0

WatchDog:

Enable Analog WatchDog Mode false

#### 7.4. CAN1

#### mode: Activated

#### 7.4.1. Parameter Settings:

#### **Bit Timings Parameters:**

Prescaler (for Time Quantum) 16

Time Quantum

1000.0 \*

Time Quanta in Bit Segment 1

1 Time

Time Quanta in Bit Segment 2

1 Time

Time for one Bit

3000 \*

Baud Rate

333333 \*

ReSynchronization Jump Width 1 Time

**Basic Parameters:** 

Time Triggered Communication Mode

Automatic Bus-Off Management

Disable

Automatic Wake-Up Mode

Disable

Automatic Retransmission

Disable

Receive Fifo Locked Mode

Disable

Transmit Fifo Priority

Disable

**Advanced Parameters:** 

Operating Mode Normal

#### 7.5. RCC

#### High Speed Clock (HSE): Crystal/Ceramic Resonator

#### 7.5.1. Parameter Settings:

#### **System Parameters:**

VDD voltage (V) 3.3
Instruction Cache Enabled
Prefetch Buffer Enabled
Data Cache Enabled

Flash Latency(WS) 0 WS (1 CPU cycle)

**RCC Parameters:** 

HSI Calibration Value 16

TIM Prescaler Selection Disabled

HSE Startup Timout Value (ms) 100

LSE Startup Timout Value (ms) 5000

**Power Parameters:** 

Power Regulator Voltage Scale Power Regulator Voltage Scale 3

Power Over Drive Disabled

#### 7.6. SPI2

#### **Mode: Full-Duplex Master**

#### 7.6.1. Parameter Settings:

#### **Basic Parameters:**

Frame Format Motorola

Data Size 8 Bits

First Bit MSB First

**Clock Parameters:** 

Prescaler (for Baud Rate) 2

Baud Rate 8.0 MBits/s \*

Clock Polarity (CPOL) Low
Clock Phase (CPHA) 1 Edge

**Advanced Parameters:** 

CRC Calculation Disabled
NSS Signal Type Software

#### 7.7. SPI3

## **Mode: Full-Duplex Master**

#### 7.7.1. Parameter Settings:

#### **Basic Parameters:**

Frame Format Motorola

Data Size 8 Bits

First Bit MSB First

**Clock Parameters:** 

Prescaler (for Baud Rate)

Baud Rate 8.0 MBits/s \*

Clock Polarity (CPOL) Low
Clock Phase (CPHA) 1 Edge

**Advanced Parameters:** 

CRC Calculation Disabled
NSS Signal Type Software

#### 7.8. SYS

Debug: JTAG (4 pins)

Timebase Source: SysTick

#### 7.9. TIM12

**Trigger Source: ITR0** 

**Channel2: PWM Generation CH2** 

#### 7.9.1. Parameter Settings:

#### **Counter Settings:**

Prescaler (PSC - 16 bits value) 0
Counter Mode Up
Counter Period (AutoReload Register - 16 bits value) 65535
Internal Clock Division (CKD) No Division auto-reload preload Disable

Slave Mode Controller Slave mode disable

#### **PWM Generation Channel 2:**

Mode PWM mode 1

Pulse (16 bits value) 0

Output compare preload Enable

Fast Mode Disable

CH Polarity High

#### 7.10. UART5

### **Mode: Asynchronous**

### 7.10.1. Parameter Settings:

#### **Basic Parameters:**

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

**Advanced Parameters:** 

Data Direction Receive and Transmit

Over Sampling 16 Samples

#### 7.11. USART1

#### **Mode: Asynchronous**

### 7.11.1. Parameter Settings:

#### **Basic Parameters:**

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

#### **Advanced Parameters:**

Data Direction Receive and Transmit

Over Sampling 16 Samples

#### \* User modified value

# 8. System Configuration

## 8.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull	Max	User Label
				down	Speed	
ADC1	PC0	ADC1_IN10	Analog mode	No pull-up and no pull-down	n/a	ANAL11_ADC_IN10
	PA0-WKUP	ADC1_IN0	Analog mode	No pull-up and no pull-down	n/a	ANAL1_ADC_IN0
	PA1	ADC1_IN1	Analog mode	No pull-up and no pull-down	n/a	ANAL2_ADC_IN1
	PA2	ADC1_IN2	Analog mode	No pull-up and no pull-down	n/a	ANAL3_ADC_IN2
	PA3	ADC1_IN3	Analog mode	No pull-up and no pull-down	n/a	ANAL4_ADC_IN3
	PA4	ADC1_IN4	Analog mode	No pull-up and no pull-down	n/a	ANAL5_ADC_IN4
	PA5	ADC1_IN5	Analog mode	No pull-up and no pull-down	n/a	ANAL6_ADC_IN5
	PA6	ADC1_IN6	Analog mode	No pull-up and no pull-down	n/a	ANAL7_ADC_IN6
	PA7	ADC1_IN7	Analog mode	No pull-up and no pull-down	n/a	ANAL8_ADC_IN7
	PB0	ADC1_IN8	Analog mode	No pull-up and no pull-down	n/a	ANAL9_ADC_IN8
	PB1	ADC1_IN9	Analog mode	No pull-up and no pull-down	n/a	ANAL10_ADC_IN9
ADC2	PC4	ADC2_IN14	Analog mode	No pull-up and no pull-down	n/a	POT1_ADC_IN14
	PC5	ADC2_IN15	Analog mode	No pull-up and no pull-down	n/a	POT2_ADC_IN15
ADC3	PC2	ADC3_IN12	Analog mode	No pull-up and no pull-down	n/a	REF_5V_ADC_IN12
	PC3	ADC3_IN13	Analog mode	No pull-up and no pull-down	n/a	REF_24V_ADC_IN13
CAN1	PA11	CAN1_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	SN65HVD23x_R_CAN1_R X
	PA12	CAN1_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	SN65HVD23x_D_CAN1_T X
RCC	PH0- OSC_IN	RCC_OSC_IN	n/a	n/a	n/a	
	PH1- OSC_OUT	RCC_OSC_OUT	n/a	n/a	n/a	
SPI2	PC1	SPI2_MOSI	Alternate Function Push Pull	No pull-up and no pull-down	Very High	ADC1283IPT_DIN_SPI2_ MOSI
	PB10	SPI2_SCK	Alternate Function Push Pull	No pull-up and no pull-down	Very High	ADC1283IPT_SCLK_SPI2 _SCK
	PB14	SPI2_MISO	Alternate Function Push Pull	No pull-up and no pull-down	Very High	ADC1283IPT_DOUT_SPI2 _MISO
SPI3	PB2	SPI3_MOSI	Alternate Function Push Pull	No pull-up and no pull-down	Very High	M95256_D_SPI3_MOSI
	PC10	SPI3_SCK	Alternate Function Push Pull	No pull-up and no pull-down	Very High	M95256_C_SPI3_SCK
	PC11	SPI3_MISO	Alternate Function Push Pull	No pull-up and no pull-down	Very High	M95256_Q_SPI3_MISO

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
SYS	PA13	SYS_JTMS- SWDIO	n/a	n/a	n/a	
	PA14	SYS_JTCK- SWCLK	n/a	n/a	n/a	
	PA15	SYS_JTDI	n/a	n/a	n/a	
	PB3	SYS_JTDO- SWO	n/a	n/a	n/a	
TIM12	PB15	TIM12_CH2	Alternate Function Push Pull	No pull-up and no pull-down	Low	NMOS_G_TIM12_PWM
UART5	PC12	UART5_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	ADS112U04_RX_UART5_ TX
	PD2	UART5_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	ADS112U04_TX_UART5_ RX
USART1	PA9	USART1_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	T_VCP_TX_USART1_TX
	PA10	USART1_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	T_VCP_RX_USART1_RX
GPIO	PC13	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	SHTDWN3_GPIO_IN
	PC14- OSC32_IN	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	SHTDWN4_GPIO_IN
	PC15- OSC32_OU T	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	ADC1283IPT_nCS_GPIO_ OUT
	PB12	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	M95256_nW_GPIO_OUT
	PB13	GPIO_Output	Outroot Book Bull	A1 11 1 11 11	Low	M95256_nS_GPIO_OUT
		Of 10_Output	Output Push Pull	No pull-up and no pull-down	Low	W93230_N3_ON NO_OON
	PC6	GPIO_Output	Output Push Pull	No pull-up and no pull-down  No pull-up and no pull-down	Low	LED_STAT3_GPIO_OUT
	PC6 PC7		·			
		GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LED_STAT3_GPIO_OUT
	PC7	GPIO_Output GPIO_Output	Output Push Pull Output Push Pull	No pull-up and no pull-down	Low	LED_STAT3_GPIO_OUT
	PC7 PC8	GPIO_Output GPIO_Output GPIO_Output	Output Push Pull Output Push Pull Output Push Pull	No pull-up and no pull-down  No pull-up and no pull-down  No pull-up and no pull-down	Low Low Low	LED_STAT3_GPIO_OUT LED_STAT1_GPIO_OUT
	PC7 PC8 PC9	GPIO_Output GPIO_Output GPIO_Output GPIO_Output	Output Push Pull Output Push Pull Output Push Pull Output Push Pull	No pull-up and no pull-down	Low Low Low	LED_STAT3_GPIO_OUT LED_STAT1_GPIO_OUT LED_WARN_GPIO_OUT
	PC7 PC8 PC9 PA8	GPIO_Output GPIO_Output GPIO_Output GPIO_Output GPIO_Output	Output Push Pull External Interrupt Mode with	No pull-up and no pull-down	Low Low Low Low	LED_STAT3_GPIO_OUT LED_STAT1_GPIO_OUT LED_WARN_GPIO_OUT LED_ERR_GPIO_OUT ADS112U04_nDRDY_GPI
	PC7 PC8 PC9 PA8 PB5	GPIO_Output GPIO_Output GPIO_Output GPIO_Output GPIO_Output GPIO_EXTI5	Output Push Pull External Interrupt Mode with Rising edge trigger detection	No pull-up and no pull-down	Low Low Low Low n/a	LED_STAT3_GPIO_OUT LED_STAT1_GPIO_OUT LED_WARN_GPIO_OUT LED_ERR_GPIO_OUT ADS112U04_nDRDY_GPI O_IN
	PC7 PC8 PC9 PA8 PB5	GPIO_Output GPIO_Output GPIO_Output GPIO_Output GPIO_Output GPIO_EXTI5	Output Push Pull External Interrupt Mode with Rising edge trigger detection Input mode	No pull-up and no pull-down	Low Low Low Low n/a	LED_STAT3_GPIO_OUT LED_STAT2_GPIO_OUT LED_STAT1_GPIO_OUT LED_WARN_GPIO_OUT LED_ERR_GPIO_OUT ADS112U04_nDRDY_GPI O_IN BSPD_ERR_GPIO_IN

## 8.2. DMA configuration

nothing configured in DMA service

## 8.3. NVIC configuration

## 8.3.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority	
Non maskable interrupt	true	0	0	
Hard fault interrupt	true	0	0	
Memory management fault	true	0	0	
Pre-fetch fault, memory access fault	true	0	0	
Undefined instruction or illegal state	true	0	0	
System service call via SWI instruction	true	0	0	
Debug monitor	true	0	0	
Pendable request for system service	true	0	0	
System tick timer	true	15	0	
PVD interrupt through EXTI line 16		unused		
Flash global interrupt		unused		
RCC global interrupt	unused			
ADC1, ADC2 and ADC3 interrupts	unused			
CAN1 TX interrupt	unused			
CAN1 RX0 interrupt	unused			
CAN1 RX1 interrupt	unused			
CAN1 SCE interrupt		unused		
EXTI line[9:5] interrupts	unused			
SPI2 global interrupt		unused		
USART1 global interrupt		unused		
TIM8 break interrupt and TIM12 global interrupt		unused		
SPI3 global interrupt		unused		
UART5 global interrupt		unused		
FPU global interrupt		unused		

## 8.3.2. NVIC Code generation

Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true

sensor_	_board	Project
Config	uration	Report

\* User modified value

# 9. System Views

- 9.1. Category view
- 9.1.1. Current



System Core	Analog	Timers	Connectivity	Multimedia	Computing
DMA	ADC1 🤣	TIM12 🤡	CAN1 📀		
GPIO <b>⊘</b>	ADC2 ❷		SPI2 ❷		
NVIC 📀	ADC3 ⊘		SPI3 ⊘		
RCC ⊘			UART5 ❷		
sys 🤡			USART1 🕢		

### 10. Docs & Resources

Type Link

BSDL files https://www.st.com/resource/en/bsdl\_model/stm32f446\_bsdl.zip lBIS models https://www.st.com/resource/en/ibis\_model/stm32f446\_ibis.zip

System View https://www.st.com/resource/en/svd/stm32f4\_svd.zip

Description

BSDL files https://www.st.com/resource/en/bsdl\_model/stm32f446\_bsdl.zip

IBIS models https://www.st.com/resource/en/ibis\_model/stm32f446\_ibis.zip

System View https://www.st.com/resource/en/svd/stm32f4\_svd.zip

Description

Presentations https://www.st.com/resource/en/product\_presentation/stm32-

stm8\_embedded\_software\_solutions.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32\_eval-

tools\_portfolio.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32\_stm8\_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product\_presentation/stm32-

stm8\_software\_development\_tools.pdf

Training Material https://www.st.com/resource/en/sales\_guide/sg\_sc2154.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstmcsuite.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32trust.pdf

Product https://www.st.com/resource/en/certification\_document/stm32\_authenticat

Certifications ion\_can.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1181-electrostatic-

discharge-sensitivity-measurement-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2606-stm32-

microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application\_note/an2639-soldering-recommendations-and-package-information-for-leadfree-ecopack-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an2834-how-to-get-the-best-adc-accuracy-in-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an2867-oscillator-design-guide-for-stm8afals-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an2945-stm8s-and-stm32-mcus-a-consistent-832bit-product-line-for-painless-migration-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3070-managing-the-driver-enable-signal-for-rs485-and-iolink-communications-with-the-stm32s-usart-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3154-can-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3364-migration-and-compatibility-guidelines-for-stm32-microcontroller-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3997-audio-playback-and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an3998-pdm-audio-software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4013-stm32-crossseries-timer-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4031-using-the-stm32f2-stm32f4-and-stm32f7-series-dma-controller-

- stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4229-how-to-implement-a-vocoder-solution-using-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4230-stm32-microcontroller-random-number-generation-validation-using-the-nist-statistical-test-suite-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4277-using-stm32-device-pwm-shutdown-features-for-motor-control-and-digital-power-conversion-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4286-spi-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4488-getting-started-with-stm32f4xxxx-mcu-hardware-development-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4640-peripherals-interconnections-on-stm32f4057xx-stm32f4157xx-stm32f42xxx-stm32f43xxx-stm32f446xx-and-stm32f469479xx-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4658-migration-of-applications-from-stm32f429439-lines-to-stm32f446-line-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4739-stm32cube-firmware-examples-for-stm32f4-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4759-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-

- stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4838-managing-memory-protection-unit-in-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4850-stm32-mcusspreadspectrum-clock-generation-principles-properties-andimplementation-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4879-usb-hardware-and-pcb-guidelines-using-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4908-stm32-usart-automatic-baud-rate-detection-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an4995-using-anelectromyogram-technique-to-detect-muscle-activitystmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5020-digital-camera-interface-dcmi-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5036-thermal-management-guidelines-for-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5073-receiving-spdif-audio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5156-introduction-to-stm32-microcontrollers-security-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5225-usb-typec-power-delivery-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application\_note/an5543-enhanced-

methods-to-handle-spi-communication-on-stm32-devicesstmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4760-quadspi-

interface-on-stm32-microcontrollers-and-microprocessors--

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4899-stm32-

microcontroller-gpio-hardware-settings-and-lowpower-consumption-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5612-esd-protection-

of-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an1202\_freertos\_guide-

for related Tools freertos-guide-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an1602\_semihosting\_in for related Tools truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an1801\_stm32cubeprog

for related Tools rammer\_in\_truestudio-installing-stm32cubeprogrammer-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/atollic\_editing\_keyboard

for related Tools \_shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application note/iar to atollic truestudio

for related Tools \_\_migration\_guide-truestudio-for-arm-migration-guide-iar-embedded-

& Software workbench-to-truestudio-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/stm32cubemx\_installatio

for related Tools n\_in\_truestudio-stm32cubemx-installation-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an2656-stm32f10xxx-

& Software

Application Notes https://www.st.com/resource/en/application\_note/an2790-tft-lcd-

for related Tools interfacing-with-the-highdensity-stm32f10xxx-fsmc-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3078-stm32-for related Tools inapplication-programming-over-the-ic-bus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3116-stm32s-adc-

for related Tools modes-and-their-applications-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3174-implementing-for related Tools receivers-for-infrared-remote-control-protocols-using-stm32f10xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3241-qvga-tftlcd-for related Tools direct-drive-using-the-stm32f10xx-fsmc-peripheral-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3307-guidelines-for-for related Tools obtaining-iec-60335-class-b-certification-for-any-stm32-application-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3364-migration-and-

for related Tools compatibility-guidelines-for-stm32-microcontroller-applications-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an3965-

for related Tools stm32f40xstm32f41x-inapplication-programming-using-the-usart-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an3969-eeprom-

for related Tools emulation-in-stm32f40xstm32f41x-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3990-upgrading-for related Tools stm32f4discovery-board-firmware-using-a-usb-key-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3997-audio-playback-for related Tools and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an3998-pdm-audio-for related Tools software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4044-floating-point-

for related Tools unit-demonstration-on-stm32-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4187-using-the-crc-for related Tools peripheral-in-the-stm32-family-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4323-getting-started-for related Tools with-stemwin-library-stmicroelectronics.pdf

& Software

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4365-using-stm32f4-for related Tools mcu-power-modes-with-best-dynamic-efficiency-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4435-guidelines-for-for related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32- & Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4457-implementing-for related Tools an-emulated-uart-on-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4499-stm32-for related Tools nrf51822-bluetooth-low-energy-system-solution-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4502-stm32-for related Tools smbuspmbus-embedded-software-expansion-for-stm32cube-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4657-stm32-for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4666-parallel-for related Tools synchronous-transmission-using-gpio-and-dma-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4678-full-duplex-spifor related Tools emulation-for-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an4701-proprietary-for related Tools code-readout-protection-on-microcontrollers-of-the-stm32f4-series-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4739-stm32cube-

for related Tools firmware-examples-for-stm32f4-series-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4758-proprietary-for related Tools code-readout-protection-on-stm32l4-stm32l4-stm32g4-and-stm32wb-

& Software series-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4759-using-the-

for related Tools hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-

& Software stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4841-digital-signal-for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an4852-programming-

for related Tools an-external-flash-memory-using-the-uart-bootloader-builtin-stm32-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an4968-proprietary-for related Tools code-read-out-protection-pcrop-on-stm32f72xxx-and-stm32f73xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5054-secure-for related Tools programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application\_note/an5056-integration-

for related Tools guide-for-the-xcubesbsfu-stm32cube-expansion-package-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5418-how-to-build-a-for related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application\_note/an5426-migrating-for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5464-position-control-

for related Tools of-a-threephase-permanent-magnet-motor-using-xcubemcsdk-or-

& Software xcubemcsdkful-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5698-adapting-the-for related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application\_note/an5731-stm32cubemx-

for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

& Software

Errata Sheets https://www.st.com/resource/en/errata\_sheet/es0298-stm32f446xcxe-

device-limitations-stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/dm00141306.pdf

Programming https://www.st.com/resource/en/programming\_manual/pm0214-stm32Manuals cortexm4-mcus-and-mpus-programming-manual-stmicroelectronics.pdf

Reference https://www.st.com/resource/en/reference manual/rm0390-stm32f446xx-

Manuals advanced-armbased-32bit-mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn0516-overview-of-the-& Articles stm32f0xf100xxf103xx-and-stm32f2xxf30xf4xx-mcus-pmsm-singledual-

foc-sdk-v40-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical\_note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

**Technical Notes** https://www.st.com/resource/en/technical\_note/tn1205-tape-and-reel-& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packagesstmicroelectronics.pdf **Technical Notes** https://www.st.com/resource/en/technical\_note/tn1206-tape-and-reel-& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packagesstmicroelectronics.pdf **Technical Notes** https://www.st.com/resource/en/technical\_note/tn1207-tape-and-reel-& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packagesstmicroelectronics.pdf **Technical Notes** https://www.st.com/resource/en/technical\_note/tn1208-tape-and-reel-& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-

packages-stmicroelectronics.pdf