To start using jQuery, include it in your HTML file:

## **CDN** (Recommended)

<script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>

## **Local File**

.on

```
Download the jQuery library from jQuery.com, then include it:

<script src="jquery.min.js"></script>

$('#id)
```

## Changing the text

```
<!DOCTYPE html>
<html>
<head>
 <script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>
</head>
<body>
 <button id="loadData">Load Data/button>
 <div id="result"></div>
 <script>
  $(document).ready(function() {
   $('#loadData').click(function() {
     $.ajax({
      url: 'https://jsonplaceholder.typicode.com/posts/1',
      type: 'GET',
      success: function(data) {
       $('#result').html('<h3>' + data.title + '</h3>' + data.body + '');
      },
      error: function() {
       $('#result').text('Error loading data');
      }
    });
   });
  });
 </script>
</body>
</html>
```

```
Dom manipulation
$(selector).action
$("mydiv").html(" this is a paragraph");
$("mydiv").addClass("active");
$("#myButton").click(function(){
 alert("Button clicked!");
});
$("#myDiv").hover(
 function() { $(this).css("background-color", "yellow"); },
 function() { $(this).css("background-color", ""); }
);
$("#myDiv").on("click", function() {
 alert("Div clicked!");
});
AJAX
$.ajax({
 url: "myfile.php",
 type: "GET",
//it is a callback func that executes if AJAX ewq is successful
 success: function(response) {
  $("#result").html(response);
 }
});
```

\$("#myDiv").fadeIn(1000); // Fade in over 1 second