


Load under the piston (ø50 = 1963 mm²)

kPa	total kg	1 kg discs	trim kg
5	1.00	0	0.43
10	2.00	1	0.43
15	3.00	2	0.43
20	4.00	3	0.43
25	5.00	4	0.43

moving part without discs ≈ 0.57 kg ≈ 2.9 kPa (minimum)

Parts


#	part
1	Al base plate 340×260×25, 3 levelling feet
2	2 columns Al 40×80 × 326, cross-beam 80×80 × 340
3	igus drylin RJ4JP-01-12 in the beam, Invar rod ø12
4	partial piston Al ø50×20, steel ball ø8
5	carrier Al ø120×8, steel discs ø120 (1 kg)
6	printed cell ø160 + sand ø100×100 (V03)
7	XPS sleeve ø240 × 130, XPS slab 40, 3 G10 pads
8	Invar post ø16: LVDT arm + camera target arm
9	(1) camera + RPi 5 box, 11-line laser (V02)
10	(2) LVDT RDP DCTH400AG (V02)
11	point M: CS645, Pt100, optical fibre (existing)

side view y–z through the axis; the Al frame only GUIDES the load; rev. B per measurement review

Rig C rev. B – dead weight on a partial piston, free surface


status	DRAFT	drawn	Claude Code (draft)	checked: —
units	mm	project	E7 – freeze–thaw loading tests	date 2026-10-27
scale	**≈ 1 : 2.5**	drawing no.	**E7-V01**	sheet 1 / 5

(a) LASER TRIANGULATION – section y–z 1 : 1.25



heave Δh moves the hit point by Δy = Δh / tan 68° = 0.40 Δh (open circle);
no collar shadow: the laser sits above the cavity edge

(b) CAMERA VIEW – 11 laser lines, whole surface



(c) LVDT ON INVAR POST 1 : 2.6

What is measured

method	signal	resolution	interval
(1) camera + 11 lines	map h(x, y) of the whole surface	≈ 10 µm	every 10 / 1 min
(2) LVDT	carrier = piston	≈ 1 µm	CR1000, 10 / 1 min
Invar target	camera / frame drift	≈ 10 µm	every photo

Evaluation per freeze–thaw cycle

quantity	how
surface map	Δh(x, y) on 11 profiles → contour map, whole ⌀100
heave, free surface	mean Δh over the annulus (minus rim)
heave under load	Δh_load = LVDT (check: (1) on the piston)
settlement on thawing	drop from the maximum to the end of thaw
residual per cycle	height at end of thaw − start of cycle
effect of the load	Δh_free − Δh_load
strain	Δh / 100 mm
frost depth	0 °C isotherm from Pt100 / fibre / CS645 (M)

Procedure


1 blank run, Al dummy instead of sand, full cycle: drift of (1) and (2) vs cell temperature (≈ 50 µm / 20 K, smooth) → fit and subtract
2 calibrate (1): shims 0.1 / 0.5 / 1.0 mm under a flat plate, camera px → mm for free sand and piston top
3 load, 24 h at +10 °C, then zero (1) and (2)
4 cycle 24 h −10 °C / 24 h +10 °C (fan on); CR1000 C5 pulse triggers the photo; laser on only for the photo
5 weigh the cell before / after each cycle; log air RH
6 expected heave for Sr ≈ 0.4 is small (tens of µm) – decide Sr first

heave while freezing, settlement while thawing, residual per cycle


Deformation measurement – (1) camera + laser, (2) LVDT

status	DRAFT	drawn	Claude Code (draft)	checked: —
units	mm	project	E7 – freeze–thaw loading tests	date 2026-10-27
scale	**various**	drawing no.	**E7-V02**	sheet 2 / 5

SECTION A–A 1 : 1.25 (along the TDR axis)



PLAN 1 : 2.4



Point M (existing sensors)

	sensor	position
TDR	Campbell CS645	3 rods 75, pitch 8.9, in the port, depth 36/45/54
OF	optical fibre	at the top rod, tip 37.5 from the wall
Pt100	37 mm (25 metal)	vertical, r 37.5 at 315° (free annulus, off the laser)

- The piston ⌀50 (dashed) covers the centre; the Pt100 sits in the free annulus on the camera side so it never crosses the laser line.
- Sand 100 mm (z 26–126), 34 mm free above (piston 20 + travel).
- Print: PETG(-CF) 0.2 mm, jacket 10 % infill = insulation; 100 % infill under the cavity, cavity wall ≈ 5 mm (≈ 8 perimeters).
- Inside: epoxy coat + PTFE spray + silicone grease.
- Cables: TDR head + fibre through the port, Pt100 straight up.
- Rev. B: stands on 3 G10 pads ⌀20×40 in an XPS slab; XPS sleeve 40 around the jacket (collar free) → freezing from the top.
- Full dimensions: cad/E7_V04_cell.dxf.

per drawing M. Vrána 23.06.2026; z = 0 at the underside; CAD: cad/E7_V04_cell.dxf

Printed cell ⌀160 (Column_one_body_version_1) with point M

status	DRAFT	drawn	Claude Code (draft)	checked: —
units	mm	project	E7 – freeze–thaw loading tests	date 2026-10-27
scale	**1 : 1.25**	drawing no.	**E7-V03**	sheet 3 / 5

To buy

tag	item	EUR	CR1000
CAM	Raspberry Pi 5 4 GB + PSU, SD, camera cable (RPishop)	105–120 *	– (Ethernet, NTP)
+	Raspberry Pi HQ Camera C/CS, IMX477 (RPishop OFI060)	50–62 *	C5 trigger
+	Raspberry Pi 6 mm CS wide-angle lens (RPishop / Pi Hut)	20–30	–
+	camera box XPS 30, double glass; houses the RPi 5 (no heater)	20–40	–
+	SHT45 RH/T sensor on the RPi (I2C), freezer air	15–25	– (RPi)
LAS	Picotronic DOE253-635-1-6(10x22), 11 lines, 635 nm, 1 mW, 5 V	92 *	– (RPi GPIO)
LVDT	RDP DCTH400AG ±10 mm, spring (Elkome)	581 *	SE1, ±5000 mV
+	Mean Well HDR-15-24, 24 V DIN (floating supply) (TME)	11–14 *	C4 relay
+	Campbell 4WPB100 (for the existing Pt100) (Ekotechnika)	60–120	DIFF1
Tair	Campbell 109-L, REQUIRED: air = boundary condition	150–220	SE3, VX1
+	fan 80 mm 12 V, air mixing in the freezer	10–20	C4 relay
CAL	shims 0.1 / 0.5 / 1.0 mm (feeler gauge set) for camera px → mm	10–25	–

Mechanics (estimate)

item	EUR
Al base plate 340 × 260 × 25 (machined)	80–150
Al profiles 2× 40×80 × 326 + 80×80 × 340, core bolts	80–170
igus drylin RJ4JP-01-12 + Invar 36 rod ⌀12 ground × 250 + ball ⌀8	60–140
Invar 36 post ⌀16 × 405 + arms (LVDT, camera target)	60–140
XPS 40: sleeve ⌀240 × 130 + slab ⌀240; 3 G10 pads ⌀20 × 40	20–50
Al partial piston ⌀50 × 20 + carrier ⌀120 × 8 (machined)	40–80
steel discs ⌀120: 4 × 1 kg + 0.5 kg + trim washers	40–90
camera bracket + laser bracket (Al strip), cable glands	15–40

Total ≈ 1519–2209 EUR excl. VAT (≈ 38–55 tis. Kč). Already available: printed cell, CS645 + TDR100/200, Pt100, optical fibre, CR1000.

CR1000 channel plan


terminal	connected to	measurement
SE1	(2) LVDT	VoltSE ±5000 mV
DIFF1	Pt100 via 4WPB100	BrHalf4W, VX2 2500 mV
SE3	Tair 109 (required)	Therm109, VX1
C1–C3	TDR100/200 → CS645	SDM
C4	relay: LVDT supply	on for the scan
C5	pulse → RPi GPIO (opto)	triggers photo + laser
–	(1) camera + RH sensor	RPi 5 in the camera box
–	optical fibre	own reader


Notes
- CR1000 and TDR outside; RPi 5 inside the camera box (no CSI ribbon through the seal, its ≈ 5 W heat the box). Through the lid seal: Ethernet, 5 V, LVDT, sensor cables.
- Scan 10 min, 1 min around 0 °C; the photo is triggered by the CR1000 (C5) → same time stamps without NTP.
- Fan in the freezer evens out the on/off air swings.
- No pressure cells: the load is a known dead weight.

existing = already in the lab; prices ≈ EUR excl. VAT, * = dealer price found, rest estimated

Sensors, CR1000 wiring and costs

status	DRAFT	drawn	Claude Code (draft)	checked: —
units	mm	project	E7 – freeze–thaw loading tests	date 2026-10-27
scale	–	drawing no.	**E7-V04**	sheet 4 / 5





Fit check

item	size	value	status
base plate	340 × 260	tray ≈ 530 × 340	OK
rig height	plate + frame + discs	538 above tray	check
highest point	above freezer floor	598	≈ 52 spare
load travel	± 25 mm above the beam	max 623	lid closes?

Notes

- The free end of the freezer stays empty (cable bundle, a second rig).
- Highest point is the disc stack; with 4 discs ≈ 50 mm under the lid – measure the freezer and the tray before ordering the profiles.
- Camera box and laser hang inside the frame – nothing outside the plate.
- Rev. B: +40 mm insulation under the cell, beam gap 200 → 160: the total height is unchanged.
- 80 mm fan on the free end mixes the air; run the blank test first.

same freezer as E6 (≈ 900 × 550 × 650, to be measured); CR1000 outside the freezer

Rig C rev. B in the chest freezer

status	DRAFT	drawn	Claude Code (draft)	checked: —
units	mm	project	E7 – freeze–thaw loading tests	date 2026-10-27
scale	**1 : 5**	drawing no.	**E7-V05**	sheet 5 / 5