

# Package ‘siland’

May 17, 2018

**Type** Package

**Title** Spatial Influence of Landscape

**Version** 1.2

**Date** 2017-10-29

**Author** Carpentier F. and Martin O.

**Maintainer** Martin Olivier <olivier.martin@inra.fr>

**Description** Method to estimate the spatial influence scales of landscape variables on a response variable. The method is based on Chandler and Hepinstall-Cymerman (2016) Estimating the spatial scales of landscape effects on abundance, Landscape ecology, 31: 1383-1394, <doi:10.1007/s10980-016-0380-z>.

**License** GPL (>=2.0) | file LICENSE

**Depends** base, graphics, stats, lme4, sp, raster, rgdal, fields

**NeedsCompilation** no

## R topics documented:

siland-package . . . . .	2
dataSiland . . . . .	3
landSiland . . . . .	4
plotcontri . . . . .	5
plotsif . . . . .	6
plotsiland . . . . .	6
plotsiland.land . . . . .	7
plotsiland.sif . . . . .	8
print.siland . . . . .	9
siland . . . . .	9
siland.quantile . . . . .	11
summary.siland . . . . .	12

<b>Index</b>	<b>13</b>
--------------	-----------

siland-package

*Spatial Influence of Landscape***Description**

Method to estimate the spatial influence scales of landscape variables on a response variable. The method is based on Chandler and Hepinstall-Cymerman (2016) Estimating the spatial scales of landscape effects on abundance, *Landscape ecology*, 31: 1383-1394, <doi:10.1007/s10980-016-0380-z>. This package allows for statistical inference about the scales at which landscape variables affect an ecological variable. This ecological variable can be continuous (mean of different measurements), an abundance (counting) or a proportion. The approach is based on the method proposed by Chandler et al., Estimating the spatial scales of landscape effects on abundance, 2016, *Landscape Ecology*, 31, 1383-1394.

**Details**

The DESCRIPTION file:

```
Package:      siland
Type:         Package
Title:         Spatial Influence of Landscape
Version:       1.2
Date:          2017-10-29
Author:        Carpentier F. and Martin O.
Maintainer:    Martin Olivier <olivier.martin@inra.fr>
Description:    Method to estimate the spatial influence scales of landscape variables on a response variable. The method is based on Chandler and Hepinstall-Cymerman (2016) Estimating the spatial scales of landscape effects on abundance, Landscape ecology, 31: 1383-1394, <doi:10.1007/s10980-016-0380-z>. This package allows for statistical inference about the scales at which landscape variables affect an ecological variable. This ecological variable can be continuous (mean of different measurements), an abundance (counting) or a proportion. The approach is based on the method proposed by Chandler et al., Estimating the spatial scales of landscape effects on abundance, 2016, Landscape Ecology, 31, 1383-1394.
License:        GPL (>=2.0) | file LICENSE
Depends:        base, graphics, stats, lme4, sp, raster, rgdal, fields
```

Index of help topics:

dataSiland	A simulated data set that represents observations.
landSiland	A list of simulated data sets that describes landscape.
plotcontri	Plot contributions
plotsif	Plot density and cumulative density for sif function
plotsiland	Plot results from siland function
plotsiland.land	Spatial representation of the landscape influence
plotsiland.sif	Plot the estimated spatial influence functions.
print.siland	print for an object of class siland
siland	Estimation of spatial influence of landscape
siland-package	Spatial Influence of Landscape
siland.quantile	Quantile computation for spatial influence

	functions
summary.siland	The function gives a detailed summary of an object of class siland

The principal function is the function siland(). Two functions for graphical displays are available: plotsiland() and plotcontri().

### Author(s)

Carpentier F. and Martin O. Maintainer: Martin Olivier <olivier.martin@inra.fr>

---

dataSiland	<i>A simulated data set that represents observations.</i>
------------	---

---

### Description

The data set has 5 columns, X, Y, conv, varloc and y. Columns X and Y represents the location for the observed data. Column locfac corresponds to an explanatory factor with two levels. Column locvar corresponds to a continuous explanatory variable. Column y corresponds to a continuous response variable simulated with a gaussian model.

### Usage

```
data("dataSiland")
```

### Format

A data frame with 80 simulated data and 5 variables.

X a numeric vector

Y a numeric vector

locfac a local factor with two levels

locvar a continuous local variable

y a numeric vector

### Note

dataSiland\$y have been simulated using the locfac variable and the landscape landSiland with a gaussian model. The locvar variable has not been used to simulate data y. To simulate the data, parameters have been fixed to the following values: Intercept=-5, locfac=3, L1 =50, L2=-50, SIF.L1=400, SIF.L2=200 and sigma=2. The spatial influence function was exponential.

## Examples

```
data(dataSiland)
data(landSiland)
nrow(dataSiland)
#Plot for landscape variables
plot(landSiland[[1]],col=2,pch=".")
points(landSiland[[2]],col=3,pch=".")
#Locations of observations
points(dataSiland[,c("X","Y")])
```

---

landSiland

*A list of simulated data sets that describes landscape.*

---

## Description

Each component of the list is a dataframe that corresponds to a landscape variable. For each data set, the columns X and Y indicate the locations of the different "pixels".

## Usage

```
data("landSiland")
```

## Format

The format is: List of 2 \$ L1: 'data.frame': 9513 obs. of 2 variables: ..\$ X: num [1:9513] 0 43 86.1 129.1 172.2 ... ..\$ Y: num [1:9513] 9535 9535 9535 9535 9535 ... \$ L2: 'data.frame': 3615 obs. of 2 variables: ..\$ X: num [1:3615] 387 430 473 516 560 ... ..\$ Y: num [1:3615] 9535 9535 9535 9535 9535 ...

## Note

The landscape comes from the north of France. Two features of the landscape are considered and they are denoted L1 and L2.

## Examples

```
data(landSiland)
names(landSiland)
#locations for the two landscape variables b1 and b2
plot(landSiland[[1]],col=2,pch=".")
points(landSiland[[2]],col=3,pch=".")
```

---

plotcontri	<i>Plot contributions</i>
------------	---------------------------

---

**Description**

Plot contributions for the different landscape variables

**Usage**

```
plotcontri(res, land, data, type = 0, numvar = NULL)
```

**Arguments**

res	a result form siland estimation
land	the landscape associated to the estimation res
data	the observations associated to the estimation res
type	type of plot, 1 or 2. For type equal to 0 (by default), a graphic for each local and landscape variable is displayed. For type equal to 1, the rate of landscape with local contriptions is displayed.
numvar	a number indicating the variable that has to be displayed. If NULL (by default), graphics are displayed following the argument type.

**Note**

A local model with only continuous variables can be currently considered. The function doesn't work if local model includes random effect(s) or categorical variables (factor). These cases are ongoing developements.

**Examples**

```
data(landSiland)
data(dataSiland)
res=siland(y~locvar,land=landSiland,data=dataSiland,sif="exponential",family=gaussian)

plotcontri(res,landSiland,dataSiland)

plotcontri(res,landSiland,dataSiland,type=1)
plotcontri(res,landSiland,dataSiland,numvar=2)
```

plotsif

*Plot density and cumulative density for sif function***Description**

The function represents the density and the cumulative density for a given distance *d* and the shape of the spatial influence function.

**Usage**

```
plotsif(d = NULL, sif = "exponential")
```

**Arguments**

<i>d</i>	a positive numeric value that represents the parameter for the spatial influence function
<i>sif</i>	character that gives the shape of the spatial influence function, "exponential" (by default) or "gaussian".

**Value**

a list of two dataframes. First element gives the density values for the spatial influence function, and the second gives the cumulative density.

**Examples**

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

plotsif(d=300,sif="exponential")
```

plotsiland

*Plot results from siland function***Description**

Plot locations of observed data and locations of landscape variables. The location of black points corresponds to the locations of observed data, and the size is proportional to numeric values. The locations of different landscape variables are displayed with small points of different colours. Estimated mean distance of spatial influence for each landscape variable is indicated beside the graphic with a continuous line. Dashed line indicates the radius that gives 95 percent of the total influence of landscape variable.

**Usage**

```
plotsiland(res, land, data)
```

**Arguments**

res	a dataframe obtained from the function siland
land	a list with the location of the landscape variables. Each component of the list is a dataframe with two columns "X" and "Y" indicating the locations of each landscape variable.
data	a dataframe with the response variable and the local variables

**Examples**

```
data(dataSiland)
data(landSiland)
res=siland(loc.model=y~locfac,land=landSiland,data=dataSiland,sif="exponential",family="gaussian")
plotsiland(res,landSiland, dataSiland)
```

---

plotsiland.land	<i>Spatial representation of the landscape influence</i>
-----------------	--

---

**Description**

The function gives a spatial representation of landscape variable influences. Representation can be done for each variable, or for the cumulative effects of all variables.

**Usage**

```
plotsiland.land(x, land, data, var = 0, lw = 100)
```

**Arguments**

x	an object of class siland
land	a list containing the location of the landscape variables. Each component of the list is a dataframe with two columns "X" and "Y" indicating the locations of pixels for a given landscape variable. The list must be the same than the one used to obtain the object x.
data	a dataframe containing the response variable and the local variables. The dataframe must be the same than the one used to obtain the object x.
var	a numeric value that gives the landscape variable for the spatial representation. If var=0 (by default), the representation gives the cumulative effects for all landscape variables.
lw	the number of pixels on x-axis and y-axis for the graphical representation. A too high value can lead to memory allocation problems. By default lw=100.

**Value**

a list with three component for graphical representation: x-axis, y-axis and a matrix for the level of the landscape variable influence for all coordinates (x,y) of the map.

**See Also**

siland

**Examples**

```
data(dataSiland)
data(landSiland)
resE=siland(y~locvar,land=landSiland,data=dataSiland,sif="exponential",family=gaussian)

plotsiland.land(x=resE,land=landSiland,data=dataSiland)
plotsiland.land(x=resE,land=landSiland,data=dataSiland,var=1,lw=20)
```

---

plotsiland.sif

---

*Plot the estimated spatial influence functions.*


---

**Description**

Graphic representations on the form of the decrease for the different influence functions estimated with the function siland().

**Usage**

```
plotsiland.sif(x)
```

**Arguments**

x must be an object of type siland, that is an object resulting from function siland().

**Value**

no value is returned

**See Also**

siland



**Examples**

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

data(dataSiland)
data(landSiland)
resE=siland(y~locvar,land=landSiland,data=dataSiland,sif="exponential",family=gaussian)
plotsiland.sif(x=resE)
```

---

print.siland	<i>print for an object of class siland</i>
--------------	--

---

**Description**

The function print an object of class siland. It gives the model used and the estimated parameters

**Usage**

```
## S3 method for class 'siland'
print(x,...)
```

**Arguments**

x	an object of class siland
...	the same arguments that the default print

---

siland	<i>Estimation of spatial influence of landscape</i>
--------	---

---

**Description**

siland is used to fit spatial influence of landscape.

**Usage**

```
siland(loc.model, land=NULL, data, initSIF = NULL, sif = "exponential",
family = "gaussian", test = FALSE)
```

**Arguments**

<code>loc.model</code>	a symbolic description (see <code>lm()</code> or <code>glm()</code> ) of the response variable concerning local variables. Random effects are also allowed according to the syntax in package <code>lme4</code> (see <code>lmer()</code> function in package <code>lme4</code> ).
<code>land</code>	a list containing the location of the landscape variables. Each component of the list is a dataframe with two columns "X" and "Y" indicating the locations of pixels for a given landscape variable.
<code>data</code>	a dataframe containing the response variable and the local variables.
<code>initSIF</code>	a vector indicating the starting values for the estimation of the mean distance of the spatial influence functions. The length of <code>initSIF</code> has to be equal to the length of list <code>land</code> . By default, initialisation is equal to 100 for each landscape variable.
<code>sif</code>	the family of the spatial influence function. <code>sif</code> can be "exponential", "gaussian" or "uniform".
<code>family</code>	the distribution of response variable. <code>family</code> can be "gaussian", "poisson" or "binomial" and the associated link function are identity, log and logit respectively.
<code>test</code>	logical value. If TRUE, a ratio likelihood test is performed for each explanatory variable (local and spatial). By default, the value is FALSE since performing tests for all the variables can be heavy computing.

**Value**

`siland` returns an object of type list.

<code>coefficients</code>	vector of estimated coefficients
<code>local</code>	an object of class formula that indicates the local model used
<code>landcontri</code>	a dataframe of estimated contributions of each spatial variable (in column) to each observation (in row). The number of columns is equal to the length of list <code>land</code>
<code>loglik</code>	log-likelihood for the estimated parameters
<code>loglik0</code>	log-likelihood for the local model
<code>fitted</code>	fitted values
<code>sif</code>	the family of the spatial influence function
<code>resoptim</code>	an object of class <code>optim</code> or <code>optimize</code> giving informations about the optimization procedure see <code>optim()</code> or <code>optimize()</code> for further details.
<code>AIC</code>	akaike information criterion
<code>AIC0</code>	akaike information criterion for local model (no landscape variable)
<code>nparam</code>	number of parameters
<code>pval0</code>	p.value of the test of global effect of spatial variables. Obtained from the likelihood ratio test between the complete model and the local model.
<code>pval</code>	if test is TRUE, vector of p.values of the test of effect of each landscape variables
<code>family</code>	family distribution for the model

sd.error	standard error for gaussian family, NA in other case
model.Type	type of local model: GLM for generalised model, LMM for linear mixed model or GLMM for generalised linear mixed model
rand.StdDev	standard deviation of random effects for LMM or GLMM
nparam	number of model parameters

**Author(s)**

Carpentier, F. and Martin, O.

**References**

Chandler R. and Hepinstall-Cymerman J. (2016) Estimating the spatial scales of landscape effects on abundance. *Landscape ecology*, 31: 1383-1394.

**Examples**

```
data(dataSiland)
data(landSiland)
resE=siland(y~locvar,land=landSiland,data=dataSiland,sif="exponential",family=gaussian)
resE
resE$AIC
```

---

siland.quantile	<i>Quantile computation for spatial influence functions</i>
-----------------	---

---

**Description**

The function computes the radius for which the integrated influence for the different landscape variables are equal to p.

**Usage**

```
siland.quantile(x, p = 0.95)
```

**Arguments**

x	an object of class siland resulting from function siland()
p	a vector of probabilities

**Value**

returned value is matrix. The number of rows cooresponds to the number of landscape variables, and the number of columns the number of probabilities in argument p.

**Author(s)**

O. Martin and F. Carpentier

**Examples**

```
data(dataSiland)
data(landSiland)
resE=siland(y~locvar,land=landSiland,data=dataSiland,sif="exponential",family=gaussian)
siland.quantile(x=resE,p=c(0.5,0.95))
```

---

summary.siland

*The function gives a detailed summary of an object of class siland*

---

**Description**

The function gives a detailed summary of an object of class siland. It aims to give results as the summary for an object of type glm or lm.

**Usage**

```
## S3 method for class 'siland'
summary(object,...)
```

**Arguments**

object	an object of type siland
...	Dots are not take into account in this version

# Index

\*Topic **\textasciitildekw1**

plotsiland.land, [7](#)

plotsiland.sif, [8](#)

\*Topic **\textasciitildekw2**

plotsiland.land, [7](#)

plotsiland.sif, [8](#)

\*Topic **datasets**

dataSiland, [3](#)

landSiland, [4](#)

\*Topic **package**

siland-package, [2](#)

dataSiland, [3](#)

landSiland, [4](#)

plotcontri, [5](#)

plotsif, [6](#)

plotsiland, [6](#)

plotsiland.land, [7](#)

plotsiland.sif, [8](#)

print.siland, [9](#)

siland, [9](#)

siland-package, [2](#)

siland.quantile, [11](#)

summary.siland, [12](#)