


# SVM (Support Vector Machine):

- used for classification
- we to separate data with the hyperplane and with the biggest margin  $\frac{2}{\|w\|}$  between the points
- we basically minimize the objective function using QP(Quadratic programming) = maximizing the margin while applying the constraint that each classified point must be  $\geq 1$

## Input data:

i	$x_{1i}$	$x_{2i}$	label $y_i$
0	1	1	a
1	2	0.5	a
2	40	40	b
3	50	35	b



## Constraint:

- $\forall i$  for all  $i$
- $w$  is the weight

$$y_i(w^T \cdot x + b) \geq 1 \quad \forall i \quad (1)$$

- verify the constraint is true

$$y_i = 1:$$

$$1(w^T \cdot x + b) \geq 1 \rightarrow (w^T \cdot x + b) \geq 1 \quad (2)$$

$$y_i = -1:$$

$$-1(w^T \cdot x + b) \geq 1 \rightarrow (w^T \cdot x + b) \leq -1$$

## Primal problem - objective function:

$$\min \frac{1}{2} \|w\|^2 \quad (3)$$

## QP (Quadratic Programming)-equation:

- it is used to solve optimization problems where the objective function is quadratic, and the constraints (if any) are typically linear

$$\min \frac{1}{2} x^T \cdot P \cdot x + q^T \cdot x \quad (5)$$

- in the code we can skip (set to zero) the linear term  $q^T \cdot x$  because we try to find the maximum margin between classes without any offset or linear bias:

## QP (Quadratic Programming)-code:

- relabel the values and add bias to the matrix

```
import numpy as np
from scipy.optimize import minimize

# Input data
X = np.array([[1, 1], [2, 0.5], [40, 40], [50, 35]])
y = np.array(['a', 'a', 'b', 'b'])

✓ 0.0s

# Re-label data to {-1, 1} for SVM compatibility
y = np.where(y == 'a', -1, 1)
y

✓ 0.0s  Open 'y' in Data Wrangler

array([-1, -1,  1,  1])

# Add a bias term to the feature matrix (append a column of ones)
X_with_bias = np.hstack((X, np.ones((X.shape[0], 1))))
X_with_bias

✓ 0.0s  Open 'X_with_bias' in Data Wrangler

array([[ 1. ,  1. ,  1. ],
       [ 2. ,  0.5,  1. ],
       [40. , 40. ,  1. ],
       [50. , 35. ,  1.]])
```

- Define matrices P and q

```
# Define identity matrix (P = I for quadratic term)
P = np.eye(X_with_bias.shape[1])
P

✓ 0.0s  Open 'P' in Data Wrangler

array([[1., 0., 0.],
       [0., 1., 0.],
       [0., 0., 1.]])

# Define quadratic term-setting it into zero we neglect the impact (we are interested in maximizing the margin)
q = np.zeros(X_with_bias.shape[1])
q

✓ 0.0s  Open 'q' in Data Wrangler

array([0., 0., 0.])
```

- **define objective function** and **constraint** with the initial guess and run the optimization

```

# Objective function: 1/2 * w^T * P * w + q^T * w
def objective(w):
    return 0.5 * np.dot(w.T, np.dot(P, w)) + np.dot(q.T, w)

# Constraints: y_i * (w^T x_i + b) - 1 >= 0 for each data point
def constraints(w):
    return y * (np.dot(X_with_bias, w)) - 1
✓ 0.0s

# Initial guess for the variables: weights + bias
w0 = np.zeros(X_with_bias.shape[1])

# Solve the optimization problem using SLSQP
result = minimize(objective, w0, constraints={'type': 'ineq', 'fun': constraints}, method='SLSQP')
✓ 0.0s

# Print the result
if result.success:
    print("Optimal weights (w1, w2):", result.x[:-1])
    print("Optimal bias (b):", result.x[-1])
else:
    print("Optimization failed:", result.message)
✓ 0.0s

Optimal weights (w1, w2): [0.01709402 0.03418803]
Optimal bias (b): -1.0512820512820509

```

- predict the values and calculate the accuracy

$$y_i = \text{sign}(w^T \cdot x + b)$$

(6)

```

# Predict function to evaluate the decision function on the training data
def predict(X, w, b):
    return np.sign(np.dot(X, w) + b)

# Extract the weights and bias from the result
optimal_weights = result.x[:-1]
optimal_bias = result.x[-1]

# Make predictions on the training data
predictions = predict(X, optimal_weights, optimal_bias)


# Print predictions and true labels
print("Predictions:", predictions)
print("True Labels:", y)

# Calculate and print accuracy
accuracy = np.mean(predictions == y)
print("Accuracy:", accuracy)
✓ 0.0s

Predictions: [-1. -1.  1.  1.]
True Labels: [-1 -1  1  1]
Accuracy: 1.0

```

-print results



- test model for new data

```
# Make predictions on the training data
new_point1 = np.array([0,20])
predictions = predict(new_point1, optimal_weights, optimal_bias)
predictions
✓ 0.0s
-1.0

# Make predictions on the training data
new_point2 = np.array([0,40])
predictions = predict(new_point2, optimal_weights, optimal_bias)
predictions
✓ 0.0s
1.0
```

## Dual Problem

### Lagrangian for the primal problem:

$L(w, b, \lambda) = \text{objective function} - \text{constraint}$

$$L(w, b, \lambda) = \min \frac{1}{2} \|w\|^2 - \sum_{i=1}^n \lambda_i [y_i (w^T \cdot x + b) - 1]$$

$$\frac{\partial L}{\partial w} = 0 \rightarrow w \quad (4)$$

$$\frac{\partial L}{\partial b} = 0 \rightarrow b$$

### Dual objective function:

$$\max_{(\lambda)} \left( \sum_{i=1}^n \lambda_i - \frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n \lambda_i \lambda_j y_i y_j (x_i^T x_j) \right) \quad (4)$$