



deeplearning.ai

Setting up your optimization problem

Gradient Checking

Gradient check for a neural network

Take $W^{[1]}$, $b^{[1]}$, ..., $W^{[L]}$, $b^{[L]}$ and reshape into a big vector θ .

concatenate

$$J(w^{[1]}, b^{[1]}, \dots, w^{[L]}, b^{[L]}) = J(\theta)$$

Take $dW^{[1]}$, $db^{[1]}$, ..., $dW^{[L]}$, $db^{[L]}$ and reshape into a big vector $d\theta$.

Is $d\theta$ the gradient of $J(\theta)$?

Gradient checking (Grad check)

$$J(\theta) = J(\theta_1, \theta_2, \theta_3, \dots)$$

for each i :

$$\rightarrow \underline{d\theta_{\text{approx}}[i]} = \frac{J(\theta_1, \theta_2, \dots, \overset{\downarrow}{\theta_i + \epsilon}, \dots) - J(\theta_1, \theta_2, \dots, \overset{\downarrow}{\theta_i - \epsilon}, \dots)}{2\epsilon}$$

$$\approx \underline{d\theta[i]} = \frac{\partial J}{\partial \theta_i} \quad | \quad d\theta_{\text{approx}} \approx d\theta$$

Check

$$\rightarrow \frac{\|d\theta_{\text{approx}} - d\theta\|_2}{\|d\theta_{\text{approx}}\|_2 + \|d\theta\|_2}$$
$$\underline{\epsilon = 10^{-7}}$$

$$\approx \frac{10^{-7}}{10^{-5}} - \text{great!} \leftarrow$$
$$\rightarrow 10^{-3} - \text{worry.} \leftarrow$$



deeplearning.ai

Setting up your optimization problem

Gradient
Checking
implementation

Gradient checking implementation notes

- Don't use in training – only to debug

$$\frac{d\theta_{\text{approx}}[\bar{i}]}{\uparrow \uparrow} \longleftrightarrow \frac{d\theta[\bar{i}]}{\uparrow}$$

- If algorithm fails grad check, look at components to try to identify bug.

$$\underline{db_{\bar{i}}^{[L]}} \quad \underline{dw_{\bar{i}}^{[L]}}$$

- Remember regularization.

$$\underline{J(\theta)} = \frac{1}{n} \sum_i \ell(y^{(i)}, \hat{y}^{(i)}) + \frac{\lambda}{2n} \sum_k \|w^{(2,k)}\|_F^2$$

$d\theta = \text{gradient of } J \text{ wrt. } \theta$

- Doesn't work with dropout.

J

$$\underline{\text{keep-prob} = 1.0}$$

- Run at random initialization; perhaps again after some training.

$$\underline{w, b \approx 0}$$