

# Machine Learning and Pattern Recognition Practice

## Session IV

Martin Palazzo

Universite de Technologie de Troyes  
Universidad Tecnologica Nacional Buenos Aires

*[mpalazzo@frba.utn.edu.ar](mailto:mpalazzo@frba.utn.edu.ar)*

December 13, 2022

- 1 Support Vector Machines - Binary Case
- 2 Soft Margin
- 3 SVM and the kernel trick

# Support Vector Machines - Binary Case

# Support Vector Machines


- Support Vector Classification [1] can build a nonlinear rule by constructing a linear boundary in a transformed and high dimensional version of the feature space.
- In binary classification the goal is to estimate a function  $f : \mathbb{R} \rightarrow \{+1, -1\}$  from training data samples  $x_i$  with label  $Y_i$ . SVC aims to estimate a hyperplane

$$x : f(x) = x^T \omega + \omega_0 = 0 \quad (1)$$


corresponding to the decision function:

$$D(x) = \text{sign} \left[ x^T \omega + \omega_0 \right] \quad (2)$$

# Support Vector Machines



$$\begin{aligned} \min \quad & \frac{1}{2} \|w\|^2 \\ \text{s.t.} \quad & y_i(w x_i + b) \geq 1 \\ & x \in \mathbb{R}^d \quad y \in \{-1, 1\} \end{aligned}$$



**Figure:** The SVM boundary is the optimal hyperplane obtained after solving a convex quadratic optimization with a global minima.

# Soft Margin

# Support Vector Machines

The decision function  $D$  obtained corresponds to the hyperplane which maximizes the separating margin  $M$  between the two classes where  $M = 1 / \|\omega\|$ . Now suppose that both classes overlap and are not linearly separable. A set of slack variables  $\xi = (\xi_1, \dots, \xi_m)$  are defined to allow some miss classifications when a sample fall on the wrong side of the margin [1].

Then a convex optimization problem is expressed in equation 10 where the cost  $C$  parameter penalizes every miss classification.

$$\min \frac{1}{2} \|\omega\|^2 + C \sum_{i=1}^m \xi_i \quad (3)$$

$$s.t. \xi_i \geq 0; y_i (x^T \omega + \omega_0) \geq 1 - \xi_i \quad (4)$$

After a quadratic programming solution applying Lagrange Multipliers the solution of  $\omega$  is expressed as

$$\hat{\omega} = \sum_1^m \hat{\alpha}_i y_i x_i \quad (5)$$

with non zero coefficient  $\hat{\alpha}_i$  only for the samples lying on the edge of the margin or for the miss classified ones. These samples are known as support vectors [1].



## SVM and the kernel trick


# Support Vector Machines and the Kernel trick

The core idea is to apply a transformation/mapping to the input feature vector  $X$  and then use linear models in the new space [1]. The transformation is denoted as  $\phi$  where  $\phi_m$  corresponds to the  $m_{th}$  transformation of  $X$  and  $m = 1 \dots M$ . Then the decision function can be written as

$$f(x) = \phi(x)^T w + w_0 = \sum_{i=1}^M \alpha_i y_i \langle \phi(x), \phi(x') \rangle + w_0 \quad (6)$$

where  $\phi(x)$  is used only for inner products. For this reason it is not necessary to determine the transformation  $\phi(x)$  but it is required to know the positive and semi-definite kernel function  $K(x_i, x_j) = \langle \phi(x_i), \phi(x_j) \rangle$  responsible to compute the inner products in the transformed space.

# Support Vector Machines and the Kernel trick



**Figure:** By using non-linear kernel functions it is possible to non-linear map the samples to a high dimensional hilbert space where the linear SVM is solved.



Palazzo, M., Beausery, P., Yankilevich, P. (2019). Hepatocellular Carcinoma tumor stage classification and gene selection using machine learning models. Electronic Journal of SADIO (EJS), 18(1), 26-42.



Bishop, C. M. (2006). Pattern recognition and machine learning. springer.



Friedman, J., Hastie, T., Tibshirani, R. (2001). The elements of statistical learning (Vol. 1, No. 10). New York: Springer series in statistics.



Shawe-Taylor, J., Cristianini, N. (2004). Kernel methods for pattern analysis. Cambridge university press.