

Module 07

"Object Lifetime"



Agenda

- ▶ **Introducing Lifetime**
- ▶ Enter Garbage Collection
- ▶ Class Destructors
- ▶ The Disposable Pattern



Lifespan of an Object

- ▶ An object is created
 - Memory is allocated
 - Memory is initialized into an object by running the constructor
- ▶ Object is alive and kicking
 - It is passed in and out of methods and operations are invoked
- ▶ The object is destroyed
 - The object is de-initialized into unused memory
 - Memory is then deallocated



Objects, Values, and Scope

- ▶ Local variables live only throughout the scope in which they are declared
 - Fixed lifetime
 - Scheduled destruction
- ▶ Objects can outlive the scope in which they were allocated
 - Unbounded lifetime
 - Undetermined destruction


```
static void Main()
{
    bool b = true;
    A longLivingVariable;
    if( b )
    {
        int i = 0;
        while( true )
        {
            A a = new A( i );
            if( ++i % 100 == 0 )
            {
                longLivingVariable = a;
            }
        }
    }
}
```





The Stack and The Heap


- ▶ Local variables are allocated on the *Stack*
- ▶ Objects are allocated on the *Heap*





Allocating Objects

- ▶ A new object is always allocated at The Next Object Pointer
 - This pointer is then advanced to the next block



- ▶ Can this go on forever?





Deallocating Objects

- ▶ There is no construct in C# to explicitly destroy objects
 - This is to avoid
 - Forgetting to destroy objects
 - Destroying more than once
 - Dangling references
 - ...
- ▶ The garbage collector *finalizes* the objects back into unused memory




Agenda

- ▶ Introducing Lifetime
- ▶ **Enter Garbage Collection**
- ▶ Class Destructors
- ▶ The Disposable Pattern



Object Graphs


- ▶ 1. Allocation is paused for a short while
- ▶ 2. Object graphs are created






Heap Compaction

- ▶ 3. Those objects which are not referenced from *Application Roots* are deallocated
- ▶ 4. The Heap is then compacted



Generations

- ▶ 5. Generations are updated
- ▶ 6. New object is allocated as first new Generation 0 object





The System.GC Type

Name	Characteristics
<code>Collect()</code>	Forces a garbage collection given <ul style="list-style-type: none">• a generation• a mode
<code>SuppressFinalize()</code>	Instructs that the object should not have its Finalize() method invoked
<code>WaitForPendingFinalizers()</code>	Suspends thread until all pending finalizable objects have been finalized
<code>ReRegisterForFinalize()</code>	Requests that the system calls the finalizer for the specified object
<code>AddMemoryPressure()</code>	Informs the CLR of a large allocation of unmanaged memory
<code>RemoveMemoryPressure()</code>	Informs the CLR of the deallocation of a large amount of unmanaged memory
<code>KeepAlive()</code>	Forces the object alive





Agenda

- ▶ Introducing Lifetime
- ▶ Enter Garbage Collection
- ▶ **Class Destructors**
- ▶ The Disposable Pattern



The `Finalize()` Method

- ▶ The garbage collector needs to know how to destroy objects
- ▶ The cleanup logic for objects is performed in the **`Finalize()`** method inherited from **`System.Object`**
- ▶ This virtual method cannot be overridden or called directly
- ▶ Implement a *class destructor* to override **`Finalize()`**
- ▶ If present, the garbage collector will invoke destructor just before turning object back into unused memory



Defining Destructors

- ▶ Put cleanup logic in the destructor
- ▶ Similar to constructors, the destructor is named after the class (but with ~)
- ▶ Similar to constructors, destructors have no return type
- ▶ No access modifier is allowed
- ▶ Just a single destructor (with no parameters!) is allowed

```
class DataHandler
{
    ...
    FileStream fs;

    ~DataHandler()
    {
        fs.Close();
    }
}
```





Destructors and Inheritance

- ▶ Destructors are invoked by following the inheritance chain from most specialized first to most general last

```
class A
{
    public A()
    {
        Console.WriteLine( "A()" );
    }
    ~A()
    {
        Console.WriteLine( "~A()" );
    }
}
```

```
class B : A
{
    public B()
    {
        Console.WriteLine( "B()" );
    }
    ~B()
    {
        Console.WriteLine( "~B()" );
    }
}
```

```
B b = new B();
b = null;
GC.Collect();
GC.WaitForPendingFinalizers(); // ???
```





Be Careful Out There!

- ▶ The finalization process takes place after “ordinary” garbage collection
- ▶ If your class has only managed resources, you should use a destructor!
- ▶ Avoid destructors whenever possible
 - Costs time
 - Hard to debug
 - Prolongs object life and memory usage
- ▶ Cannot know exactly when finalization takes place...!



Agenda

- ▶ Introducing Lifetime
- ▶ Enter Garbage Collection
- ▶ Class Destructors
- ▶ **The Disposable Pattern**



Two Approaches to Cleaning Up

- ▶ Solution 1: Implement a destructor with cleanup logic
- ▶ Solution 2: Implement an explicit **Dispose()** method and remember to invoke it!
- ▶ Both solutions have shortcomings...
- ▶ Best solution is to *combine* 1 + 2:
 - Try to remember to invoke **Dispose()** for deterministic cleanup
 - If you don't, the garbage collector will eventually clean it up
- ▶ This is the philosophy behind implementing **IDisposable**

```
public interface IDisposable
{
    void Dispose();
}
```



Implementing **IDisposable**

```
public class A : IDisposable
{
    private bool _disposed = false;
    public void Dispose()
    {
        CleanUp( true );
        GC.SuppressFinalize( this );
    }
    private void CleanUp(bool disposing)
    {
        if( _disposed == false )
        {
            if( disposing )
            {
                // Dispose managed here
            }
            // Clean up unmanaged here.
        }
        _disposed = true;
    }
}
```

```
~A()
{
    CleanUp( false );
}
```





Disposing Classes

- ▶ Many .NET Framework classes implement **IDisposable**
- ▶ You should always invoke **Dispose()** on objects if they implement **IDisposable**
- ▶ In order to make the built-in classes more “natural”, there is often a **Close()** method which does the **same** as **Dispose()**
 - This of course makes it even more confusing... ☹

```
static void Main()
{
    FileStream fs =
        new FileStream( "file.txt", FileMode.OpenOrCreate );

    // These method both closes!
    fs.Close();    // WTF???
    fs.Dispose();
}
```



The using Statement

- ▶ The **using** statement is a convenient shorthand to help you to remember to **Dispose()**

```
using( MyResourceWrapper rw = new MyResourceWrapper() )  
{  
    rw.DoStuff();  
    ...  
}
```

- ▶ **Dispose()** is always invoked at the end of the using block – even in the presence of exceptions!
- ▶ Strive to use **using** whenever possible instead of manually invoking **Dispose()**





Quiz: Object Lifetime – Right or Wrong?

```
class A
{
    ...
    ~A( int i )
    {
        Console.WriteLine( i );
    }

    public void DoStuff() { ... }
}
```

```
class B : IDisposable
{
    public void Dispose() { ... }

    public DoStuff() { ... }
}
```

```
A a = new A();
~A();
```

```
A a = new A();
a.DoStuff();
a = null;
```

```
A a = new A();
a.DoStuff();
a.Dispose();
```

```
B b = new B();
b.DoStuff();
b.Dispose();
```

```
using( B b = new B() )
{
    b.DoStuff();
}
```



Summary

- ▶ Introducing Lifetime
- ▶ Enter Garbage Collection
- ▶ Class Destructors
- ▶ The Disposable Pattern



Question

- ▶ You are creating a class referencing unmanaged resources. Also it maintains references to managed resources on other objects. You must ensure that the class can be explicitly cleaned up. Which three actions should you perform?

(Each correct answer presents part of the solution. Choose three.)



Question (Cont'd)

- a) Make the class derive from the `System.GC.CleanUp` class.
- b) Make the class implement the `IDisposable` interface.
- c) Create a `Dispose` method which cleans up unmanaged resources and calls methods to release the referenced managed resources.
- d) Create a `Dispose` method that calls `System.GC.Collect` to force garbage collection.
- e) Create a class destructor that releases the unmanaged resources.
- f) Create a class destructor that calls methods to release the referenced managed resources.



TEKNOLOGISK
INSTITUT