

Martin Hynes  
16390836

Sales Employee.java

```
//Create abstract SalesEmployee class, so there can be no instance of
it.
public abstract class SalesEmployee{//open class

    //Instance Variables:

    //private name and PPS. String for PPS because of letters in it.
    private String name;
    private String pps;
    //protected sales and commission variables, so they can be easily
accessed in subclasses.
    protected double sales;
    protected double commission;

    //Abstract Methods

    //abstract calculateCommission method, has to be overwritten in
subclasses.
    abstract double calculateCommission();

    //Constructors

    //General constructor for no inputs. Set all values to 0 or
String equivalent.
    public SalesEmployee(){//open constructor
        this.name = "unassigned";
        this.pps = "unassigned";
        this.sales = 0;
        this.commission = 0;
    }//close constructor

    //Overload constructor. Take Name, PPS, and Sales as input.
Calculate commission from given sales.
    public SalesEmployee(String Name,String PPS, double Sales){//open
overload constructor
        this.name = Name;
        this.pps = PPS;
        this.sales = Sales;
        this.commission = this.calculateCommission();
    }//close overload constructor
```

```

//Accessor methods

//Getter and Setter for name
public String getName(){//open Name getter
    return this.name;
};//close name getter

public void setName(String Name){//open name setter
    this.name = Name;
};//close name setter

//Getter and Setter for PPS
public String getPPS(){//open pps getter
    return this.pps;
};//close pps getter

public void setPPS(String PPS){//open pps setter
    this.pps = PPS;
};//close pps setter

//Getter and Setter for Sales
public double getSales(){//open sales getter
    return this.sales;
};//close sales getter
//Changing sales automatically updates the commission value.
public void setSales(double Sales){//open sales setter
    this.sales = Sales;
    this.commission = this.calculateCommission();
};//close sales setter
//Get commission method
public double getCommission(){//open commission getter
    return this.commission;
};//close comission getter

//Overwritten toString to summarise stored variables.
public String toString(){//open toString overwrite method
    return "Sales Employee. Name: " + this.name + " PPS: " +
this.pps + " Sales: " + this.sales + " Commission: " +
this.commission;
};//close toString overwrite method
};//close class

```

SalesAgent.java

```

//SalesAgent class, subclass of Sales Employee
public class SalesAgent extends SalesEmployee{//open class

```

```

//Constructors

```

```

//Use superclass constructor for generic constructor
public SalesAgent(){//open constructor
    super();
}//close constructor

//Set instance variables to given values.
public SalesAgent(String Name, String PPS, double Sales){//open
overload constructor
    super();
    this.setName(Name);
    this.setPPS(PPS);
    this.sales = Sales;
    //use calculateCommission method to set commission variable
    this.commission = this.calculateCommission();
}//close overload constructor

//Methods

//CalculateCommission uses 10% commission for Sales Agents
public double calculateCommission(){//open calculateCommission
method
    return this.sales * 0.10;
}//close calculateCommission method

//Overwrite toString method
public String toString(){//open toString override
    return "Sales Agent. Name: "+this.getName()+" PPS: " +
this.getPPS() + " Sales: " + this.getSales() + " Commission: " +
this.getCommission();
}//close toString override
}//close class

```

#### **SalesPerson.java**

```

//SalesPerson class, subclass of Sales Employee
public class SalesPerson extends SalesEmployee{//open class

//Constructors

//Use constructor from superclass for generic constructor
public SalesPerson(){//open Constructor
    super();
}//close Constructor

```

```

        //Set instance variables to inputted arguments in overload
constructor
    public SalesPerson(String Name, String PPS, double Sales){//open
Overload Constructor
    super();
    this.setName(Name);
    this.setPPS(PPS);
    this.sales = Sales;
    //Set commission using the Sales value
    this.commission = this.calculateCommission();
} //close Overload Constructor

//Methods

//CalculateCommission used 15% commission for SalesPerson
public double calculateCommission(){//open calculateCommission
method
    return this.sales * 0.15;
} //close calculateCommission method

//Overwrite toString
public String toString(){//open toString overwrite method
    return "Sales Person. Name: "+this.getName()+" PPS: " +
this.getPPS() + " Sales: " + this.getSales() + " Commission: " +
this.getCommission();
} //close toString overwrite method
} //close class

```

### SalesEmployeeTest.java

```

//Import java util for ArrayList and Iterator
import java.util.*;

//Sales Employee Tester Class
public class SalesEmployeeTest{//open class
    public static void main(String[] args){//open main method

        //Create ArrayList for SalesEmployee objects, called
EmployeeList.
        ArrayList<SalesEmployee> EmployeeList = new
ArrayList<SalesEmployee>();
        //Populate ArrayList with 5 Employees, mix of SalesPerson
and SalesAgent object types.
        //No SalesEmployee objects because it is an abstract class.
        EmployeeList.add(new SalesPerson("Adam","123456A",5000));
        EmployeeList.add(new SalesAgent("Bob","123456B",10000));
        EmployeeList.add(new
SalesPerson("Charlie","123456C",15000));
    }
}

```

```
EmployeeList.add(new SalesAgent("Dan","123456D",20000));
EmployeeList.add(new SalesPerson("Ellie","123456E",25000));
//Create iterator to traverse the ArrayList.
Iterator itr = EmployeeList.iterator();

//While loop for displaying values of objects.
while(itr.hasNext()){//open while loop
    //Defining Emp to be the next object in the list each
iteration
    SalesEmployee Emp = (SalesEmployee)itr.next();
    //pring out Emp's Name, PPS, Sales, and Commission
    System.out.println("Name: " + Emp.getName() );
    System.out.println("PPS: " + Emp.getPPS());
    System.out.println("Sales: " + Emp.getSales());
    System.out.println("Commission: "+
Emp.getCommission());
    System.out.println();
} //close while loop
} //close main method
} //close class
```

```
Name: Adam
PPS: 123456A
Sales: 5000.0
Commission: 750.0
```

```
Name: Bob
PPS: 123456B
Sales: 10000.0
Commission: 1000.0
```

```
Name: Charlie
PPS: 123456C
Sales: 15000.0
Commission: 2250.0
```

```
Name: Dan
PPS: 123456D
Sales: 20000.0
Commission: 2000.0
```

```
Name: Ellie
PPS: 123456E
Sales: 25000.0
Commission: 3750.0
```