Martin Jaime

CPE301 – SPRING 2016

Design Assignment 1

DO NOT REMOVE THIS PAGE DURING SUBMISSION:

The student understands that all required components should be submitted in complete for grading of this assignment.

NO	SUBMISSION ITEM	COMPLETED (Y/N)	MARKS (/MAX)
0.	COMPONENTS LIST AND CONNECTION BLOCK DIAGRAM w/ PINS		
1.	INITIAL CODE OF TASK 1/A		
2.	INCREMENTAL / DIFFERENTIAL CODE OF TASK 2/B		
3.	INCREMENTAL / DIFFERENTIAL CODE OF TASK 3/C		
4.	INCREMENTAL / DIFFERENTIAL CODE OF TASK 4/D		
5.	INCREMENTAL / DIFFERENTIAL CODE OF TASK 5/E		
6.	SCHEMATICS		
7.	SCREENSHOTS OF EACH TASK OUTPUT		
8.	SCREENSHOT OF EACH DEMO		
9.	VIDEO LINKS OF EACH DEMO		
10.	GOOGLECODE LINK OF THE DA		

0.	COMPONENTS LIST AND CONNECTION BLOCK DIAGRAM w/ PINS		

The only component used in this assignment is AVR Studio 7 simulator. Instead of showing block diagrams, here is the complete code used. In later sections, only part of the following will be shown to point out how a particular task was accomplished.

```
.def    count   =       r22
.def    temp    =       r25
.def    zero    =       r0

.cseg
;******************** Task a ********************;
        sub             zero,   zero    ;; make zero register.
        ;; Initialize X and Y pointers to point to ramend / 2
        ldi             xl,     low(ramend / 2)
        ldi             xh,     high(ramend / 2)
        movw            yl,     xl      ;; Y = X
        mov             r16,    xl      ;; r16 = low(x)
        ldi             count,  25      ;; count = 25
loop25:         ;; Store 25 integers into ramend/2 and up.
        st              y+,     r16     ;; *y = r16; y++
        inc             r16             ;; r16++
        dec             count           ;; count--
        brne            loop25          ;; goto to loop25 if count == 0
;******************** Task b ********************;
        ;; reset y register to x
        movw            yl,     xl      ;; y = x
        ldi             count,  25      ;; counter = 25
        ldi             r17,    7       ;; r17 = 7 // divisor
        call            Add25           ;; call Add25 routine
        mov             r20,    r10     ;; get return values.
        mov             r21,    r11     ;;    r21:r20 <- r11:r10
;******************** Task d ********************;
        ;; if r21:r20 is larger than 8 bits, set bit 3 in r7
        cp              r21,    zero    ;; check if high byte is 0
        breq            lessthan8bits7
        mov             temp,   zero
        sbr             temp,   4
        mov             r7,             temp    ;; set bit 3 in r7 is true
lessthan8bits7:
;******************** Task c ********************;
        ;; reset y register to x
        movw            yl,     xl      ;; y <- x
        ldi             count,  25      ;; counter = 25
        ldi             r17,    3       ;; r17 = 3 // divisor
        call            Add25
        mov             r23,    r10
        mov             r24,    r11     ;; r24:r23 <- r11:r10
;******************** Task d ********************;
        ;; if r24:r23 is larger than 8 bits, set bit 3 in r7
        cp              r24,    zero    ;; check if high byte is 0
        breq            lessthan8bits3
        mov             temp,   zero
        sbr             temp,   4
        mov             r7,     temp    ;; set bit 3 in r7 is true
lessthan8bits3:
end:
        rjmp end

;; Routine to add 25 integers previously stored divisible by 3.
;; Registers used:
;;              r1, r16, r15, r17, r18, r20,
Add25:
        clr             r10             ;; Clear registers r11:r10
```

```
       clr           r11
add25Loop:
       ld            r1,    y+     ;; get next value
       mov           r16,   r1     ;; store it in r16
       call   div8u                ;; call divide routine
       cp            r15,   zero   ;; Check if remainder is 0
       brne   notDivByR            ;;
       add           r10,   r1           ;; Add if remainder is 0
       adc           r11,   zero   ;; add values
notDivByR:
       dec           count         ;; loop counter
       brne   add25Loop
       ret                         ;; return to calling routine

;**** A P P L I C A T I O N   N O T E   A V R 2 0 0 ************************
;*
;* Title:             Multiply and Divide Routines
;* Version:           1.1
;* Last updated:      97.07.04
;* Target:            AT90Sxxxx (All AVR Devices)
;*
;* Support E-mail:    avr@atmel.com
;*
;***************************************************************************
;*
;* "div8u" - 8/8 Bit Unsigned Division
;*
;* This subroutine divides the two register variables "dd8u" (dividend) and
;* "dv8u" (divisor). The result is placed in "dres8u" and the remainder in
;* "drem8u".
;*
;* Number of words    :14
;* Number of cycles   :97
;* Low registers used:1 (drem8u)
;* High registers used  :3 (dres8u/dd8u,dv8u,dcnt8u)
;*
;***************************************************************************
;***** Subroutine Register Variables

.def   drem8u =r15          ;remainder
.def   dres8u =r16          ;result
.def   dd8u   =r16          ;dividend
.def   dv8u   =r17          ;divisor
.def   dcnt8u =r18          ;loop counter
;***** Code
div8u: sub    drem8u,drem8u ;clear remainder and carry
       ldi    dcnt8u,9      ;init loop counter
d8u_1: rol    dd8u          ;shift left dividend
       dec    dcnt8u        ;decrement counter
       brne   d8u_2         ;if done
       ret                  ;    return
d8u_2: rol    drem8u        ;shift dividend into remainder
       sub    drem8u,dv8u   ;remainder = remainder - divisor
       brcc   d8u_3         ;if result negative
       add    drem8u,dv8u   ;    restore remainder
       clc                  ;    clear carry to be shifted into result
       rjmp   d8u_1         ;else
d8u_3: sec                  ;    set carry to be shifted into result
       rjmp   d8u_1
```

Application note from AVR was used to perform unsigned 8-bit division to obtain the remainder of an operation.

1.	INITIAL CODE OF TASK A		

Store 25 numbers starting from the RAMEND/2 location. Capture the lower 8bits of the variable/memory location RAM_MIDDLE = RAMEND/2 address and use them as your values. You can increment or decrement from RAM_MIDDLE location to get the subsequent 24 numbers. Use the X/Y/Z registers as pointers to fill up 25 numbers starting from location=RAM_MIDDLE.

```
;******************* Task a *******************;
      sub         zero, zero  ;; make zero register.
      ;; Initialize X and Y pointers to point to ramend / 2
      ldi         xl,   low(ramend / 2)
      ldi         xh,   high(ramend / 2)
      movw        yl,   xl    ;; Y = X
      mov         r16,  xl    ;; r16 = low(x)
      ldi         count,      25    ;; count = 25
loop25:           ;; Store 25 integers into ramend/2 and up.
      st          y+,   r16   ;; *y = r16; y++
      inc         r16         ;; r16++
      dec         count       ;; count--
      brne        loop25            ;; goto to loop25 if count == 0
```

2.	INITIAL CODE OF TASK B		

Use X/Y/Z register to parse through the 25 numbers and add all numbers divisible by 7 and place the result in R20:21.

```
;******************* Task b *******************;
      ;; reset y register to x
      movw        yl,   xl    ;; y = x
      ldi         count,      25    ;; counter = 25
      ldi         r17,  7     ;; r17 = 7 // divisor
      call        Add25       ;; call Add25 routine
      mov         r20,  r10   ;; get return values.
      mov         r21,  r11   ;;    r21:r20 <- r11:r10
```

The line

```
      call        Add25       ;; call Add25 routine
```

calls the subroutine Add25, which takes as parameters `count`, and `r17` to add 25 unsigned integers from the location at Y and up. Add25 is implemented as follows.

```
Add25:
      clr         r10         ;; Clear registers r11:r10
      clr         r11
add25Loop:
      ld          r1,   y+    ;; get next value
      mov         r16,  r1    ;; store it in r16
      call  div8u             ;; call divide routine
      cp          r15,  zero  ;; Check if remainder is 0
      brne  notDivByR         ;;
      add         r10,  r1          ;; Add if remainder is 0
      adc         r11,  zero  ;; add values
notDivByR:
```

```
      dec         count       ;; loop counter
      brne        add25Loop
      ret                     ;; return to calling routine
```

3.	INITIAL CODE OF TASK C		

Use X/Y/Z register to parse through the 25 numbers and add all numbers divisible by 3 and place the result in R23:24. Parsing of the numbers for task b and c has to be done simultaneously.

```
;******************** Task c ********************;
      ;; reset y register to x
      movw        yl,   xl    ;; y <- x
      ldi         count,      25    ;; counter = 25
      ldi         r17,  3     ;; r17 = 3 // divisor
      call        Add25
      mov         r23,  r10
      mov         r24,  r11   ;; r24:r23 <- r11:r10
```

Notice that task C also calls the `Add25` subroutine.

4.	INITIAL CODE OF TASK D		

Check and set register R07.3 if the sum is greater than 8-bits.

```
;******************** Task d ********************;
      ;; if r24:r23 is larger than 8 bits, set bit 3 in r7
      cp          r24,  zero  ;; check if high byte is 0
      breq        lessthan8bits3
      mov         temp, zero
      sbr         temp, 4
      mov         r7,   temp  ;; set bit 3 in r7 is true
```

Task D is implemented twice. Once after Task B, and again after Task C to check the result of the operations for both tasks. For both tasks, the sum was greater than 8 bits.

For Task B,	For Task C,
0x85 +0x8c + 0x93 = **0x01A4**	0x81 + 0x84 + 0x87 + 0x8a + 0x8d + 0x90 + 0x93 + 0x96 = **0x045C**

4.	INITIAL CODE OF TASK D		

Determine the execution time @ 16MHz/#cycles of your algorithm using the simulation.



6.	SCHEMATICS		

There were no schematics in this assignment.

7.	SCREENSHOTS OF EACH TASK OUTPUT		

TASK A:

Starting at RAMEND/2, memory should hold values corresponding to the lower byte of their memory location. If RAMEND = 0x08FF, RAMEND/2 = 0x047F.

Before Task A:



After Task A:



Task B:

Add all numbers previously stored that are divisible by 7 and place them in r21:r20.

Before Task B:



After Task B:



Task C:

Add all numbers previously stored that are divisible by 3 and place them in r24:r23.

Before Task C:



After Task C:



Task D:

Set bit 3 in register r7 if the result is greater than 8-bits. The following illustrates this task after task b is computed.

Before Task D:



After Task D:



8.	SCREENSHOT OF EACH DEMO		

See simulation output on previous section.

9.	VIDEO LINKS OF EACH DEMO		
Videos were not requested.			
10.	Github Repository		
https://github.com/martinjaime/CpE301_Assignments2016S.git			

Student Academic Misconduct Policy
http://studentconduct.unlv.edu/misconduct/policy.html

"This assignment submission is my own, original work".
Martin Jaime