

Import and connect to database

```
In [44]: import pandas as pd
        from scipy import stats
        import numpy as np
        import sqlite3
        import matplotlib
        import matplotlib.pyplot as plt
        import matplotlib.ticker as ticker
        from math import pi

        conn = sqlite3.connect("data.db")
        act = pd.read_sql_query("select rowid, * from actors where valid=1;", conn)
```

Constants

```
In [78]: def exp_format(x, pos=None):
        names = {1: 'Delay',
                  2: 'Delay PD',
                  3: 'No delay'}
        return names[x]

        pair_dict2 = [{'aName': 'Delay', 'bName': 'Delay PD', 'a': 0, 'b': 1},
                      {'aName': 'Delay', 'bName': 'No delay', 'a': 0, 'b': 2},
                      {'aName': 'Delay PD', 'bName': 'No delay', 'a': 1, 'b': 2}]
```

Significance, Paired sample t-test and Cohen's D

```

In [41]: from numpy import std, mean, sqrt

def welch_dof(x,y):
    dof = (x.var()/x.size + y.var()/y.size)**2 / ((x.var()/x.size)**2 / (x.size-1) + (y.var()/y.size)**2 / (y.size-1))
    return dof

def dependent_dof(x,y):
    return (len(x)+len(y))/2-1

def cohen_d(x,y):
    x = x.tolist()
    y = y.tolist()
    nx = len(x)
    ny = len(y)
    dof = nx + ny - 2
    return (mean(x) - mean(y)) / sqrt(((nx-1)*std(x, ddof=1) ** 2 + (ny-1)*std(y, ddof=1) ** 2) / dof)

def print_sig(a, b, equal_var=False, dependent=True):
    if len(a) == len(b):
        t_stat, p_value = stats.ttest_rel(b, a)
        dof = dependent_dof(a, b)
    else:
        dependent = False
        t_stat, p_value = stats.ttest_ind(b, a, equal_var=equal_var)
        dof = welch_dof(a,b)
    d_value = cohen_d(b, a)

    if dependent:
        if p_value < 0.001:
            print('t({:.0f})={:.2f}, p<$.001, d={:.3f}'.format(dof, t_stat, d_value))
        else:
            print('t({:.0f})={:.2f}, p={:.3f}, d={:.3f}'.format(dof, t_stat, p_value, d_value))
    else:
        if p_value < 0.001:
            print('t({:.2f})={:.2f}, p<$.001, d={:.3f}'.format(dof, t_stat, d_value))
        else:
            print('t({:.2f})={:.2f}, p={:.3f}, d={:.3f}'.format(dof, t_stat, p_value, d_value))

```

Recorded data

```

In [14]: all_act = pd.read_sql_query("select * from actors where valid=1;", conn)
all_hits = pd.read_sql_query("select * from hits where valid=1;", conn)
all_survey = pd.read_sql_query("select * from survey where valid=1;", conn)
print('A total of {} data points were collected'.format(all_act.size+all_hits.size+all_survey.size))

```

A total of 11865 data points were collected

Task times

```
In [15]: times = pd.read_sql_query("select start, end from actors where valid=1;", conn)
length = np.array(times['end']-times['start'])
minutes = length.mean()/60-length.mean()/60%1
seconds = (length.mean()/60)%1*60
minutes_std = length.std()/60-length.std()/60%1
seconds_std = (length.std()/60)%1*60

print('Subjects used on average {:.0f} minutes and {:.0f} seconds with a standard deviation of {:.0f}min and {:.0f}s'
      .format(minutes, seconds, minutes_std, seconds_std))
```

Subjects used on average 10 minutes and 56 seconds with a standard deviation of 1min and 12s

Demographics

```

In [12]: valid_n = len(pd.read_sql_query("select age, gender, education, computer, eye
e from actors where valid=1;", conn))
non_valid = pd.read_sql_query("select age, gender, education, computer, eye
from actors where valid=0;", conn)
female = pd.read_sql_query("select age, gender, education, computer, eye fro
m actors where gender=1 and valid=1;", conn)
male = pd.read_sql_query("select age, gender, education, computer, eye from
actors where gender=0 and valid=1;", conn)
ages_df = pd.read_sql_query("select age from actors where valid=1;", conn)
ages = np.array(ages_df)
game = []
frequency = ['Daily', 'Weekly', 'Monthly', 'Yearly', 'Never']
print('Gaming:')
for i in range(5):
    query = "select * from actors where valid=1 and game={};".format(i)
    n_people = len(pd.read_sql_query(query, conn))
    print('{: {}}, {:.1f}'.format(frequency[i], n_people, n_people/valid_n*1
00))

print('{} total participants, {} excluded'.format(valid_n+len(non_valid),len
(non_valid) ))
print('{} males {:.1f}, {} females {:.1f}'.format(len(male), len(male)/valid
_n*100, len(female), len(female)/valid_n*100))
# print(' {:.1f}% females'.format(len(female)/valid_n*100))
print('Average age of {:.1f} years with a SD of {:.2f}'.format(float(ages.me
an(axis=0)), float(ages.std(axis=0))))
print('100% said they use computer on a daily basis ')
# print('Gaming: daily {:.0f}%, weekly {:.0f}%, monthly {:.0f}%, yearly {:.0
f}% and never {:.0f}%'.format(*[i/valid_n*100 for i in game]))

Gaming:
Daily: 2, 3.5
Weekly: 15, 26.3
Monthly: 8, 14.0
Yearly: 17, 29.8
Never: 15, 26.3
58 total participants, 1 excluded
38 males 66.7, 19 females 33.3
Average age of 24.7 years with a SD of 1.45
100% said they use computer on a daily basis

```

Performance normalized

```

In [148]: def output_statistical_information(normalized_values, group_name='All', subset=False):
    """
    Parameters
    -----
    normalized_values : a Nx3 numpy matrix with normalized values

    group_name : str with the group or subgroup

    subset : if subset, it will print "n" instead of "N"
    """
    if subset:
        n = 'n'
    else:
        n = 'N'

    norm = normalized_values
    display_means = norm.mean(axis=0)
    display_std = norm.std(axis=0)
    display_max = norm.max(axis=0)
    display_min = norm.min(axis=0)
    print('{} {}={}'.format(group_name, n, len(norm)))
    print('\tScore\n')
    for exp_idx in range(3):
        print('\t{:<10} Mean: {:>5.2f}, SD: {:>.2f}'
              .format(exp_format(exp_idx+1), display_means[exp_idx], display_std[exp_idx]))

    print('\n\tPaired difference\n')
    for di in pair_dict2:
        a = norm[...,di['a']]
        b = norm[...,di['b']]

        print('\t{:<10}- {:<10}'.format(di['aName'], di['bName']), end='')
        print('\t{:>6.2f}\%' .format((b.mean()/a.mean()-1)*100), end='')
        print_sig(a,b)
    print('')

def boxplot(normalized_values, filename=None):
    """
    Parameters
    -----
    normalized_values : a Nx3 numpy matrix with normalized values

    filename : str, if defined figure will be saved
    """
    norm = normalized_values
    fig, ax = plt.subplots(figsize=(4,4))
    ax.boxplot(norm, whis=2, widths=0.5)
    ax.xaxis.set_major_formatter(ticker.FuncFormatter(exp_format))
    plt.ylabel('Score')
    plt.show()
    if filename:
        fig.savefig('../img/{}.png'.format(filename), bbox_inches='tight')

def normalize_array(array):

```

```

"""
Parameters
-----
array : a Nx3 numpy matrix

Returns
-----
array : a Nx3 numpy matrix with normalized values
"""
hits = array
total_mean = hits.mean()
norm = np.zeros((hits.shape[0],3))
for i, row in enumerate(hits):
    user_mean = np.array([row[0], row[1], row[2]]).mean()
    norm[i,0] = row[0]/user_mean*total_mean
    norm[i,1] = row[1]/user_mean*total_mean
    norm[i,2] = row[2]/user_mean*total_mean
return norm

```

All

```
In [149]: hits = np.array(pd.read_sql_query("select tothitsexp0, tothitsexp1, tothitsexp2 from actors where valid=1;", conn))
norm = normalize_array(hits)
output_statistical_information(norm)
boxplot(norm, 'performance_norm')
```


All N=57

Score

Delay	Mean:	6.24	SD:	1.39
Delay PD	Mean:	7.52	SD:	1.43
No delay	Mean:	15.87	SD:	1.99

Paired difference

Delay	- Delay PD	20.62\%	t(56)=4.80, p<\$.001, d=0.904
Delay	- No delay	154.37\%	t(56)=23.15, p<\$.001, d=5.569
Delay PD	- No delay	110.88\%	t(56)=19.66, p<\$.001, d=4.772



Gender

```
In [117]: genders = ['Male', 'Female']

for gender_idx, gender in enumerate(genders):
    hits = np.array(pd.read_sql_query("select tothitsexp0, tothitsexp1, toth
itsexp2 from actors where gender={0} and valid=1;"
                                     .format(gender_idx), conn))
    norm = normalize_array(hits)
    output_statistical_information(norm, gender, True)
```

Male n=38

Score

Delay	Mean: 6.65, SD: 1.25
Delay PD	Mean: 7.95, SD: 1.43
No delay	Mean: 17.30, SD: 1.71

Paired difference

Delay	- Delay PD	19.62\%	t(37)=3.84, p<\$.001, d=0.960
Delay	- No delay	160.31\%	t(37)=24.66, p<\$.001, d=7.031
Delay PD	- No delay	117.61\%	t(37)=19.67, p<\$.001, d=5.861

Female n=19

Score

Delay	Mean: 5.39, SD: 1.49
Delay PD	Mean: 6.61, SD: 1.35
No delay	Mean: 13.10, SD: 2.17

Paired difference

Delay	- Delay PD	22.57\%	t(18)=2.82, p=0.011, d=0.835
Delay	- No delay	142.85\%	t(18)=9.43, p<\$.001, d=4.033
Delay PD	- No delay	98.14\%	t(18)=8.35, p<\$.001, d=3.495

Gaming


```
In [118]: gamers = ['Daily', 'Weekly', 'Montly', 'Yearly', 'Never']

for gamer_idx, gamer in enumerate(gamers):
    hits = np.array(pd.read_sql_query("select tothitsexp0, tothitsexp1, toth
itsexp2 from actors where game={} and valid=1;"
                                     .format(gamer_idx), conn))
    norm = normalize_array(hits)
    output_statistical_information(norm, gamer, True)
```

Daily n=2

Score

Delay	Mean: 7.92, SD: 0.37
Delay PD	Mean: 10.21, SD: 1.40
No delay	Mean: 18.36, SD: 1.77

Paired difference

Delay	- Delay PD	28.88\%	t(1)=2.22, p=0.269, d=1.578
Delay	- No delay	131.77\%	t(1)=4.87, p=0.129, d=5.762
Delay PD	- No delay	79.83\%	t(1)=2.57, p=0.236, d=3.606

Weekly n=15

Score

Delay	Mean: 6.27, SD: 1.22
Delay PD	Mean: 8.17, SD: 1.51
No delay	Mean: 17.62, SD: 2.04

Paired difference

Delay	- Delay PD	30.32\%	t(14)=3.85, p=0.002, d=1.336
Delay	- No delay	180.98\%	t(14)=14.18, p<\$.001, d=6.534
Delay PD	- No delay	115.62\%	t(14)=10.48, p<\$.001, d=5.090

Montly n=8

Score

Delay	Mean: 7.05, SD: 1.32
Delay PD	Mean: 7.77, SD: 0.64
No delay	Mean: 17.68, SD: 0.95

Paired difference

Delay	- Delay PD	10.26\%	t(7)=1.04, p=0.334, d=0.652
Delay	- No delay	150.84\%	t(7)=12.76, p<\$.001, d=8.660
Delay PD	- No delay	127.51\%	t(7)=27.89, p<\$.001, d=11.448

Yearly n=17

Score

Delay	Mean: 6.65, SD: 1.26
Delay PD	Mean: 7.66, SD: 1.73
No delay	Mean: 15.98, SD: 2.25

Paired difference

Delay	- Delay PD	15.24\%	t(16)=2.00, p=0.063, d=0.650
Delay	- No delay	140.31\%	t(16)=11.65, p<\$.001, d=4.971
Delay PD	- No delay	108.53\%	t(16)=8.74, p<\$.001, d=4.025

Never n=15

Score

Delay	Mean: 5.06, SD: 1.46
Delay PD	Mean: 6.21, SD: 1.16

No delay Mean: 12.73, SD: 1.79

Paired difference

Delay	- Delay PD	22.54\%	t(14)=2.21, p=0.044, d=0.836
Delay	- No delay	151.31\%	t(14)=9.38, p<\$.001, d=4.529
Delay PD	- No delay	105.09\%	t(14)=9.22, p<\$.001, d=4.169

Gamers vs non gamers

```
In [121]: gamers = np.array(pd.read_sql_query("select tothitsexp0, tothitsexp1, tothitsexp2 from actors where valid=1 and game<=1;", conn))
non_gamers = np.array(pd.read_sql_query("select tothitsexp0, tothitsexp1, tothitsexp2 from actors where valid=1 and game>1;", conn))

output_statistical_information(normalize_array(gamers), 'Gamers', True)
output_statistical_information(normalize_array(non_gamers), 'Non gamers', True)
```

Gamers n=17

Score

Delay	Mean: 6.46, SD: 1.19
Delay PD	Mean: 8.40, SD: 1.53
No delay	Mean: 17.73, SD: 2.08

Paired difference

Delay	- Delay PD	30.13\%	t(16)=4.34, p<\$.001, d=1.376
Delay	- No delay	174.64\%	t(16)=14.93, p<\$.001, d=6.463
Delay PD	- No delay	111.05\%	t(16)=10.83, p<\$.001, d=4.965

Non gamers n=40

Score

Delay	Mean: 6.12, SD: 1.41
Delay PD	Mean: 7.16, SD: 1.39
No delay	Mean: 15.09, SD: 1.93

Paired difference

Delay	- Delay PD	16.91\%	t(39)=3.20, p=0.003, d=0.731
Delay	- No delay	146.46\%	t(39)=18.16, p<\$.001, d=5.237
Delay PD	- No delay	110.80\%	t(39)=16.21, p<\$.001, d=4.655

Load index

Absolute

```

In [130]: tlx_metrics = ['Mental', 'Physical', 'Temporal', 'Performance', 'Effort', 'Frustration']
filename = 'nasa_tlx_bar'
plt.style.use('default')
plt.style.use('thesis.mplstyle')

n_partic = pd.read_sql_query("select rowid from actors where valid=1 ;", conn).size
fig1, ax1 = plt.subplots(figsize=(5,4))
tlx_answers = []


bar_width= 0.13

for idx, metric in enumerate(tlx_metrics):
    data = np.zeros([n_partic,3])
    for exp in range(3):
        load = pd.read_sql_query("select {} from survey where valid=1 and experiment={};".format(metric, exp), conn)
        data[...,exp] = np.reshape(np.array(load),(57,))
    if metric == 'Performance':
        data = np.ones_like(data)*10-data
    mean_ = data.mean(axis=0)
    std_ = data.std(axis=0)
    x_pos = np.arange(3)+1 - bar_width*3 +idx*bar_width+bar_width/2
    tlx_answers.append(data)

    ax1.bar(x_pos, mean_, bar_width, yerr=std_, label=metric,
            edgecolor='k',
            linewidth=1,
            capsize=2,
            error_kw={'linewidth':0.8})

ax1.xaxis.set_major_formatter(ticker.FuncFormatter(exp_format))
ax1.set_xticks(np.arange(3)+1)
plt.ylim(0,10)
plt.legend(ncol=2, fontsize='small')
plt.show()
# fig1.savefig('../img/{}.png'.format(filename), bbox_inches='tight')
for idx, metric in enumerate(tlx_answers):
    output_statistical_information(metric, tlx_metrics[idx])

```



Mental N=57

Score

Delay Mean: 5.67, SD: 2.05
 Delay PD Mean: 5.51, SD: 2.25
 No delay Mean: 3.56, SD: 2.03

Paired difference

5
 2
 Delay - Delay PD -2.79\% t(56)=-0.67, p=0.504, d=-0.073
 Delay - No delay -37.15\% t(56)=-9.31, p<\$.001, d=-1.02
 Delay PD - No delay -35.35\% t(56)=-6.36, p<\$.001, d=-0.90

Physical N=57

Score

Delay Mean: 2.88, SD: 2.14
 Delay PD Mean: 2.84, SD: 2.19
 No delay Mean: 2.18, SD: 1.84

Paired difference

Delay - Delay PD -1.22\% t(56)=-0.16, p=0.874, d=-0.016
 Delay - No delay -24.39\% t(56)=-3.10, p=0.003, d=-0.349
 Delay PD - No delay -23.46\% t(56)=-3.15, p=0.003, d=-0.327

Temporal N=57

Score

Delay Mean: 5.84, SD: 2.08
 Delay PD Mean: 5.67, SD: 2.10
 No delay Mean: 5.39, SD: 2.30

Paired difference

Delay - Delay PD -3.00\% t(56)=-0.79, p=0.431, d=-0.083
 Delay - No delay -7.81\% t(56)=-1.93, p=0.059, d=-0.206
 Delay PD - No delay -4.95\% t(56)=-0.97, p=0.335, d=-0.126

Performance N=57

Score

Delay Mean: 5.53, SD: 2.29
 Delay PD Mean: 4.74, SD: 2.05
 No delay Mean: 2.70, SD: 1.60

Paired difference

15
 8
 Delay - Delay PD -14.29\% t(56)=-3.24, p=0.002, d=-0.360
 Delay - No delay -51.11\% t(56)=-11.76, p<\$.001, d=-1.4
 Delay PD - No delay -42.96\% t(56)=-9.58, p<\$.001, d=-1.09

Effort N=57

Score

Delay	Mean: 6.02, SD: 1.94
Delay PD	Mean: 5.77, SD: 1.99
No delay	Mean: 4.67, SD: 2.08

Paired difference

5	Delay	- Delay PD	-4.08\%	t(56)=-1.05, p=0.298, d=-0.124
	Delay	- No delay	-22.45\%	t(56)=-6.34, p<\$.001, d=-0.66
	Delay PD	- No delay	-19.15\%	t(56)=-4.59, p<\$.001, d=-0.53

Frustration N=57

Score

Delay	Mean: 5.65, SD: 2.35
Delay PD	Mean: 5.04, SD: 2.13
No delay	Mean: 2.44, SD: 1.79

Paired difference

24	Delay	- Delay PD	-10.87\%	t(56)=-2.15, p=0.036, d=-0.271
	Delay	- No delay	-56.83\%	t(56)=-10.70, p<\$.001, d=-1.5
	Delay PD	- No delay	-51.57\%	t(56)=-8.23, p<\$.001, d=-1.31

Significance

```
In [316]: metric = 0
g0 = tlx_answers[metric][...,1]
g1 = tlx_answers[metric][...,2]
print_sig(g1, g0)
answers_means = np.copy(tlx_answers[metric]).mean(axis=0)
print(answers_means)
print('{:.0f}% decrease in subjective latency using predictor screen'.format
((1-answers_means[1]/answers_means[0])*100))

t(56)=6.36, p<$.001, d=0.902
[5.66666667 5.50877193 3.56140351]
3% decrease in subjective latency using predictor screen
```

Subjective delay vs frustration

```

In [182]: def avg_actor_delay(id):
            avg_delay = np.array(pd.read_sql_query("select delay from survey where v
            alid=1 and actor={}".format(id), conn)).mean()
            return avg_delay

def avg_actor_frustration(id):
    avg_frus = np.array(pd.read_sql_query("select frustration from survey wh
    ere valid=1 and actor={}".format(id), conn)).mean()
    return avg_frus

total_avg_frustration = np.array(pd.read_sql_query("select frustration from
    survey where valid=1", conn)).mean()
total_avg_delay = np.array(pd.read_sql_query("select delay from survey where
    valid=1", conn)).mean()

act = pd.read_sql_query("select rowid, * from actors where valid=1;", conn)
actor_ids = act.rowid.values
answ = [[],[]]

normalize = True
sel_exp = None
filename = 'delay_vs_frustration'

for actor_id in actor_ids:
    avg_delay = avg_actor_delay(actor_id)
    avg_frustration = avg_actor_frustration(actor_id)
    for exp in range(3):
        sur = pd.read_sql_query("select frustration, delay from survey where
        valid=1 and actor={} and experiment={}"
                                .format(actor_id, exp), conn)

        if normalize:
            frustration = float(sur['frustration'])/avg_frustration*total_av
            g_frustration
            delay = float(sur['delay'])/avg_delay*total_avg_delay
        else:
            frustration = float(sur['frustration'])
            delay = float(sur['delay'])

        if sel_exp is None or exp in sel_exp:
            answ[0].append(frustration)
            answ[1].append(delay)

x = answ[1]
y = answ[0]

linreg = stats.linregress(x,y)
# print(linreg)
x_min = min(x)
x_max = max(x)
print('$R^2={:.2f}$, p={:.5f}, err={:.5f}'.format(linreg.rvalue**2, linreg.p
value, linreg.stderr))


plt.style.use('default')
plt.style.use('thesis.mplstyle')
fig, ax = plt.subplots(figsize=(5,4))
ax.scatter(x,y, marker='o', alpha=0.5, label='Original\ndata')
ax.plot(np.arange(x_min, x_max), np.arange(x_min, x_max)*linreg.slope+linreg

```



```
.intercept, label='Fitted line\n  $R^2$ ={:.2f}'
    .format(linreg.rvalue**2))
ax.legend()
plt.ylabel('Frustration')
plt.xlabel('Subjective delay [ms]')
plt.ylim([-0.5,10])
plt.show()
# fig.savefig('../img/{}.png'.format(filename), bbox_inches='tight')
```

$R^2=0.35$, $p=0.00000$, $err=0.00038$



Delay times


```
In [100]: data = pd.DataFrame()
for exp in range(3):
    data[exp] = pd.read_sql_query("select delay from survey where valid=1 and
    d experiment={} order by actor asc;".format(exp), conn)
times = np.array(data)
```

Absolute

```

In [101]: filename = 'subjective_delay_abs'
matplotlib.rcParams.update({'font.size': 11})
fig, ax = plt.subplots(figsize=(4,4))
ax.boxplot(times, widths=0.5)
ax.xaxis.set_major_formatter(ticker.FuncFormatter(exp_format))
ax.plot([0.6,1.4], [750, 750], 'k', alpha=0.3, label='Actual delay')
ax.plot([1.6,2.4], [750, 750], 'k', alpha=0.3)
ax.plot([2.6,3.4], [250, 250], 'k', alpha=0.3)
ax.legend()
plt.ylabel('Delay [s]')
plt.ylim([-100,2100])
plt.show()
# fig.savefig('../img/{}.png'.format(filename), bbox_inches='tight')

```




Normalized

```

In [103]: sums = times.sum(axis=1)
averages = np.copy(times).mean(axis=0)
total_delay_average = np.copy(times).mean()
normalized = np.copy(times)
for idx, row in enumerate(normalized):
    user_avg = np.array([row[0], row[1], row[2]]).mean()
    row[0] = row[0]/user_avg*total_delay_average
    row[1] = row[1]/user_avg*total_delay_average
    row[2] = row[2]/user_avg*total_delay_average

```

```
In [104]: plt.style.use('classic')
plt.style.use('thesis.mplstyle')
filename = 'subjective_delay_norm'
fig, ax = plt.subplots(figsize=(5,4))
ax.boxplot(normalized, widths=0.5)
ax.plot([0.6,1.4], [750, 750], 'k', alpha=0.5, label='Actual delay')
ax.plot([1.6,2.4], [750, 750], 'k', alpha=0.5)
ax.plot([2.6,3.4], [250, 250], 'k', alpha=0.5)
ax.legend()
ax.xaxis.set_major_formatter(ticker.FuncFormatter(exp_format))
plt.ylabel('Delay [s]')
plt.ylim([-100,1800])
plt.show()
# fig.savefig('../img/{}.png'.format(filename), bbox_inches='tight')
```



```
In [244]: norm_avg = np.copy(normalized).mean(axis=0)
print('{:.0f}% decrease in subjective latency using predictor screen'.format
((1-norm_avg[1]/norm_avg[0])*100))
print_sig(normalized[... ,1], normalized[... ,0])
```


11% decrease in subjective latency using predictor screen
t(56)=1.40, p=0.167, d=0.356

Key presses

```
In [95]: data = pd.read_sql_query("select keydowns0, keydowns1, keydowns2 from actors
where valid=1;", conn)
keys = np.array(data)
```

Absolute

```
In [96]: filename = 'keypresses'
matplotlib.rcParams.update({'font.size': 10})
fig, ax = plt.subplots(figsize=(5,4))
ax.boxplot(keys, widths=0.5)
ax.xaxis.set_major_formatter(ticker.FuncFormatter(exp_format))
plt.ylabel('Key presses')
plt.show()
# fig.savefig('../img/{}.png'.format(filename), bbox_inches='tight')
```



Learning effect

```

In [93]: def condition_format(x, pos=None):
          names = ['#1', '#2', '#3']*3
          return names[x-1]

          filename = 'learning_effect'

          pos = [[0,1,2,4,3,5],
                  [2,3,0,5,1,4],
                  [4,5,1,3,0,2]]


          all_li = []

          for exp in range(3):
              first = pd.read_sql_query("select tothitsexp{} from actors where valid=1
              and crowd={} or crowd={};"
              .format(exp, pos[exp][0], pos[exp][1]), conn)
              middle = pd.read_sql_query("select tothitsexp{} from actors where valid=
              1 and crowd={} or crowd={};"
              .format(exp, pos[exp][2], pos[exp][3]), conn)
              last = pd.read_sql_query("select tothitsexp{} from actors where valid=1
              and crowd={} or crowd={};"
              .format(exp, pos[exp][4], pos[exp][5]), conn)

              li = [first['tothitsexp'+str(exp)], middle['tothitsexp'+str(exp)], last[
              'tothitsexp'+str(exp)]]
              all_li.extend(li)

          fig, ax = plt.subplots(figsize=(5,4))
          ax.boxplot([list(i) for i in all_li])
          ax.plot([3.5, 3.5],[0,23])
          ax.plot([6.5, 6.5],[0,23])
          plt.ylabel('Score')
          plt.text(2, 20, 'Delay', fontsize=10, ha='center')
          plt.text(5, 20, 'Delay PD', fontsize=10, ha='center')
          plt.text(8, 4, 'No delay', fontsize=10, ha='center')
          ax.xaxis.set_major_formatter(ticker.FuncFormatter(condition_format))
          plt.ylim([0,23])
          plt.show()
          # fig.savefig('../img/{}.png'.format(filename), bbox_inches='tight')

```



```
In [142]: num1 = 6
num2 = num1+1
ns = min(len(all_li[num1]), len(all_li[num2]))
print(ns)

print_sig(all_li[num1][:ns], all_li[num2][:ns])

18
t(17)=3.26, p=0.005, d=0.902
```

```
In [181]: for group in range(6):
           hits = pd.read_sql_query("select tothitsexp0, tothitsexp1, tothitsexp2 f
           rom actors where valid=1 and crowd={}".format(group), conn)
           norm = normalize_array(np.array(hits))
           output_statistical_information(norm, 'Group {}'.format(group), True)
```

Group 0 n=9

Score

Delay Mean: 5.08, SD: 1.21

Delay PD Mean: 7.40, SD: 1.13

No delay Mean: 15.40, SD: 1.83

Paired difference

Delay - Delay PD 45.58\%

t(8)=4.49, p=0.002, d=1.867

Delay - No delay 203.00\%

t(8)=10.11, p<\$.001, d=6.274

Delay PD - No delay 108.13\%

t(8)=8.11, p<\$.001, d=4.960

Group 1 n=10

Score

Delay Mean: 6.24, SD: 0.72

Delay PD Mean: 8.45, SD: 0.96

No delay Mean: 17.41, SD: 1.02

Paired difference

Delay - Delay PD 35.42\%

t(9)=4.89, p<\$.001, d=2.474

Delay - No delay 179.12\%

t(9)=22.73, p<\$.001, d=12.050

Delay PD - No delay 106.11\%

t(9)=14.59, p<\$.001, d=8.602

Group 2 n=10

Score

Delay Mean: 6.65, SD: 1.15

Delay PD Mean: 6.32, SD: 1.03

No delay Mean: 17.04, SD: 1.51

Paired difference

Delay - Delay PD -4.98\%

t(9)=-0.63, p=0.544, d=-0.288

Delay - No delay 156.29\%

t(9)=12.57, p<\$.001, d=7.347

Delay PD - No delay 169.73\%

t(9)=13.93, p<\$.001, d=7.884

Group 3 n=10

Score

Delay Mean: 6.58, SD: 1.52

Delay PD Mean: 6.57, SD: 0.57

No delay Mean: 16.76, SD: 1.59

Paired difference

Delay - Delay PD -0.13\%

t(9)=-0.01, p=0.988, d=-0.007

Delay - No delay 154.87\%

t(9)=9.99, p<\$.001, d=6.211

Delay PD - No delay 155.19\%

t(9)=16.53, p<\$.001, d=8.081

Group 4 n=9

Score

Delay Mean: 6.78, SD: 0.91

Delay PD Mean: 8.42, SD: 1.33

No delay Mean: 14.69, SD: 1.45

Paired difference

Delay	- Delay PD	24.34\%	$t(8)=2.66, p=0.029, d=1.366$
Delay	- No delay	116.81\%	$t(8)=11.05, p<$.001, d=6.163$
Delay PD	- No delay	74.38\%	$t(8)=6.74, p<$.001, d=4.248$

Group 5 n=9

Score

Delay	Mean: 6.03, SD: 1.84
Delay PD	Mean: 8.04, SD: 1.45
No delay	Mean: 13.59, SD: 2.58

Paired difference

Delay	- Delay PD	33.42\%	$t(8)=2.74, p=0.026, d=1.147$
Delay	- No delay	125.50\%	$t(8)=5.06, p<$.001, d=3.190$
Delay PD	- No delay	69.02\%	$t(8)=4.18, p=0.003, d=2.503$


Gamers

```
In [122]: def game_format(x, pos=None):
            names = {1: 'Delay',
                      2: 'Delay\ngamer',
                      3: 'Delay PD',
                      4: 'Delay PD\ngamer',
                      5: 'No delay',
                      6: 'No delay\ngamer'}
            return names[x]

            gamers = pd.read_sql_query("select rowid, * from actors where valid=1 and game<=1;", conn)
            ga = np.array(gamers[['tothitsexp0', 'tothitsexp1', 'tothitsexp2']])
            non_gamers = pd.read_sql_query("select rowid, * from actors where valid=1 and game >1;", conn)
            no = np.array(non_gamers[['tothitsexp0', 'tothitsexp1', 'tothitsexp2']])

            game_per = len(gamers)/(len(gamers)+len(non_gamers))

            filename = 'gamer_performance'
            fig1, ax1 = plt.subplots(figsize=(5,4))
            # ax1.set_title('Performance gamers vs non gamers')
            ax1.boxplot([no[... ,0], ga[... ,0], no[... ,1], ga[... ,1], no[... ,2], ga[... ,2]
                        ])
            ax1.xaxis.set_major_formatter(ticker.FuncFormatter(game_format))
            plt.ylabel('Score')
            plt.text(0.7, 21, 'gamer: plays weekly or more\n                        {:.0f}% of participants'.format(game_per*100), fontsize=10)
            plt.xticks(rotation=-30)
            plt.ylim([0,23.5])
            plt.show()
            # fig1.savefig('../img/{}.png'.format(filename), bbox_inches='tight')
```



```
In [157]: exp = 2  
          print_sig(no[...],0], no[...],1])  
          print_sig(ga[...],0], ga[...],1])
```

t(39)=3.27, p=0.002, d=0.577

t(16)=4.17, p<.001, d=1.018