





▼ **COS 332 S1 2020** 

Course videos

Tests and exams

Blackboard Collaborate Ultra

My Progress

Tools

Help

[clickUP help site](#)

Review Test Submission: Semester test 1

User	Mr S (Shivek) S Goodoon
Course	COS 332 S1 2020
Test	Semester test 1
Started	6/2/20 4:56 PM
Submitted	6/2/20 6:10 PM
Due Date	6/2/20 8:30 PM
Status	Completed
Attempt Score	22 out of 40 points
Time Elapsed	1 hour, 13 minutes out of 2 hours
Instructions	This is a closed-book test. You are not allowed to obtain help from any person or other source while writing the test.
You have two hours to complete the test after you started writing. However, all writing will be suspended at 19:30, even if you started writing less than two hours before that time.	
Results Displayed	Submitted Answers, Correct Answers

Question 1 0 out of 0 points

Do you promise not to consult any prohibited resources while writing this test?

Selected Answer:  True
Correct Answer:  True

Question 2 1 out of 1 points

Which ISO OSI layer's functionality can be informally described as being a 'pipe'?

Selected Answer:  4
Correct Answer:  4

Question 3 0 out of 1 points

Most layer 3 protocols accomplish routing by

Selected Answer:  Using pathfinder packets to scout the network and determine a route to reach a particular node.
Correct Answer:  Consulting routing tables compiled by layer 7 routing applications.

Question 4 0 out of 1 points

Peer in ISO OSI terminology refers to

Selected Answer:  A node in a network that does not have servers and hosts, but consists of equals
Correct Answer:  Software on the same layer as other software

Question 5 1 out of 1 points

Layer 6 of ISO/OSI is the ... layer.

Selected Answer:  Presentation
Correct Answer:  Presentation

Question 6 1 out of 1 points

Which ISO OSI layer provides process-to-process delivery?

Selected Answer:  4
Correct Answer:  4

Question 7 1 out of 1 points

The following command (followed by an IP address) may be used on a *nix host to obtain details about the owner of the specified IP address:

Selected Answer:  whois
Correct Answer:  whois

Question 8 1 out of 1 points

IP is deemed to be a reliable protocol (in the same sense as TCP) because

Selected Answer:  IP is, in fact, deemed to be unreliable.
Correct Answer:  IP is, in fact, deemed to be unreliable.

Question 9 1 out of 1 points

RIP (Routing Information Protocol)

Selected Answer:  More than one of the above
Correct Answer:  More than one of the above

Question 10 0 out of 1 points

Which term does not fit with the rest?

Selected Answer:  Cell
Correct Answer:  Header

Question 11 Unicode Selected Answer: ☒ All of the above Correct Answer: ☒ All of the above	1 out of 1 points
Question 12 Which of the following statements regarding DHCP is false? Selected Answer: ☒ DHCP will not assign an address assigned to computer A to a computer B before A has been switched of. Correct Answer: ☒ DHCP will not assign an address assigned to computer A to a computer B before A has been switched of.	1 out of 1 points
Question 13 Some of the core Internet protocols were, amongst others, designed by ...around 1980. Selected Answer: ☒ Vinton Cerf Correct Answer: ☒ Vinton Cerf	1 out of 1 points
Question 14 What role(s) do RFCs fulfil for the Internet? Selected Answer: ☒ More than one of the above Correct Answer: ☒ More than one of the above	1 out of 1 points
Question 15 Let S be the source address of an IP datagram. Let D be the destination address of an IP datagram. Let N be the netmask used on a router. Let & represent the logical and operation. If $S \& N = D \& N$ then the router will Selected Answer: ☐ Use source routing. Correct Answer: ☒ Directly deliver the packet.	0 out of 1 points
Question 16 The ISO OSI session layer is positioned (exactly) between the ... and ... layers. Selected Answer: ☒ Transport, Presentation Correct Answer: ☒ Transport, Presentation	1 out of 1 points
Question 17 An IPv6 address consists of Selected Answer: ☐ 128 bits. Correct Answer: ☒ All of the above	0 out of 1 points
Question 18 UDP headers do not contain sequence numbers. How does the node that transmits UDP data ensure that packets arrive in the correct sequence? Selected Answer: ☐ UDP is never used to send any data that resembles a stream --- hence the fact that packets may arrive in a different sequence than the sequence in which they were sent is not a problem. Correct Answer: ☒ UDP is only used to carry streams of data where the application still functions sufficiently well even if some UDP datagrams are received in the incorrect order.	0 out of 1 points
Question 19 EBNF is Selected Answer: ☒ More than one of the above Correct Answer: ☒ More than one of the above	1 out of 1 points
Question 20 The primary reason for including the host: header in the HTTP protocol is to Selected Answer: ☒ Enable virtual hosting. Correct Answer: ☒ Enable virtual hosting.	1 out of 1 points
Question 21 Protocols designed to determine network routes usually operate on ISO OSI layer ... Selected Answer: ☒ 7 Correct Answer: ☒ 7	1 out of 1 points
Question 22 ICMP is used to Selected Answer: ☐ More than one of the above Correct Answer: ☒ All of the above	0 out of 1 points
Question 23	1 out of 1 points

A MIME multipart/alternative message should consist of components that

Selected Answer:  The same message, encoded in different (alternative) manners.

Correct Answer:  The same message, encoded in different (alternative) manners.

Question 24

1 out of 1 points

IPv6

Selected Answer:  Is already in use on a number of networks.

Correct Answer:  Is already in use on a number of networks.

Question 25

0 out of 1 points

If the leading octet in a UTF-8 character is E1 (hex), how many octets will follow this octet to complete the character?

Selected Answer:  3

Correct Answer:  2

Question 26

0 out of 1 points

If a TCP segment is lost, TCP reacts by

Selected Answer:  Retransmitting the segment.

Correct Answer:  More than one of the above

Question 27

1 out of 1 points

Assume processes A and B are communicating using TCP. For the sake of this question assume that all actions are atomic; when a message is sent, it is received immediately at the other end. Stated differently, two events will never overlap. Assume A has just sent a message to B with SEQ=100, LEN=500, ACK=1000 and WIN=2000. Immediately after that B sent a message to A with LEN=300 and WIN=1000. Then the following events happen in sequence:

1. A sends a message to B with LEN=200.
2. B consumes 500 bytes from its buffer.
3. A sends a message to B with LEN=600.
4. B sends a message to A with LEN=200.
5. A consumes 1000 bytes from its buffer.
6. A sends a message to B with LEN=300

Below events 1, 3, 4 and 6 will be referred to as messages 1, 3, 4 and 6, respectively.

What is the window advertisement value sent along with message 1?

Selected Answer:  1700

Correct Answer:  1,700

Answer range +/- 0 (1700 - 1700)

Question 28

0 out of 1 points

Assume processes A and B are communicating using TCP. For the sake of this question assume that all actions are atomic; when a message is sent, it is received immediately at the other end. Stated differently, two events will never overlap. Assume A has just sent a message to B with SEQ=100, LEN=500, ACK=1000 and WIN=2000. Immediately after that B sent a message to A with LEN=300 and WIN=1000. Then the following events happen in sequence:

1. A sends a message to B with LEN=200.
2. B consumes 500 bytes from its buffer.
3. A sends a message to B with LEN=600.
4. B sends a message to A with LEN=200.
5. A consumes 1000 bytes from its buffer.
6. A sends a message to B with LEN=300

Below events 1, 3, 4 and 6 will be referred to as messages 1, 3, 4 and 6, respectively.

What is the ACK value sent along with message 3?

Selected Answer:  [None Given]

Correct Answer:  1,300

Answer range +/- 0 (1300 - 1300)

Question 29

0 out of 1 points

Assume processes A and B are communicating using TCP. For the sake of this question assume that all actions are atomic; when a message is sent, it is received immediately at the other end. Stated differently, two events will never overlap. Assume A has just sent a message to B with SEQ=100, LEN=500, ACK=1000 and WIN=2000. Immediately after that B sent a message to A with LEN=300 and WIN=1000. Then the following events happen in sequence:

1. A sends a message to B with LEN=200.
2. B consumes 500 bytes from its buffer.
3. A sends a message to B with LEN=600.
4. B sends a message to A with LEN=200.
5. A consumes 1000 bytes from its buffer.
6. A sends a message to B with LEN=300

Below events 1, 3, 4 and 6 will be referred to as messages 1, 3, 4 and 6, respectively.

What is the window advertisement value sent along with message 4?

Selected Answer:  400

Correct Answer:  700

Answer range +/- 0 (700 - 700)

Question 30

0 out of 1 points

Assume processes A and B are communicating using TCP. For the sake of this question assume that all actions are atomic; when a message is sent, it is received immediately at the other end. Stated differently, two events will never overlap. Assume A has just sent a message to B with SEQ=100, LEN=500, ACK=1000 and WIN=2000. Immediately after that B sent a message to A with LEN=300 and WIN=1000. Then the following events happen in sequence:

1. A sends a message to B with LEN=200.
2. B consumes 500 bytes from its buffer.
3. A sends a message to B with LEN=600.

3. A sends a message to B with LEN=500.
4. B sends a message to A with LEN=200.
5. A consumes 1000 bytes from its buffer.
6. A sends a message to B with LEN=300

Below events 1, 3, 4 and 6 will be referred to as messages 1, 3, 4 and 6, respectively.

What is the ACK value sent along with message 1?

Selected Answer:  [None Given]

Correct Answer:  1,300

Answer range +/- 0 (1300 - 1300)

Question 31

0 out of 1 points

Assume processes A and B are communicating using TCP. For the sake of this question assume that all actions are atomic; when a message is sent it is received immediately at the other end. Stated differently, two events will never overlap. Assume A has just sent a message to B with SEQ=100, LEN=500, ACK=1000 and WIN=2000. Immediately after that B sent a message to A with LEN=300 and WIN=1000. Then the following events happen in sequence:

1. A sends a message to B with LEN=200.
2. B consumes 500 bytes from its buffer.
3. A sends a message to B with LEN=600.
4. B sends a message to A with LEN=200.
5. A consumes 1000 bytes from its buffer.
6. A sends a message to B with LEN=300

Below events 1, 3, 4 and 6 will be referred to as messages 1, 3, 4 and 6, respectively.

What is the SEQ value sent along with message 4?

Selected Answer:  [None Given]

Correct Answer:  1,300

Answer range +/- 0 (1300 - 1300)

Question 32

1 out of 1 points

Your company uses 172.31.0.0/16 as its network address. The company plans to open a new branch. The subnet 172.31.64.0/18 is assigned to this branch. You are tasked to subnet this subnet, such that at least 100 departments in this branch may each be assigned its own subnet address and each of these subnets should be able to handle at least 100 hosts.

The network address of department 4 at this branch will have the form 172.31.X.Y/Z. What is the value of Z?

Selected Answer:  25

Correct Answer:  25

Answer range +/- 0 (25 - 25)

Question 33

0 out of 1 points

Your company uses 172.31.0.0/16 as its network address. The company plans to open a new branch. The subnet 172.31.64.0/18 is assigned to this branch. You are tasked to subnet this subnet, such that at least 100 departments in this branch may each be assigned its own subnet address and each of these subnets should be able to handle at least 100 hosts.

What is the host number of the computer at address 172.31.123.141?

Selected Answer:  18

Correct Answer:  13

Answer range +/- 0 (13 - 13)

Question 34

0 out of 1 points

Your company uses 172.31.0.0/16 as its network address. The company plans to open a new branch. The subnet 172.31.64.0/18 is assigned to this branch. You are tasked to subnet this subnet, such that at least 100 departments in this branch may each be assigned its own subnet address and each of these subnets should be able to handle at least 100 hosts.

The broadcast address of department 4 at this branch will have the form 172.31.X.Y. What is the value of X?

Selected Answer:  65

Correct Answer:  66

Answer range +/- 0 (66 - 66)

Question 35

0 out of 1 points

Your company uses 172.31.0.0/16 as its network address. The company plans to open a new branch. The subnet 172.31.64.0/18 is assigned to this branch. You are tasked to subnet this subnet, such that at least 100 departments in this branch may each be assigned its own subnet address and each of these subnets should be able to handle at least 100 hosts.

The broadcast address of department 4 at this branch will have the form 172.31.X.Y. What is the value of Y?

Selected Answer:  255

Correct Answer:  127

Answer range +/- 0 (127 - 127)

Question 36

0 out of 1 points

Your company uses 172.31.0.0/16 as its network address. The company plans to open a new branch. The subnet 172.31.64.0/18 is assigned to this branch. You are tasked to subnet this subnet, such that at least 100 departments in this branch may each be assigned its own subnet address and each of these subnets should be able to handle at least 100 hosts.

The network address of department 4 at this branch will have the form 172.31.X.Y/Z. What is the value of Y?

Selected Answer:  255

Correct Answer:  0

Answer range +/- 0 (0 - 0)

Question 37

1 out of 1 points

Provide the missing text in each of the questions below. Only provide the missing text: In a question that includes U+____, don't repeat the U+. For answers that consist of byte sequences, leave one space between byte values. When an answer requires hexadecimal digits in the range A to F, you may use upper or lower case.

Questions of the form "How many ... ?" should be answered in decimal. All encoding and decoding questions should be answered in hexadecimal (unless the question includes clear instructions that some other base should be used). Do not indicate the base you used in your answer; just provide the number.

The ASN.1 encoding mechanism that leaves one with the greatest choice of how to represent data is abbreviated as ____.

Selected Answer: BER

Correct Answer:

Evaluation Method	Correct Answer	Case Sensitivity
Exact Match	BER	

Question 38

1 out of 1 points

Provide the missing text in each of the questions below. Only provide the missing text: In a question that includes U+____, don't repeat the U+. For answers that consist of byte sequences, leave one space between byte values. When an answer requires hexadecimal digits in the range A to F, you may use upper or lower case.

Questions of the form "How many ... ?" should be answered in decimal. All encoding and decoding questions should be answered in hexadecimal (unless the question includes clear instructions that some other base should be used). Do not indicate the base you used in your answer; just provide the number.

How many characters (including special characters) are represented by the American version of ASCII?

Selected Answer: 128

Correct Answer: 128

Answer range +/- 0 (128 - 128)

Question 39

1 out of 1 points

Provide the missing text in each of the questions below. Only provide the missing text: In a question that includes U+____, don't repeat the U+. For answers that consist of byte sequences, leave one space between byte values. When an answer requires hexadecimal digits in the range A to F, you may use upper or lower case.

Questions of the form "How many ... ?" should be answered in decimal. All encoding and decoding questions should be answered in hexadecimal (unless the question includes clear instructions that some other base should be used). Do not indicate the base you used in your answer; just provide the number.

The UTF-8 byte string E0 B8 BF represents the Unicode character U+_____.

Selected Answer: 0E3F

Correct Answer:

Evaluation Method	Correct Answer	Case Sensitivity
Exact Match	0E3F	
Exact Match	E3F	

Question 40

0 out of 1 points

Provide the missing text in each of the questions below. Only provide the missing text: In a question that includes U+____, don't repeat the U+. For answers that consist of byte sequences, leave one space between byte values. When an answer requires hexadecimal digits in the range A to F, you may use upper or lower case.

Questions of the form "How many ... ?" should be answered in decimal. All encoding and decoding questions should be answered in hexadecimal (unless the question includes clear instructions that some other base should be used). Do not indicate the base you used in your answer; just provide the number.

Convert U+1EB9 to UTF-8.

Selected Answer: E1BAB9

Correct Answer:

Evaluation Method	Correct Answer	Case Sensitivity
Exact Match	E1 BA B9	

Question 41

1 out of 1 points

Provide the missing text in each of the questions below. Only provide the missing text: In a question that includes U+____, don't repeat the U+. For answers that consist of byte sequences, leave one space between byte values. When an answer requires hexadecimal digits in the range A to F, you may use upper or lower case.

Questions of the form "How many ... ?" should be answered in decimal. All encoding and decoding questions should be answered in hexadecimal (unless the question includes clear instructions that some other base should be used). Do not indicate the base you used in your answer; just provide the number.

How many bytes are needed to represent U+2665 in UTF-8?

Selected Answer: 3

Correct Answer: 3

Answer range +/- 0 (3 - 3)

Question 42

0 out of 0 points

Have you cheated while writing this test?

Selected Answer: False

Correct Answer: False

Wednesday, July 1, 2020 5:15:39 PM SAST

← OK