

Atmosfire Development Kit Design Overview Version 1.0








This page is intentionally left blank.





Revision History					
Version Date		Updates			
Rev.A	070516	First Atmosfire revision			

Without our written consent in each particular case, this document must not under any circumstances and under penalty of law be reproduced, improperly used, handed over or otherwise communicated to a third part.

Arrow Engineering Sweden, Timmernabben, Sweden







 \Box

1.02 Description:

0

Daniel Nilsson Atmosfire STR710 PMEE Expansion 2007-02-06 External Bus Interface Design:

ARROW ENGINEERING

(


 \bigcirc

 $_{\Omega}$

 \triangleleft

0

 ∞



Bill Of Material STR7-Atmosfire

Date:	2007-02-11
Aut:	Daniel Nilsson
Schematic:	V1.02

	Ref Des	Qty	Partnumber	Value	Package	Manufacturer	Description
1	C3-24 C26 C29-30	28		100nF	0402	Any	X7R 10V 10% Ceramic Cap
	C38 C40-41						
2	C31-32	2		12pF	0402	Any	NP0 25V 5% Ceramic Cap
3	C25 C28	2		1uF	0805	Any	X7R 16V 10% Ceramic Cap
4	R16-18	3		0R	0402	Any	Metalfilm resistor 1%
5	R7-8 R12-13 R15	20		10K	0402	Any	Metalfilm resistor 1%
	R19 R21-29 R53-57						
6	R2	1		180K	0402	Any	Metalfilm resistor 1%
	R14 R32-33 R50	4		180R	0402	Any	Metalfilm resistor 1%
	R1 R6	2		1K	0402	Any	Metalfilm resistor 1%
	R5	1		1K5	0402	Any	Metalfilm resistor 1%
	R3	1		1M2	0402	Any	Metalfilm resistor 1%
	R4 R9-11 R20 R34-	19		22R	0402	Any	Metalfilm resistor 1%
	47	10		ZZIX	0402	/ ury	INCLAMINITY COLOCOT 170
12	R30-31 R48-49	4		2K2	0402	Any	Metalfilm resistor 1%
	R51-52	2		4K7	0402	Any	Metalfilm resistor 1%
14	J8		10033526-N3212LF	4 pole	USB Type B	FCI Connect	Type-B Mini USB connector
	IC5		74LVCH16244AEV		VFBGA56	NXP	16-bit bus buffer with bus hold
16	IC7		74LVCH16245AEV		VFBGA56	NXP	16-bit Bus XCVR with bus hold
17	IC2		ATMEGA48-20MU		MLF-32	Atmel	8-bit 20Mhz RISC MCU with OCD and E2PROM
18	L1		B82422H1472K100	4.7uH/430mA	1210	Epcos	+-10% 1210 SMD Choke
19	D9		BAT54SW		SC-70	NXP	Double schottky diode
	C1-2 C27 C35-37		C3216X5R0J106M	10uF	1206	TDK	X5R 6.3V 10% Ceramic Cap
	C39						
21	L2-3	2	CS201212-100K	10uH	0805	Bourns	Chip inductor 0805
22	IC3-4		CY7C1041CV33-10BAX		48-FBGA	Cypress	256Kbx16 Fast Async SRAM, 10ns
23	IC6	1	LC4064ZC-37MN56I		csBGA56	Lattice	64MC 32 I/O ispJTAG 1.8V 5ns IND Pb-Free
24	X1	1	LF XTAL003000	32.768kHz	SMX 85 SMD	CMAC	32,768kHz SMD Crystal
25	IC10	1	LMV331IDBVT		SOT-23-5	TI	SOT-23 Comparator Open Drain Output
26	LD9-10	2	LTST-C155KGJRKT		3.2 x 2.7mm Chip	LiteOn	BiColor Red/Green LED
27	LD1-8	8	LTW-C191TL5		0603	LiteOn	White High intesity LED
28	IC12	1	M25PE16-VMP6G		MLP8	STMicroelectronics	16Mb Serial flash with SPI interface
29	Q1-2	2	PDTC123EU		SC-70	NXP	10k + 10k Digital NPN Transistor
30	J1, J4, J7	1	SMM-130-02-S-D-P	60 Pole	SMD 2 row socket	Samtec	SMD dual row 2mm socket
	IC9	1	STP08CL596		TSSOP-16	STMicroelectronics	8-bit SPI driven LED Driver 15-90mA
	IC1	1	STR710Z2H6		LFBGA144	STMicroelectronics	Integrated ARM7 MCU, USB, 4xUART and HDLC interface.
33	J10	1	TMM-105-01	10 Pole		Samtec	Dual row 1M Header
34	J2-3, J5-6	4	TMM-130-01-F-D-SM	60 Pole	SMD 2 row header	Samtec	SMD dual row 2mm pinheader
	IC8	1	TPS61070DDC		SOT-23-6	TI	SOT-23 Boost DC-DC Converter
36	IC11	1	USBUF01W6		SC-70-6	STMicroelectronics	SC-70 USB ESD Protection
37	Plastic Spacer	1				Skylt & Gravyr	Plastic lasercut acrylspacer
38	Overlay	1				Screen Service	Plastic overlay with frosted logos
39	PCB	1	Atmosfire			NCAB	Atmosfire 6-layer PCB

