

Assignment 7 – Selected Model Answers

EXERCISE 1. Implement operators on the class AVL returning the elements in the tree:

- (i) Define an operator that exploits a *depth-first search* through the tree and returns the elements in the order of this search.
- (ii) Define an operator that exploits a *breadth-first search* through the tree and returns the elements in the order of this search.
- (iii) Use one of these operators to implement a function *range* on AVL class, which for arguments x and y returns those elements in the tree that satisfy $x \leq e \leq y$.

EXERCISE 2. Take a text of your choice with a length of around one page and build a dictionary with the words in the text. Use a TRIE data structure.

Then implement a procedure, which in case that a search for a word in the dictionary fails return suggested alternatives:

- (i) Return words from the dictionary that extend the given word (not found in the dictionary) by one symbol.
- (ii) Return words from the dictionary that are prefixes of the given word (not found in the dictionary) with one or two symbols less.
- (iii) Return words from the dictionary that differ from the given word (not found in the dictionary) by exactly one symbol.

EXERCISE 3.

- (i) Prove that the total number of comparisons in a search in an (a, b) -tree with n nodes is bounded by $\lceil \log b \rceil (2 + \log_a((n-1)/2))$.
- (ii) Assuming $b \leq 2a$ show that the number in (i) is in $O(\log b) + O(\log n)$.

SOLUTION.

- (i) The root of an (a, b) -tree has at least two children, and all other non-leaf nodes have at least a children. Thus, in a tree of height h the number of nodes is at most

$$1 + 2 \sum_{i=0}^{h-1} a^i = 1 + 2 \frac{a^h - 1}{a - 1} .$$

This implies

$$\frac{(n-1)(a-1)}{2} + 1 \geq a^h$$

and hence

$$h \leq \log_a \left(\frac{(n-1)(a-1)}{2} + 1 \right) \leq 1 + \log_a \frac{n-1}{2} + \log_a(a-1) \leq 2 + \log_a \frac{n-1}{2} .$$

The height determines the length of a search path, and in each node along the path there are at most b elements stored in an ordered way. For binary search in a node we need at most $\lceil \log b \rceil$ comparisons.

Hence the total number of comparisons is bounded by $\lceil \log b \rceil (2 + \log_a((n-1)/2))$.

(ii) Using the result from (i) the number of comparisons is bounded by

$$\left(\log_a \frac{n-1}{2} + 2 \right) \cdot \log_2 b = \frac{\log_2 b}{\log_2 a} \log_2 \frac{n-1}{2} + 2 \log_2 b .$$

As we assume $b \leq 2a$, we get $\log_2 b \leq 1 + \log_2 a$, which gives

$$\frac{\log_2 b}{\log_2 a} \log_2 \frac{n-1}{2} + 2 \log_2 b = \left(\frac{1}{\log_2 a} + 1 \right) \log_2 \frac{n-1}{2} + 2 \log_2 b ,$$

which is in $O(\log n) + O(\log b)$ as claimed.